

FCC Test Report

(Spot Check: Part 24 – GSM, WCDMA B2, LTE B2)

Report No.: RFBGTL-WTW-P22070227-7

FCC ID: APYHRO00316

Received Date: Feb. 19, 2022

Test Date: Jul. 26 ~ Jul. 27, 2022

Issued Date: Aug. 25, 2022

Applicant: SHARP Corporation Mobile Communication BU

Address: 2-13-1 Iida Hachihonmatsu Higashi-hiroshima City, Hiroshima 730-0192, Japan

Manufacturer: Sharp Corporation

Address: 1 Takumi-cho, Sakai-ku, Sakai City, Osaka 590-8522, Japan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location (1): No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

Test Location (2): No. 70, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan

FCC Registration / 788550 / TW0003

Designation Number: 281270 / TW0032



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	5
2.2 Test Site and Instruments	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Configuration of System under Test	9
3.2.1 Description of Support Units	9
3.3 Test Mode Applicability and Tested Channel Detail	10
3.4 EUT Operating Conditions	11
3.5 General Description of Applied Standards and References	11
4 Test Types and Results	12
4.1 Output Power Measurement	12
4.1.1 Limits of Output Power Measurement	12
4.1.2 Test Procedures	12
4.1.3 Test Setup	12
4.1.4 Test Results	13
4.2 Radiated Emission Measurement	27
4.2.1 Limits of Radiated Emission Measurement	27
4.2.2 Test Procedure	27
4.2.3 Deviation from Test Standard	27
4.2.4 Test Setup	28
4.2.5 Test Results	29
5 Pictures of Test Arrangements	38
Appendix – Information of the Testing Laboratories	39



Release Control Record

Issue No.	Description	Date Issued
RFBGTL-WTW-P22070227-7	Original Release	Aug. 25, 2022

2 Summary of Test Results

Applied Standard: FCC Part 24 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 24.232	Effective Isotropically Radiated Power	Pass	Meet the requirement of limit.
2.1053 24.238	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -30.53dB at 36.79MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (\pm)
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.00 dB
	30MHz ~ 200MHz	2.91 dB
	200MHz ~ 1000MHz	2.92 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	1.76 dB
	18GHz ~ 40GHz	1.77 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver Rohde & Schwarz	ESR3	102579	Jul. 01, 2022	Jun. 30, 2023
Spectrum Analyzer KEYSIGHT	N9020B	MY60110462	Dec. 21, 2021	Dec. 20, 2022
BILOG Antenna SCHWARZBECK	VULB9168	995	Oct. 28, 2021	Oct. 27, 2022
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-404	Nov. 14, 2021	Nov. 13, 2022
HORN Antenna SCHWARZBECK	BBHA 9170	995	Nov. 14, 2021	Nov. 13, 2022
Loop Antenna EMCI	EM-6879	269	Sep. 16, 2021	Sep. 15, 2022
Preamplifier EMCI	EMC330N	980783	Jan. 17, 2022	Jan. 16, 2023
Preamplifier EMCI	EMC118A45SE	980810	Dec. 30, 2021	Dec. 29, 2022
Preamplifier EMCI	EMC184045SE	980787	Jan. 17, 2022	Jan. 16, 2023
RF signal cable EMCI	EMC104-SM-SM- (9000+2000+1000)	201230+ 201242+ 210101	Jan. 17, 2022	Jan. 16, 2023
RF signal cable EMCI	EMCCFD400-NM- NM- (9000+300+500)	201252+ 201250+ 201245	Jan. 17, 2022	Jan. 16, 2023
RF signal cable EMCI	EMC101G-KM-KM- (5000+3000+2000)	201261+201258+ 201249	Jan. 17, 2022	Jan. 16, 2023
Software BV CPS	ADT_Radiated_V7. 6.15.9.5	NA	NA	NA
Turn Table Max-Full	MFT-151SS-0.5T	NA	NA	NA
Turn Table Controller Max-Full	MF-7802BS	MF780208675	NA	NA
Antenna Tower KaiTuo	NA	NA	NA	NA
Antenna Tower Controller KaiTuo	KT-2000	NA	NA	NA
USB Wideband Power Sensor KEYSIGHT	U2021XA	MY55050005/MY55190 004/MY55190007/MY55 210005	Jul. 13, 2022	Jul. 12, 2023
Radio Communication Analyzer Anritsu	MT8821C	6261806803	Feb. 16, 2022	Feb. 15, 2023

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in WM Chamber 7.

3 General Information

3.1 General Description of EUT

Product	Smart Phone			
Brand	SHARP			
Sample Status	Engineering Sample			
Power Supply	5.0Vdc (from adapter)			
Rating	3.87Vdc (Battery)			
Modulation Type	GSM, GPRS: GMSK WCDMA: BPSK, QPSK HSDPA: BPSK HSUPA: QPSK LTE: QPSK, 16QAM, 64QAM			
Operating Frequency	GSM, GPRS	1850.2MHz ~ 1909.8MHz		
	WCDMA Band 2	1852.4MHz ~ 1907.6MHz		
	LTE Band 2 (Channel Bandwidth 1.4MHz)	1850.7MHz ~ 1909.3MHz		
	LTE Band 2 (Channel Bandwidth 3MHz)	1851.5MHz ~ 1908.5MHz		
	LTE Band 2 (Channel Bandwidth 5MHz)	1852.5MHz ~ 1907.5MHz		
	LTE Band 2 (Channel Bandwidth 10MHz)	1855.0MHz ~ 1905.0MHz		
	LTE Band 2 (Channel Bandwidth 15MHz)	1857.5MHz ~ 1902.5MHz		
	LTE Band 2 (Channel Bandwidth 20MHz)	1860.0MHz ~ 1900.0MHz		
Max. EIRP Power	GSM	487.528mW (26.88dBm)		
	GPRS	497.737mW (26.97dBm)		
	WCDMA Band 2	100.925mW (20.04dBm)		
		QPSK	16QAM	64QAM
	LTE Band 2 (Channel Bandwidth 1.4MHz)	77.090mW (18.87dBm)	62.087mW (17.93dBm)	48.084mW (16.82dBm)
	LTE Band 2 (Channel Bandwidth 3MHz)	77.446mW (18.89dBm)	61.802mW (17.91dBm)	47.643mW (16.78dBm)
	LTE Band 2 (Channel Bandwidth 5MHz)	76.560mW (18.84dBm)	60.814mW (17.84dBm)	47.643mW (16.78dBm)
	LTE Band 2 (Channel Bandwidth 10MHz)	76.736mW (18.85dBm)	61.094mW (17.86dBm)	48.195mW (16.83dBm)
	LTE Band 2 (Channel Bandwidth 15MHz)	77.446mW (18.89dBm)	61.802mW (17.91dBm)	47.534mW (16.77dBm)
	LTE Band 2 (Channel Bandwidth 20MHz)	96.828mW (19.86dBm)	77.268mW (18.88dBm)	59.979mW (17.78dBm)
Antenna Type	Refer to note			
Antenna Connector	Refer to note			
Accessory Device	Refer to note			
Cable Supplied	NA			

Note:

1. This report is a supplementary report to the original BV CPS report no.: RFBGTL-WTW-P22020475-7. Exhibit prepared for FCC Spot Check Verification report, the format, test items and amount of spot-check test data are decided by applicant's engineering judgment, for more details please refer to declaration letter exhibit. Radiated emission and output power verification worst test refer to original report.
2. There are differences between FCC ID: APYHRO00314 & FCC ID: APYHRO00316:

FCC ID	APYHRO00314	APYHRO00316
FM Radio	Supports	Doesn't support

3. The EUT contains following support units.



Product	Brand	Model	Description
Adapter (Support unit)	Salom	XN-2QC25	Input: 100-240Vac, 50/60Hz, 0.2A Output: 5.0Vdc, 800mA
Battery	-	-	3.87Vdc, Rated 4870mAh (18.9Wh), Typ. 5000mAh (19.4Wh)
Headset (Support unit)	Ambibio	AB-HI02JS	-
USB cable (Support unit)	Luxshare-ICT	L6KU2007-CS-H	0.95m shielded cable without core

4. The antenna information is listed as below.

Ant. No.	Type	Connector	Gain (dBi)										
			GSM 850	GSM 1900	WCDMA B2 / LTE B2	WCDMA B4 / LTE B4	WCDMA B5 / LTE B5	LTE B7	LTE B12	LTE B13	LTE B17	LTE B38	LTE B41
1	PIFA	IPEX	-	-2.9	-2.9	-4.9	-	-1.8	-	-	-	-1.9	-1.9
3	PIFA	IPEX	-4.8	-	-	-	-4.8	-	-5.6	-5.3	-5.6	-	-

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

3.2 Configuration of System under Test



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Adapter	Salom	XN-2QC25	N/A	N/A	Provided by client
B.	Headset	Ambibio	AB-HI02JS	N/A	N/A	Provided by client
C.	Radio Communication Analyzer	Anritsu	MT8821C	6261806803	NA	-

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item C acted as a communication partner to transfer data.

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	Earphone Cable	1	1.1	N	0	Provided by client
2.	USB Cable	1	1	Y	0	Provided by client

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	Radiated Emission
GSM	Z-plane
WCDMA Band 2	Z-plane
LTE Band 2	Z-plane

GSM Mode

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Modulation
-	EIRP	512 to 810	512 (1850.2MHz), 661 (1880.0MHz), 810 (1909.8MHz)	GSM, GPRS
-	Radiated Emission	512 to 810	661 (1880.0MHz)	GSM

WCDMA Band 2

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	EIRP	9262 to 9538	9262 (1852.4MHz), 9400 (1880.0MHz), 9538 (1907.6MHz)	WCDMA, HSDPA, HSUPA
-	Radiated Emission	9262 to 9538	9400 (1880.0MHz)	WCDMA

LTE Band 2

EUT Configure Mode	Test item	Available channel	Tested Channel	Channel Bandwidth	Modulation	RB #
-	EIRP	18607 to 19193	18607 (1850.7MHz), 18900 (1880.0MHz), 19193 (1909.3MHz)	1.4MHz	QPSK / 16QAM / 64QAM	1 Half Full
		18615 to 19185	18615 (1851.5MHz), 18900 (1880.0MHz), 19185 (1908.5MHz)	3MHz	QPSK / 16QAM / 64QAM	1 Half Full
		18625 to 19175	18625 (1852.5MHz), 18900 (1880.0MHz), 19175 (1907.5MHz)	5MHz	QPSK / 16QAM / 64QAM	1 Half Full
		18650 to 19150	18650 (1855.0MHz), 18900 (1880.0MHz), 19150 (1905.0MHz)	10MHz	QPSK / 16QAM / 64QAM	1 Half Full
		18675 to 19125	18675 (1857.5MHz), 18900 (1880.0MHz), 19125 (1902.5MHz)	15MHz	QPSK / 16QAM / 64QAM	1 Half Full
		18700 to 19100	18700 (1860.0MHz), 18900 (1880.0MHz), 19100 (1900.0MHz)	20MHz	QPSK / 16QAM / 64QAM	1 Half Full
-	Radiated Emission	18700 to 19100	18900 (1880.0MHz)	20MHz	QPSK	1

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
EIRP	25deg. C, 60%RH	3.87Vdc	Willy Cheng
Radiated Emission	27deg. C, 66%RH	120Vac, 60Hz	Edison Lee, Wade Huang

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test Standard:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

ANSI/TIA/EIA-603-E 2016

ANSI 63.26-2015

References Test Guidance:

KDB 971168 D01 Power Meas License Digital Systems v03r01

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 2 watts e.i.r.p.

4.1.2 Test Procedures

Conducted Power Measurement:

The EUT was set up for the maximum power with GSM, WCDMA and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

Maximum EIRP / ERP

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is

given in Equation as follows:

$$\text{EIRP} = P_{\text{Meas}} + G_T$$

$$\text{ERP} = P_{\text{Meas}} + G_T - 2.15$$

where


ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively
(expressed in the same units as P_{Meas} , e.g., dBm or dBW)

P_{Meas} measured transmitter output power or PSD, in dBm or dBW

G_T gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

4.1.3 Test Setup

Conducted Power Measurement:



4.1.4 Test Results

Conducted Output Power (dBm)

Band	GSM 1900		
Channel	512	661	810
Frequency	1850.2	1880	1909.8
GSM	29.68	29.78	29.78
GPRS 1Tx Slot	29.85	29.87	29.69
GPRS 2Tx Slot	27.73	27.80	27.70
GPRS 3Tx Slot	26.30	26.35	26.21
GPRS 4Tx Slot	25.35	25.47	25.26

Band	WCDMA II		
TX Channel	9262	9400	9538
Rx Channel	9662	9800	9938
Frequency	1852.4	1880	1907.6
RMC 12.2K	22.87	22.94	22.86
HSDPA Subtest-1	21.77	21.96	21.87
HSDPA Subtest-2	20.54	20.85	21.00
HSDPA Subtest-3	20.13	20.35	20.47
HSDPA Subtest-4	20.04	20.27	20.48
HSUPA Subtest-1	20.60	20.76	21.05
HSUPA Subtest-2	18.58	18.81	19.06
HSUPA Subtest-3	19.56	19.76	19.98
HSUPA Subtest-4	18.61	18.88	18.97
HSUPA Subtest-5	20.55	20.76	20.97

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18700	18900	19100
		Frequency (MHz)		1860	1880	1900
20M	QPSK	1	0	22.58	22.76	22.61
		1	50	22.34	22.57	22.38
		1	99	22.29	22.45	22.37
		50	0	21.37	21.59	21.42
		50	25	21.42	21.52	21.43
		50	50	21.32	21.50	21.40
		100	0	21.52	21.69	21.60
20M	16QAM	1	0	21.54	21.78	21.61
		1	50	21.51	21.65	21.52
		1	99	21.49	21.58	21.46
		50	0	20.54	20.62	20.55
		50	25	20.41	20.63	20.51
		50	50	20.42	20.51	20.41
		100	0	20.40	20.58	20.47
20M	64QAM	1	0	20.42	20.68	20.55
		1	50	20.38	20.62	20.53
		1	99	20.44	20.56	20.41
		50	0	19.46	19.62	19.53
		50	25	19.48	19.64	19.50
		50	50	19.43	19.51	19.48
		100	0	19.59	19.70	19.67

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18675	18900	19125
		Frequency (MHz)		1857.5	1880	1902.5
15M	QPSK	1	0	21.61	21.79	21.62
		1	37	21.42	21.61	21.46
		1	74	21.37	21.50	21.35
		36	0	20.51	20.60	20.47
		36	19	20.45	20.63	20.55
		36	39	20.45	20.62	20.47
		75	0	20.61	20.76	20.60
15M	16QAM	1	0	20.56	20.81	20.66
		1	37	20.59	20.66	20.63
		1	74	20.44	20.65	20.60
		36	0	19.50	19.77	19.63
		36	19	19.47	19.59	19.55
		36	39	19.48	19.65	19.49
		75	0	19.49	19.72	19.51
15M	64QAM	1	0	19.53	19.67	19.53
		1	37	19.49	19.61	19.57
		1	74	19.48	19.60	19.53
		36	0	18.52	18.67	18.65
		36	19	18.54	18.67	18.56
		36	39	18.40	18.60	18.49
		75	0	18.61	18.78	18.70

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18650	18900	19150
		Frequency (MHz)		1855	1880	1905
10M	QPSK	1	0	21.60	21.75	21.68
		1	24	21.37	21.58	21.48
		1	49	21.29	21.48	21.35
		25	0	20.45	20.60	20.48
		25	12	20.45	20.57	20.51
		25	25	20.47	20.61	20.43
		50	0	20.61	20.73	20.57
10M	16QAM	1	0	20.61	20.76	20.62
		1	24	20.59	20.76	20.61
		1	49	20.53	20.70	20.54
		25	0	19.59	19.76	19.59
		25	12	19.49	19.58	19.55
		25	25	19.40	19.60	19.47
		50	0	19.55	19.69	19.61
10M	64QAM	1	0	19.53	19.73	19.62
		1	24	19.49	19.66	19.49
		1	49	19.43	19.65	19.48
		25	0	18.52	18.69	18.63
		25	12	18.45	18.66	18.61
		25	25	18.47	18.66	18.48
		50	0	18.62	18.76	18.67

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18625	18900	19175
		Frequency (MHz)		1852.5	1880	1907.5
5M	QPSK	1	0	21.58	21.74	21.60
		1	12	21.39	21.55	21.45
		1	24	21.30	21.51	21.38
		12	0	20.51	20.58	20.51
		12	6	20.43	20.58	20.53
		12	13	20.41	20.56	20.48
		25	0	20.58	20.76	20.64
5M	16QAM	1	0	20.61	20.74	20.67
		1	12	20.52	20.74	20.65
		1	24	20.49	20.61	20.60
		12	0	19.50	19.69	19.66
		12	6	19.44	19.63	19.47
		12	13	19.40	19.57	19.54
		25	0	19.52	19.67	19.57
5M	64QAM	1	0	19.50	19.65	19.57
		1	12	19.51	19.68	19.50
		1	24	19.45	19.61	19.45
		12	0	18.57	18.72	18.65
		12	6	18.51	18.64	18.53
		12	13	18.41	18.65	18.47
		25	0	18.57	18.78	18.72

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18615	18900	19185
		Frequency (MHz)		1851.5	1880	1908.5
3M	QPSK	1	0	21.64	21.79	21.65
		1	7	21.38	21.63	21.46
		1	14	21.30	21.56	21.42
		8	0	20.42	20.68	20.55
		8	3	20.47	20.65	20.49
		8	7	20.45	20.61	20.49
		15	0	20.59	20.74	20.58
3M	16QAM	1	0	20.61	20.81	20.64
		1	7	20.55	20.75	20.63
		1	14	20.53	20.71	20.53
		8	0	19.56	19.70	19.65
		8	3	19.51	19.61	19.57
		8	7	19.44	19.64	19.49
		15	0	19.48	19.68	19.57
3M	64QAM	1	0	19.48	19.68	19.60
		1	7	19.52	19.62	19.57
		1	14	19.49	19.65	19.52
		8	0	18.51	18.68	18.64
		8	3	18.46	18.66	18.61
		8	7	18.45	18.62	18.49
		15	0	18.58	18.76	18.70

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18607	18900	19193
		Frequency (MHz)		1850.7	1880	1909.3
1.4M	QPSK	1	0	21.64	21.74	21.65
		1	2	21.44	21.61	21.50
		1	5	21.35	21.50	21.36
		3	0	21.43	21.66	21.49
		3	1	21.49	21.61	21.51
		3	3	21.37	21.59	21.46
		6	0	20.60	20.69	20.67
1.4M	16QAM	1	0	20.57	20.83	20.71
		1	2	20.49	20.71	20.63
		1	5	20.49	20.62	20.52
		3	0	20.59	20.75	20.66
		3	1	20.47	20.59	20.54
		3	3	20.46	20.59	20.54
		6	0	19.48	19.64	19.52
1.4M	64QAM	1	0	19.56	19.67	19.52
		1	2	19.42	19.68	19.58
		1	5	19.39	19.66	19.54
		3	0	19.52	19.72	19.61
		3	1	19.50	19.68	19.55
		3	3	19.39	19.58	19.45
		6	0	18.62	18.80	18.72

EIRP Power (dBm)

Band	GSM 1900		
Channel	512	661	810
Frequency	1850.2	1880	1909.8
GSM	26.78	26.88	26.88
GPRS 1Tx Slot	26.95	26.97	26.79
GPRS 2Tx Slot	24.83	24.90	24.80
GPRS 3Tx Slot	23.40	23.45	23.31
GPRS 4Tx Slot	22.45	22.57	22.36

*EIRP = Conducted + antenna gain (-2.90dBi)

Band	WCDMA II		
TX Channel	9262	9400	9538
Rx Channel	9662	9800	9938
Frequency	1852.4	1880	1907.6
RMC 12.2K	19.97	20.04	19.96
HSDPA Subtest-1	18.87	19.06	18.97
HSDPA Subtest-2	17.64	17.95	18.10
HSDPA Subtest-3	17.23	17.45	17.57
HSDPA Subtest-4	17.14	17.37	17.58
HSUPA Subtest-1	17.70	17.86	18.15
HSUPA Subtest-2	15.68	15.91	16.16
HSUPA Subtest-3	16.66	16.86	17.08
HSUPA Subtest-4	15.71	15.98	16.07
HSUPA Subtest-5	17.65	17.86	18.07

*EIRP = Conducted + antenna gain (-2.90dBi)

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18700	18900	19100
		Frequency (MHz)		1860	1880	1900
20M	QPSK	1	0	19.68	19.86	19.71
		1	50	19.44	19.67	19.48
		1	99	19.39	19.55	19.47
		50	0	18.47	18.69	18.52
		50	25	18.52	18.62	18.53
		50	50	18.42	18.60	18.50
		100	0	18.62	18.79	18.70
20M	16QAM	1	0	18.64	18.88	18.71
		1	50	18.61	18.75	18.62
		1	99	18.59	18.68	18.56
		50	0	17.64	17.72	17.65
		50	25	17.51	17.73	17.61
		50	50	17.52	17.61	17.51
		100	0	17.50	17.68	17.57
20M	64QAM	1	0	17.52	17.78	17.65
		1	50	17.48	17.72	17.63
		1	99	17.54	17.66	17.51
		50	0	16.56	16.72	16.63
		50	25	16.58	16.74	16.60
		50	50	16.53	16.61	16.58
		100	0	16.69	16.80	16.77

*EIRP = Conducted + antenna gain (-2.90dBi)

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18675	18900	19125
		Frequency (MHz)		1857.5	1880	1902.5
15M	QPSK	1	0	18.71	18.89	18.72
		1	37	18.52	18.71	18.56
		1	74	18.47	18.60	18.45
		36	0	17.61	17.70	17.57
		36	19	17.55	17.73	17.65
		36	39	17.55	17.72	17.57
		75	0	17.71	17.86	17.70
15M	16QAM	1	0	17.66	17.91	17.76
		1	37	17.69	17.76	17.73
		1	74	17.54	17.75	17.70
		36	0	16.60	16.87	16.73
		36	19	16.57	16.69	16.65
		36	39	16.58	16.75	16.59
		75	0	16.59	16.82	16.61
15M	64QAM	1	0	16.63	16.77	16.63
		1	37	16.59	16.71	16.67
		1	74	16.58	16.70	16.63
		36	0	15.62	15.77	15.75
		36	19	15.64	15.77	15.66
		36	39	15.50	15.70	15.59
		75	0	15.71	15.88	15.80

*EIRP = Conducted + antenna gain (-2.90dBi)

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18650	18900	19150
		Frequency (MHz)		1855	1880	1905
10M	QPSK	1	0	18.70	18.85	18.78
		1	24	18.47	18.68	18.58
		1	49	18.39	18.58	18.45
		25	0	17.55	17.70	17.58
		25	12	17.55	17.67	17.61
		25	25	17.57	17.71	17.53
		50	0	17.71	17.83	17.67
10M	16QAM	1	0	17.71	17.86	17.72
		1	24	17.69	17.86	17.71
		1	49	17.63	17.80	17.64
		25	0	16.69	16.86	16.69
		25	12	16.59	16.68	16.65
		25	25	16.50	16.70	16.57
		50	0	16.65	16.79	16.71
10M	64QAM	1	0	16.63	16.83	16.72
		1	24	16.59	16.76	16.59
		1	49	16.53	16.75	16.58
		25	0	15.62	15.79	15.73
		25	12	15.55	15.76	15.71
		25	25	15.57	15.76	15.58
		50	0	15.72	15.86	15.77

*EIRP = Conducted + antenna gain (-2.90dBi)

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18625	18900	19175
		Frequency (MHz)		1852.5	1880	1907.5
5M	QPSK	1	0	18.68	18.84	18.70
		1	12	18.49	18.65	18.55
		1	24	18.40	18.61	18.48
		12	0	17.61	17.68	17.61
		12	6	17.53	17.68	17.63
		12	13	17.51	17.66	17.58
		25	0	17.68	17.86	17.74
5M	16QAM	1	0	17.71	17.84	17.77
		1	12	17.62	17.84	17.75
		1	24	17.59	17.71	17.70
		12	0	16.60	16.79	16.76
		12	6	16.54	16.73	16.57
		12	13	16.50	16.67	16.64
		25	0	16.62	16.77	16.67
5M	64QAM	1	0	16.60	16.75	16.67
		1	12	16.61	16.78	16.60
		1	24	16.55	16.71	16.55
		12	0	15.67	15.82	15.75
		12	6	15.61	15.74	15.63
		12	13	15.51	15.75	15.57
		25	0	15.67	15.88	15.82

*EIRP = Conducted + antenna gain (-2.90dBi)

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18615	18900	19185
		Frequency (MHz)		1851.5	1880	1908.5
3M	QPSK	1	0	18.74	18.89	18.75
		1	7	18.48	18.73	18.56
		1	14	18.40	18.66	18.52
		8	0	17.52	17.78	17.65
		8	3	17.57	17.75	17.59
		8	7	17.55	17.71	17.59
		15	0	17.69	17.84	17.68
3M	16QAM	1	0	17.71	17.91	17.74
		1	7	17.65	17.85	17.73
		1	14	17.63	17.81	17.63
		8	0	16.66	16.80	16.75
		8	3	16.61	16.71	16.67
		8	7	16.54	16.74	16.59
		15	0	16.58	16.78	16.67
3M	64QAM	1	0	16.58	16.78	16.70
		1	7	16.62	16.72	16.67
		1	14	16.59	16.75	16.62
		8	0	15.61	15.78	15.74
		8	3	15.56	15.76	15.71
		8	7	15.55	15.72	15.59
		15	0	15.68	15.86	15.80

*EIRP = Conducted + antenna gain (-2.90dBi)

LTE Band 2						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		18607	18900	19193
		Frequency (MHz)		1850.7	1880	1909.3
1.4M	QPSK	1	0	18.74	18.84	18.75
		1	2	18.54	18.71	18.60
		1	5	18.45	18.60	18.46
		3	0	18.53	18.76	18.59
		3	1	18.59	18.71	18.61
		3	3	18.47	18.69	18.56
		6	0	17.70	17.79	17.77
1.4M	16QAM	1	0	17.67	17.93	17.81
		1	2	17.59	17.81	17.73
		1	5	17.59	17.72	17.62
		3	0	17.69	17.85	17.76
		3	1	17.57	17.69	17.64
		3	3	17.56	17.69	17.64
		6	0	16.58	16.74	16.62
1.4M	64QAM	1	0	16.66	16.77	16.62
		1	2	16.52	16.78	16.68
		1	5	16.49	16.76	16.64
		3	0	16.62	16.82	16.71
		3	1	16.60	16.78	16.65
		3	3	16.49	16.68	16.55
		6	0	15.72	15.90	15.82

*EIRP = Conducted + antenna gain (-2.90dBi)

4.2 Radiated Emission Measurement

4.2.1 Limits of Radiated Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

4.2.2 Test Procedure

- a. In the semi-anechoic chamber, EUT placed on the 0.8m (below or equal 1GHz) and/or 1.5m (above 1GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- c. Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP/ERP level.
- d. Following C63.26 section 5.5 and 5.2.7
 - $\text{EIRP (dBm)} = E (\text{dB}\mu\text{V/m}) + 20\log(D) - 104.8$; where D is the measurement distance (in the far field region) in m.
 - $\text{ERP (dBm)} = E (\text{dB}\mu\text{V/m}) + 20\log(D) - 104.8 - 2.15$; where D is the measurement distance (in the far field region) in m.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.
2. The emission levels were against the limit of frequency range 9 kHz ~ 30 MHz:
The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

4.2.3 Deviation from Test Standard


No deviation.

4.2.4 Test Setup

For radiated emission 30MHz to 1GHz



For radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.5 Test Results


Below 1GHz
GSM

RF Mode	TX PCS 1900	Channel	CH 661 : 1880 MHz
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	94.99	-65.49	-13.00	-52.49	2.00 H	29	48.36	-113.85
2	191.02	-65.88	-13.00	-52.88	1.00 H	162	45.38	-111.26
3	279.29	-68.43	-13.00	-55.43	1.50 H	333	40.28	-108.71
4	419.94	-64.88	-13.00	-51.88	1.50 H	231	40.29	-105.17
5	528.58	-62.49	-13.00	-49.49	1.00 H	179	40.35	-102.84
6	585.81	-60.94	-13.00	-47.94	1.00 H	41	40.58	-101.52

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.




RF Mode	TX PCS 1900	Channel	CH 661 : 1880 MHz
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	37.76	-45.10	-13.00	-32.10	1.00 V	132	64.01	-109.11
2	148.34	-63.41	-13.00	-50.41	1.00 V	171	45.11	-108.52
3	191.02	-70.26	-13.00	-57.26	2.00 V	115	41.00	-111.26
4	517.91	-63.01	-13.00	-50.01	1.00 V	241	40.02	-103.03
5	576.11	-60.40	-13.00	-47.40	1.50 V	82	41.41	-101.81
6	643.04	-60.07	-13.00	-47.07	1.00 V	37	40.35	-100.42

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.




WCDMA

RF Mode	TX WCDMA Band II	Channel	CH 9400 : 1880 MHz
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	95.96	-64.91	-13.00	-51.91	1.00 H	184	48.95	-113.86
2	148.34	-65.21	-13.00	-52.21	2.00 H	143	43.31	-108.52
3	215.27	-63.70	-13.00	-50.70	1.00 H	130	48.49	-112.19
4	425.76	-64.71	-13.00	-51.71	1.50 H	46	40.28	-104.99
5	506.27	-61.81	-13.00	-48.81	2.00 H	250	41.47	-103.28
6	658.56	-59.98	-13.00	-46.98	1.00 H	4	40.31	-100.29

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.




RF Mode	TX WCDMA Band II	Channel	CH 9400 : 1880 MHz
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	36.79	-43.53	-13.00	-30.53	1.00 V	208	65.80	-109.33
2	54.25	-58.53	-13.00	-45.53	1.50 V	114	50.22	-108.75
3	171.62	-68.15	-13.00	-55.15	1.00 V	129	40.96	-109.11
4	277.35	-68.81	-13.00	-55.81	1.00 V	51	39.99	-108.80
5	384.05	-62.13	-13.00	-49.13	2.00 V	338	43.90	-106.03
6	526.64	-62.54	-13.00	-49.54	1.00 V	285	40.32	-102.86

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.




LTE Band 2 (Channel Bandwidth 20MHz)

RF Mode	TX LTE Band II-20MHz	Channel	CH 18900 : 1880 MHz
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	46.49	-64.21	-13.00	-51.21	2.00 H	326	44.31	-108.52
2	94.99	-65.49	-13.00	-52.49	1.00 H	29	48.36	-113.85
3	210.42	-68.33	-13.00	-55.33	1.00 H	2	43.90	-112.23
4	320.03	-67.17	-13.00	-54.17	1.00 H	348	40.47	-107.64
5	760.41	-55.94	-13.00	-42.94	1.50 H	144	42.54	-98.48
6	855.47	-57.44	-13.00	-44.44	1.00 H	75	39.83	-97.27

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.




RF Mode	TX LTE Band II-20MHz	Channel	CH 18900 : 1880 MHz
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	50.37	-55.32	-13.00	-42.32	2.00 V	109	53.19	-108.51
2	74.62	-63.67	-13.00	-50.67	1.00 V	129	48.37	-112.04
3	104.69	-66.97	-13.00	-53.97	1.00 V	310	45.25	-112.22
4	334.58	-65.88	-13.00	-52.88	1.00 V	328	41.28	-107.16
5	424.79	-64.75	-13.00	-51.75	1.00 V	252	40.28	-105.03
6	459.71	-63.66	-13.00	-50.66	1.50 V	105	40.46	-104.12

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.



Above 1GHz

GSM

RF Mode	TX PCS 1900	Channel	CH 661 : 1880 MHz
Frequency Range	1GHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-47.60	-13.00	-34.60	1.00 H	153	49.30	-96.90

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-47.90	-13.00	-34.90	2.57 V	256	49.00	-96.90

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

WCDMA Band 2

RF Mode	TX WCDMA Band II	Channel	CH 9400 : 1880 MHz
Frequency Range	1GHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-52.40	-13.00	-39.40	1.02 H	144	44.38	-96.78
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-53.70	-13.00	-40.70	1.69 V	355	43.08	-96.78

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

LTE Band 2 (Channel Bandwidth 20MHz)

RF Mode	TX LTE Band II-20MHz	Channel	CH 18900 : 1880 MHz
Frequency Range	1GHz ~ 20GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-51.39	-13.00	-38.39	2.60 H	130	45.39	-96.78
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3760.00	-51.14	-13.00	-38.14	1.11 V	139	45.64	-96.78

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).



Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---