

**FCC ID PER PART 15 B**  
**EMI MEASUREMENT AND TEST REPORT**


For

**NMB Technologies Inc.**

9730 Independence Ave.,  
Chatsworth, CA 91311

<b>FCC ID: AQ6-7D30</b>
-------------------------

April 19, 2002

<b>This Report Concerns:</b> <input checked="" type="checkbox"/> Original Report	<b>Equipment Type:</b> Keyboard - Peripheral, ITE
<b>Test Engineer:</b> Jerry Wang	
<b>Report No.:</b> R0204093	
<b>Test Date:</b> April 9, 2002	
<b>Reviewed By:</b> 	
John Y. Chan - Engineering Manager	
<b>Prepared By:</b> Bay Area Compliance Laboratory Corporation 230 Commercial Street Sunnyvale, CA 94085 Tel: (408) 732-9162 Fax: (408) 732-9164	

**Note:** This test report is limited to the above client company and product sample only. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

**TABLE OF CONTENTS**

<b>1 - GENERAL INFORMATION.....</b>	<b>3</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	3
1.2 OBJECTIVE .....	3
1.3 RELATED SUBMITTAL(S)/GRANT(S).....	3
1.4 TEST METHODOLOGY .....	3
1.5 TEST FACILITY .....	3
1.6 TEST EQUIPMENT LIST .....	4
1.7 LOCAL SUPPORT EQUIPMENT LIST AND DETAILS.....	4
1.8 EXTERNAL I/O CABLING LIST AND DETAILS .....	5
<b>2 - SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
2.1 JUSTIFICATION .....	6
2.2 EUT EXERCISE SOFTWARE .....	6
2.3 SPECIAL ACCESSORIES.....	6
2.4 BLOCK DIAGRAM .....	6
2.5 EQUIPMENT MODIFICATIONS .....	6
2.6 CONFIGURATION OF TEST SYSTEM.....	7
2.7 TEST SETUP BLOCK DIAGRAM .....	7
<b>3 - CONDUCTED EMISSIONS TEST DATA.....</b>	<b>8</b>
3.1 MEASUREMENT UNCERTAINTY .....	8
3.2 EUT SETUP.....	8
3.3 SPECTRUM ANALYZER SETUP .....	8
3.4 TEST PROCEDURE .....	9
3.5 SUMMARY OF TEST RESULTS .....	9
3.6 CONDUCTED EMISSIONS TEST DATA .....	9
3.7 PLOT OF CONDUCTED EMISSIONS TEST DATA .....	10
<b>4 - RADIATED EMISSION DATA .....</b>	<b>11</b>
4.1 MEASUREMENT UNCERTAINTY .....	11
4.2 EUT SETUP.....	11
4.3 SPECTRUM ANALYZER SETUP .....	11
4.4 TEST PROCEDURE .....	12
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION .....	12
4.6 SUMMARY OF TEST RESULTS .....	13
4.7 RADIATED EMISSIONS TEST RESULT DATA .....	13

---

## 1 - GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

The *NMB Technologies Inc.* 's product, model name: *RT7D30* or the "EUT" as referred to in this report is a standard plastic keyboard which measures approximately 16.5 "Lx 7.25"Wx 1.25"H.

### 1.2 Objective

This Class B report is prepared on behalf of *NMB Technologies Inc.* in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules and to ICES-003 of the Canadian Interference-Causing Equipment Regulations.

The objective of the manufacturer is to demonstrate compliance with FCC Part 15 Class B limits for conducted and radiated margin and to ICES-003 requirements for Information Technology Equipment.

### 1.3 Related Submittal(s)/Grant(s)

No Related Submittals

### 1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4 –1992, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory, Corp. The radiated testing was performed at an antenna-to-EUT distance of 10 meters.

### 1.5 Test Facility

The Open Area Test site used by Bay Area Compliance Laboratory Corporation to collect radiated and conducted emission measurement data is located in the back parking lot of the building at 230 Commercial Street, Sunnyvale, California, USA.

Test site at Bay Area Compliance Laboratory Corporation has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-1992.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratory Corporation is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (NVLAP). The scope of the accreditation covers the FCC Method - 47 CFR Part 15 - Digital Devices, IEC/CISPR 22: 1998, and AS/NZS 3548: Electromagnetic Interference - Limits and Methods of Measurement of Information Technology Equipment test methods under NVLAP Lab Code 200167-0.

### 1.6 Test Equipment List

Manufacturer	Description	Model	Serial Number	Cal. Due Date
HP	Spectrum Analyzer	8568B	2610A02165	12/6/02
HP	Spectrum Analyzer	8593B	2919A00242	12/20/02
HP	Amplifier	8349B	2644A02662	12/20/02
HP	Quasi-Peak Adapter	85650A	917059	12/6/02
HP	Amplifier	8447E	1937A01046	12/6/02
A.H. System	Horn Antenna	SAS0200/571	261	12/27/02
Com-Power	Log Periodic Antenna	AL-100	16005	11/2/02
Com-Power	Biconical Antenna	AB-100	14012	11/2/02
Solar Electronics	LISN	8012-50-R-24-BNC	968447	12/28/02
Com-Power	LISN	LI-200	12208	12/20/02
Com-Power	LISN	LI-200	12005	12/20/02
BACL	Data Entry Software	DES1	0001	12/20/02

\* Statement of Traceability: Bay Area Compliance Laboratory Corp. certifies that all calibration has been performed using suitable standards traceable to National Institute of Standards and Technology (NIST).

### 1.7 Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number	FCC ID
DELL	PC System	Dimension 4300	US-03F364-03731-196-5123	DOC
Everex	Modem	EV-945	None	E3E5UVEV-945
KDS	Monitor	KD-1731	891265478	EUOKD-1731
Lightech	Mouse	X04-72174	52463-OEM	DOC
HP	Printer	2225C	2821S14783	DS16XU2225

**1.8 External I/O Cabling List and Details**

Cable Description	Length (M)	Port/From	To
Shielded Keyboard Cable	2.1	PS/2 KB Port/Host	EUT
Shielded Mouse Cable	1.8	Mouse Port/Host	Mouse
Shielded Video Cable	1.8	Video Port/Host	Monitor
Shielded Parallel Cable	1.5	Parallel Port/Host	Printer
Shielded Serial Cable	1.2	Serial Port/Host	Modem

---

## 2 - SYSTEM TEST CONFIGURATION

---

### 2.1 Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

The following I/O ports were also provided by the host system: one serial port, one parallel port, two USB ports, one PS/2 keyboard port, one PS/2 mouse port, one floppy interface connector, and two IDE interface connectors.

Since the EUT was tested under native (normal) mode for the final qualification test.

The parallel port (LPT1), serial port and PS/2 mouse port were also tested in the final qualification test along with an *NEWTON* power supply.

### 2.2 EUT Exercise Software

The EUT exercising program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The software, H pattern, contained on the hard drive, is started in a DOS window under the Windows 98 operating system. Once loaded, the program sequentially exercises each system component.

The sequence used is as follows:

1. Lines of Hs scroll across the VGA monitor.
2. The modem(s) receives Hs.
3. The printer output Hs.

The complete cycle takes approximately 5 ~ 10 seconds and the process is continuously repeated.

### 2.3 Special Accessories

As shown in section 2.5, all interface cables used for compliance testing are shielded as normally supplied by INMAC, Y.C. Cable and from their respective support equipment manufacturers. The EUT, modem, printer and VGA monitor featured shielded metal connectors.


### 2.4 Block Diagram

Please refer to Appendix A.


### 2.5 Equipment Modifications

No modification(s) were necessary for the EUT to comply with the applicable standards and limits.

## 2.6 Configuration of Test System



## 2.7 Test Setup Block Diagram



### 3 - CONDUCTED EMISSIONS TEST DATA

---

#### 3.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at BACL is  $\pm 2.4$  dB.

#### 3.2 EUT Setup

The measurement was performed at the **Open Area Test Site**, using the same setup per ANSI C63.4 - 1992 measurement procedure. Specification used was with the EN55022 Class B limits.

The EUT was connected to the host PC. The host PC system was placed on the center back of the test table and connected to 110Vac/60Hz power source. The monitor and the modem were placed on the one side of the host PC in sequence and the printer was on the other side. The rear of the host system and peripherals were placed flushed with the rear of the tabletop.

The EUT keyboard was placed directly in front of the host PC. The mouse was placed next to the EUT.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped over edge of the test table and bundle when necessary.

#### 3.3 Spectrum Analyzer Setup

The spectrum analyzer was set with the following configurations during the conducted emission test:

Start Frequency.....	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10 kHz
Video Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth .....	9 kHz
Quasi-Peak Adapter Mode.....	Normal



### 3.4 Test Procedure

During the conducted emission test, the host PC power cord was connected to the auxiliary outlet of the first LISN with the VGA monitor and all support equipment power cords connected to the second LISN.

Since the EUT has only one operating mode, this mode was tested with the *NEWTON* Power supply to represent worst case results for the final qualification test. Therefore, these results were used for final test data recorded in the table listed under section 3.6 of this report.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance using all installation combination. All data was recorded in the peak detection mode. Quasi-peak readings were only performed when an emission was found to be marginal (within -4 dB $\mu$ V of specified limitation). Quasi-peak readings are distinguished with a "Qp".

### 3.5 Summary of Test Results

According to the data in section 3.6, the EUT complied with the EN55022 Conducted margin for a Class B device, with the *worst* margin reading of:

**-13.0 dB $\mu$ V at 0.21 MHz in the *Line* mode for the *NEWTON* power supply, Model: *NPS-90CB A***


**REV: 01, 0.15 - 30 MHz**

### 3.6 Conducted Emissions Test Data

LINE CONDUCTED EMISSIONS				EN55022 CLASS B	
Frequency MHz	Amplitude dB $\mu$ V	Detector Qp/Ave/Peak	Phase Line/Neutral	Limit dB $\mu$ V	Margin dB
0.21	50.2	QP	Line	63.21	-13.0
0.69	40.6	QP	Line	56	-15.4
0.15	48.4	QP	Neutral	66	-17.6
3.43	34.6	QP	Line	56	-21.4
2.90	33.2	QP	Neutral	56	-22.8
15.67	30.9	QP	Neutral	60	-29.1

### 3.7 Plot of Conducted Emissions Test Data

Plot of Conducted Emissions test data for the *NEWTON* power adapter, model *NPS-90CB A REV: 01* is presented hereinafter as reference.



## 4 - RADIATED EMISSION DATA

---

### 4.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at BACL is  $\pm 4.0$  dB.

### 4.2 EUT Setup

The radiated emission tests were performed in the open area 10-meter test site, using the setup in accordance with the ANSI C63.4 - 1992. The specification used was the EN55022 Class B limits.

The EUT was connected to the host PC. The host PC system was placed on the center back of the test table and connected to 110Vac/60Hz power source. The monitor and the modem were placed on the one side of the host PC in sequence and the printer was on the other side. The rear of the host system and peripherals were placed flushed with the rear of the tabletop.

The EUT keyboard was placed directly in front of the host PC. The mouse, the microphone and the recorder were placed on one side of the keyboard.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped over edge of the test table and bundle when necessary.

### 4.3 Spectrum Analyzer Setup

According to FCC CFR 47, Section 15.31, the system was tested to 1000 MHz.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Start Frequency .....	30 MHz
Stop Frequency .....	1000 MHz
Sweep Speed .....	Auto
IF Bandwidth .....	100 kHz
Video Bandwidth .....	1 MHz
Quasi-Peak Adapter Bandwidth .....	120 kHz
Quasi-Peak Adapter Mode .....	Normal
Resolution Bandwidth .....	1MHz

#### 4.4 Test Procedure

For the radiated emissions test, the host system, VGA monitor and all support equipment power cords were connected to the AC floor outlet.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB $\mu$ V of specified limitation), and are distinguished with a "Qp" in the data table.

Since the EUT has only one operating mode, this mode was tested with a host system to represent the worst case for the final qualification test. Therefore, these results were used for final test data recorded in the table listed under section 4.7 of this report as reference.

The parallel port (LPT1), serial port and PS/2 mouse ports were also tested.

#### 4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB $\mu$ V means the emission is 7dB $\mu$ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Class B Limit}$$

#### 4.6 Summary of Test Results

According to the data in section 4.7, the EUT complied with the EN55022 Class B standards, and had the worst margin of:

**-4.4 dB $\mu$ V at 576 MHz in the Horizontal polarization, 30-1000MHz, 10 meters**

#### 4.7 Radiated Emissions Test Result Data

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	EN55022 CLASS B	
Frequency MHz	Ampl. dB $\mu$ V/m	Angle Degree	Height Meter	Polar H/ V	Antenna dB $\mu$ V/m	Cable dB	Amp. dB	Corr. Ampl. dB $\mu$ V/m	Limit dB $\mu$ V/m	Margin dB
576	31.6	300	2.5	H	17.9	8.1	25.0	32.6	37	-4.4
122	36.2	30	1.2	V	11.1	3.0	25.0	25.3	30	-4.7
286	32.6	250	1.2	V	19.2	5.3	25.0	32.1	37	-4.9
492	33.2	30	2.0	H	16.0	7.4	25.0	31.6	37	-5.4
432	33.8	0	1.2	V	15.8	6.8	25.0	31.4	37	-5.6
160	33.4	270	1.2	V	12.4	3.6	25.0	24.4	30	-5.6
482	32.8	45	2.0	H	16.2	7.3	25.0	31.3	37	-5.7
60	38.5	90	1.2	V	8.9	1.8	25.0	24.2	30	-5.8
384	35.1	0	1.2	V	14.5	6.3	25.0	30.9	37	-6.1
416	34.2	320	1.5	V	15.0	6.6	25.0	30.8	37	-6.2
168	32.0	300	1.2	V	13.0	3.6	25.0	23.6	30	-6.4
528	31.1	45	1.2	V	16.6	7.5	25.0	30.2	37	-6.8
286	30.9	45	2.5	H	19.0	5.3	25.0	30.2	37	-6.8
112	34.9	270	1.2	V	10.4	2.7	25.0	23.0	30	-7.0
160	31.4	180	2.5	H	12.9	3.6	25.0	22.9	30	-7.1
118	32.4	320	1.2	V	10.8	3.0	25.0	21.2	30	-8.8
112	33.2	90	2.0	H	10.3	2.7	25.0	21.2	30	-8.8
140	30.9	300	1.2	V	11.5	3.1	25.0	20.5	30	-9.5