

Model: RS-2O-H1

FCC ID: AQQ-RS-2BSU-2B

IC: 10138A-RS2BSU2B



IP65 rated for use in wet
indoor and outdoor locations

Maximum ambient temperature (85°C)

Open Energy
Management Equipment
3WG4
Elec 12-24VDC 150mW
Class 2

enlighted

www.enlightedinc.com

Model: RS-2O-H2

FCC ID: AQQ-RS-2BSU-2B

IC: 10138A-RS2BSU2B



IP65 rated for use in wet
indoor and outdoor locations

Maximum ambient temperature (85°C)

Open Energy
Management Equipment
3WG4
Elec 12-24VDC 150mW
Class 2

enlighted

www.enlightedinc.com

Model: RS-2O-S1

FCC ID: AQQ-RS-2BSU-2B

IC: 10138A-RS2BSU2B



IP65 rated for use in wet
indoor and outdoor locations

Maximum ambient temperature (85°C)

Open Energy
Management Equipment
3WG4
Elec 12-24VDC 150mW
Class 2

enlighted

www.enlightedinc.com

Model: RS-2O-S2

FCC ID: AQQ-RS-2BSU-2B

IC: 10138A-RS2BSU2B



IP65 rated for use in wet
indoor and outdoor locations

Maximum ambient temperature (85°C)

Open Energy
Management Equipment
3WG4
Elec 12-24VDC 150mW
Class 2

enlighted

www.enlightedinc.com

enlighted

www.enlightedinc.com

model: SU-20-00

FCC ID: AQQ-RS-2BSU-2B

IC: 10138A-RS2BSU2B

enlighted

www.enlightedinc.com

model: SU-20-HB

FCC ID: AQQ-RS-2BSU-2B

IC: 10138A-RS2BSU2B





