

RF Exposure Exhibit

EUT Name: Enlighted, Inc

Model No.: SU-4E

CFR 47 Part 2.1093

Prepared for:

Deepak Kumar
Enlighted, Inc
930 Benecia Avenue
Sunnyvale, CA 94085 USA
Tel: 650-964-1094

Prepared by:

TUV Rheinland of North America, Inc.
1279 Quarry Lane
Pleasanton, CA 94566
Tel: (925) 249-9123
Fax: (925) 249-9124
<http://www.tuv.com/>

Report/Issue Date: April 10, 2016
Project Number: 0000134928
Report Number: 31563521.001

RF Exposure Exhibit	1
1 RF Exposure	3
1.1 Test Methodology	3
1.2 RF Exposure Limit	3
1.2.1 RF Exposure Limit	3
1.2.2 EUT Operating Condition	4
1.2.3 Classification	4
1.2.4 Test Results	4
1.2.5 Sample Calculation	5

1 RF Exposure

1.1 Test Methodology

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this calculation is declared by the manufacturer, and the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

1.2 RF Exposure Limit

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

1.2.1 RF Exposure Limit

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b). RSS- 102 Section 2.5.2 and IEEE C95.3 are also applicable

FCC Limit:

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

RSS 102 Limit:

**Table 2: RF Field Strength Limits for Devices Used by the General Public
 (Uncontrolled Environment)**

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ <i>f</i>	-	6**
1.1-10	87/ <i>f</i> ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ <i>f</i> ^{0.25}	0.1540/ <i>f</i> ^{0.25}	8.944/ <i>f</i> ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 <i>f</i> ^{0.3417}	0.008335 <i>f</i> ^{0.3417}	0.02619 <i>f</i> ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> ^{1.2}
150000-300000	0.158 <i>f</i> ^{0.5}	4.21 x 10 ⁻⁴ <i>f</i> ^{0.5}	6.67 x 10 ⁻⁵ <i>f</i>	616000/ <i>f</i> ^{1.2}
<p>Note: <i>f</i> is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).</p>				

1.2.2 EUT Operating Condition

The software provided by Manufacturer enabled the EUT to transmit data at lowest, middle and highest channel individually.

1.2.3 Classification

The antenna of the product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in user's manual. So, this device is classified as a **Mobile Device**.

1.2.4 Test Results

1.2.4.1 Antenna Gain

The transmitting antenna was integrated. The antenna gain was +0.0 dBi or 1.68 (numeric).

1.2.4.2 Output Power into Antenna & RF Exposure value at distance 20cm:

FCC:		
Controlled Exposures - Limit =	5	mW/cm ²
Uncontrolled Exposures - Limit =	1	mW/cm ²
Pd =	0.0003870	mW/cm ²
Controlled Margin to Limit =	4.9996	mW/cm ²
Uncontrolled Margin to Limit =	0.9996	mW/cm ²

Note: * = Plane-wave equivalent power density

IC:		
Controlled Exposures to Limit =	32.16831618	W/m ²
Uncontrolled Exposures Limit =	5.474221277	W/m ²
Pd =	0.003870	W/m ²
Controlled Margin to Limit =	32.1644	W/m ²
Uncontrolled Margin to Limit =	5.4704	W/m ²

Note: Refer to section 4 of RSS-102 for limits and time averaging for frequencies below 10 MHz and above 150 GHz.

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

1.2.5 Sample Calculation

The Friss transmission formula: $Pd = (Pout * G) / (4 * \pi * R^2)$

Where;

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

$\pi \approx 3.1416$

R = distance between observation point and center of the radiator in cm

Ref. : David K. Cheng, Field and Wave Electromagnetics, Second Edition, Page 640, Eq. (11-133).