

MA-WC54-DS17TR

4.9-5.9 GHz Dual Slant Base Station Antenna, 65°

Preliminary

Specifications

Electrical

Frequency range	4.9-5.9 GHz
GAIN, typ.	4 x 17 dBi
VSWR, max.	1.7 : 1
Polarization	2 x Dual Slant $\pm 45^\circ$
3dB Beam-Width, H-Plane, typ.	65°
3dB Beam-Width, E-Plane, typ.	7°
Side Lobes, typ.	-12 dB
Cross Polarization, min.	-15 dB
Port to Port Isolation, min.	-20 dB
Front to Back Ratio, min.	-25 dB
Input power, max.	20 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

Mechanical

Dimensions (HxWxD)	355 x 310 x 15 mm
Connector	4 x SMA ,Female
Weight	TBD
Mounting	Provision for Telrad Radio
Radome	Provided by Telrad
Back Plane	Aluminum protected through chemical passivation

Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Flammability	UL-94

Mars Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 58861, P.O.Box 5 AZOR 58008, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com