

OSIM INTERNATIONAL Pte. LTD.

SAR COMPLIANCE REPORT

Report Type:

FCC SAR assessment report

Model:

OS-8208 uDream

REPORT NUMBER:

201201053SHA-002

ISSUE DATE:

January 13, 2021

DOCUMENT CONTROL NUMBER:

TTRFFCCSAR-01_V1 © 2018 Intertek





Intertek Testing Services Shanghai Building No.86, 1198 Qinzhou Road (North) Caohejing Development Zone Shanghai 200233, China

Telephone: 86 21 6127 8200

www.intertek.com

Report no.: 201201053SHA-002

Applicant: OSIM INTERNATIONAL Pte. LTD.

65 Ubi Ave 1, OSIM Headquarters, Singapore 408939

Manufacturer: OSIM INTERNATIONAL Pte. LTD.

65 Ubi Ave 1, OSIM Headquarters, Singapore 408939

Factory 1: DT-OSIM Healthcare Appliances (Suzhou) Co., Ltd.

China-Singapore Suzhou Industrial Park,

No. 69 Longpu Road, Xinglong Street, Suzhou, China

Factory 2: Daito Healthcare Appliances (Taicang) Co., Ltd.

20 Fengnan road, Shuangfeng, Taicang, Jiangsu province, China

FCC ID: ARG-OS-8208


SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06 FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

PREPARED BY:	REVIEWED BY:	
Co/M. Sap		
Project Engineer	Reviewer	
Colin Sun	Wakeyou Wang	


This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.





Revision History

Report No.	Version	Description	Issued Date
201201053SHA-002	Rev. 01	Initial issue of report	January 13, 2021






1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Massage Chair
Type/Model:	OS-8208 uDream
	There is one model only.
Description of EUT:	The device contains Bluetooth function (BR+EDR). There is only one model and the worst data were listed in the report.
Rating:	110-120V~60Hz
Category of EUT:	Class B
EUT type:	☐ Table top ☒ Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	December 15, 2020
Date of test:	December 15, 2020– Jan 13, 2021

1.2 Technical Specification

Frequency Range:	2402MHz ~ 2480MHz
Support Standards:	Bluetooth 4.2 (BR+EDR)
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Type of Modulation:	GFSK, π/4 DQPSK, 8DPSK
Channel Number:	79 (0 - 78)
Data Rate:	1Mbps, 2Mbps, 3Mbps
Channel Separation:	1 MHz
Antenna:	Internal PCB antenna, 2dBi Peak gain






1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is	CNAS Accreditation Lab
recognized,	Registration No. CNAS L0139
certified, or accredited by these organizations:	FCC Accredited Lab Designation Number: CN1175
o i game action of	IC Registration Lab Registration code No.: 2042B-1
	VCCI Registration Lab Registration No.: R-4243, G-845, C-4723, T-2252
	NVLAP Accreditation Lab NVLAP LAB CODE: 200849-0
	A2LA Accreditation Lab Certificate Number: 3309.02






2 SAR Assessment

Test result: Pass

2.1 SAR Test Exclusion Limit

100 MHz - 6 GHz and \le 50 mm

MHz	5	10	15	20	25	mm				
150	39	77	116	155	194					
300	27	55	82	110	137					
450	22	45	67	89	112					
835	16	33	49	66	82					
900	16	32	47	63	79					
1500	12	24	37	49	61	SAR Test Exclusion				
1900	11	22	33	44	54	Threshold (mW)				
2450	10	19	29	38	48	CSC.W (M. 17)				
3600	8	16	24	32	40					
5200	7	13	20	26	33					
5400	6	13	19	26	32					
5800	6	12	19	25	31					
MHz	30	35	40	45	50	mm				
150	232	271	310	349	387					
300	164	192	219	246	274					
450	134	157	179	201	224					
835	98	115	131	148	164					
900	95	111	126	142	158	G 4 D 77 /				
1500	73	86	98	110	122	SAR Test Exclusion				
1900	65	76	87	98	109	Threshold (mW)				
2450	57	67	77	86	96	, ,				
3600	47	55	63	71	79					
5200	39	46	53	59	66					
5400	39	45	52	58	65					
5800	37	44	50	56	62					






TEST REPORT

100 MHz - 6 GHz and > 50 mm

MHz	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	mm
100	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567	
150	387	397	407	417	427	437	447	457	467	477	487	497	507	517	527	
300	274	294	314	334	354	374	394	414	434	454	474	494	514	534	554	
450	224	254	284	314	344	374	404	434	464	494	524	554	584	614	644	
835	164	220	275	331	387	442	498	554	609	665	721	776	832	888	943	
900	158	218	278	338	398	458	518	578	638	698	758	818	878	938	998	
1500	122	222	322	422	522	622	722	822	922	1022	1122	1222	1322	1422	1522	mW
1900	109	209	309	409	509	609	709	809	909	1009	1109	1209	1309	1409	1509	
2450	96	196	296	396	496	596	696	796	896	996	1096	1196	1296	1396	1496	
3600	79	179	279	379	479	579	679	779	879	979	1079	1179	1279	1379	1479	
5200	66	166	266	366	466	566	666	766	866	966	1066	1166	1266	1366	1466	
5400	65	165	265	365	465	565	665	765	865	965	1065	1165	1265	1365	1465	
5800	62	162	262	362	462	562	662	762	862	962	1062	1162	1262	1362	1462	

< 100	MHz	and <	200	mm													
MHz	< 50	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	mm
100	237	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567	
50	308	617	625	634	643	651	660	669	677	686	695	703	712	721	729	738	
10	474	948	961	975	988	1001	1015	1028	1041	1055	1068	1081	1095	1108	1121	1135	
1	711	1422	1442	1462	1482	1502	1522	1542	1562	1582	1602	1622	1642	1662	1682	1702	mW
0.1	948	1896	1923	1949	1976	2003	2029	2056	2083	2109	2136	2163	2189	2216	2243	2269	
0.05	1019	2039	2067	2096	2125	2153	2182	2211	2239	2268	2297	2325	2354	2383	2411	2440	
0.01	1185	2370	2403	2437	2470	2503	2537	2570	2603	2637	2670	2703	2737	2770	2803	2837	





TEST REPORT

2.2 Assessment Results

The highest EIRP is 5.49dBm = 3.54mW < 10mW (Test Exclusion Thresholds of 2450MHz
at 5mm). Therefore, the SAR requirement is deemed to be satisfied without test.
