



Note: Serial No.: LTMPJJAL0100001



Code 39

Serial No.: LTMPJJAL0100001

- Unit number (5 digits)
- Week
- Year (G=2006, H=2007, J=2008, K=2009)
- Revision (A= 1st Production release)
- Model
- Panel supplier
- Factory ( TT= Fuqing, TZ = Suzhou, TG=Juarez, TJ=TSCEM, TM=Xiamen)
- Product Type (L=LCD, P=Plasma)

FIRST USED ON:

PART NO:

X40G420-997-11A

REVISION

VERSION A

陈瑾

Sep-10-10

Panel Supplier Table Year Table

Code	Supplier
A	AUO
C	CPT
I	Innolux
L	LGE
M	CMO
P	LG-Philips
S	Samsung
T	Panasonic

- J = 2008
- K = 2009
- L = 2010
- M = 2011
- N = 2012
- P = 2013
- Q = 2014
- R = 2015
- S = 2016
- T = 2017
- U = 2018
- V = 2019
- W = 2020
- X = 2021
- Y = 2022
- Z = 2023

NOTE:

- Printing as the above drawing. 印刷版面见上图。
- Dimension: 80x80mm (Tolerance: +0/-0.5mm), as the above drawing. 尺寸: 80x80mm (公差: +0/-0.5mm), 具体见上图所示。
- Material: PET with glue on the backside (material must be certified by UL laboratory) 材质: PET带不干背胶(材质需经过UL认证)
- Background color: Black, Fonts color: Silver 底色: 黑色; 字体颜色: 银色
- Stickiness strength : Cut label into 25mm width ,one end paste on the plate , with 180° direction pulling the other end of the tape, the pull is stickiness strength. With stickiness strength instrument for testing. 粘力: 将label切成25mm宽, 一端粘贴于钢板上, 以180°方向的力拉胶带另一端, 所得拉力即为粘力。用粘力测试仪进行测试。
- The normal temperature test: The range of temperature on plate is -20~100°C. In 80 ~ 100 ° C to maintain 8 hours , the label should not be warp, delamination, frothy and so on. The range of temperature on plastic and carton is -20 ~ 65°C. In 65°C to maintain 8 hours, the label should not be warp, delamination, frothy and so on. 正常耐温测试: 在钢板上耐温范围为-20~100°C, 在80~100°C保持8小时后不翘角不分层不脱落不起泡等。在塑胶、纸箱上耐温范围为-20~65°C, 在65°C保持8小时后不翘角不分层不脱落不起泡等。
- Temperature and humidity cycle test : Cycle conditions(stick on texture(PET), stick on texture/carton(art paper): In temperature of -20~60°C and humidity of 30~90% to maintain 96 hours , the label should not be warp, delamination, frothy and so on. 耐温湿度循环测试: 循环条件(贴在塑胶咬花面(PET)贴在塑胶咬花面/纸箱(铜板纸)): 温度-20~60°C, 湿度30~90%, 时间96小时后不翘角不分层不脱落不起泡等。
- Printing ink can not have overflow and printing color can not be uneven etc. 印刷不可有溢墨及颜色不均等不良现象
- The content of the red frame printed by the factory barcode group and the specific content provided by SS. 红色框内内容由于厂内打印, 具体内容业务提供。
- Packing style: coil and there should be a toothed hole between the link of two pieces 包装方式: 卷状, 连接处打齿孔。

wireless FCC ID no.

TPV reserve code	Platform	vendor code	wireless
1 2 3 4 5 6 7 8 9 10 11 12 13 14			
A R S - B 4 3 1 9 - L - W L			
A R S - B 4 3 1 9 - A - W L			

Bluetooth FCC ID

TPV reserve code	vendor code	Bluetooth code
1 2 3 4 5 6 7 8 9 10 11 12		
A R S - 9 2 P 2 - F B T		

CHECKED BY

冠捷显示科技(厦门)有限公司  
TPV Display Technology (Xiamen) Co.,Ltd  
地址(Add):中国福建厦门翔安区翔海路1号  
Xianghai No.1,Xiang'an District,Xiamen  
City,Fujian Province,PRC  
电话(Tel): +86-592-3686666  
邮编(Postcode):361101