



# RF EXPOSURE REPORT

**REPORT NO.:** SA990812D09

**MODEL NO.:** M421VT\*\*\*\*\*

**FCC ID:** ARS-92P2-FBT

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT :** TOP VICTORY ELECTRONICS (TAIWAN) CO., LTD.

**ADDRESS :** 10F.,No.230,Liancheng Rd.,Zhonghe City, Taipei  
County 23553,Taiwan (R.O.C.)

**ISSUED BY :** Bureau Veritas Consumer Products Services (H.K.)  
Ltd., Taoyuan Branch

**LAB ADDRESS :** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,  
Taipei Hsien, 244 Taiwan

## Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

	Pout (dBm)	Pout (mW)
Conducted Power	0.1	1.0
EIRP Power	-0.7	0.9

**\*Note:** The antenna is PCB antenna with -0.76dBi gain

Threshold for no SAR evaluation is 24.58mW  
 Transmitter power is 1.0mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

---END---