

Top Victory Electronics (Taiwan) Co. Ltd.

TEST REPORT

Model:

SAT1001R-02, SAT1001****

REPORT NUMBER

221100115THC-001

ISSUE DATE

Dec. 20, 2022

PAGES

21

DOCUMENT CONTROL NUMBER

GFT-OP-10h (28-Nov-2018)

© 2020 Intertek



Radio Spectrum TEST REPORT

Applicant:	Top Victory Electronics (Taiwan) Co. Ltd. 9F., No. 230, Liancheng Rd., Zhonghe Dist., New Taipei City 23553, Taiwan
Product:	Home Monitoring Platform
Model No.:	SAT1001R-02, SAT1001****
FCC ID:	ARS-SAT1001
Test Method/ Standard:	47 CFR FCC Part 15.249 & ANSI C63.10 2013
Test By:	Intertek Testing Services Taiwan Ltd., Hsinchu Laboratory No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li, Shiang-Shan District, Hsinchu City, Taiwan



Mark Chang

Mark Chang
Engineer

Rico Deng

Rico Deng
Reviewer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Report No.	Issue Date	Revision Summary
221100115THC-001	Dec. 20, 2022	Original report

Table of Contents

Summary of Tests	4
1. General Information	5
1.1 Identification of the EUT	5
1.2 Additional information about the EUT	5
1.3 Antenna description	5
1.4 Peripherals equipment	5
2. Test specifications.....	6
2.1 Test standard	6
2.2 Operation mode	6
3. 20dB Bandwidth test	7
3.1 Operating environment	7
3.2 Test setup & procedure	7
3.3 Measured data of modulated bandwidth test results	7
4. Radiated emission test FCC 15.249 (C).....	9
4.1 Operating environment	9
4.2 Test setup & procedure	9
4.3 Emission limit	11
4.3.1 Fundamental and harmonics emission limits	11
4.3.2 General radiated emission limits.....	12
4.4 Radiated spurious emission test data	13
4.4.1 Measurement results: frequency range from 9 kHz to 30 MHz.....	13
4.4.2 Measurement results: frequencies equal to or less than 1 GHz.....	14
4.4.3 Measurement results: frequency above 1GHz.....	15
4.4.4 Measurement results: Fundamental.....	15
5. Conducted emission test FCC 15.207	16
5.1 Operating environment	16
5.2 Test setup & procedure	16
5.3 Emission limit	16
5.4 Conducted emission data FCC 15.207	17
Appendix A: Test equipment list.....	19
Appendix B: Measurement Uncertainty.....	21

Summary of Tests

Test	Reference	Results
20dB Bandwidth	15.215(c)	Pass
Radiated Emission test	15.249(c), 15.209	Pass
Emission on the Band Edge	15.249(d)	Pass
Conducted Emission of AC Power	15.207	Pass
Antenna Requirement	15.203	Pass

Note: Please note that the test results with statement of conformity, the decision rules which are based on: Safety Testing: the specification, standard or IEC Guide 115.

Other Testing: the specification, standard and not taking into account the measurement uncertainty.

1. General Information

1.1 Identification of the EUT

Product:	Home Monitoring Platform
Model No.:	SAT1001R-02
Operating Frequency:	915 MHz
Channel Number:	1 channel
Rated Power:	100-240Vac, 50/60Hz
Power Cord:	N/A
Sample receiving date:	2022/11/07
Sample condition:	Workable
Test Date(s):	2022/11/28~ 2022/12/07

1.2 Additional information about the EUT

The customer confirmed SAT1001**** is a series model to SAT1001R-02 (EUT), the different model numbers are served as marketing strategy.

Explanation of model designation SAT1001****:

The customer confirmed the "*" can be any alphanumeric character including blank, for marketing differences.

1.3 Antenna description

Antenna Type: Chip Antenna

Connector Type: Fixed

1.4 Peripherals equipment

Peripherals	Brand	Model No.	Serial No.	Data cable
Notebook PC	HP	HP Probook 440 G3	5CD8021S99	USB shielded cable 1.5m
Fixture	N/A	N/A	N/A	Type-B USB 1.5m

2. Test specifications

2.1 Test standard


The EUT was performed according to the procedures in FCC Part 15 Subpart C Paragraph 15.249 for non-spread spectrum devices.

The test of radiated measurements according to FCC Part15 Section 15.33(a) had been conducted and the field strength of this frequency band were all meet limit requirement, thus we evaluate the EUT pass the specified test.


2.2 Operation mode

TX mode: EUT use 「SmartRF Studio 7 v2.27.0」 entering test mode to transmit.


The signal is maximized through rotation and placement in the three orthogonal axes.



X axis



Y axis



Z axis

After verifying three axes, we found the maximum electromagnetic field was occurred at Y axis. The final test data was executed under this configuration.

Mode	Frequency (MHz)	Signal on time(ms)	Signal on & off time(ms)	Duty cycle	Duty Cycle factor
GFSK	915	100	100	1.000	0.000

TEST REPORT**3. 20dB Bandwidth test****3.1 Operating environment**

Temperature:	20	°C
Relative Humidity:	65	%
Test date:	2022/12/07	

3.2 Test setup & procedure

Step 1: The 20dB bandwidth was measured using a 50 ohm spectrum analyzer

Step 2: The span range for the SA display shall be between two times and five times the OBW.

Step 3: The nominal IF filter bandwidth (3 dB RBW) should be approximately 1 % to 5 % of the OBW, unless otherwise specified, depending on the applicable requirement.


Step 4: The test was performed at 1 channel. The maximum 20dB modulation bandwidth is in the following Table.

3.3 Measured data of modulated bandwidth test results

Mode	Frequency (MHz)	20dB Occupied Bandwidth (MHz)
GFSK	915	0.1013

Please see the plot below.

20dB Bandwidth @ 915MHz




4. Radiated emission test FCC 15.249 (C)

4.1 Operating environment


Temperature:	20-26	°C
Relative Humidity:	56-60	%
Atmospheric Pressure:	2022/11/28 ~ 2022/12/05	

4.2 Test setup & procedure


Radiated emission from 9kHz to 30MHz uses Loop Antenna:



Radiated emission below 1GHz using Bilog Antenna



Radiated emission above 1GHz using Horn Antenna



TEST REPORT

Radiated emissions were investigated cover the frequency range from 30MHz to 1000MHz using a receiver RBW of 120kHz record QP reading, and the frequency over 1GHz using a spectrum analyzer RBW of 1MHz and 10Hz VBW record Average reading. (15.209 paragraph), the Peak reading (1 MHz RBW/ 3 MHz VBW) recorded also on the report.

The EUT for testing is arranged on a turntable. If some peripherals apply to the EUT, the peripherals will be connected to EUT and the whole system. During the test, all cables were arranged to produce worst-case emissions. The signal is maximized through rotation. The height of antenna and polarization is changing constantly for exploring for maximum signal level. The height of antenna can be up to 4 meters and down to 1 meter.

The measurement for radiated emission will be done at the distance of three meters unless the signal level is too low to measure at that distance. In the case of the reading under noise floor, a pre-amplifier is used and/or the test is conducted at a closer distance. And then all readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance.

4.3 Emission limit

4.3.1 Fundamental and harmonics emission limits

Frequency (MHz)	Field Strength of Fundamental		Field Strength of Harmonics	
	(mV/m@3m)	(dBuV/m@3m)	(uV/m@3m)	(dBuV/m@3m)
902-928	50	94	500	54

TEST REPORT**4.3.2 General radiated emission limits**

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

Frequency MHz	15.209 Limits (dBμV/m@3m)
30-88	40
88-216	43.5
216-960	46
Above 960	54

Remark:

1. In the above table, the tighter limit applies at the band edges.
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system

TEST REPORT

4.4 Radiated spurious emission test data

4.4.1 Measurement results: frequency range from 9 kHz to 30 MHz

Antenna Polarity	Frequency (MHz)	Detector	Correction Factor (dB/m)	Reading (dBµV)	Corrected Reading (dBµV/m)	Limit @ 3 m (dBµV/m)	Margin (dB)
Perpendicular	0.489	AV	18.79	41.18	59.97	93.82	-33.85
Perpendicular	0.969	QP	19.08	33.73	52.81	67.88	-15.07
Perpendicular	1.479	QP	19.10	29.28	48.38	64.20	-15.82
Perpendicular	1.958	QP	19.10	24.57	43.67	69.54	-25.87
Perpendicular	2.468	QP	19.10	21.84	40.94	69.54	-28.60
Perpendicular	3.368	QP	19.18	16.86	36.04	69.54	-33.50

Remark: Corr. Factor = Antenna Factor + Cable Loss

Antenna Polarity	Frequency (MHz)	Detector	Correction Factor (dB/m)	Reading (dBµV)	Corrected Reading (dBµV/m)	Limit @ 3 m (dBµV/m)	Margin (dB)
Parallel	0.489	AV	18.79	36.76	55.55	93.82	-38.27
Parallel	0.969	QP	19.08	29.54	48.62	67.88	-19.26
Parallel	1.179	QP	19.10	26.16	45.26	66.17	-20.91
Parallel	1.479	QP	19.10	25.19	44.29	64.20	-19.91
Parallel	1.958	QP	19.10	21.65	40.75	69.54	-28.79
Parallel	2.468	QP	19.10	19.41	38.51	69.54	-31.03

Remark: Corr. Factor = Antenna Factor + Cable Loss

Antenna Polarity	Frequency (MHz)	Detector	Correction Factor (dB/m)	Reading (dBµV)	Corrected Reading (dBµV/m)	Limit @ 3 m (dBµV/m)	Margin (dB)
Ground-parallel	0.489	AV	18.79	30.49	49.28	93.82	-44.54
Ground-parallel	0.999	QP	19.10	23.65	42.75	67.61	-24.86
Ground-parallel	1.479	QP	19.10	19.44	38.54	64.20	-25.66
Ground-parallel	1.988	QP	19.10	17.73	36.83	69.54	-32.71
Ground-parallel	4.238	QP	19.40	12.71	32.11	69.54	-37.43
Ground-parallel	6.187	QP	19.93	12.71	32.64	69.54	-36.90

Remark: Corr. Factor = Antenna Factor + Cable Loss

TEST REPORT

4.4.2 Measurement results: frequencies equal to or less than 1 GHz

Antenna Polarity (H/V)	Frequency (MHz)	Spectrum Analyzer Detector	Correction Factor (dB/m)	Reading (dBμV)	Corrected Reading (dBμV/m)	Limit @ 3 m (dBμV/m)	Margin (dB)
Horizontal	80.44	QP	13.57	21.22	34.79	40.00	-5.21
Horizontal	191.02	QP	17.37	11.39	28.76	43.50	-14.74
Horizontal	334.58	QP	23.04	7.76	30.80	46.00	-15.20
Horizontal	498.51	QP	26.25	5.60	31.85	46.00	-14.15
Horizontal	731.31	QP	29.45	2.06	31.51	46.00	-14.49
Horizontal	819.58	QP	31.20	4.25	35.45	46.00	-10.55

Remark: Corr. Factor = Antenna Factor + Cable Loss

Antenna Polarity (H/V)	Frequency (MHz)	Spectrum Analyzer Detector	Correction Factor (dB/m)	Reading (dBμV)	Corrected Reading (dBμV/m)	Limit @ 3 m (dBμV/m)	Margin (dB)
Vertical	56.19	QP	18.41	17.23	35.64	40.00	-4.36
Vertical	80.44	QP	13.57	24.65	38.22	40.00	-1.78
Vertical	130.88	QP	22.95	5.50	28.45	43.50	-15.05
Vertical	166.77	QP	18.89	8.52	27.41	43.50	-16.09
Vertical	372.41	QP	23.91	4.75	28.66	46.00	-17.34
Vertical	644.01	QP	29.56	2.05	31.61	46.00	-14.39

Remark: Corr. Factor = Antenna Factor + Cable Loss

TEST REPORT

4.4.3 Measurement results: frequency above 1GHz

Mode	Frequency (MHz)	Spectrum Analyzer Detector	Ant. Pol. (H/V)	Correction Factor (dB/m)	Reading (dBμV)	Corrected Reading (dBμV/m)	Limit @ 3 m (dBμV/m)	Margin (dB)
GFSK	2134	PK	H	-17.97	59.70	41.73	74	-32.27
	2745	PK	H	-15.64	58.89	43.25	74	-30.75
	3313	PK	H	-14.79	60.23	45.44	74	-28.56
	3988	PK	H	-11.38	53.96	42.58	74	-31.42
	2071	PK	V	-18.86	68.50	49.64	74	-24.36
	2745	PK	V	-15.64	61.00	45.36	74	-28.64
	3997	PK	V	-11.31	59.80	48.49	74	-25.51
	4258	PK	V	-10.43	66.99	56.56	74	-17.44
	4258	AV	V	-10.43	52.99	42.56	54	-11.44
	5500	PK	V	-5.84	53.72	47.88	74	-26.12

Remark: Correction Factor = Antenna Factor + Cable Loss + High Pass Filter Loss - Pre_Amplifier Gain

4.4.4 Measurement results: Fundamental

Mode	Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polarity (H/V)	Correction Factor (dB/m)	Reading (dBμV)	Corrected Reading (dBμV/m)	Limit @ 3 m (dBμV/m)	Margin (dB)
GFSK	915	PK	H	32.80	60.49	93.29	114.00	-20.71
	915	PK	V	32.80	57.18	89.98	114.00	-24.02


Remark: Correction Factor = Antenna Factor + Cable Loss

5. Conducted emission test FCC 15.207

5.1 Operating environment

Temperature:	23	°C
Relative Humidity:	55	%
Atmospheric Pressure:	1006	hPa

5.2 Test setup & procedure



The EUT are connected to the main power through a line impedance stabilization network (LISN). This provides a 50 ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination.

Both sides (Line and Neutral) of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4/2003 on conducted measurement.

The bandwidth of the field strength meter (R & S Test Receiver ESCI 30) is set at 9kHz.


5.3 Emission limit

Freq. (MHz)	Conducted Limit (dBuV)	
	Q.P.	Ave.
0.15~0.50	66 – 56*	56 – 46*
0.50~5.00	56	46
5.00~30.0	60	50

*Decreases with the logarithm of the frequency.

TEST REPORT

5.4 Conducted emission data FCC 15.207




Test voltage :AC 120V/60Hz
 Temp. / R.H. :23°C / 55%RH
 Atmospheric pressure :1006hPa

Phase	Frequency (MHz)	Corr. Factor (dB)	Reading QP (dBuV)	Level QP (dBuV)	Limit QP (dBuV)	Reading AV (dBuV)	Level AV (dBuV)	Limit AV (dBuV)	Margin (dB)	
									QP	AV
LINE	0.182	9.65	17.95	27.60	64.42	6.54	16.19	54.42	-36.82	-38.23
LINE	0.373	9.66	15.20	24.85	58.43	7.65	17.30	48.43	-33.58	-31.13
LINE	0.464	9.66	27.60	37.26	56.63	18.96	28.62	46.63	-19.37	-18.01
LINE	0.928	9.69	22.04	31.73	56.00	12.31	22.00	46.00	-24.27	-24.00
LINE	1.197	9.69	19.23	28.92	56.00	12.35	22.05	46.00	-27.08	-23.95
LINE	18.920	9.83	21.41	31.25	60.00	10.65	20.48	50.00	-28.75	-29.52

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Level (dBuV) = Corr. Factor (dB) + Reading (dBuV)
3. Margin (dB) = Level (dBuV) – Limit (dBuV)

TEST REPORT



Test voltage : AC 120V/60Hz
 Temp. / R.H. : 23°C / 55%RH
 Atmospheric pressure : 1006hPa

Phase	Frequency (MHz)	Corr. Factor (dB)	Reading QP (dBuV)	Level QP (dBuV)	Limit QP (dBuV)	Reading AV (dBuV)	Level AV (dBuV)	Limit AV (dBuV)	Margin (dB)	
									QP	AV
NEUTRAL	0.172	9.66	20.08	29.75	64.86	5.03	14.70	54.86	-35.11	-40.16
NEUTRAL	0.262	9.66	12.44	22.11	61.38	2.28	11.94	51.38	-39.27	-39.44
NEUTRAL	0.464	9.67	20.88	30.55	56.63	15.44	25.11	46.63	-26.08	-21.52
NEUTRAL	0.853	9.70	14.45	24.15	56.00	8.37	18.07	46.00	-31.85	-27.93
NEUTRAL	1.210	9.71	12.43	22.14	56.00	5.39	15.10	46.00	-33.86	-30.90
NEUTRAL	20.486	9.93	19.21	29.13	60.00	11.17	21.10	50.00	-30.87	-28.90

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Level (dBuV) = Corr. Factor (dB) + Reading (dBuV)
3. Margin (dB) = Level (dBuV) – Limit (dBuV)

Appendix A: Test equipment list

Test Equipment/ Test site	Brand	Model No.	Serial No.	Calibration Date	Next Calibration Date
EMI Test Receiver	Rohde & Schwarz	ESR7	101822	2022/08/09	2023/08/08
Signal Analyzer	Agilent	N9030A	MY51380492	2022/08/09	2023/08/08
Active Loop Antenna	SCHWARZBECK MESS-ELEKTRONIC	FMZB1519	1519-067	2022/04/13	2023/04/12
Bilog Hybrid Antenna	ETC	MCTD 2786B	BLB17J04019 & JB-5-019	2022/10/04	2023/10/03
Horn Antenna	SHWARZBECK	BBHA 9120 D	9120D-456	2022/01/21	2023/01/20
Broadband Amplifier	SGH	SGH118(45dB)	20220105-1	2022/01/07	2023/01/06
Power Meter	Anritsu	ML2495A	0844001	2022/07/04	2023/07/03
Power Sensor	Anritsu	MA2491A	031543	2022/03/07	2023/03/06
966-2(A) Cable	SUHNER	SMA / EX 100	N/A	2022/03/04	2023/03/03
966-2(B) Cable	SUHNER	SUCOFLEX 104P	CB0005	2022/03/04	2023/03/03
966-2 Cable	SUHNER	SUCOFLEX 104P	9403/4P	2022/11/25	2023/11/24
966-2_3m Semi-Anechoic Chamber	966_2	CEM-966_2	N/A	2022/01/14	2023/01/13
20dB Attenuator	Mini-Circuits	BW-S20W5+	N/A	2022/05/25	2023/05/24
Test software	Audix	e3	V9	NCR	NCR

Note: No Calibration Required (NCR).

TEST REPORT

Test Equipment	Brand	Model No.	Serial No.	Calibration Date	Next Calibration Date
EMI Test Receiver	R&S	ESCI	100018	2022/11/07	2023/11/06
LISN	R&S	ENV216	101160	2022/07/13	2023/07/12
CON-2 Cable	SUHNER	EMCCFD300-B M-NM-6000	170502	2022/04/29	2023/04/28
Test software	Audix	e3	V4.20040112L	NCR	NCR

Note: No Calibration Required (NCR).

Appendix B: Measurement Uncertainty

This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level using a coverage factor of $k=2$.

Item	Uncertainty
Vertically polarized radiated disturbances from 30MHz~1GHz in a semi-anechoic chamber at a distance of 3m	5.16 dB
Horizontally polarized radiated disturbances from 30MHz~1GHz in a semi-anechoic chamber at a distance of 3m	5.02 dB
Radiated disturbances from 1GHz~18GHz in a semi-anechoic chamber at a distance of 3m	5.17 dB
Vertically polarized Radiated disturbances from 18GHz~26.5GHz in a semi-anechoic chamber at a distance of 1m	2.39 dB
Horizontally polarized Radiated disturbances from 18GHz~26.5GHz in a semi-anechoic chamber at a distance of 1m	2.39 dB
Radiated disturbances from 9kHz~30MHz in a semi-anechoic chamber at a distance of 3m	3.70 dB
Emission on the Band Edge Test	4.32 dB
Occupied Bandwidth	7.78 %
AC Power Line Conducted Emission	3.08 dB