

FCC Test Report

Report No.: RF180613D06

FCC ID: ARS-WPCWATXMPA5

Model No: MX38VC

Series Model: MX38V****(The "*" can be any alphanumeric character including blank, for marketing differences)

Received Date: Jun. 13, 2018

Test Date: Jun. 26 ~ 28, 2018

Issued Date: Jul. 13, 2018

Applicant: TOP VICTORY ELECTRONICS (TAIWAN) CO., LTD.

Address: 10F., No 230, Liancheng Rd., Zhonghe Dist., New Taipei City 23553, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**FCC Registration /
Designation Number:** 198487 / TW2021



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	5
2.2 Modification Record	5
3 General Information	6
3.1 General Description of EUT	6
3.2 Description of Test Modes	7
3.2.1 Test Mode Applicability and Tested Channel Detail	8
3.3 Description of Support Units	9
3.3.1 Configuration of System under Test	9
3.4 General Description of Applied Standards	10
4 Test Types and Results	11
4.1 Radiated Emission and Bandedge Measurement.....	11
4.1.1 Limits of Radiated Emission and Bandedge Measurement	11
4.1.2 Test Instruments	12
4.1.3 Test Procedures.....	13
4.1.4 Deviation from Test Standard	13
4.1.5 Test Set Up	14
4.1.6 EUT Operating Conditions.....	14
4.1.7 Test Results	15
4.2 Conducted Emission Measurement	19
4.2.1 Limits of Conducted Emission Measurement	19
4.2.2 Test Instruments	19
4.2.3 Test Procedures.....	20
4.2.4 Deviation from Test Standard	20
4.2.5 Test Setup.....	20
4.2.6 EUT Operating Conditions.....	20
4.2.7 Test Results	21
4.3 Channel Bandwidth	25
4.3.1 Test Setup.....	25
4.3.2 Test Instruments	25
4.3.3 Test Procedure	25
4.3.4 Deviation from Test Standard	25
4.3.5 EUT Operating Condition	25
4.3.6 Test Results	26
5 Pictures of Test Arrangements	28
Appendix – Information on the Testing Laboratories	29

Release Control Record

Issue No.	Description	Date Issued
RF180613D06	Original release.	Jul. 13, 2018

1 Certificate of Conformity

Product: LCD MONITOR (with Wireless Qi Charger 15W)

Brand: ASUS

Model No: MX38VC

Series Model: MX38V**** (The “*” can be any alphanumeric character including blank, for marketing differences)

Sample Status: Engineering sample

Applicant: TOP VICTORY ELECTRONICS (TAIWAN) CO., LTD.

Test Date: Jun. 26 ~ 28, 2018

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.209)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :



, Date: Jul. 13, 2018

Jessica Cheng / Senior Specialist

Approved by :



, Date: Jul. 13, 2018

Rex Lai / Associate Technical Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.209)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -6.50dB at 0.15000MHz.
15.209	Radiated Emission Test	PASS	Meet the requirement of limit. Minimum passing margin is -7.30dB at 720.88MHz.
15.215	Channel Bandwidth Measurement		

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (\pm)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.79 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	2.38 dB
	30MHz ~ 1000MHz	5.54 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	LCD MONITOR (with Wireless Qi Charger 15W)
Brand	ASUS
Model No	MX38VC
Series Model	MX38V**** (The "*" can be any alphanumeric character including blank, for marketing differences)
Model Difference	For marketing purpose
Status of EUT	Engineering sample
Nominal Voltage	19.5Vdc from Adapter For Monitor 5Vdc from Monitor For Wireless Qi Charger
Modulation Type	Load Modulation
Operating Frequency	127-128kHz
Tested Frequency	127kHz, 128kHz
Antenna Type	Loop antenna
Antenna Connector	N/A
Accessory Device	Adapter
Data Cable Supplied	N/A
Maximum power output from the charging coil	Less than 15W

Note:

1. The EUT is a LCD MONITOR with Wireless Qi Charger.
2. The LCD MONITOR contains module as the following:

➤ BT V4.0 LE Dual Mode Bluetooth Stereo Audio Module			
Brand	Model No.	FCC ID	IC ID
Liteon	WB117C	PPQ-WB117C	4491A-WB117C

3. The EUT uses following adapter.

Brand	DELTA
Model	ADP-230EB T
Input Power	100-240V, 3.2A, 50-60Hz
Output Power	19.5V, 11.8A
Power Cord	Non-shielded AC 3-Pin cable (1.8m) Non-shielded DC cable with two ferrite cores (1.8m)

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

2 channels are provided to this EUT:

Channel	Frequency (kHz)
1	127
2	128

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO		DESCRIPTION
	RE<1G	PLC	
A	√	√	Charging Mode With Load
B	√	√	Standby Mode

Where **RE<1G**: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

Radiated Emission Test (Below 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL
A	1
B	2

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL
A	1
B	2

Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CHANNEL
A	1
B	2

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
PLC	26deg. C, 73% RH	120Vac, 60Hz	Ian Chang
RE<1G	25deg. C, 77% RH	120Vac, 60Hz	James Wei
APCM	25deg. C, 77% RH	120Vac, 60Hz	Saxon Lee

3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Load	N/A	N/A	N/A	N/A	Supplied by client


Note: All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC cable	1	1.8	N	2	Supplied by client
2.	AC Power Cord	1	1.8	N	0	Supplied by client


Note: The core(s) is(are) originally attached to the cable(s).

3.3.1 Configuration of System under Test

Mode A:



Mode B:



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.209)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

FOR FREQUENCY BELOW 30MHz

FREQUENCY (MHz)	FIELD STRENGTH (dBuV/m)		MEASUREMENT DISTANCE (meters)
	uV/m	dBuV/m	
0.009 – 0.490	2400 / F (kHz)	48.52-13.80	300
0.490 – 1.705	24000 / F (kHz)	33.80-22.97	30
1.705 – 30.0	30	29.54	30

FOR FREQUENCY BETWEEN 30-1000MHz

FREQUENCY (MHz)	Class A (at 10m)		Class B (at 3m)	
	uV/m	dBuV/m	uV/m	dBuV/m
30-88	90	39.1	100	40.0
88-216	150	43.5	150	43.5
216-960	210	46.4	200	46.0
Above 960	300	49.5	500	54.0

4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
HP Preamplifier	8447D	2432A03504	Feb. 21, 2018	Feb. 20, 2019
HP Preamplifier	8449B	3008A01201	Feb. 22, 2018	Feb. 21, 2019
MITEQ Preamplifier	AMF-6F-260400-33-8P	892164	Feb. 21, 2018	Feb. 20, 2019
Agilent TEST RECEIVER	N9038A	MY51210129	Feb. 6, 2018	Feb. 5, 2019
Schwarzbeck Antenna	VULB 9168	139	Nov. 29, 2017	Nov. 28, 2018
Schwarzbeck Antenna	VHBA 9123	480	May 19, 2017	May 18, 2019
Schwarzbeck Horn Antenna	BBHA-9170	212	Dec. 1, 2017	Nov. 30, 2018
Schwarzbeck Horn Antenna	BBHA 9120-D1	D130	Dec. 1, 2017	Nov. 30, 2018
ADT. Turn Table	TT100	0306	NA	NA
ADT. Tower	AT100	0306	NA	NA
Software	Radiated_V7.6.15.9.5	NA	NA	NA
SUHNER RF cable With 4dB PAD	SF104	CABLE-CH6	Aug. 14, 2017	Aug. 13, 2018
SUHNER RF cable With 3dB PAD	SF102	Cable-CH8-3.6m	Aug. 14, 2017	Aug. 13, 2018
KEYSIGHT Spectrum Analyzer	N9030A	MY54490260	Jul. 26, 2017	Jul. 25, 2018
Loop Antenna EMCI	LPA600	270	Aug. 11, 2017	Aug. 10, 2019
EMCO Horn Antenna	3115	00028257	Nov. 30, 2017	Nov. 29, 2018
Highpass filter Wainwright Instruments	WHK 3.1/18G-10SS	SN 8	NA	NA
ROHDE & SCHWARZ Spectrum Analyzer	FSV40	101042	Sep. 29, 2017	Sep. 28, 2018
Anritsu Power Sensor	MA2411B	0738404	Apr. 26, 2018	Apr. 25, 2019
Anritsu Power Meter	ML2495A	0842014	Apr. 26, 2018	Apr. 25, 2019

- NOTE:**
1. The calibration interval of the above test instruments is 12/24 months. And the calibrations are traceable to NML/ROC and NIST/USA.
 2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 3. The test was performed in Chamber No. 6.
 4. The Industry Canada Reference No. IC 7450E-6.

4.1.3 Test Procedures

For Frequency range 9kHz~30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Frequency range 30 ~ 1000MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Set Up

For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

Test Mode A:

- Connected the Adapter to EUT.
- Turned on the power of all equipment.
- The load which supplied by the client is meant to simulate the charging condition.
- EUT charged to Load continuously.

Test Mode B:

Connected the Adapter to EUT.

4.1.7 Test Results

Below 30MHz Data:

Test Frequency	127kHz	Detector Function	Quasi-Peak
Frequency Range	9 kHz ~ 30 MHz		
Test Mode	A		

Antenna Polarity & Test Distance: Loop Antenna Open At 3m

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*0.127	84.69 QP	105.53	-20.84	1.00	8	69.78	14.91
2	0.254	49.69 QP	99.51	-49.82	1.00	332	40.73	8.96
3	0.381	53.86 QP	95.99	-42.13	1.00	25	48.07	5.79
4	0.508	37.66 QP	73.49	-35.83	1.00	320	33.66	4.00
5	1.659	30.06 QP	63.21	-33.15	1.00	117	31.52	-1.46
6	8.317	26.66 QP	69.54	-42.88	1.00	23	30.45	-3.79

Antenna Polarity & Test Distance: Loop Antenna Close At 3m

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*0.127	74.82 QP	105.53	-30.71	1.00	88	59.91	14.91
2	0.254	50.29 QP	99.51	-49.22	1.00	312	41.33	8.96
3	0.381	49.24 QP	95.99	-46.75	1.00	182	43.45	5.79
4	0.508	41.04 QP	73.49	-32.45	1.00	164	37.04	4.00
5	1.688	30.72 QP	63.06	-32.34	1.00	115	32.23	-1.51
6	5.947	33.01 QP	69.54	-36.53	1.00	128	36.65	-3.64

Antenna Polarity & Test Distance: Loop Antenna Ground-parallel At 3m

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*0.127	73.64 QP	105.53	-31.89	1.00	142	58.73	14.91
2	0.254	50.04 QP	99.51	-49.47	1.00	0	41.08	8.96
3	0.381	51.28 QP	95.99	-44.71	1.00	201	45.49	5.79
4	0.508	38.42 QP	73.49	-35.07	1.00	318	34.42	4.00
5	5.767	28.05 QP	69.54	-41.49	1.00	105	31.69	-3.64
6	9.126	26.33 QP	69.54	-43.21	1.00	44	30.29	-3.96

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. “ * “: Fundamental frequency.
6. Loop antenna was used for all radiated emission below 30MHz.
7. Limit @3m=Limit@300m+40log(300 / 3)=Limit@300m+80
8. Limit @3m=Limit@30m+40log(30 / 3)=Limit@30m+40

Test Frequency	128kHz	Detector Function	Quasi-Peak
Frequency Range	9 kHz ~ 30 MHz		
Test Mode	B		

Antenna Polarity & Test Distance: Loop Antenna Open At 3m

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*0.128	80.51 QP	105.46	-24.95	1.00	329	65.66	14.85
2	0.256	48.24 QP	99.44	-51.20	1.00	260	39.35	8.89
3	0.384	52.33 QP	95.92	-43.59	1.00	0	46.60	5.73
4	0.512	36.05 QP	73.42	-37.37	1.00	76	32.09	3.96
5	5.287	24.60 QP	69.54	-44.94	1.00	58	28.22	-3.62
6	19.743	26.08 QP	69.54	-43.46	1.00	274	31.28	-5.20

Antenna Polarity & Test Distance: Loop Antenna Close At 3m

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*0.128	74.85 QP	105.46	-30.61	1.00	204	60.00	14.85
2	0.256	48.96 QP	99.44	-50.48	1.00	132	40.07	8.89
3	0.384	55.05 QP	95.92	-40.87	1.00	60	49.32	5.73
4	0.512	39.50 QP	73.42	-33.92	1.00	19	35.54	3.96
5	5.257	25.92 QP	69.54	-43.62	1.00	111	29.54	-3.62
6	13.745	26.73 QP	69.54	-42.81	1.00	145	30.63	-3.90

Antenna Polarity & Test Distance: Loop Antenna Ground-parallel At 3m

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*0.128	74.80 QP	105.46	-30.66	1.00	0	59.95	14.85
2	0.256	50.29 QP	99.44	-49.15	1.00	131	41.40	8.89
3	0.384	48.31 QP	95.92	-47.61	1.00	354	42.58	5.73
4	0.512	37.45 QP	73.42	-35.97	1.00	214	33.49	3.96
5	5.407	26.15 QP	69.54	-43.39	1.00	111	29.78	-3.63
6	9.186	27.92 QP	69.54	-41.62	1.00	22	31.88	-3.96

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. “ * “: Fundamental frequency.
6. Loop antenna was used for all radiated emission below 30MHz.
7. Limit @3m=Limit@300m+40log(300 / 3)=Limit@300m+80
8. Limit @3m=Limit@30m+40log(30 / 3)=Limit@30m+40

Below 1GHz Data:

Test Frequency	127kHz	Detector Function	Quasi-Peak
Frequency Range	30 MHz ~ 1GHz		
Test Mode	A		

Antenna Polarity & Test Distance: Horizontal At 3m

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	50.08	20.53 QP	40.00	-19.47	2.28 H	78	27.56	-7.03
2	123.36	23.63 QP	43.50	-19.87	2.04 H	110	32.67	-9.04
3	511.51	29.20 QP	46.00	-16.80	2.77 H	184	29.91	-0.71
4	637.66	29.95 QP	46.00	-16.05	2.41 H	160	27.96	1.99
5	720.88	38.70 QP	46.00	-7.30	2.31 H	292	35.58	3.12
6	917.21	34.53 QP	46.00	-11.47	2.94 H	94	27.90	6.63

Antenna Polarity & Test Distance: Vertical At 3m

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	34.07	29.42 QP	40.00	-10.58	1.09 V	272	38.08	-8.66
2	123.41	30.76 QP	43.50	-12.74	1.17 V	60	39.80	-9.04
3	511.70	29.20 QP	46.00	-16.80	1.83 V	92	29.91	-0.71
4	574.85	31.12 QP	46.00	-14.88	1.55 V	170	30.59	0.53
5	720.20	38.04 QP	46.00	-7.96	2.03 V	127	34.97	3.07
6	902.18	34.68 QP	46.00	-11.32	1.75 V	162	28.45	6.23

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

Standby Mode

Test Frequency	128kHz	Detector Function	Quasi-Peak
Frequency Range	30 MHz ~ 1GHz		
Test Mode	B		

Antenna Polarity & Test Distance: Horizontal At 3m

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	54.98	20.06 QP	40.00	-19.94	1.18 H	149	27.35	-7.29
2	543.57	28.21 QP	46.00	-17.79	1.56 H	37	28.42	-0.21
3	603.90	30.50 QP	46.00	-15.50	2.27 H	180	29.17	1.33
4	720.45	36.46 QP	46.00	-9.54	2.01 H	332	33.37	3.09
5	812.84	32.48 QP	46.00	-13.52	1.76 H	288	27.62	4.86
6	911.88	34.16 QP	46.00	-11.84	1.43 H	205	27.60	6.56

Antenna Polarity & Test Distance: Vertical At 3m

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	32.72	30.44 QP	40.00	-9.56	1.58 V	329	39.18	-8.74
2	123.36	30.27 QP	43.50	-13.23	1.11 V	2	39.31	-9.04
3	511.36	28.26 QP	46.00	-17.74	1.72 V	105	28.97	-0.71
4	619.03	29.65 QP	46.00	-16.35	1.68 V	299	27.89	1.76
5	727.48	32.21 QP	46.00	-13.79	1.77 V	112	28.72	3.49
6	847.37	32.82 QP	46.00	-13.18	1.56 V	250	27.59	5.23

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
ROHDE & SCHWARZ TEST RECEIVER	ESR3	102413	Feb. 8, 2018	Feb. 7, 2019
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH2-Z5	100104	Dec. 6, 2017	Dec. 5, 2018
LISN With Adapter (for EUT)	AD10	C09Ada-001	Dec. 6, 2017	Dec. 5, 2018
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	847265/023	Nov. 03, 2017	Nov. 02, 2018
SCHWARZBECK Artificial Mains Network (For EUT)	NNLK8129	8129229	May 3, 2018	May 2, 2019
Software	Cond_V7.3.7.4	NA	NA	NA
RF cable (JYEBAO) With 10dB PAD	5D-FB	Cable-C09.01	Feb. 21, 2018	Feb. 20, 2019
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010789	May 8, 2018	May 7, 2019

Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in Shielded Room No. 9.

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as item 4.1.6.

4.2.7 Test Results


Charging Mode

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.15000	10.11	43.84	38.84	53.95	48.95	66.00
2	0.45498	10.16	25.40	22.53	35.56	32.69	56.78	46.78	-21.22	-14.09
3	1.05913	10.25	25.12	19.40	35.37	29.65	56.00	46.00	-20.63	-16.35
4	1.64620	10.30	24.18	9.35	34.48	19.65	56.00	46.00	-21.52	-26.35
5	5.90321	10.53	23.68	8.32	34.21	18.85	60.00	50.00	-25.79	-31.15
6	20.32720	11.13	17.01	4.65	28.14	15.78	60.00	50.00	-31.86	-34.22

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.15000	10.12	43.96	39.38	54.08	49.50	66.00
2	0.45107	10.17	25.10	21.84	35.27	32.01	56.86	46.86	-21.59	-14.85
3	1.05131	10.27	24.86	15.80	35.13	26.07	56.00	46.00	-20.87	-19.93
4	1.36020	10.29	26.21	18.67	36.50	28.96	56.00	46.00	-19.50	-17.04
5	5.60214	10.53	22.91	7.89	33.44	18.42	60.00	50.00	-26.56	-31.58
6	20.28810	10.91	17.79	5.20	28.70	16.11	60.00	50.00	-31.30	-33.89

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Charging Mode

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.11	29.70	3.04	39.81	13.15	66.00	56.00	-26.19	-42.85
2	0.36114	10.14	10.59	4.02	20.73	14.16	58.70	48.70	-37.97	-34.54
3	0.62512	10.19	13.26	6.23	23.45	16.42	56.00	46.00	-32.55	-29.58
4	1.13342	10.26	6.87	2.73	17.13	12.99	56.00	46.00	-38.87	-33.01
5	2.09528	10.33	8.15	5.67	18.48	16.00	56.00	46.00	-37.52	-30.00
6	4.84010	10.50	4.94	2.67	15.44	13.17	56.00	46.00	-40.56	-32.83
7	19.39271	11.10	7.93	5.87	19.03	16.97	60.00	50.00	-40.97	-33.03

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Standby Mode

Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.15000	10.12	27.03	2.88	37.15	13.00	66.00
2	0.36896	10.16	13.91	2.96	24.07	13.12	58.52	48.52	-34.45	-35.40
3	0.61730	10.20	13.10	5.30	23.30	15.50	56.00	46.00	-32.70	-30.50
4	1.11387	10.28	10.32	5.43	20.60	15.71	56.00	46.00	-35.40	-30.29
5	4.84792	10.51	4.79	4.65	15.30	15.16	56.00	46.00	-40.70	-30.84
6	12.08101	10.70	7.60	5.23	18.30	15.93	60.00	50.00	-41.70	-34.07


Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.3 Channel Bandwidth

4.3.1 Test Setup



4.3.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.3 Test Procedure

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.3.4 Deviation from Test Standard

No deviation.


4.3.5 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.3.6 Test Results


Mode A

Channel	Frequency (kHz)	20dB Bandwidth (kHz)
1	127	2.5760



Mode B

Channel	Frequency (kHz)	20dB Bandwidth (kHz)
2	128	2.6050



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---