



FCC TEST REPORT

REPORT NO.: F901009A16

MODEL NO.: LM800, LM800A, AS4611UT

PART NO.: ZAN1-CM

RECEIVED: Oct. 9, 2001

TESTED: Oct. 11~15, 2001

APPLICANT: Top Victory Electronics (Taiwan) Co., Ltd.

ADDRESS: 18F, No. 738, Chung Cheng Road, Chung Ho,
Taipei Hsien, Taiwan 235

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei,
Taiwan, R.O.C.

This test report consists of 21 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528



Lab Code: 200102-0



Table of Contents

1	CERTIFICATION.....	3
2	SUMMARY OF TEST RESULTS.....	4
3	GENERAL INFORMATION	5
3.1	GENERAL DESCRIPTION OF EUT	5
3.2	DESCRIPTION OF TEST MODES	5
3.3	DESCRIPTION OF SUPPORT UNITS.....	6
4	EMISSION TEST	7
4.1	CONDUCTED EMISSION MEASUREMENT.....	7
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	7
4.1.2	TEST INSTRUMENTS	7
4.1.3	TEST PROCEDURE	8
4.1.4	DEVIATION FROM TEST STANDARD	8
4.1.5	TEST SETUP	8
4.1.6	EUT OPERATING CONDITIONS.....	9
4.1.7	TEST RESULTS.....	10
4.2	RADIATED EMISSION MEASUREMENT	12
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	12
4.2.2	TEST INSTRUMENTS	13
4.2.3	TEST PROCEDURE	13
4.2.4	DEVIATION FROM TEST STANDARD	14
4.2.5	TEST SETUP	14
4.2.6	EUT OPERATING CONDITIONS.....	14
4.2.7	TEST RESULTS.....	15
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	19
6	APPENDIX - INFORMATION ON THE TESTING LABORATORIES.....	21



1 CERTIFICATION

PRODUCT: 18" LCD MONITOR
BRAND NAME: AOC, Iiyama
MODEL NO.: LM800, LM800A, AS4611UT
PART NO.: ZAN1-CM
TEST ITEM: ENGINEERING SAMPLE
APPLICANT: TOP VICTORY ELECTRONICS (TAIWAN) CO., LTD.
STANDARDS: FCC Part 15, Subpart B, Class B
CISPR 22: 1997, Class B
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample (model: LM800) of the designation has been tested in our facility on Oct. 11 to 15, 2001. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

TESTED BY: Jone Lin, DATE: 10.15.2001
(Jone Lin)

CHECKED BY: Betty Yen, DATE: 10.15.2001
(Betty Yen)

APPROVED BY: Mike Su, DATE: 10.15.2001
(Mike Su, Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

Standard	Test Type	Result	Remarks
FCC Part 15, Subpart B, Class B	Conducted Test	PASS	Meets Class B Limit Minimum passing margin is -11.39 dB at 3.423 MHz
CISPR 22: 1997, Class B	Radiated Test	PASS	Meets Class B Limit Minimum passing margin is -2.10 dB at 112.18 MHz

NOTE: For conducted emission test, the test limit used is according to FCC Part 15.107. In this part, conducted emission test for telecom port is not mentioned and therefore this item is not tested.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	18" LCD MONITOR
MODEL NO.	LM800, LM800A, AS4611UT
PART NO.	ZAN1-CM
POWER SUPPLY	Switching Power adapter Brand: Chi Model: CH1205 Input rating: 100-240Vac, 1.5A, 47-63Hz Output rating: 12Vdc, 5.0A, 60W Power Cord: Non-shielded AC, 3 pin (1.8m) Non-shielded DC (0.8m) with a ferrite core
DATA CABLE	Shielded (1.8m) with a ferrite core

NOTE: The EUT is a 18" COLOR MONITOR with resolution up to 1280x1024.

The EUT has three model names, which are identical to each other in all aspects except for their brand names and customer's requirement:

- ✧ LM800 -AOC
- ✧ LM800A -AOC (For different customer's requirement.)
- ✧ AS4611UT -Ilyama

For the final test, model: LM800 was selected as the representative model for the test and its data is recorded in this report.

For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

3.2 DESCRIPTION OF TEST MODES

The EUT was pre-tested under the following resolution & horizontal synchronization speed modes:

- ◆ 1280x1024 mode (75Hz/80kHz),
- ◆ 1024x768 mode (75Hz/60kHz),
- ◆ 640x480 mode (60Hz/31.5kHz)

The worst emission levels were found when the EUT was tested under **1280x1024 mode (75Hz/80kHz)** resolution. Therefore, only the test data of EUT tested under this mode is recorded in this report.



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PERSONAL COMPUTER	NTI	PI I-450T	P201141	FCC DoC APPROVED
2	PRINTER	HP	2225C+	2949S63865	DSI6XU2225
3	MODEM	ACEEX	1414	980020505	IFAXDM1414
4	PS/2 KEYBOARD	FORWARD	FDA-104GA	FDKB8110127	F4ZDA-104G
5	PS/2 MOUSE	LOGITECH	M-S43	LZE00703197	DZL211106
6	VGA CARD	GAINWARD	CD-GX2A44T	GHF19516	ICUVGA-GW710

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core.
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.
4	1.5 m foil shielded wire, terminated with PS/2 connector via metallic frame, w/o core.
5	1.8 m foil shielded wire, terminated with PS/2 connector via drain wire, w/o core.
6	NA

NOTE: All power cords of the above support units are non shielded (1.8m).



4 EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

- NOTES:**
- (1) The lower limit shall apply at the transition frequencies.
 - (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 - (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESHS30	828109/007	July 4, 2002
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH3-Z5	839135/006	July 3, 2002
* ROHDE & SCHWARZ 4-wire ISN	ENY41	837032/016	Nov. 28, 2001
* ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/016	Dec. 3, 2001
EMCO-L.I.S.N. (for peripheral)	3825/2	9204-1964	July 3, 2002
Software	Cond-V2J	NA	NA
RF cable (JYEBAO)	RG-58A/U	Cable-C02.01	July 5, 2002
HP Terminator (For EMCO LISN)	11593A	E1-01-298	Feb. 20, 2002
HP Terminator (For EMCO LISN)	11593A	E1-01-299	Feb. 20, 2002
Shielded Room	Site 2	ADT-C02	NA
VCCI Site Registration No.	Site 2	C-240	NA

- NOTE:**
1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. “*”: These equipment are used for conducted telecom port test only (if tested).


4.1.3 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.



4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power of all equipment.
- b. PC ran a test program to enable all functions.
- c. PC read and wrote messages from FDD and HDD.
- d. PC sent "H" messages to monitor (EUT) and monitor displayed "H" patterns on screen.
- e. PC sent "H" messages to modem.
- f. PC sent "H" messages to printer, and the printer printed them on paper.
- g. Steps c-g were repeated.




4.1.7 TEST RESULTS

EUT	18" LCD MONITOR	MODEL NO.	LM800
MODE	1280x1024 (75Hz/80kHz)	6dB BANDWIDTH	10 kHz
INPUT POWER	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 70 % RH, 1005 hPa	TESTED BY: JONE LIN	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.189	0.10	50.95	-	51.05	-	64.08	54.08	-13.03	-
2	0.252	0.10	47.90	-	48.00	-	61.69	51.69	-13.69	-
3	0.445	0.10	40.98	-	41.08	-	56.96	46.96	-15.88	-
4	1.140	0.10	37.32	-	37.42	-	56.00	46.00	-18.58	-
5	3.423	0.24	44.37	-	44.61	-	56.00	46.00	-11.39	-
6	8.118	0.44	36.71	-	37.15	-	60.00	50.00	-22.85	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






EUT	18" LCD MONITOR	MODEL NO.	LM800
MODE	1280x1024 (75Hz/80kHz)	6dB BANDWIDTH	10 kHz
INPUT POWER	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 70 % RH, 1005 hPa	TESTED BY: JONE LIN	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.189	0.10	51.11	-	51.21	-	64.08	54.08	-12.87	-
2	0.254	0.10	48.72	-	48.82	-	61.63	51.63	-12.81	-
3	0.378	0.10	39.20	-	39.30	-	58.32	48.32	-19.02	-
4	0.762	0.10	37.48	-	37.58	-	56.00	46.00	-18.42	-
5	3.370	0.24	40.45	-	40.69	-	56.00	46.00	-15.31	-
6	10.753	0.43	39.40	-	39.83	-	60.00	50.00	-20.17	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT FOR FREQUENCY BELOW 1000 MHz

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 10m)
	dBuV/m	dBuV/m
30 – 230	40	30
230 - 1000	47	37

LIMIT OF RADIATED EMISSION OF FCC PART 15, SUBPART B FOR FREQUENCY ABOVE 1000 MHz

FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80.0	60.0	74.0	54.0

- Note:** (1) The lower limit shall apply at the transition frequencies.
 (2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
HP Spectrum Analyzer	8590L	3544A01042	April 16, 2002
HP Preamplifier	8447D	2944A08313	April 3, 2002
* HP Preamplifier	8449B	3008A01201	Dec. 13, 2001
* HP Preamplifier	8449B	3008A01292	Aug. 21, 2002
* ROHDE & SCHWARZ TEST RECEIVER	ESVS 30	841977/008	Oct. 14, 2002
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 23, 2001
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Jan. 25, 2002
* CHASE BILOG Antenna	CBL6111A	1647	June 27, 2002
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	July 6, 2002
* EMCO Horn Antenna	3115	9312-4192	April 15, 2002
* EMCO Turn Table	1016	1722	NA
* EMCO Tower	1051	1825	NA
* Software	AS61D4	NA	NA
* ANRITSU RF Switches	MP59B	M28342	June 27, 2002
* TIMES RF cable	LMR-600	CABLE-ST4-01	June 27, 2002
Open Field Test Site	Site 4	ADT-R04	June 8, 2002
VCCI Site Registration No.	Site 4	R-1038	NA

NOTE: 1. The measurement uncertainty is less than +/- 3.0dB, which is calculated as per the NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

3. "*" = These equipment are used for the final measurement.

4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz.

4.2.3 TEST PROCEDURE


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10-meter open field site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the ratable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi- peak method or average method as specified and then reported In Data sheet peak mode and QP mode.
- g. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the interference antenna and the detect function was set to Peak or Average.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.




4.2.7 TEST RESULTS

EUT	18" LCD MONITOR	MODEL NO.	LM800
MODE	1280x1024 (75Hz/80kHz)	FREQUENCY RANGE	30-1000 MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 70 % RH, 1005 hPa	TESTED BY: JONE LIN	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10 M												
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Gain (dB)	Correction Factor (dB/m)	
1	112.41	24.8 QP	30.00	-5.20	4.00H	109	12.40	11.45	0.95	0.00	-12.40	
2	168.25	20.8 QP	30.00	-9.20	4.00H	352	9.94	9.55	1.30	0.00	-10.86	
3	196.38	20.8 QP	30.00	-9.20	4.00H	211	10.39	9.00	1.41	0.00	-10.41	
4	224.38	22.9 QP	30.00	-7.10	4.00H	43	10.79	10.62	1.48	0.00	-12.11	
5	392.56	28.9 QP	37.00	-8.10	1.89H	270	11.07	15.76	2.06	0.00	-17.83	
6	403.20	32.6 QP	37.00	-4.40	1.49H	116	14.45	16.07	2.09	0.00	-18.15	
7	541.70	30.3 QP	37.00	-6.70	1.86H	124	7.68	20.27	2.35	0.00	-22.63	
8	566.50	32.5 QP	37.00	-4.50	1.79H	134	9.55	20.50	2.45	0.00	-22.95	

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB/m) = Pre-Amplifier Gain (dB) - Antenna Factor (dB/m) - Cable Factor (dB)
 3. Pre-Amplifier Gain (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.






EUT	18" LCD MONITOR	MODEL NO.	LM800
MODE	1280x1024 (75Hz/80kHz)	FREQUENCY RANGE	30-1000 MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 70 % RH, 1005 hPa	TESTED BY: JONE LIN	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 10 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Gain (dB)	Correction Factor (dB/m)
1	40.50	20.1 QP	30.00	-9.90	1.00V	262	6.35	13.17	0.58	0.00	-13.75
2	79.45	20.3 QP	30.00	-9.70	1.37V	238	12.56	6.90	0.84	0.00	-7.75
3	84.14	18.9 QP	30.00	-11.10	1.28V	14	10.32	7.69	0.89	0.00	-8.59
4	112.18	27.9 QP	30.00	-2.10	1.00V	8	15.50	11.45	0.95	0.00	-12.40
5	168.23	25.4 QP	30.00	-4.60	1.00V	1	14.50	9.55	1.30	0.00	-10.86
6	224.31	26.4 QP	30.00	-3.60	1.00V	5	14.29	10.62	1.48	0.00	-12.12
7	308.20	31.3 QP	37.00	-5.70	1.00V	114	16.12	13.52	1.66	0.00	-15.18
8	399.60	32.4 QP	37.00	-4.60	1.00V	145	14.38	15.95	2.07	0.00	-18.02
9	403.20	33.2 QP	37.00	-3.80	3.02V	212	15.05	16.07	2.09	0.00	-18.15
10	566.50	31.1 QP	37.00	-5.90	4.00V	154	8.15	20.50	2.45	0.00	-22.95

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB/m) = Pre-Amplifier Gain (dB) - Antenna Factor (dB/m) - Cable Factor (dB)
 3. Pre-Amplifier Gain (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.






EUT	18" LCD MONITOR	MODEL NO.	LM800
MODE	1280x1024 (75Hz/80kHz)	FREQUENCY RANGE	1000-2000 MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak, 1MHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 70 % RH, 1005 hPa	TESTED BY: JONE LIN	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Gain (dB)	Correction Factor (dB/m)
1	1332.00	40.0 pk	74.00	-34.00	1.00V	114	46.60	25.56	3.92	36.14	6.65
2	1457.00	44.7 pk	74.00	-29.30	1.18H	185	50.60	25.81	4.25	35.96	5.90
3	1711.00	37.7 pk	74.00	-36.30	1.00H	141	42.00	26.58	4.85	35.73	4.30

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB/m) = Pre-Amplifier Gain (dB) - Antenna Factor (dB/m) - Cable Factor (dB)
 3. Pre-Amplifier Gain (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.






EUT	18" LCD MONITOR	MODEL NO.	LM800
MODE	1280x1024 (75Hz/80kHz)	FREQUENCY RANGE	1000-2000 MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak, 1MHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 70 % RH, 1005 hPa	TESTED BY: JONE LIN	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-Amp. Gain (dB)	Correction Factor (dB/m)
1	1457.00	45.8 pk	74.00	-28.20	1.36V	150	51.69	25.81	4.25	35.96	5.90
2	1710.00	43.8 pk	74.00	-30.20	1.00V	176	48.10	26.58	4.85	35.73	4.30

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB/m) = Pre-Amplifier Gain (dB) - Antenna Factor (dB/m) - Cable Factor (dB)
 3. Pre-Amplifier Gain (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.



5 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST



RADIATED EMISSION TEST





6 APPENDIX - INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP, UL
Germany	TUV Rheinland
Japan	VCCI
New Zealand	MoC
Norway	NEMKO, DNV
Canada	INDUSTRY CANADA
R.O.C.	CNLA, BSMI

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab:
Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC Lab:
Tel: 886-35-935343
Fax: 886-35-935342

Lin Kou Safety Lab:
Tel: 886-2-26093195
Fax: 886-2-26093184

Lin Kou RF & Telecom Lab.
Tel: 886-3-3270910
Fax: 886-3-3270892

Email: service@mail.adt.com.tw
Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.