



**Federal Communications Commission  
Office of Engineering and Technology  
Equipment Authorization Division  
Application Processing Branch**

Global Product Compliance Laboratory  
MH 5A-115, Alcatel-Lucent  
600, Mountain Avenue  
Murray Hill, NJ 07974-0636

**7435 Oakland Mills Road  
Columbia, MD 21046**

December 11, 2013

Dear Examiner:

In accordance with **Parts 2, and 27** of the Commission’s Rules and Regulations, we are submitting herewith, statements and supporting data to show compliance with the requirements of the Commission for Product Certification of the Alcatel-Lucent “LTE **TD-RRH8X20-25**”, henceforth ‘**RRH**’, **FCC ID: AS5BBTRX-15**. The RRH is radio, amplifier and filter combination cabinet systems uses the 3GPP standards Long time Evolution (LTE) technology, for use in Domestic Broadband Radio Service (BRS) and the Educational Broadband Service (EBS) bands.

This application for the RRH under FCC ID: AS5BBTRX-15, is for operation in the domestic Broadband Radio Service (BRS) and the Educational Broadband Service (EBS) bands with a LTE signal. The data summarized below is in the form presently used by the Commission’s Radio Equipment List.

<b>Manufacturer</b>	<b>Alcatel-Lucent</b>
<b>Equipment Identification</b>	<b>AS5BBTRX-15</b>
<b>Rules Part Number</b>	<b>27.5 (h) (1) (i) and 27.53(m)</b>
<b>Frequency Range</b>	<b>2496 -2690MHz</b>
<b>Output Power</b>	<b>+3 dBm (.002W) to 40dBm (10W) for 20MHz BW or +43dBm (20W) for 40MHz BW Varied by Software</b>
<b>Frequency Tolerance</b>	<b>+/- 0.05 ppm</b>
<b>Emission Designator</b>	<b>18M5F9W for 20 MHz Bands and 38M7F9W for 40 MHz Bands</b>

The RRH, under FCC ID: AS5BBTRX-15 is designed to be operated and marketed as RF cabinet system. Each of the RRH contains eight identical Transceiver paths and ports. Each transceiver ports outputs 20W maximum of at the External antenna connector (EAC) port. The RRH will be typically operated in Multiple and input and Multiple output (MIMO) mode using multiple antennas. Each Transceiver path is supported by its own RF path filter. The RRH were evaluated total of eight transceiver ports. During all antenna port conducted emissions, the transceiver ports were randomly selected for each of the tests. The RRH will be marketed as indoor/outdoor cabinets.

The RRH is designed operate at large number of sub-carriers which are modulated with QPSK, 16QAM, and 64QAM formats. The RRH was evaluated and data is provided for all three modulation formats.

- (a) QPSK
- (b) 16QAM
- (c) 64QAM


The actual power level delivered by the **RRH** to transmit antenna is under the software control of remotely located radio equipment control (REC) through its Common Public Radio Interface (CPRI).

The **RRH /AS5BBTRX-15** is designed and manufactured by Alcatel-Lucent.

List of exhibits attached with this submission is indicated in the following page of this cover letter.

The attached exhibits contain the technical data, and the required statements and documents for Product Certification. The technical contact at Alcatel-Lucent will comply with any request for additional information should the need arise.

Sincerely,



Dheena Moongilan  
Distinguished Member of Technical Staff  
Global Product Compliance Laboratory  
phone: (908) 582 5539  
email: moongilan@alcatel-lucent.com

**List of Exhibits**

	<p><b>COVER LETTER</b>                  Cover Letter                  Product Configuration – Explained in test reports                  Letter for Confidential Treatment of Exhibits</p>
<p>Section 2.911 (d)                  Section 2.1033 (c) (1,2)                  Section 2.1033 (c) (4-7)</p>	<p><b>ATTESTATION STATEMENT</b>                  Qualifications and Certifications                  Manufacturers, FCC Identification                  Emissions, Frequency Range, Power Level</p>
<p>Section 2.1033 (c) (3)</p>	<p><b>USERS MANUAL</b>                  Users Manual</p>
<p>Section 2.1033 (c) (9)</p>	<p><b>PARTS LIST/TUNE-UP PROCEDURE</b>                  Tune-Up Procedure</p>
<p>Section 2.1033 (c) (13)</p>	<p><b>OPERATIONAL DESCRIPTION</b>                  Description of Modulation System</p>
<p>Section 2.1033 (c) (10)</p>	<p><b>SCHEMATICS</b>                  Schematic</p>
<p>Section 2.1043 (b) (2)</p>	<p>Block Diagrams</p>
<p>Section 2.1033 (c) (11) and                  2.925 (a) (1)</p>	<p><b>ID LABEL/LOCATION INFORMATION</b></p>
<p>Section 2.1033 (c) (12)</p>	<p><b>EXTERNAL PHOTOS</b></p>
<p>Section 2.1033 (c) (12)</p>	<p><b>INTERNAL PHOTOS</b>                  Internal Photos</p>
<p>Section 2.1033 (c) (8)</p>	<p><b>TEST REPORT</b>                  Measurement of DC Power</p>
<p>Section 2.1033 (c) (14)</p>	<p>Listing of Required Measurements</p>
<p>Section 2.1046</p>	<p>Measurement of Radio Frequency Power Output</p>
<p>Section 2.1047</p>	<p>Measurement of Modulation Characteristics</p>
<p>Section 2.1049 and</p>	<p>Measurement of Occupied Bandwidth</p>
<p>Section 24.238 (b) and 27.58 (g)</p>	<p>Measurement of Spurious Emissions at Antenna</p>
<p>Section 2.1051</p>	<p>Field Strength of Spurious Radiation</p>
<p>Section 2.1053</p>	<p>Measurement of Frequency Stability</p>
<p>Section 2.1055</p>	<p>Frequency Spectrum to be Investigated</p>
<p>Section 2.1057</p>	<p>Test Instruments Used for Test – See Test Reports</p>
<p>Section 24.51 (c)</p>	<p><b>RF Exposure Information</b>                  Human Exposure – Not performed</p>