

Exhibit 2

SECTION 2.1033(c)

Applications for equipment....shall be accompanied by a technical report containing the following information:

The following affirmations are required by the identified sections.

SECTION 2.1033(c) (1)

The full name and mailing address of the manufacturer of the device and the applicant for certification.

RESPONSE:

Manufacturer and Applicant **Lucent Technologies**
600 Mountain Avenue
Murray Hill, NJ 07974

The manufacturer of this product Lucent Technologies, Inc. The **AS5CMP-24** will only be marketed under the Lucent Technologies Inc. trademark.

Applicant Personnel

The following personnel are associated with this filing as identified below:
 Primary contact for administrative questions and technical requests should be placed with Ms. Jane Zakutansky who is listed on the 731 Form and below.

FCC Contact Coordinator/ Compliance Manager
 Jane Zakutansky
 Mandatory Compliance Manager
 Phone 908- 582-5029
 Email: jzakutansky@lucent.com

FCC Compliance Laboratory Manager
 Rudy J.Pillmeier
 Technical Manager
 Certification Test Group
 Phone: 973-386-3837
 email: rpillmeier@lucent.com

Filing Engineer
 W. Steve Majkowski
 Phone 973-386-3812
 Email: majkowski@lucent.com

Exhibit 2 *continued***SECTION 2.1033(c) (2)**

Identification of equipment for which Product Certification is sought.

RESPONSE: The Cellular CDMA Baseband Combiner and Radio, henceforth **BCR**, internally identified as Lucent Technologies Inc. Apparatus Code 44WR1, is to be operated under Part 22 H of the FCC Rules as **FCC ID: AS5CMP-24**.

SECTION 2.1033(c) (3)

The Frequency Range of operation.

RESPONSE: The **BCR**, FCC ID: **AS5CMP-24**, is to be operated in the Cellular Bands over the frequency range of **869 - 894 MHz**

SECTION 2.1033(c) (6)

The range of operating power values or specific operating power levels and the description of any means provided for variation of operating power.

RESPONSE: The **BCR** is operated over the power range of -30 to 0.0 dBm (+2 /-4 dB) when measured at its output connector.

The **BCR**, at its output, is typically operated over the power range of -30 to 0.0 dBm.

The maximum power is limited to 0.0 dBm (1.0 milliwatt) at the output connector and is the level for this application. The actual power levels delivered by the **BCR** is under the software control of the Mobile Switching Center of the local Cellular system. The software control only allows for adjustment in power up to the 0.0 dBm maximum.

SECTION 2.1033(c) (7)

Maximum power rating as defined in the applicable part(s) of the rules

RESPONSE: 0.0 dBm (0.001 Watts) at the output connector for a single channel +2 /-4 dB.