

EXHIBIT 3

Section 2.1033 (c)(1)

The full name and mailing address of the manufacturer of the device and the applicant for certification.

Manufacturer: Lucent Technologies
Columbus Manufacturing Facility
6200 East Broad Street, Columbus, Ohio 43213

Applicant: Lucent Technologies
600 Mountain Avenue, Murray Hill, NJ 07974
Attention: Jane M. Zakutansky

Section 2.1033(c)(2)

FCC Identifier: AS5CMP-30

Section 2.1033(c)(4)

Type or types of emission: 40K0GXW

Section 2.1033(c)(5)

Frequency range: Transmit: 1930.080 – 1989.960 MHz
Receive: 1850.010 – 1909.920 MHz

Section 2.1033(c)(6)

Range of operating power values or specific operating power levels, and description of any means provided for variation of operating power.

The FLEXENT™ PCS-TDMA Microcell J416698A-1, which incorporates the 44WR53 PCS Dual Radio Module (PDRM), subject of this application for certification under AS5CMP-30, and the 44WA28 PCS Multi Carrier Linear Amplifier (PMCLA), subject of a separate application for certification under AS5CMP-31, is designed to provide 1.2 W (30.8 dBm) per carrier at the transmit antenna terminal and a total composite power of 12.0 W (40.8 dBm) for the rated 10 carrier capability. The Microcell incorporates 5 PDRM transceivers and 1 PMCLA. Each PDRM can transmit 1 or 2 carriers with a maximum power level at the PDRM transmit terminal of + 15.5 dBm (35.5 mW) per carrier, corresponding to total composite power level of + 18.5 dBm (71 mW) per 2 carriers. The PDRM carrier frequency and power level is software controlled by an external Remote Maintenance Terminal (RMT). The power level of each PDRM carrier is continuously adjustable from a maximum of + 15.5 dBm to a minimum of – 41 dBm with a resolution of 0.1 dBm. The controlling software utilizes a calibration table, which controls a voltage-controlled attenuator.

Section 2.1033(c)(7)

Maximum power rating as defined in the applicable part (s) of the rules.

The maximum power rating of the 44WR53 PCS Dual Radio Module, subject of this application under AS5CMP-30, is + 15.5 dBm (35.5 mW) per carrier, which corresponds to a total composite power level of +18.5 dBm (71 mW) for 2 carriers. The complete FLEXENT™ PCS-TDMA Microcell J41698A-1, incorporating the PDRM (AS5CMP-30), the PMCLA (AS5CMP-31) and the duplex transmit/receive (TxDx) bandpass filter is rated at 1.2 W (30.8 dBm) per carrier at the transmit antenna terminal, corresponding to a total composite power level of 12 W (40.8 dBm) for 10 carriers.

