

Exhibit 7- Circuitry For Determining Frequency, Limiting Modulation and Power

SECTION 2.1033(c) (10)

A schematic diagram and a description of all circuitry and devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation, and for limiting power.

Section 2.1033 (c)(10) A description of all circuitry and devices for determining and stabilizing frequency.

Response: Alcatel-Lucent' Flexent® PCS UMTS-CDMA EDPD Transceiver System, which is incorporated into the FLEXENT® OneBTS® PCS CDMA Modular Cell 4.0 wireless base station, is designed to operate in the Broadband PCS frequency band. Frequency stability of the carrier frequency is achieved with an accuracy better than the rated ± 0.05 ppm by the 15 MHz reference frequency generated by a highly stable Rubidium oscillator module (OMR) plus proprietary phase locked loop circuitry (PLL).
(This data has not changed from the original filing.)

The frequency stabilization and accuracy of the PCS UMTS-CDMA EDPD Transceivers CDMA signal amplified by the P2PAM and measured at the PCS Modular Cell 4.0 J4 connector is solely a function of the input signal from the MCR-1900 (FCC ID: AS5ONEBTS-09). The Common Timing Unit (CTU) provides the time and frequency reference used by the MCR-1900 (FCC ID: AS5ONEBTS-09). The CTU is a highly accurate time and frequency unit which relies upon a signal lock of GPS satellite signals to provide the primary discipline of system timing. In the event of loss of GPS lock the Rubidium Reference Oscillator (OMU-RB) or the Crystal Oscillator Module (OMU-XO) can provides up to eight hours of flywheel operation. The system provides for automatic timing synchronization upon reacquisition of GPS lock. The system is powered by an AC-DC power converter with battery backup to provide immunity to power fluctuations and failures. A complete description of the system is fully documented in the supplied manual, Flexent® CDMA Modular Cell 4.0 Operations, Administration and Maintenance Release 25.0. This manual has been requested for confidentiality.
(This data has not changed from the original filing.)

Section 2.1033 (c)(10)

A description of all circuitry and devices for limiting modulation and power.

Response: The frequency determination, stabilization, modulation limiting and power control of the transmit signal is provided by the UMTS-CDMA Multi Carrier Radio (MCR-1900), Model BNJ64, which was previously authorized by the Federal Communications Commission under FCC ID: AS5ONEBTS-09, granted 22 February 2005 for all PCS Blocks. The MCR-1900/ AS5ONEBTS-09 supplies the modulated signals to be amplified and all power control functions. The PCS UMTS-CDMA-LTE EDPD Transceiver/ AS5ONEBTS-10 frequency conversion, stabilization and power control circuitry is fully described in the MCR-1900/AS5ONEBTS-09 filing and in Exhibit 6 which details the basic frequency reference and has not changed.

(This data has not changed from the original filing.)

This information has not changed from the original filing