1



Timco Engineering Inc.
FCC Authorized Telecommunications
Certification Body (TCB)

August 31, 2012

Sid Sanders - President Timco Engineering Inc.849 N.W. State Road 45
P.O. Box 370
Newberry, Florida 32669

Dear Mr. Sanders

Alcatel-Lucent USA Inc.
Building 28-114H
600 Mountain Avenue
New Providence, NJ 07974

The Alcatel- Lucent AWS Base Station System, the subject of this request for a Class II Permissive Change, was previously authorized under FCC ID: AS50NEBTS-16. The original authorization was for the CDMA operation using the emissions designator 1M25F9W. Subsequently FCC Class II changes were processed to add the emissions designator 5M00F9W and 3M00F9W for the AWS 2110-2155 MHz (Blocks A-F). This Class II Change requests authorization to add the emissions designator 1M40F9W for the AWS 2130-2135 MHz (Blocks C) which supports operation under the 3GPP2 Long Term Evolution (LTE) communication standard.

There were no physical, hardware or circuit changes required to either the AWS Multi Carrier Radio, MCR-1721, or to the AWS IMT Band Power Linear Amplifier Module, 60W IPAM. The MCR-1721, which is the frequency generating and stabilizing component of the AWS Base Station System authorized under FCC ID: AS5ONEBTS-16 has not changed. There is no change to the principle RF components which have been previously filed under FCC ID: AS5ONEBTS-16. These include the (1) Multi-Carrier Radio (MCR-1721), (2) 60W IPAM power amplifier, and (3) 35/45 MHz wide Dual Duplex (DDpx) low loss transmit filters covering the AWS transmit spectrum of 2110-2155 MHz and the AWS receive spectrum of 1710-1755 MHz. All required supporting exhibits, not previously submitted with the initial filing, are attached.

This Class II change applies the 1M40F9W Emissions designator to **AWS Blocks C** for operation under **FCC ID: AS50NEBTS-16**. In this Class II Change the LTE transmit power level will be 24 Watts per amplifier. Post amplifier combiners and post filter combiners are both utilized. The measurement exhibits attached to this application demonstrate full compliance with FCC Part 27.53 following the procedural requirements specified in FCC Part 2 Subpart J – Equipment Authorization Procedures. The data for this Class II change, summarized below, is in the form presently used by the Commission's Radio Equipment List.

Equipment Identification: AS5ONEBTS-16

Rules Part Number: Part 27 – Broadband AWS

Frequency Range: Transmit 2130-2135 MHz (AWS Block C)

Output Power: 0.024 to 24 Watts per amplifier

 $\begin{array}{ll} Frequency \ Tolerance: & \pm \ 0.05 \ ppm \\ Emission \ Designator: & 1M40F9W \end{array}$

Attached are the FCC Form 731 (Application for Equipment Authorization – Radio Frequency Devices), the required measurement data and exhibits specific to this request for authorization of the AWS AWS Base Station System. The technical or non-technical contact at Alcatel-Lucent will comply with any request for additional information should the need arise. The previously attached exhibits with the applicable FCC Rule section were assembled and presented in accordance with the *Table of Contents* attachment. These exhibits were previously

submitted as confidential and included is a formal letter requesting continued confidentiality for the following exhibits:

Exhibit #	FCC Rule Section	Exhibit Title
Exhibit 3	Section 2.1033 (c)(3)	Installation and Operating Instructions -> Confidential
Exhibit 5	Section 2.1033 (c)(10)	Circuit Schematic Diagrams and Parts list -> Confidential
Exhibit 7	Section 2.1033 (c)(10)	Circuitry for Determining and Stabilizing Frequency and for Limiting
		Modulation and Power -> Confidential
Exhibit 10	Section 2.1033 (c) (13)	Description of the Digital Modulation System -> Confidential

Should there be any questions or procedural issues please feel free to contact me by email and/or phone.

Sincerely,

Technical Manager FCC Compliance Test Group Murray Hill, NJ Phone: 908-582-2810

email: rudy.pillmeier@alcatel-lucent.com

Primary Administrative Contact

Rudolf J. Pillmeier
Technical Manager
FCC Compliance Test Group
Murray Hill, NJ
Phases 202, 522, 2210

Phone: 908-582-2810

email: rudy.pillmeier@alcatel-lucent.com

Filing Engineer

W. Steve Majkowski NCE CDMA Filing Lead Phone 908-582-3782

email: steve.majkowski@alcatel-lucent.com

Att. Table of Contents for the FLEXENT® AWS Base Station System Product Certification Report

TABLE OF CONTENTS

Exhibit 1	Section 2.911 (d)	Certifications and Qualifications
Exhibit 2	Section2.1033 (c) (1, 2, 4-7)	Manufacturer, Applicant, Identifier, Emission Types, Frequency Range, Operating Power Range and Maximum Power Rating
Exhibit 3	Section 2.1033 (c)(3)	Installation and Operating Instructions -> Confidential
Exhibit 4	Section 2.1033 (c)(8, 9)	DC Voltages and Currents; Tune-up Procedure
Exhibit 5	Section 2.1033 (c)(10)	Circuit Schematic Diagrams and Parts list -> Confidential
Exhibit 6	Section 2.1033 (c)(10)	Circuitry and Devices for Suppression of Spurious Radiation
Exhibit 7	Section 2.1033 (c)(10)	Circuitry for Determining and Stabilizing Frequency and for Limiting Modulation and Power -> Confidential
Exhibit 8	Section 2.1033 (c) (11)	Equipment Identification Label
Exhibit 9	Section 2.1033 (c) (12)	Photograph of the Equipment
Exhibit 10	Section 2.1033 (c) (13)	Description of the Digital Modulation System -> Confidential
Exhibit 11-17		Test Report
Exhibit 11	Section 2.1033 (c)(14)	Required Measurement Data
Exhibit 12	Section 2.1046	Measurements Required: RF Power Output
Exhibit 13	Section 2.1047	Measurements Required: Modulation Characteristics
Exhibit 14	Section 2.1049, 27.53(g)	Measurements Required: Occupied Bandwidth and Out-of-
Exhibit 15	Section 2.1051, 27.53(g)	Band Emissions Measurements Required: Spurious Emissions at Antenna Terminal
Exhibit 16	Section 2.1053, 27.53(g)	Measurements Required: Field Strength of Spurious Radiation
Exhibit 17	Section 2.1055, 27.54	Measurements Required: Frequency Stability