

EXHIBIT 4: FCC ID LABEL SAMPLE AND LOCATION INFORMATION

SECTION 2.1033(c) (11) also SECTION 2.925 (a) (1)

A photograph or drawing of the equipment identification plate or label showing the information to be placed thereon.

The Alcatel-Lucent UMTS **9341 RRH 40W 1721MHz** Base Station system, subject of this certification, is comprised of two separate units interconnected by fiber optic cable: **1**) the RF frequency Remote Radio Head (RRH), and **2**) the associated digital Base Band Unit (BBU). They have the flexibility of being installed either in close proximity to (i.e., co-located) or remotely located from each other. The associated BBU incorporates **1**) the 15 MHz reference frequency oscillator module, **2**) the digital baseband circuitry, **3**) T1/E1 and alarm interface, and **4**) the RF-to-Optical and Optical-to-RF conversion circuitry. The 40W 1721 MHz RF RRH incorporates **1**) the Future Technology Radio (FTR) transceiver, **2**) the power amplifier (PA) and **3**) the passive tuned cavity filter with single transmit (Tx0) and diversity receive functionality (Rx0, Rx1). The RF Remote Radio Head will conspicuously display the Part 2, Subpart J, Section 2.925 FCC Identifier Label “FCC ID: AS5ONEBTS-19”, as shown below.

FCC Identifier Label to be displayed on the 40W 1721 MHz RRH

