

EXHIBIT 10**Section 2.1033 (c)(13) DESCRIPTION OF THE DIGITAL MODULATION SYSTEM**

For equipment employing digital modulation techniques, a detailed description of the modulation system to be used, including the response characteristics (frequency, phase and amplitude) of any filters provided, and a description of the modulating wavetrain, shall be submitted for the maximum rated conditions under which the equipment will be operated.

Response

The Alcatel-Lucent LTE 850 RRH 2x60W supports both WCDMA and LTE advanced radio access technologies, including multiple-input multiple-output for LTE. The I/Q baseband signals from the WCDMA and LTE BBUs are input to the transceiver inside the RRH.

The hardware of the 850 LTE RRH is identical to that of the 850 UMTS RRH. There are no modifications in the transmitting and receiving frequency ranges, the basic carrier frequency determining circuitry, the basic modulation circuit, the network interface circuitry and the major RF components (transmitter and power amplifier in the RRH) certified under AS5ONEBTS-26 for the 850 UMTS RRH. Therefore, the overview and architecture description of 850 LTE and WCDMA RRH, submitted in the initial FCC certification application for UMTS 850 RRH 2x60W under the AS5ONEBTS-26 which was granted on March 26, 2012, are still valid for the 850 LTE RRH 2x60W.