

EXHIBIT 7**Section 2.1033 (c)(10) CIRCUITRY FOR DETERMINING AND STABILIZING FREQUENCY**

A description of all circuitry and devices provided for determining and stabilizing frequency.

Response

The reference timing (frequency and phase alignment) signal for the 1900 RRH is provided externally, by the BBU.

The hardware of the 1900 LTE RRH is identical to that of the 1900 UMTS RRH. There are no modifications in the RRH for the transmitting and receiving frequency ranges and the basic carrier frequency determining circuitry certified under AS5ONEBTS-27 for the 1900 UMTS RRH. The description of all circuitry and devices provided for determining and stabilizing the carrier frequency in the 1900 UMTS RRH 2x60W Distributed Base Station, submitted in the initial FCC certification application under the AS5ONEBTS-27 which was granted on March 30, 2012, are still valid for the 1900 LTE RRH 2x60W Distributed Base Station.

Section 2.1033 (c)(10) CIRCUITRY AND DEVICES FOR LIMITING MODULATION AND FOR LIMITING POWER

A description of all circuitry and devices provided for limiting modulation and for limiting power.

Response

The hardware of the 1900 LTE RRH is identical to that of the 1900 UMTS RRH. There are no modifications in the RRH for the basic modulation circuitry and the major RF components (transmitter and power amplifier in the RRH) certified under AS5ONEBTS-27 for the 1900 UMTS RRH. The description of all circuitry and devices provided for limiting modulation and for limiting power in the 1900 UMTS RRH 2x60W Distributed Base Station, submitted in the initial FCC certification application under the AS5ONEBTS-27 which was granted on March 30, 2012, are still valid for the 1900 LTE RRH 2x60W Distributed Base Station.