

RF Exposure / SAR Statement

No. : 31BE0025-SH-01-A

Applicant : Victor Company of Japan, Limited
Type of Equipment : GPS NAVIGATION SYSTEM
Model No. : KW-NT30HD
FCC ID : ASIV1B007

Victor Company of Japan, Limited declares that Model : GPS NAVIGATION SYSTEM complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091. The "KW-NT30HD" has 2.65 mW of conducted Peak Output power and 2.88 mW of EIRP. This equipment is considered as a mobile device so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "KW-NT30HD" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 2.65 mW (Maximum peak output power)
G = 1.09 Numerical Antenna gain; equal 0.36 dBi
r = 20.0 cm

For: KW-NT30HD

$$S = 0.00057 \text{ mW/cm}^2$$

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401