

Rhein Tech Laboratories
360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Report #: 2004211
FCC ID: ATH2424140
Model: 242-414x-xxx
Standards: FCC Part 90 &IC RSS-119
Date: December 17, 2004

APPENDIX A: RF EXPOSURE

Please see the SAR Report that follows.

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

DECLARATION OF COMPLIANCE SAR RF EXPOSURE EVALUATION

Test Lab

CELLTECH LABS INC.
Testing and Engineering Services
1955 Moss Court
Kelowna, B.C.
Canada V1Y 9L3
Phone: 250-448-7047
Fax: 250-448-7046
e-mail: info@celltechlabs.com
web site: www.celltechlabs.com

Applicant Information

E.F. JOHNSON CO.
123 N. State Street
Waseca, MN 56093
United States

FCC IDENTIFIER:
IC IDENTIFIER:
Model(s):

ATH2424140
933B-2424140
4140

Rule Part(s):
Test Procedure(s):
Device Classification:
Device Description:
Modulation Type:

FCC 47 CFR §2.1093; IC RSS-102 Issue 1 (Provisional)
FCC OET Bulletin 65, Supplement C (Edition 01-01)
Licensed Non-Broadcast Transmitter Held to Face (TNF)
Portable FM UHF PTT Radio Transceiver
FM (UHF)

Tx Frequency Range:
Max. RF Output Power Measured:

Antenna Type(s) Tested:
Battery Type(s) Tested:

450 - 512 MHz
36.81 dBm Conducted (450 MHz)
36.81 dBm Conducted (480 MHz)
36.80 dBm Conducted (512 MHz)
1/4- Wave Whip (P/N: 501-0017-107)
NiMH (7.5 V, 2700 mAh)

Body-Worn Accessories Tested:

Speaker-Microphone with Antenna (P/N: 589-0015-058)
Speaker-Microphone (P/N: 589-0015-057)
Boom-Microphone Headset (P/N: 589-0015-059)
Plastic Belt-Clip with Metal Spring (P/N: 585-5100-128)

Max. SAR Levels Evaluated:

Face-held: 1.65 W/kg (50% Duty Cycle)
Body-worn: 4.55 W/kg (50% Duty Cycle)

Celltech Labs Inc. declares under its sole responsibility that this wireless portable device has demonstrated compliance with the Specific Absorption Rate (SAR) RF exposure requirements specified in FCC 47 CFR §2.1093 and Health Canada's Safety Code 6. The device was tested in accordance with the measurement standards and procedures specified in FCC OET Bulletin 65, Supplement C (Edition 01-01) and Industry Canada RSS-102 Issue 1 (Provisional) for the Occupational / Controlled Exposure environment. All measurements were performed in accordance with the SAR system manufacturer recommendations.

I attest to the accuracy of data. All measurements were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

This test report shall not be reproduced partially, or in full, without the prior written approval of Celltech Labs Inc. The results and statements contained in this report pertain only to the device(s) evaluated.

Performed By:



Spencer Watson
Compliance Technologist
Celltech Labs Inc.

Reviewed By:



Russell W. Pipe
Senior Compliance Technologist
Celltech Labs Inc.



TABLE OF CONTENTS

1.0	INTRODUCTION.....	3
2.0	DESCRIPTION OF DUT.....	3
3.0	SAR MEASUREMENT SYSTEM.....	4
4.0	MEASUREMENT SUMMARY.....	5
5.0	DETAILS OF SAR EVALUATION.....	6
6.0	EVALUATION PROCEDURES.....	6
7.0	SYSTEM PERFORMANCE CHECK.....	7
8.0	SIMULATED EQUIVALENT TISSUES.....	8
9.0	SAR SAFETY LIMITS.....	8
10.0	ROBOT SYSTEM SPECIFICATIONS.....	9
11.0	PROBE SPECIFICATION.....	10
12.0	PLANAR PHANTOM.....	10
13.0	VALIDATION PHANTOM.....	10
14.0	DEVICE HOLDER.....	10
15.0	TEST EQUIPMENT LIST.....	11
16.0	MEASUREMENT UNCERTAINTIES.....	12-13
17.0	REFERENCES.....	14
APPENDIX A - SAR MEASUREMENT DATA.....		15
APPENDIX B - SYSTEM PERFORMANCE CHECK DATA.....		16
APPENDIX C - SYSTEM VALIDATION PROCEDURES.....		17
APPENDIX D - PROBE CALIBRATION.....		18
APPENDIX E - MEASURED FLUID DIELECTRIC PARAMETERS.....		19
APPENDIX F - SAR TEST SETUP & DUT PHOTOGRAPHS.....		20

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

1.0 INTRODUCTION

This measurement report demonstrates compliance of the E.F. Johnson Co. Model: 4140 Portable FM UHF PTT Radio Transceiver FCC ID: ATH2424140 with the SAR (Specific Absorption Rate) RF exposure requirements specified in FCC 47 CFR §2.1093 (see reference [1]), and Health Canada's Safety Code 6 (see reference [2]) for the Occupational / Controlled Exposure environment. The measurement procedures described in FCC OET Bulletin 65, Supplement C (Edition 01-01) (see reference [3]) and IC RSS-102 Issue 1 (Provisional) (see reference [4]), were employed. A description of the product, operating configuration, detailed summary of the test results, methodology and procedures used in the evaluation, equipment used, and the various provisions of the rules are included within this test report.

2.0 DESCRIPTION OF DEVICE UNDER TEST (DUT)

FCC Rule Part(s)	47 CFR §2.1093		
IC Rule Part(s)	RSS-102 Issue 1 (Provisional)		
Test Procedure(s)	FCC OET Bulletin 65, Supplement C (Edition 01-01)		
Device Classification	Licensed Non-Broadcast Transmitter Held to Face (TNF)		
Device Description	Portable FM UHF PTT Radio Transceiver		
FCC IDENTIFIER	ATH2424140		
IC IDENTIFIER	933B-2424140		
Model(s)	4140		
Serial No.	n/a (Identical Prototype)		
Modulation	FM (UHF)		
Tx Frequency Range	450 - 512 MHz		
Max. RF Output Power Measured	36.81 dBm	Conducted	450 MHz
	36.81 dBm	Conducted	480 MHz
	36.80 dBm	Conducted	512 MHz
Antenna Type(s) Tested	1/4-Wave Whip	Length - 140 mm	P/N: 501-0017-107
Battery Type(s) Tested	NiMH	7.5 V, 2700 mAh	P/N: n/a
Body-Worn Accessories Tested	Speaker-Microphone with Antenna		P/N: 589-0015-058
	Speaker-Microphone		P/N: 589-0015-057
	Boom-Microphone Headset		P/N: 589-0015-059
	Plastic Belt-Clip with Metal Spring		P/N: 585-5100-128

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.			3 of 20		

3.0 SAR MEASUREMENT SYSTEM

Celltech Labs Inc. SAR measurement facility utilizes the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY4 measurement system is comprised of the measurement server, robot controller, computer, near-field probe, probe alignment sensor, specific anthropomorphic mannequin (SAM) phantom, and various planar phantoms for brain and/or body SAR evaluations. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the DASY4 measurement server. The DAE4 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit. Transmission to the DASY4 measurement server is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. The sensor systems are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.



DASY4 SAR Measurement System with validation phantom



DASY4 SAR Measurement System with Plexiglas planar phantom

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						4 of 20

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

4.0 MEASUREMENT SUMMARY

SAR EVALUATION RESULTS

Test Type	Test Date	Freq. (MHz)	Chan.	Test Mode	DUT Type	Battery Type	Body-worn Accessories	Separation Distance to Planar Phantom (cm)	Cond. Power Before Test (dBm)	Measured SAR 1g (W/kg)		SAR Drift During Test (dB)	Scaled SAR 1g (W/kg)			
										Duty Cycle			Duty Cycle			
										100%	50%		100%	50%		
Face	Dec-9	480	Mid	CW	Radio	NiMH	-	2.5	36.61	2.15	1.08	-1.09	2.76	1.38		
Face	Dec-9	480	Mid	CW	SMA	NiMH	-	2.5	36.59	3.29	1.65	-0.002	3.29	1.65		
Body	Dec-10	480	Mid	CW	SMA	NiMH	Lapel-Clip	1.2	36.81	7.35	3.68	-0.925	9.09	4.55		
Body	Dec-10	450	Low	CW	SMA	NiMH	Lapel-Clip	1.2	36.81	5.88	2.94	-0.101	6.02	3.01		
Body	Dec-10	512	High	CW	SMA	NiMH	Lapel-Clip	1.2	36.80	P	6.89	3.45	-0.247	P	7.29	3.65
									36.80	S	6.62	3.31	-0.122	S	6.81	3.40
Body	Dec-11	480	Mid	CW	Radio	NiMH	Speaker-Mic and Belt-Clip	1.3	36.73	4.64	2.32	-0.131	4.78	2.39		
Body	Dec-11	480	Mid	CW	Radio	NiMH	Headset-Mic and Belt-Clip	1.3	36.72	5.04	2.52	-0.775	6.02	3.01		

ANSI / IEEE C95.1 1999 - SAFETY LIMIT
BRAIN / BODY: 8.0 W/kg (averaged over 1 gram)
Spatial Peak - Controlled Exposure / Occupational

Test Date(s)		December 9, 2004			December 10-11, 2004			Test Date(s)		Brain	Body	Unit		
										Dec 9	Dec 10	Dec 11		
Dielectric Constant ϵ_r	450 MHz Brain			450 MHz Body			Relative Humidity		30	30	30	%		
	IEEE Target		Measured		IEEE Target		Measured		Atmospheric Pressure		101.4	101.2	102.6	kPa
	43.5	$\pm 5\%$	41.9		56.7	$\pm 5\%$	Dec 10	57.2	Ambient Temperature		23.1	23.9	23.1	°C
Conductivity σ (mho/m)	450 MHz Brain			450 MHz Body			Fluid Temperature		22.5	22.4	22.4	%		
	IEEE Target		Measured		IEEE Target		Measured		Fluid Depth		≥ 15	≥ 15	≥ 15	cm
	0.87	$\pm 5\%$	0.83		0.94	$\pm 5\%$	Dec 10	0.93	ρ (Kg/m ³)		1000			

Note(s):

1. The measurement results were obtained with the DUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum SAR location of the DUT are reported in Appendix A.
2. If the scaled SAR levels evaluated at the mid channel (50% duty cycle) were ≥ 3 dB below the SAR limit, SAR evaluation for the low and high channels was optional per FCC OET Bulletin 65, Supplement C, Edition 01-01 (see reference [3]).
3. Secondary peak SAR levels measured within 2 dB of the primary were reported (P = Primary, S = Secondary).
4. The power drifts measured by the DASY4 system for the duration of the SAR evaluations were added to the measured SAR levels to report scaled SAR results as shown in the above test data table.
5. A SAR-versus-Time power drift evaluation was performed in the test configuration that reported the maximum-scaled SAR level (Speaker-Microphone with Antenna, body-worn, mid channel). See Appendix A (SAR Test Plots) for SAR-versus-Time power drift evaluation plot.
6. The ambient and fluid temperatures were measured prior to, and during, the fluid dielectric parameter check and the SAR evaluation. The temperatures reported were consistent for all measurement periods.
7. The dielectric parameters of the simulated tissue mixture were measured prior to the evaluation using an HP 85070C Dielectric Probe Kit and an HP 8753E Network Analyzer (see Appendix E for printout of measured fluid dielectric parameters).
8. The SAR evaluations were performed within 24 hours of the system performance check.
9. Abbreviation(s): SMA - Speaker-Microphone with Antenna

Applicant:	E.F. Johnson Co.			FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver			450 - 512 MHz		
2004 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.					5 of 20	

5.0 DETAILS OF SAR EVALUATION

The E.F. Johnson Co. Model: 4140 Portable FM UHF PTT Radio Transceiver FCC ID: ATH2424140 was compliant for localized Specific Absorption Rate (Occupational / Controlled Exposure) based on the test provisions and conditions described below. The detailed test setup photographs are shown in Appendix F.

1. The Radio Transceiver (DUT) was evaluated for face-held configuration with the front of the DUT placed parallel to the outer surface of the planar phantom at a 2.5 cm separation distance.
2. The Speaker-Microphone with Antenna (DUT) was evaluated for face-held configuration connected to the Radio Transceiver with the front of the DUT placed parallel to the outer surface of the planar phantom at a 2.5 cm separation distance.
3. The Radio Transceiver (DUT) was evaluated for body-worn configuration with the back of the DUT placed parallel to the outer surface of the planar phantom. The attached belt-clip accessory was touching the outer surface of the planar phantom and provided a 1.3 cm separation distance between the back of the DUT and the planar phantom. The DUT was evaluated with the speaker-microphone and boom-microphone headset accessories consecutively.
4. The Speaker-Microphone with Antenna (DUT) was evaluated for body-worn configuration with the back of the DUT placed parallel to the outer surface of the planar phantom. The attached lapel-clip was touching the outer surface of the planar phantom and provided a 1.2 cm separation distance between the back of the DUT and the planar phantom.
5. The conducted power levels were measured prior to each test using a Gigatronics 8652A Universal Power Meter according to the procedures described in FCC 47 CFR §2.1046.
6. The power drifts measured by the DASY4 system during the SAR evaluations were added to the measured SAR levels to report scaled SAR results as shown in the test data table (pages 5).
7. A SAR-versus-Time power drift evaluation was performed in the test configuration that reported the maximum scaled SAR level. See Appendix A (SAR Test Plots) for SAR-versus-Time power drift evaluation data.
8. The area scan evaluation was performed with a fully charged battery. After the area scan was completed the DUT was cooled down to room temperature and the battery was replaced with a fully charged battery prior to the zoom scan evaluation.
9. The DUT was tested in unmodulated continuous transmit operation (Continuous Wave mode at 100% duty cycle) with the transmit key constantly depressed. For a push-to-talk device the 50% duty cycle compensation reported assumes a transmit/receive cycle of equal time base.
10. The SAR evaluations were performed using a Plexiglas planar phantom.

6.0 EVALUATION PROCEDURES

- a. (i) The evaluation was performed in the applicable area of the phantom depending on the type of device being tested. For devices held to the ear during normal operation, both the left and right ear positions were evaluated using the SAM phantom.
(ii) For face-held and body-worn devices a planar phantom was used.
- b. The SAR was determined by a pre-defined procedure within the DASY4 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 15mm x 15mm.

An area scan was determined as follows:

- c. Based on the defined area scan grid, a more detailed grid is created to increase the points by a factor of 10. The interpolation function then evaluates all field values between corresponding measurement points.
- d. A linear search is applied to find all the candidate maxima. Subsequently, all maxima are removed that are >2 dB from the global maximum. The remaining maxima are then used to position the cube scans.

A 1g and 10g spatial peak SAR was determined as follows:

- e. Extrapolation is used to find the points between the dipole center of the probe and the surface of the phantom. This data cannot be measured, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.4 mm (see probe calibration document in Appendix D). The extrapolation was based on trivariate quadratics computed from the previously calculated 3D interpolated points nearest the phantom surface.
- f. Interpolated data is used to calculate the average SAR over 1g and 10g cubes by spatially discretizing the entire measured cube. The volume used to determine the averaged SAR is a 1mm grid (42875 interpolated points).
- g. A zoom scan volume of 32 mm x 32 mm x 30 mm (5 x 5 x 7 points) centered at the peak SAR location determined from the area scan is used for all zoom scans for devices with a transmit frequency < 800 MHz. Zoom scans for frequencies ≥ 800 MHz are determined with a scan volume of 30 mm x 30 mm x 30 mm (7 x 7 x 7) to ensure complete capture of the peak spatial-average SAR.

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						6 of 20

7.0 SYSTEM PERFORMANCE CHECK

Prior to the SAR evaluation a system check was performed using a planar phantom with a 450MHz dipole (see Appendix C for system validation procedure). The dielectric parameters of the simulated tissue mixture were measured prior to the system performance check using an HP 85070C Dielectric Probe Kit and an HP 8753E Network Analyzer (see Appendix E for printout of measured fluid dielectric parameters). A forward power of 250mW was applied to the dipole and the system was verified to a tolerance of $\pm 10\%$ (see Appendix B for system performance check test plots).

SYSTEM PERFORMANCE CHECK													
Test Date	450MHz Equiv. Tissue	SAR 1g (W/kg)		Dielectric Constant ϵ_r		Conductivity σ (mho/m)		ρ (Kg/m ³)	Amb. Temp. (°C)	Fluid Temp. (°C)	Fluid Depth (cm)	Humid. (%)	Barom. Press. (kPa)
		IEEE Target	Measured	IEEE Target	Measured	IEEE Target	Measured						
12/09/04	Brain	1.23 ($\pm 10\%$)	1.25 (+1.6%)	43.5 $\pm 5\%$	41.9	0.87 $\pm 5\%$	0.83	1000	23.1	22.5	≥ 15	30	101.9
12/10/04	Brain	1.23 ($\pm 10\%$)	1.27 (+3.3%)	43.5 $\pm 5\%$	42.5	0.87 $\pm 5\%$	0.84	1000	23.2	22.3	≥ 15	30	101.8
12/11/04	Brain	1.23 ($\pm 10\%$)	1.28 (+4.1%)	43.5 $\pm 5\%$	42.8	0.87 $\pm 5\%$	0.86	1000	22.8	22.6	≥ 15	31	102.5

Note(s):

1. The ambient and fluid temperatures were measured prior to, and during, the fluid dielectric parameter check and the system performance check. The temperatures reported in the table above were consistent for all measurement periods.




Figure 1. System Performance Check Setup Diagram

450MHz Dipole Setup

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140		Portable FM UHF PTT Radio Transceiver		450 - 512 MHz	
2004 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				7 of 20	

8.0 SIMULATED EQUIVALENT TISSUES

The 450MHz simulated tissue mixtures consist of a viscous gel using hydroxethylcellulose (HEC) gelling agent and saline solution. Preservation with a bactericide is added and visual inspection is made to ensure air bubbles are not trapped during the mixing process. The fluid was prepared and measured for dielectric parameters (permittivity and conductivity) according to standardized procedures.

SIMULATED TISSUE MIXTURES		
INGREDIENT	450 MHz Brain	450 MHz Body
	System Check & DUT Evaluation	DUT Evaluation
Water	38.56 %	52.00 %
Sugar	56.32 %	45.65 %
Salt	3.95 %	1.75 %
HEC	0.98 %	0.50 %
Bactericide	0.19 %	0.10 %

9.0 SAR SAFETY LIMITS

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10g)	4.0	20.0

Notes:

1. Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.
2. Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.			8 of 20		

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

10.0 ROBOT SYSTEM SPECIFICATIONS

Specifications

POSITIONER:	Stäubli Unimation Corp. Robot Model: RX60L
Repeatability:	0.02 mm
No. of axis:	6

Data Acquisition Electronic (DAE) System

Cell Controller

Processor:	AMD Athlon XP 2400+
Clock Speed:	2.0 GHz
Operating System:	Windows XP Professional

Data Converter

Features:	Signal Amplifier, multiplexer, A/D converter, and control logic
Software:	DASY4 software
Connecting Lines:	Optical downlink for data and status info. Optical uplink for commands and clock

DASY4 Measurement Server

Function:	Real-time data evaluation for field measurements and surface detection
Hardware:	PC/104 166MHz Pentium CPU; 32 MB chipdisk; 64 MB RAM
Connections:	COM1, COM2, DAE, Robot, Ethernet, Service Interface

E-Field Probe

Model:	ET3DV6
Serial No.:	1387
Construction:	Triangular core fiber optic detection system
Frequency:	10 MHz to 6 GHz
Linearity:	±0.2 dB (30 MHz to 3 GHz)

Phantom(s)

Evaluation Phantom

Type:	Planar Phantom
Shell Material:	Plexiglas
Bottom Thickness:	2.0 mm ± 0.1 mm
Outer Dimensions:	75.0 cm (L) x 22.5 cm (W) x 20.5 cm (H); Back Plane: 25.7 cm (H)

Validation Phantom (≤ 450MHz)

Type:	Planar Phantom
Shell Material:	Plexiglas
Bottom Thickness:	6.2 mm ± 0.1 mm
Outer Dimensions:	86.0 cm (L) x 39.5 cm (W) x 21.8 cm (H)

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140		Portable FM UHF PTT Radio Transceiver		450 - 512 MHz	
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				9 of 20

11.0 PROBE SPECIFICATION (ET3DV6)

Construction: Symmetrical design with triangular core
Built-in shielding against static charges
PEEK enclosure material (resistant to organic solvents, e.g. glycol)

Calibration: In air from 10 MHz to 2.5 GHz
In brain simulating tissue at frequencies of 900 MHz and 1.8 GHz (accuracy \pm 8%)

Frequency: 10 MHz to > 6 GHz; Linearity: \pm 0.2 dB
(30 MHz to 3 GHz)

Directivity: \pm 0.2 dB in brain tissue (rotation around probe axis)
 \pm 0.4 dB in brain tissue (rotation normal to probe axis)

Dynamic Range: 5 μ W/g to > 100 mW/g; Linearity: \pm 0.2 dB

Surface Detection: \pm 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces

Dimensions: Overall length: 330 mm
Tip length: 16 mm
Body diameter: 12 mm
Tip diameter: 6.8 mm
Distance from probe tip to dipole centers: 2.7 mm

Application: General dosimetry up to 3 GHz
Compliance tests of mobile phone



ET3DV6 E-Field Probe

12.0 PLANAR PHANTOM

The planar phantom is constructed of Plexiglas material with a 2.0 mm shell thickness for face-held and body-worn SAR evaluations of handheld and body-worn radio transceivers. The planar phantom is mounted on the side of the DASY4 compact system table.



Planar Phantom

13.0 VALIDATION PLANAR PHANTOM

The validation planar phantom is constructed of Plexiglas material with a 6.0 mm shell thickness for system validations at 450MHz and below. The validation planar phantom is mounted in the table of the DASY4 compact system.



Validation Planar Phantom

14.0 DEVICE HOLDER

The DASY4 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65°. The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections.



Device Holder

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						10 of 20

15.0 TEST EQUIPMENT LIST

TEST EQUIPMENT	SERIAL NO.	CALIBRATION DATE
Schmid & Partner DASY4 System	-	-
-DASY4 Measurement Server	1078	N/A
-Robot	599396-01	N/A
-DAE3	370	May 2004
-DAE3	353	July 2004
-ET3DV6 E-Field Probe	1387	Mar 2004
-ET3DV6 E-Field Probe	1590	May 2004
-300MHz Validation Dipole	135	Oct 2004
-450MHz Validation Dipole	136	Nov 2004
-835MHz Validation Dipole	411	Mar 2004
-900MHz Validation Dipole	054	June 2004
-1800MHz Validation Dipole	247	June 2004
-1900 MHz Validation Dipole	151	June 2004
-2450MHz Validation Dipole	150	Sept 2004
-SAM Phantom V4.0C	1033	N/A
-Barski Planar Phantom	03-01	N/A
-Plexiglas Planar Phantom	161	N/A
-Validation Planar Phantom	137	N/A
HP 85070C Dielectric Probe Kit	N/A	N/A
Gigatronics 8651A Power Meter	8650137	April 2004
Gigatronics 8652A Power Meter	1835267	April 2004
Gigatronics 80701A Power Sensor	1833535	April 2004
Gigatronics 80701A Power Sensor	1833542	April 2004
Gigatronics 80701A Power Sensor	1834350	April 2004
HP 8594E Spectrum Analyzer	3543A02721	April 2004
HP 8753E Network Analyzer	US38433013	April 2004
HP 8648D Signal Generator	3847A00611	April 2004
Amplifier Research 5S1G4 Power Amplifier	26235	N/A

16.0 MEASUREMENT UNCERTAINTIES

UNCERTAINTY BUDGET FOR DEVICE EVALUATION						
Error Description	Uncertainty Value ±%	Probability Distribution	Divisor	c_i 1g	Standard Uncertainty ±% (1g)	v_i or v_{eff}
Measurement System						
Probe calibration	± 4.0	Normal	1	1	± 4.0	∞
Axial isotropy of the probe	± 4.7	Rectangular	$\sqrt{3}$	$(1-c_p)$	± 1.9	∞
Spherical isotropy of the probe	± 9.6	Rectangular	$\sqrt{3}$	(c_p)	± 3.9	∞
Spatial resolution	± 0.0	Rectangular	$\sqrt{3}$	1	± 0.0	∞
Boundary effects	± 5.5	Rectangular	$\sqrt{3}$	1	± 3.2	∞
Probe linearity	± 4.7	Rectangular	$\sqrt{3}$	1	± 2.7	∞
Detection limit	± 1.0	Rectangular	$\sqrt{3}$	1	± 0.6	∞
Readout electronics	± 1.0	Normal	1	1	± 1.0	∞
Response time	± 0.8	Rectangular	$\sqrt{3}$	1	± 0.5	∞
Integration time	± 1.4	Rectangular	$\sqrt{3}$	1	± 0.8	∞
RF ambient conditions	± 3.0	Rectangular	$\sqrt{3}$	1	± 1.7	∞
Mech. constraints of robot	± 0.4	Rectangular	$\sqrt{3}$	1	± 0.2	∞
Probe positioning	± 2.9	Rectangular	$\sqrt{3}$	1	± 1.7	∞
Extrapolation & integration	± 3.9	Rectangular	$\sqrt{3}$	1	± 2.3	∞
Test Sample Related						
Device positioning	± 6.0	Normal	$\sqrt{3}$	1	± 6.7	12
Device holder uncertainty	± 5.0	Normal	$\sqrt{3}$	1	± 5.9	8
Power drift	± 5.0	Rectangular	$\sqrt{3}$		± 2.9	∞
Phantom and Setup						
Phantom uncertainty	± 4.0	Rectangular	$\sqrt{3}$	1	± 2.3	∞
Liquid conductivity (target)	± 5.0	Rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Liquid conductivity (measured)	± 5.0	Rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Liquid permittivity (target)	± 5.0	Rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Liquid permittivity (measured)	± 5.0	Rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Combined Standard Uncertainty						
Expanded Uncertainty (k=2)						
± 13.03						
± 26.07						

Measurement Uncertainty Table in accordance with IEEE Standard 1528-2003 (see reference [5])

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				12 of 20	

MEASUREMENT UNCERTAINTIES (Cont.)

UNCERTAINTY BUDGET FOR SYSTEM VALIDATION						
Error Description	Uncertainty Value ±%	Probability Distribution	Divisor	c_i 1g	Standard Uncertainty ±% (1g)	v_i or v_{eff}
Measurement System						
Probe calibration	± 4.0	Normal	1	1	± 4.0	∞
Axial isotropy of the probe	± 4.7	Rectangular	$\sqrt{3}$	$(1-c_p)$	± 1.9	∞
Spherical isotropy of the probe	± 9.6	Rectangular	$\sqrt{3}$	(c_p)	± 3.9	∞
Spatial resolution	± 0.0	Rectangular	$\sqrt{3}$	1	± 0.0	∞
Boundary effects	± 5.5	Rectangular	$\sqrt{3}$	1	± 3.2	∞
Probe linearity	± 4.7	Rectangular	$\sqrt{3}$	1	± 2.7	∞
Detection limit	± 1.0	Rectangular	$\sqrt{3}$	1	± 0.6	∞
Readout electronics	± 1.0	Normal	1	1	± 1.0	∞
Response time	± 0.8	Rectangular	$\sqrt{3}$	1	± 0.5	∞
Integration time	± 1.4	Rectangular	$\sqrt{3}$	1	± 0.8	∞
RF ambient conditions	± 3.0	Rectangular	$\sqrt{3}$	1	± 1.7	∞
Mech. constraints of robot	± 0.4	Rectangular	$\sqrt{3}$	1	± 0.2	∞
Probe positioning	± 2.9	Rectangular	$\sqrt{3}$	1	± 1.7	∞
Extrapolation & integration	± 3.9	Rectangular	$\sqrt{3}$	1	± 2.3	∞
Dipole						
Dipole Axis to Liquid Distance	± 2.0	Rectangular	$\sqrt{3}$	1	± 1.2	∞
Input Power	± 4.7	Rectangular	$\sqrt{3}$	1	± 2.7	∞
Phantom and Setup						
Phantom uncertainty	± 4.0	Rectangular	$\sqrt{3}$	1	± 2.3	∞
Liquid conductivity (target)	± 5.0	Rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Liquid conductivity (measured)	± 5.0	Rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Liquid permittivity (target)	± 5.0	Rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Liquid permittivity (measured)	± 5.0	Rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Combined Standard Uncertainty						
Expanded Uncertainty (k=2)						
± 9.58						
± 19.16						

Measurement Uncertainty Table in accordance with IEEE Standard 1528-2003 (see reference [5])

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				13 of 20		

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

17.0 REFERENCES

- [1] Federal Communications Commission, "Radiofrequency radiation exposure evaluation: portable devices", Rule Part 47 CFR §2.1093: 1999.
- [2] Health Canada, "Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency Range from 3 kHz to 300 GHz", Safety Code 6.
- [3] Federal Communications Commission, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields", OET Bulletin 65, Supplement C (Edition 01-01), FCC, Washington, D.C.: June 2001.
- [4] Industry Canada, "Evaluation Procedure for Mobile and Portable Radio Transmitters with respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields", Radio Standards Specification RSS-102 Issue 1 (Provisional): September 1999.
- [5] IEEE Std 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques": June 2003.

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						14 of 20

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

APPENDIX A - SAR MEASUREMENT DATA

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz	 EFJohnson	
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						15 of 20

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

Date Tested: 12/09/04

Face-Held SAR - Radio Transceiver

DUT: E.F. Johnson Model: 4140; Type: Portable FM UHF PTT Radio Transceiver; Serial: n/a (Identical Prototype)

Ambient Temp: 23.1 °C; Fluid Temp: 22.5 °C; Barometric Pressure: 101.4 kPa; Humidity: 30%

Communication System: FM UHF
7.5V 2700mAh NiMH Battery Pack
Frequency: 480 MHz; Duty Cycle: 1:1
RF Output Power: 36.61 dBm (Conducted)
Medium: HSL450 ($\sigma = 0.83$ mho/m; $\epsilon_r = 41.9$; $\rho = 1000$ kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(7.5, 7.5, 7.5); Calibrated: 18/03/2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 14/05/2004
- Phantom: Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Face-Held - 2.5 cm Separation Distance - Mid Channel/Area Scan (8x22x1):

Measurement grid: dx=15mm, dy=15mm


Face-Held - 2.5 cm Separation Distance - Mid Channel/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 51.9 V/m; Power Drift = -1.09 dB

Peak SAR (extrapolated) = 3.27 W/kg

SAR(1 g) = 2.15 mW/g; SAR(10 g) = 1.56 mW/g



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

Date Tested: 12/09/04

Face-Held SAR - Speaker-Microphone with Antenna

DUT: E.F. Johnson Model: 4140; Type: Portable FM PTT Speaker-Microphone with Antenna; P/N: 589-0015-058

Ambient Temp: 23.1 °C; Fluid Temp: 22.5 °C; Barometric Pressure: 101.4 kPa; Humidity: 30%

Communication System: FM UHF
7.5V 2700mAh NiMH Battery Pack
Frequency: 480 MHz; Duty Cycle: 1:1
RF Output Power: 36.59 dBm (Conducted)
Medium: HSL450 ($\sigma = 0.83$ mho/m; $\epsilon_r = 41.9$; $\rho = 1000$ kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(7.5, 7.5, 7.5); Calibrated: 18/03/2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 14/05/2004
- Phantom: Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Face-Held - 2.5 cm Separation Distance - Mid Channel/Area Scan (8x17x1):

Measurement grid: dx=15mm, dy=15mm


Face-Held - 2.5 cm Separation Distance - Mid Channel/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 59.3 V/m; Power Drift = -0.002 dB


Peak SAR (extrapolated) = 5.17 W/kg

SAR(1 g) = 3.29 mW/g; SAR(10 g) = 2.32 mW/g



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						

Z-Axis Scan



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

Date Tested: 12/10/04

Body-Worn SAR - Speaker-Microphone with Antenna

DUT: E.F. Johnson Model: 4140; Type: Portable FM PTT Speaker-Microphone with Antenna; P/N: 589-0015-058

Body-Worn Accessories: Lapel-Clip

Ambient Temp: 23.9 °C; Fluid Temp: 22.4 °C; Barometric Pressure: 101.2 kPa; Humidity: 30%

Communication System: FM UHF

7.5V 2700mAh NiMH Battery Pack

Frequency: 480 MHz; Duty Cycle: 1:1

RF Output Power: 36.81 dBm (Conducted)

Medium: M450 ($\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 57.2$; $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(7.6, 7.6, 7.6); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn353; Calibrated: 06/07/2004

- Phantom: Planar; Type: Plexiglas; Serial: 161

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - 1.2 cm Lapel-Clip Separation Distance - Mid Channel/Area Scan (8x17x1):

Measurement grid: dx=15mm, dy=15mm


Body-Worn - 1.2 cm Lapel-Clip Separation Distance - Mid Channel/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 93.9 V/m; Power Drift = -0.925 dB


Peak SAR (extrapolated) = 11.6 W/kg

SAR(1 g) = 7.35 mW/g; SAR(10 g) = 5.14 mW/g



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						


Z-Axis Scan



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				

SAR-versus-Time Power Drift Evaluation

Body-Worn Configuration
Speaker-Microphone with Antenna
NiMH Battery Pack
Whip Antenna (1/4-Wave)
Mid Channel - 480 MHz



High SAR: 7.58636 mW/g
 Low SAR: 5.38315 mW/g (-1.490 dB)
 SAR after 340s: 5.69073 mW/g (-1.249 dB)
 (340s = Zoom Scan Duration)
 (840s = Area Scan Duration)

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

Date Tested: 12/10/04

Body-Worn SAR - Speaker-Microphone with Antenna

DUT: E.F. Johnson Model: 4140; Type: Portable FM PTT Speaker-Microphone with Antenna; P/N: 589-0015-058

Body-Worn Accessories: Lapel-Clip

Ambient Temp: 23.9 °C; Fluid Temp: 22.4 °C; Barometric Pressure: 101.2 kPa; Humidity: 30%

Communication System: FM UHF

7.5V 2700mAh NiMH Battery Pack

Frequency: 450 MHz; Duty Cycle: 1:1

RF Output Power: 36.81 dBm (Conducted)

Medium: M450 ($\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 57.2$; $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(7.6, 7.6, 7.6); Calibrated: 18/03/2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn353; Calibrated: 06/07/2004
- Phantom: Planar; Type: Plexiglas; Serial: 161
- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - 1.2 cm Lapel-Clip Separation Distance - Low Channel/Area Scan (8x17x1):

Measurement grid: dx=15mm, dy=15mm


Body-Worn - 1.2 cm Lapel-Clip Separation Distance - Low Channel/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 78.2 V/m; Power Drift = -0.101 dB

Peak SAR (extrapolated) = 9.28 W/kg

SAR(1 g) = 5.88 mW/g; SAR(10 g) = 4.12 mW/g



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

Date Tested: 12/10/04

Body-Worn SAR - Speaker-Microphone with Antenna

DUT: E.F. Johnson Model: 4140; Type: Portable FM PTT Speaker-Microphone with Antenna; P/N: 589-0015-058

Body-Worn Accessories: Lapel-Clip

Ambient Temp: 23.9 °C; Fluid Temp: 22.4 °C; Barometric Pressure: 101.2 kPa; Humidity: 30%

Communication System: FM UHF

7.5V 2700mAh NiMH Battery Pack

Frequency: 512 MHz; Duty Cycle: 1:1

RF Output Power: 36.80 dBm (Conducted)

RF Output Power: 36.80 dBm (Conducted) 2nd Maximum

Medium: M450 ($\sigma = 0.93$ mho/m; $\epsilon_r = 57.2$; $\rho = 1000$ kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(7.6, 7.6, 7.6); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn353; Calibrated: 06/07/2004

- Phantom: Planar; Type: Plexiglas; Serial: 161

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - 1.2 cm Lapel-Clip Separation Distance - High Channel/Area Scan (8x17x1):

Measurement grid: dx=15mm, dy=15mm

Body-Worn - 1.2 cm Lapel-Clip Separation Distance - High Channel/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 84.9 V/m; Power Drift = -0.247 dB

Peak SAR (extrapolated) = 10.9 W/kg

SAR(1 g) = 6.89 mW/g; SAR(10 g) = 4.78 mW/g


Body-Worn - 1.2 cm Lapel-Clip Separation Distance - High Channel/Zoom Scan 2 (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 86.2 V/m; Power Drift = -0.122 dB

Peak SAR (extrapolated) = 10.5 W/kg

SAR(1 g) = 6.62 mW/g; SAR(10 g) = 4.41 mW/g



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

Date Tested: 12/11/04

Body-Worn SAR - Radio Transceiver

DUT: E.F. Johnson Model: 4140; Type: Portable FM UHF PTT Radio Transceiver; Serial: n/a (Identical Prototype)

Body-Worn Accessories: Belt-Clip (P/N: 585-5100-128), Speaker-Microphone (P/N: 589-0015-057)

Ambient Temp: 23.1 °C; Fluid Temp: 22.4 °C; Barometric Pressure: 102.6 kPa; Humidity: 30%

Communication System: FM UHF

7.5V 2700mAh NiMH Battery Pack

Frequency: 480 MHz; Duty Cycle: 1:1

RF Output Power: 36.73 dBm (Conducted)

Medium: M450 ($\sigma = 0.91 \text{ mho/m}$; $\epsilon_r = 56.9$; $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(7.6, 7.6, 7.6); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn353; Calibrated: 06/07/2004

- Phantom: Planar; Type: Plexiglas; Serial: 161

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - 1.3 cm Belt-Clip Separation Distance - Mid Channel/Area Scan (8x22x1):

Measurement grid: dx=15mm, dy=15mm


Body-Worn - 1.3 cm Belt-Clip Separation Distance - Mid Channel/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 72.3 V/m; Power Drift = -0.131 dB

Peak SAR (extrapolated) = 7.91 W/kg

SAR(1 g) = 4.64 mW/g; SAR(10 g) = 3.13 mW/g



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

Date Tested: 12/11/04

Body-Worn SAR - Radio Transceiver

DUT: E.F. Johnson Model: 4140; Type: Portable FM UHF PTT Radio Transceiver; Serial: n/a (Identical Prototype)

Body-Worn Accessories: Belt-Clip (P/N: 585-5100-128), Boom-Microphone Headset (P/N: 589-0015-059)

Ambient Temp: 23.1 °C; Fluid Temp: 22.4 °C; Barometric Pressure: 102.6 kPa; Humidity: 30%

Communication System: FM UHF

7.5V 2700mAh NiMH Battery Pack

Frequency: 480 MHz; Duty Cycle: 1:1

RF Output Power: 36.72 dBm (Conducted)

Medium: M450 ($\sigma = 0.91 \text{ mho/m}$; $\epsilon_r = 56.9$; $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(7.6, 7.6, 7.6); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn353; Calibrated: 06/07/2004

- Phantom: Planar; Type: Plexiglas; Serial: 161

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body-Worn - 1.3 cm Belt-Clip Separation Distance - Mid Channel/Area Scan (8x22x1):

Measurement grid: dx=15mm, dy=15mm


Body-Worn - 1.3 cm Belt-Clip Separation Distance - Mid Channel/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 70.8 V/m; Power Drift = -0.775 dB


Peak SAR (extrapolated) = 8.58 W/kg

SAR(1 g) = 5.04 mW/g; SAR(10 g) = 3.42 mW/g



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						

Z-Axis Scan



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

APPENDIX B - SYSTEM PERFORMANCE CHECK DATA

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				16 of 20	

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

Date Tested: 12/09/04

System Performance Check - 450 MHz Dipole

DUT: Dipole 450 MHz; Model: D450V2; Type: System Performance Check; Serial: 136; Calibrated: 11/04/2004

Ambient Temp: 23.1 °C; Fluid Temp: 22.5 °C; Barometric Pressure: 101.9 kPa; Humidity: 30%

Communication System: CW

Forward Conducted Power: 250 mW

Frequency: 450 MHz; Duty Cycle: 1:1

Medium: HSL450 ($\sigma = 0.83 \text{ mho/m}$; $\epsilon_r = 41.9$; $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(7.5, 7.5, 7.5); Calibrated: 18/03/2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 14/05/2004
- Phantom: Validation Planar; Type: Plexiglas; Serial: 137
- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

450 MHz Dipole - System Performance Check/Area Scan (6x11x1):

Measurement grid: dx=15mm, dy=15mm


450 MHz Dipole - System Performance Check/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 40.2 V/m; Power Drift = -0.1 dB


Peak SAR (extrapolated) = 2.21 W/kg

SAR(1 g) = 1.25 mW/g; SAR(10 g) = 0.803 mW/g



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		380 - 470 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						

Z-Axis Scan



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		380 - 470 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

Date Tested: 12/10/04

System Performance Check - 450 MHz Dipole

DUT: Dipole 450 MHz; Model: D450V2; Type: System Performance Check; Serial: 136; Calibrated: 11/04/2004

Ambient Temp: 23.2 °C; Fluid Temp: 22.3 °C; Barometric Pressure: 101.8 kPa; Humidity: 30%

Communication System: CW

Forward Conducted Power: 250 mW

Frequency: 450 MHz; Duty Cycle: 1:1

Medium: HSL450 ($\sigma = 0.84 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(7.5, 7.5, 7.5); Calibrated: 18/03/2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn370; Calibrated: 14/05/2004
- Phantom: Validation Planar; Type: Plexiglas; Serial: 137
- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

450 MHz Dipole - System Performance Check/Area Scan (6x11x1):

Measurement grid: dx=15mm, dy=15mm


450 MHz Dipole - System Performance Check/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 39.9 V/m; Power Drift = -0.0 dB


Peak SAR (extrapolated) = 2.22 W/kg

SAR(1 g) = 1.27 mW/g; SAR(10 g) = 0.815 mW/g



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		380 - 470 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						

Z-Axis Scan



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		380 - 470 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

Date Tested: 12/11/04

System Performance Check - 450 MHz Dipole

DUT: Dipole 450 MHz; Model: D450V2; Type: System Performance Check; Serial: 136; Calibrated: 11/04/2004

Ambient Temp: 22.8 °C; Fluid Temp: 22.6 °C; Barometric Pressure: 102.5 kPa; Humidity: 31%

Communication System: CW

Forward Conducted Power: 250 mW

Frequency: 450 MHz; Duty Cycle: 1:1

Medium: HSL450 ($\sigma = 0.86$ mho/m; $\epsilon_r = 42.8$; $\rho = 1000$ kg/m³)

- Probe: ET3DV6 - SN1387; ConvF(7.5, 7.5, 7.5); Calibrated: 18/03/2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn353; Calibrated: 06/07/2004
- Phantom: Validation Planar; Type: Plexiglas; Serial: 137
- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

450 MHz Dipole - System Performance Check/Area Scan (6x11x1):

Measurement grid: dx=15mm, dy=15mm


450 MHz Dipole - System Performance Check/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 39.7 V/m; Power Drift = -0.0 dB


Peak SAR (extrapolated) = 2.26 W/kg

SAR(1 g) = 1.28 mW/g; SAR(10 g) = 0.822 mW/g



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						

Z-Axis Scan



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

APPENDIX C - SYSTEM VALIDATION

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						17 of 20

450 MHz SYSTEM VALIDATION DIPOLE

Type:

450 MHz Validation Dipole

Serial Number:

136

Place of Calibration:

Celltech Labs Inc.

Date of Calibration:

November 4, 2004

Celltech Labs Inc. hereby certifies that this device has been calibrated on the date indicated above.

Calibrated by:



Approved by:




1. Dipole Construction & Electrical Characteristics

The validation dipole was constructed in accordance with the IEEE Std "Recommended Practice for Determining the Spatial-Peak Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques". The electrical properties were measured using an HP 8753E Network Analyzer. The network analyzer was calibrated to the validation dipole N-type connector feed point using an HP85032E Type N calibration kit. The dipole was placed parallel to a planar phantom at a separation distance of 15.0mm from the simulating fluid using a loss-less dielectric spacer. The measured input impedance is:

Feed point impedance at 450MHz $\text{Re}\{Z\} = 54.041\Omega$


$\text{Im}\{Z\} = 5.5258\Omega$


Return Loss at 450MHz -23.744dB



4 Nov 2004 09:03:54

1: -23.744 dB 450.000 000 MHz





2. Validation Dipole Dimensions

Frequency (MHz)	L (mm)	h (mm)	d (mm)
300	420.0	250.0	6.2
450	288.0	167.0	6.2
835	161.0	89.8	3.6
900	149.0	83.3	3.6
1450	89.1	51.7	3.6
1800	72.0	41.7	3.6
1900	68.0	39.5	3.6
2000	64.5	37.5	3.6
2450	51.8	30.6	3.6
3000	41.5	25.0	3.6




3. Validation Phantom

The validation phantom was constructed using relatively low-loss tangent Plexiglas material. The inner dimensions of the phantom are as follows:

Length: 83.5 cm
 Width: 36.9 cm
 Height: 21.8 cm

The bottom section of the validation phantom is constructed of 6.2 ± 0.1 mm Plexiglas.


4. Dimensions of Plexiglas Planar Phantom



5. 450 MHz System Validation Setup



450 MHz Validation Dipole Setup



6. Measurement Conditions

The planar phantom was filled with brain simulating tissue having the following parameters at 450 MHz:

Relative Permittivity: 42.9
 Conductivity: 0.85 mho/m
 Fluid Temperature: 21.9 °C
 Fluid Depth: ≥ 15.0 cm

Environmental Conditions:


Ambient Temperature: 22.4 °C
 Humidity: 31 %
 Barometric Pressure: 103.2 kPa

The 450 MHz simulated brain tissue mixture consists of the following ingredients:

Ingredient	Percentage by weight
Water	38.56%
Sugar	56.32%
Salt	3.95%
HEC	0.98%
Dowicil 75	0.19%
450 MHz Target Dielectric Parameters at 22 °C	$\epsilon_r = 43.5$ $\sigma = 0.87 \text{ S/m}$

7. SAR Measurement

The SAR measurement was performed with the E-field probe in mechanical detection mode only. The setup and determination of the forward power into the dipole was performed using the following procedures.



First the power meter PM1 (including attenuator Att1) is connected to the cable to measure the forward power at the location of the dipole connector (X). The signal generator is adjusted for the desired forward power at the dipole connector (taking into account the attenuation of Att1) as read by power meter PM2. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter PM2. If the signal generator does not allow adjustment in 0.01dB steps, the remaining difference at PM2 must be taken into consideration. PM3 records the reflected power from the dipole to ensure that the value is not changed from the previous value. The reflected power should be 20dB below the forward power.

8. Validation Dipole SAR Test Results

Ten SAR measurements were performed in order to achieve repeatability and to establish an average target value.

Validation Measurement	SAR @ 0.25W Input averaged over 1g	SAR @ 1W Input averaged over 1g	SAR @ 0.25W Input averaged over 10g	SAR @ 1W Input averaged over 10g	Peak SAR @ 0.25W Input
Test 1	1.22	4.88	0.782	3.128	1.29
Test 2	1.23	4.92	0.791	3.164	1.30
Test 3	1.23	4.92	0.789	3.156	1.30
Test 4	1.23	4.92	0.790	3.160	1.31
Test 5	1.24	4.96	0.793	3.172	1.31
Test 6	1.24	4.96	0.792	3.168	1.31
Test 7	1.23	4.92	0.791	3.164	1.31
Test 8	1.23	4.92	0.789	3.156	1.30
Test 9	1.24	4.96	0.791	3.164	1.31
Test 10	1.23	4.92	0.789	3.156	1.31
Average Value	1.23	4.93	0.790	3.16	1.31

The results have been normalized to 1W (forward power) into the dipole.

IEEE Target over 1cm³ (1g) of tissue: 4.9 mW/g (+/- 10%)

Averaged over 1cm (1g) of tissue: 4.93 mW/g (deviation +0.6%)

IEEE Target over 10cm³ (10g) of tissue: 3.3 mW/g (+/- 10%)

Averaged over 10cm (10g) of tissue: 3.16 mW/g (deviation -4.2%)

450 MHz System Validation - November 4, 2004

DUT: Dipole 450 MHz; Model: D450V2; Serial: 136; Calibrated: 11/04/2004

Ambient Temp: 22.4 °C; Fluid Temp: 21.9 °C; Barometric Pressure: 103.2 kPa; Humidity: 31%

Communication System: CW

Frequency: 450 MHz; Duty Cycle: 1:1

Medium: HSL450 ($\sigma = 0.85 \text{ mho/m}$; $\epsilon_r = 42.9$; $\rho = 1000 \text{ kg/m}^3$)

- Probe: ET3DV6 - SN1387; ConvF(7.5, 7.5, 7.5); Calibrated: 18/03/2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn370; Calibrated: 14/05/2004

- Phantom: Validation Planar; Type: Plexiglas; Serial: 137

- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

450 MHz System Validation/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

450 MHz System Validation/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 39.3 V/m; Power Drift = -0.1 dB

Peak SAR (extrapolated) = 2.15 W/kg

SAR(1 g) = 1.22 mW/g; SAR(10 g) = 0.782 mW/g

450 MHz System Validation/Zoom Scan 2 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 39.2 V/m; Power Drift = -0.0 dB

Peak SAR (extrapolated) = 2.16 W/kg

SAR(1 g) = 1.23 mW/g; SAR(10 g) = 0.791 mW/g

450 MHz System Validation/Zoom Scan 3 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 39.1 V/m; Power Drift = -0.004 dB

Peak SAR (extrapolated) = 2.16 W/kg

SAR(1 g) = 1.23 mW/g; SAR(10 g) = 0.789 mW/g

450 MHz System Validation/Zoom Scan 4 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 39.2 V/m; Power Drift = -0.0 dB

Peak SAR (extrapolated) = 2.18 W/kg

SAR(1 g) = 1.23 mW/g; SAR(10 g) = 0.790 mW/g

450 MHz System Validation/Zoom Scan 5 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 39.2 V/m; Power Drift = 0.009 dB

Peak SAR (extrapolated) = 2.18 W/kg

SAR(1 g) = 1.24 mW/g; SAR(10 g) = 0.793 mW/g

450 MHz System Validation/Zoom Scan 6 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 39.1 V/m; Power Drift = 0.007 dB

Peak SAR (extrapolated) = 2.18 W/kg

SAR(1 g) = 1.24 mW/g; SAR(10 g) = 0.792 mW/g

450 MHz System Validation/Zoom Scan 7 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 39.2 V/m; Power Drift = 0.004 dB

Peak SAR (extrapolated) = 2.18 W/kg

SAR(1 g) = 1.23 mW/g; SAR(10 g) = 0.791 mW/g

450 MHz System Validation/Zoom Scan 8 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 39.2 V/m; Power Drift = 0.0 dB

Peak SAR (extrapolated) = 2.16 W/kg

SAR(1 g) = 1.23 mW/g; SAR(10 g) = 0.789 mW/g

450 MHz System Validation/Zoom Scan 9 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 39.4 V/m; Power Drift = 0.0 dB

Peak SAR (extrapolated) = 2.19 W/kg


SAR(1 g) = 1.24 mW/g; SAR(10 g) = 0.791 mW/g

450 MHz System Validation/Zoom Scan 10 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 39.1 V/m; Power Drift = 0.007 dB


Peak SAR (extrapolated) = 2.16 W/kg

SAR(1 g) = 1.23 mW/g; SAR(10 g) = 0.789 mW/g



1 g average of 10 measurements: 1.23 mW/g

10 g average of 10 measurements: 0.790 mW/g



450MHz System Validation

Measured Fluid Dielectric Parameters (Brain)

November 04, 2004

Frequency	e'	e"
350.000000 MHz	45.3974	39.4988
360.000000 MHz	45.0834	38.7858
370.000000 MHz	44.8651	38.1777
380.000000 MHz	44.6622	37.6103
390.000000 MHz	44.3761	37.1472
400.000000 MHz	44.1745	36.5919
410.000000 MHz	43.8392	36.0417
420.000000 MHz	43.6277	35.5608
430.000000 MHz	43.3443	34.9958
440.000000 MHz	43.1200	34.5629
450.000000 MHz	42.8999	34.1583
460.000000 MHz	42.7154	33.7478
470.000000 MHz	42.4773	33.4083
480.000000 MHz	42.2998	33.0563
490.000000 MHz	42.0302	32.7340
500.000000 MHz	41.8641	32.3576
510.000000 MHz	41.6518	31.9703
520.000000 MHz	41.4863	31.6232
530.000000 MHz	41.2685	31.3144
540.000000 MHz	41.1027	30.8977
550.000000 MHz	40.9455	30.6347

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

APPENDIX D - PROBE CALIBRATION

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						18 of 20

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

Client

Celltech

CALIBRATION CERTIFICATE

Object(s)	ET3DV6 - SN:1387
Calibration procedure(s)	QA CAL-01.v2 Calibration procedure for dosimetric E-field probes
Calibration date:	March 18, 2004
Condition of the calibrated item	In Tolerance (according to the specific calibration document)

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature 22 +/- 2 degrees Celsius and humidity < 75%.

Calibration Equipment used (M&TE critical for calibration)

Model Type	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter EPM E4419B	GB41293874	2-Apr-03 (METAS, No 252-0250)	Apr-04
Power sensor E4412A	MY41495277	2-Apr-03 (METAS, No 252-0250)	Apr-04
Reference 20 dB Attenuator	SN: 5086 (20b)	3-Apr-03 (METAS, No. 251-0340)	Apr-04
Fluke Process Calibrator Type 702	SN: 6295803	8-Sep-03 (Sintrel SCS No. E-030020)	Sep-04
Power sensor HP 8481A	MY41092180	18-Sep-02 (SPEAG, in house check Oct-03)	In house check: Oct 05
RF generator HP 8684C	US3642U01700	4-Aug-99 (SPEAG, in house check Aug-02)	In house check: Aug-05
Network Analyzer HP 8753E	US37390585	18-Oct-01 (SPEAG, in house check Oct-03)	In house check: Oct 05

Calibrated by: **Name** **Function** **Signature**
Nico Vetterli Technician 

Approved by: **Name** **Function** **Signature**
Katja Pokovic Laboratory Director 

Date issued: March 18, 2004

This calibration certificate is issued as an intermediate solution until the accreditation process (based on ISO/IEC 17025 International Standard) for Calibration Laboratory of Schmid & Partner Engineering AG is completed.

Probe ET3DV6

SN:1387

Manufactured:	September 21, 1999
Last calibrated:	February 26, 2003
Recalibrated:	March 18, 2004

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)

DASY - Parameters of Probe: ET3DV6 SN:1387

Sensitivity in Free Space		Diode Compression ^A		
NormX	1.62 $\mu\text{V}/(\text{V}/\text{m})^2$	DCP X	92	mV
NormY	1.71 $\mu\text{V}/(\text{V}/\text{m})^2$	DCP Y	92	mV
NormZ	1.71 $\mu\text{V}/(\text{V}/\text{m})^2$	DCP Z	92	mV

Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 7.

Boundary Effect

Head 900 MHz Typical SAR gradient: 5 % per mm

Sensor Center to Phantom Surface Distance	3.7 mm	4.7 mm
SAR _{be} [%] Without Correction Algorithm	9.3	4.4
SAR _{be} [%] With Correction Algorithm	0.0	0.1

Head 1800 MHz Typical SAR gradient: 10 % per mm

Sensor to Surface Distance	3.7 mm	4.7 mm
SAR _{be} [%] Without Correction Algorithm	14.8	10.0
SAR _{be} [%] With Correction Algorithm	0.2	0.0

Sensor Offset


Probe Tip to Sensor Center	2.7 mm
Optical Surface Detection	in tolerance

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.



^A numerical linearization parameter: uncertainty not required

Frequency Response of E-Field

(TEM-Cell:ifi110, Waveguide R22)




Receiving Pattern (ϕ), $\theta = 0^\circ$





Axial Isotropy Error $< \pm 0.2$ dB

Dynamic Range f(SAR_{head}) (Waveguide R22)



Probe Linearity $< \pm 0.2 \text{ dB}$

Conversion Factor Assessment




f [MHz]	Validity [MHz] ^B	Tissue	Permittivity	Conductivity	Alpha	Depth	ConvF	Uncertainty
835	750-950	Head	$41.5 \pm 5\%$	$0.90 \pm 5\%$	0.72	1.78	6.71	$\pm 11.9\% \text{ (k=2)}$
1750	1700-1800	Head	$40.0 \pm 5\%$	$1.40 \pm 5\%$	0.51	2.67	5.38	$\pm 9.7\% \text{ (k=2)}$
1900	1850-1950	Head	$40.0 \pm 5\%$	$1.40 \pm 5\%$	0.55	2.66	5.25	$\pm 9.7\% \text{ (k=2)}$
2450	2400-2500	Head	$39.2 \pm 5\%$	$1.80 \pm 5\%$	0.99	1.89	4.77	$\pm 9.7\% \text{ (k=2)}$

835	750-950	Body	$55.2 \pm 5\%$	$0.97 \pm 5\%$	0.56	2.04	6.24	$\pm 11.9\% \text{ (k=2)}$
1750	1700-1800	Body	$53.3 \pm 5\%$	$1.52 \pm 5\%$	0.58	2.82	4.68	$\pm 9.7\% \text{ (k=2)}$
1900	1850-1950	Body	$53.3 \pm 5\%$	$1.52 \pm 5\%$	0.62	2.77	4.57	$\pm 9.7\% \text{ (k=2)}$
2450	2400-2500	Body	$52.7 \pm 5\%$	$1.95 \pm 5\%$	1.75	1.28	4.50	$\pm 9.7\% \text{ (k=2)}$

^B The total standard uncertainty is calculated as root-sum-square of standard uncertainty of the Conversion Factor at calibration frequency and the standard uncertainty for the indicated frequency band.

Deviation from Isotropy in HSL

Error (θ, ϕ), f = 900 MHz



Additional Conversion Factors for Dosimetric E-Field Probe

Type:

ET3DV6

Serial Number:

1387

Place of Assessment:

Zurich

Date of Assessment:


March 22, 2004

Probe Calibration Date:

March 18, 2004

Schmid & Partner Engineering AG hereby certifies that conversion factor(s) of this probe have been evaluated on the date indicated above. The assessment was performed using the FDTD numerical code SEMCAD of Schmid & Partner Engineering AG. Since the evaluation is coupled with measured conversion factors, it has to be recalculated yearly, i.e., following the re-calibration schedule of the probe. The uncertainty of the numerical assessment is based on the extrapolation from measured value at 900 MHz or at 1800 MHz.

Assessed by:



Dosimetric E-Field Probe ET3DV6 SN:1387

Conversion factor (\pm standard deviation)

150 MHz	ConvF	9.1 \pm 8%	$\epsilon_r = 52.3 \pm 5\%$ $\sigma = 0.76 \pm 5\%$ mho/m (head tissue)
300 MHz	ConvF	7.8 \pm 8%	$\epsilon_r = 45.3 \pm 5\%$ $\sigma = 0.87 \pm 5\%$ mho/m (head tissue)
450 MHz	ConvF	7.5 \pm 8%	$\epsilon_r = 43.5 \pm 5\%$ $\sigma = 0.87 \pm 5\%$ mho/m (head tissue)
150 MHz	ConvF	8.7 \pm 8%	$\epsilon_r = 61.9 \pm 5\%$ $\sigma = 0.80 \pm 5\%$ mho/m (body tissue)
450 MHz	ConvF	7.6 \pm 8%	$\epsilon_r = 56.7 \pm 5\%$ $\sigma = 0.94 \pm 5\%$ mho/m (body tissue)

Important Note:

For numerically assessed probe conversion factors, parameters Alpha and Delta in the DASY software must have the following entries: Alpha = 0 and Delta = 1.

Please see also Section 4.7 of the DASY4 Manual.

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

APPENDIX E - MEASURED FLUID DIELECTRIC PARAMETERS

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz	 EFJohnson	
2004 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.					19 of 20

450 MHz System Performance Check & DUT Evaluation (Face)

Measured Fluid Dielectric Parameters (Brain)

December 09, 2004

Frequency	e'	e"
350.000000 MHz	44.3273	38.3101
360.000000 MHz	44.0912	37.6822
370.000000 MHz	43.9406	37.1106
380.000000 MHz	43.7578	36.5722
390.000000 MHz	43.4880	36.1154
400.000000 MHz	43.0976	35.5947
410.000000 MHz	42.8077	35.0873
420.000000 MHz	42.5167	34.5553
430.000000 MHz	42.3264	34.0343
440.000000 MHz	42.0815	33.6113
450.000000 MHz	41.9048	33.1416
460.000000 MHz	41.7461	32.8080
470.000000 MHz	41.6084	32.4495
480.000000 MHz	41.3624	32.1491
490.000000 MHz	41.1396	31.8238
500.000000 MHz	40.9138	31.4280
510.000000 MHz	40.6981	31.0466
520.000000 MHz	40.5395	30.6708
530.000000 MHz	40.3284	30.3822
540.000000 MHz	40.1387	29.9909
550.000000 MHz	39.9739	29.7105

450 MHz System Performance Check

Measured Fluid Dielectric Parameters (Brain)

December 10, 2004

Frequency	e'	e"
350.000000 MHz	44.9587	38.6442
360.000000 MHz	44.6630	38.0229
370.000000 MHz	44.4701	37.4782
380.000000 MHz	44.2988	37.0245
390.000000 MHz	44.0314	36.6602
400.000000 MHz	43.7753	36.1259
410.000000 MHz	43.4511	35.4648
420.000000 MHz	43.2217	34.9617
430.000000 MHz	42.9720	34.4559
440.000000 MHz	42.7478	34.0555
450.000000 MHz	42.5062	33.6013
460.000000 MHz	42.2656	33.2129
470.000000 MHz	42.1283	32.9062
480.000000 MHz	41.8822	32.5416
490.000000 MHz	41.6558	32.2413
500.000000 MHz	41.3799	31.8941
510.000000 MHz	41.1917	31.5139
520.000000 MHz	41.0438	31.1415
530.000000 MHz	40.8457	30.8239
540.000000 MHz	40.6775	30.4579
550.000000 MHz	40.4962	30.2087

450 MHz DUT Evaluation (Body)

Measured Fluid Dielectric Parameters (Muscle)

December 10, 2004

Frequency	e'	e"
350.000000 MHz	58.8827	43.2593
360.000000 MHz	58.6228	42.5081
370.000000 MHz	58.5161	41.7811
380.000000 MHz	58.3430	41.1003
390.000000 MHz	58.2189	40.4103
400.000000 MHz	58.1196	39.8322
410.000000 MHz	57.9055	39.1757
420.000000 MHz	57.7981	38.6098
430.000000 MHz	57.5629	37.9826
440.000000 MHz	57.3913	37.4873
450.000000 MHz	57.2048	37.0252
460.000000 MHz	57.0669	36.5343
470.000000 MHz	56.9501	36.0762
480.000000 MHz	56.7779	35.5929
490.000000 MHz	56.5924	35.1841
500.000000 MHz	56.4815	34.8439
510.000000 MHz	56.3594	34.4323
520.000000 MHz	56.2321	34.0529
530.000000 MHz	56.0889	33.6569
540.000000 MHz	55.9876	33.2806
550.000000 MHz	55.8296	32.9541

450 MHz System Performance Check

Measured Fluid Dielectric Parameters (Brain)

December 11, 2004

Frequency	e'	e"
350.000000 MHz	45.3406	39.5178
360.000000 MHz	44.9434	38.8615
370.000000 MHz	44.7207	38.2754
380.000000 MHz	44.4615	37.7469
390.000000 MHz	44.1958	37.2361
400.000000 MHz	43.9840	36.7231
410.000000 MHz	43.7505	36.1360
420.000000 MHz	43.5246	35.6756
430.000000 MHz	43.2615	35.0959
440.000000 MHz	42.9897	34.6494
450.000000 MHz	42.8077	34.2286
460.000000 MHz	42.6087	33.8287
470.000000 MHz	42.4043	33.4019
480.000000 MHz	42.1711	33.0241
490.000000 MHz	41.9349	32.6803
500.000000 MHz	41.7153	32.2803
510.000000 MHz	41.5300	31.9408
520.000000 MHz	41.3110	31.6531
530.000000 MHz	41.1406	31.3204
540.000000 MHz	40.9879	30.9654
550.000000 MHz	40.7874	30.7096

450 MHz DUT Evaluation (Body)

Measured Fluid Dielectric Parameters (Muscle)

December 11, 2004


Frequency	e'	e"
350.000000 MHz	58.4486	42.8125
360.000000 MHz	58.2100	42.1431
370.000000 MHz	58.0752	41.4106
380.000000 MHz	57.9065	40.7750
390.000000 MHz	57.7532	40.1234
400.000000 MHz	57.6224	39.5614
410.000000 MHz	57.4993	38.8979
420.000000 MHz	57.3240	38.2627
430.000000 MHz	57.1825	37.6185
440.000000 MHz	57.0421	37.0592
450.000000 MHz	56.8538	36.5704
460.000000 MHz	56.7415	36.1422
470.000000 MHz	56.5925	35.6918
480.000000 MHz	56.4581	35.2825
490.000000 MHz	56.2738	34.8638
500.000000 MHz	56.0532	34.4865
510.000000 MHz	55.9051	34.0904
520.000000 MHz	55.7920	33.7507
530.000000 MHz	55.6711	33.3579
540.000000 MHz	55.5722	32.9729
550.000000 MHz	55.4163	32.6378

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

APPENDIX F - SAR TEST SETUP & DUT PHOTOGRAPHS



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz	 EFJohnson	
2004 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.					20 of 20

FACE-HELD SAR TEST SETUP PHOTOGRAPHS
Radio Transceiver
2.5 cm Separation Distance to Planar Phantom



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				


FACE-HELD SAR TEST SETUP PHOTOGRAPHS
Speaker-Microphone with Antenna
2.5 cm Separation Distance to Planar Phantom



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						

BODY-WORN SAR TEST SETUP PHOTOGRAPHS


Radio Transceiver with Boom-Microphone Headset
1.3 cm Belt-Clip Separation Distance to Planar Phantom



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.						

BODY-WORN SAR TEST SETUP PHOTOGRAPHS

Radio Transceiver with Speaker-Microphone
1.3 cm Belt-Clip Separation Distance to Planar Phantom





Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				

BODY-WORN SAR TEST SETUP PHOTOGRAPHS


Speaker-Microphone with Antenna

1.2 cm Lapel-Clip Separation Distance to Planar Phantom



Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

SAR TEST SETUP PHOTOGRAPHS**Face-Held Configuration****Body-Worn Configuration**

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				

DUT PHOTOGRAPHS



Front of Radio
with 1/4-Wave Whip Antenna



Back of Radio



Back of Radio
with Belt-Clip

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

DUT PHOTOGRAPHS



Top of Radio



Bottom of Radio

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.					

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

DUT PHOTOGRAPHS



Left Side of Radio with Belt-Clip



Right Side of Radio with Belt-Clip



Belt-Clip P/N: 585-5100-128 (Plastic with metal spring)

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.					

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

DUT PHOTOGRAPHS



Radio Battery Compartment



NiMH Battery



NiMH Battery



Whip Antenna (P/N: 501-0017-107)

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.					

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

DUT PHOTOGRAPHS



Radio with Boom-Microphone Headset Accessory (P/N: 589-0015-059)



Radio with Speaker-Microphone Accessory (P/N: 589-0015-057)

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

DUT PHOTOGRAPHS
Speaker-Microphone with Antenna and Lapel-Clip



Front Side



Top Side



Left Side



Right Side

Bottom Side

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

DUT PHOTOGRAPHS

Speaker-Microphone with Antenna and Lapel-Clip



Left Side



Right Side

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

DUT PHOTOGRAPHS
Radio Transceiver and Speaker-Microphone with Antenna

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.					

Test Report S/N:	120304ATH-T600-S90U
Test Date(s):	December 09-11, 2004
Test Type:	FCC/IC SAR Evaluation

DUT PHOTOGRAPHS




Radio RF Antenna Connector



Speaker-Microphone with Antenna
Connector & Terminator



Front View of Antenna Termination



Back View of Antenna Termination

Applicant:	E.F. Johnson Co.		FCC ID:	ATH2424140	IC ID:	933B-2424140
Model(s):	4140	Portable FM UHF PTT Radio Transceiver		450 - 512 MHz		
2004 Celltech Labs Inc.		This document is not to be reproduced in whole or in part without the written permission of Celltech Labs Inc.				