

# ***FCC Part 15 Subpart C***

## ***TEST REPORT***

*of*

E.U.T. : DVD PLAYER WITH 8.5”  
OVERHEAD LCD MONITOR  
FCC ID. : ATI9R3ADV8SF  
MODEL : ADV8SF, ODM88502  
Working Frequency : 88.1~91.1 MHz

*for*

APPLICANT : ACTION ELECTRONICS CO., LTD.  
ADDRESS : 2480, TINGKAT PERUSAHAAN ENAM, PRAI  
FREE TRADE ZONE, 13600, PERAI, PENANG,  
MALAYSIA.

Test Performed by

**ELECTRONICS TESTING CENTER, TAIWAN**

NO. 34. LIN 5. DINGFU TSUEN, LINKOU SHIANG  
TAIPEI COUNTY, TAIWAN, 24442, R.O.C.

<http://www.etc.org.tw> ; e-mail : [emc@etc.org.tw](mailto:emc@etc.org.tw)  
Tel:(02)26023052 Fax:(02)26010910

Report Number: 09-03-RBF-024-02

## TEST REPORT CERTIFICATION

Applicant : ACTION ELECTRONICS CO., LTD.  
2480, TINGKAT PERUSAHAAN ENAM, PRAI FREE  
TRADE ZONE, 13600, PERAI, PENANG, MALAYSIA.


Manufacturer : ACTION ELECTRONICS CO., LTD.  
2480, TINGKAT PERUSAHAAN ENAM, PRAI FREE  
TRADE ZONE, 13600, PERAI, PENANG, MALAYSIA.

Description of EUT :  
a) Type of EUT : DVD PLAYER WITH 8.5"  
OVERHEAD LCD MONITOR  
b) Trade Name : ADVENT, AXION  
c) Model No : ADV8SF, ODM88502  
d) Working Frequency : 88.1~91.1 MHz  
e) Power Supply : DC 12V

Regulation Applied : FCC Rules and Regulations Part 15 Subpart C (2008)

I HEREBY CERTIFY THAT; The data shown in this report were made in accordance with the procedures given in ANSI C63.4 and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Issued Date : Apr. 22, 2009

Test Engineer :   
( Vincent Chang )

Approve & Authorized Signer :   
Will Yauo, Manager  
EMC Dept. II of ELECTRONICS  
TESTING CENTER, TAIWAN

## Table of Contents

<b>1. GENERAL INFORMATION .....</b>	<b>1</b>
1.1 Product Description.....	1
1.2 Test Methodology .....	1
1.3 Test Facility.....	1
<b>2. DEFINITION AND LIMITS.....</b>	<b>2</b>
2.1 Definition .....	2
2.2 Restricted Bands of Operation .....	2
2.3 Limitation.....	2
2.4 Labeling Requirement .....	3
2.5 User Information .....	3
<b>3. SYSTEM TEST CONFIGURATION .....</b>	<b>4</b>
3.1 Justification.....	4
3.2 Devices for Tested System.....	4
<b>4 RADIATED EMISSION MEASUREMENT.....</b>	<b>5</b>
4.1 Applicable Standard .....	5
4.2 Measurement Procedure.....	5
4.3 Measuring Instrument .....	7
4.4 Test Data .....	8
4.5 Field Strength Calculation.....	10
4.6 Radiated Measurement Photos.....	11
<b>5 CONDUCTED EMISSION MEASUREMENT .....</b>	<b>12</b>
5.1 Standard Applicable .....	12
<b>6 ANTENNA REQUIREMENT .....</b>	<b>13</b>
6.1 Standard Applicable .....	13
6.2 Antenna Construction .....	13
<b>7 EMISSION BAND MEASUREMENT.....</b>	<b>14</b>
7.1 Standard Applicable .....	14
7.2 Measurement Procedure.....	14
7.3 Measurement Equipment .....	14
7.4 Measurement Data.....	14

## 1. GENERAL INFORMATION

### 1.1 Product Description

- a) Type of EUT : DVD PLAYER WITH 8.5”  
OVERHEAD LCD MONITOR
- b) Trade Name : ADVENT, AXION
- c) Model No. : ADV8SF, ODM88502
- d) Frequency Modulation : 88.1~91.1 MHz
- e) Power Supply : DC 12V
- f) Model Difference : ADV8SF and ODM88502 are the same and their  
Declared by the difference is only the model and brand name designation.  
Manufacturer

### 1.2 Test Methodology

Both conducted and radiated testing was performed according to the procedures in chapter 13 of ANSI C63.4 (2003)

The FM TRANSMITTER was operated in its normal operating mode for the purpose of the measurements. The FM TRANSMITTER was installed in the DVD player. The DVD player was set to play DVD and the volume control was set to maximum.

The receiving antenna polarized horizontally was varied from 1 to 4 meters and the wooden turntable was rotated through 360 degrees to obtain the highest reading on the field strength meter or on the display of the spectrum analyzer. And also, each emission was to be maximized by changing the orientation of the FM TRANSMITTER.

### 1.3 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the roof top of Building at NO. 34. LIN 5. DINGFU TSUEN, LINKOU SHIANG TAIPEI COUNTY, TAIWAN, 24442, R.O.C.

This site has been fully described in a report submitted to your office, and accepted in a letter dated Aug. 05, 2008.

## 2. DEFINITION AND LIMITS

### 2.1 Definition

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

### 2.2 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.15
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3360-4400	Above 38.6
13.36-13.41			

Remark “\*\*\*” : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

### 2.3 Limitation

#### (1) Conducted Emission Limits :

Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency MHz	Quasi Peak dB $\mu$ V	Average dB $\mu$ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

\* Decreases with the logarithm of the frequency

**(2) Radiated Emission Limits :**

According to 15.239 the field strength of emissions from intentional radiators operated under these frequency bands shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental	
	$\mu\text{V}/\text{meter}$	$\text{dB}\mu\text{V}/\text{meter}$
88-108	250	48

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209, as following table:

Other Frequencies (MHz)	Field Strength of Fundamental	
	$\mu\text{V}/\text{meter}$	$\text{dB}\mu\text{V}/\text{meter}$
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

**(3) Antenna Requirement :**

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

**(4) Emissions Band Limits :**

According to 15.239(a), emissions from the intentional radiator shall be confined within a band 200kHz wide centered on the operating frequency. The 200 kHz band shall lie wholly within the frequency range of 88-108 MHz.

**2.4 Labeling Requirement**

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

**2.5 User Information**

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

### 3. SYSTEM TEST CONFIGURATION

#### 3.1 Justification

For both radiated and conducted emissions, the system was configured for testing in a typical fashion as a customer would normally use it. The peripherals other than EUT were connected in normally standing by situation.

All measurement were intentional to maximum the emissions from EUT by varying the connection cables, therefore, the test result is sure to meet the applicable requirement.

#### 3.2 Devices for Tested System

Device	Manufacture	Model / FCC ID.	Description
DVD PLAYER WITH 8.5" OVERHEAD LCD MONITOR *	ACTION ELECTRONICS CO., LTD.	ADV8SF, ODM88502/ AT19R3ADV8SF	0.8m Unshielded DC Power Cable 0.5m Unshielded Signal Cable 0.8m Unshielded Earphone Line
Power Supply	GW	GPC-3030D	1.5m Unshielded AC Power Core
DVD Play	SONY	DVP-NS530	1.5m Unshielded AC Power Core
LCD Monitor	Esonic	HD-0701	1.5m Unshielded AC Adaptor
Earphone	----	----	1.0m Unshielded Line

Remark "\*" means equipment under test.

## 4 RADIATED EMISSION MEASUREMENT

### 4.1 Applicable Standard

For intentional radiators, the radiated emission shall comply with §5.209(a).

### 4.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.
7. Check the three frequencies of highest emission with varying the placement of cables associated with EUT to obtain the worse case and record the result.



Figure 1 : Frequencies measured at 30MHz to 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



### 4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement:

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Test Receiver	Rohde & Schwarz	ESCI	2009/02/04	2010/02/04
Bi-Log Antenna	Schaffner	CBL 6111	2008/06/05	2009/06/05
Log-periodic Antenna	EMCO	3146	2008/10/08	2009/10/08
Biconical Antenna	EMCO	3110B	2008/09/16	2009/09/16
Spectrum	R&S	FSP3	2009/02/27	2010/02/27
Amplifier	HP	8447D	2008/05/16	2009/05/16
Spectrum	Rohde & Schwarz	FSP40	2008/09/11	2009/09/11
Amplifier	HP	83051A	2008/05/23	2009/05/23
Signal generator	HP	HP 83732B	2008/08/07	2009/08/07
Attenuator	WEINSHEL ENGINEERING	AY8986	2008/08/06	2009/08/06

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10Hz

## 4.4 Test Data

### 4.4.1 Fundamental and Harmonics

#### (1) Channel Low

##### A. Fundamental

Fundamental Frequency : 88.1 MHzTest Date : Apr. 17, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave			
88.100	43.8	***	46.1	***	-14.2	31.9	***	68.0	48.0	-16.1	178	1.0

##### B. Harmonics

Fundamental Frequency : 88.1 MHzTest Date : Apr. 17, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
176.200	V	38.9	-9.1	29.8	43.5	-13.7	192	1.0
264.300	V	34.9	-3.8	31.1	46.0	-14.9	182	1.0
352.400	V	47.2	-10.1	37.1	46.0	-8.9	182	1.0
440.500	H/V	---	-5.6	---	46.0	---	---	---
528.600	H/V	---	-5.0	---	46.0	---	---	---
616.700	H/V	---	-3.7	---	46.0	---	---	---
704.800	H/V	---	-1.0	---	46.0	---	---	---
792.900	H/V	---	0.4	---	46.0	---	---	---
881.000	H/V	---	2.3	---	46.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "\*\*\*" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Item "Margin" referred to Average limit while there is only peak result.
5. The expanded uncertainty of the radiated emission tests is 3.53 dB.

**(2) Channel Middle****A. Fundamental**Fundamental Frequency : 91.1 MHzTest Date : Apr. 17, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	Peak	Ave	Peak	Ave		Peak	Ave	Peak	Ave			
91.100	43.9	***	46.8	***	-14.0	32.8	***	68.0	48.0	-15.2	198	1.0

**B. Harmonics**Fundamental Frequency : 91.1 MHzTest Date : Apr. 17, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
182.200	V	38.8	-8.9	29.9	43.5	-13.6	192	1.0
273.300	V	24.6	-3.3	21.3	46.0	-24.7	174	1.0
364.400	V	35.7	-7.9	27.8	46.0	-18.2	182	1.0
455.500	H/V	---	-5.4	---	46.0	---	---	---
546.600	H/V	---	-5.2	---	46.0	---	---	---
637.700	H/V	---	-3.1	---	46.0	---	---	---
728.800	H/V	---	-0.7	---	46.0	---	---	---
819.900	H/V	---	1.3	---	46.0	---	---	---
911.000	H/V	---	2.3	---	46.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "\*\*\*" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Item "Margin" referred to Average limit while there is only peak result.
5. The expanded uncertainty of the radiated emission tests is 3.53 dB.

#### 4.4.2 Other Emissions

Operation Mode : FM Others

Test Date : Apr. 17, 2009 Temperature : 20 °C Humidity : 65 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
39.450	V	49.9	-11.7	38.2	40.0	-1.8	175	1.0
79.410	V	50.1	-15.1	35.0	40.0	-5.0	188	1.0
138.540	V	51.7	-10.9	40.8	43.5	-2.7	192	1.0
216.300	H	46.6	-6.1	40.5	46.0	-5.5	94	1.5
240.060	V	44.0	-4.5	39.5	46.0	-6.5	174	1.0
811.000	V	43.0	1.1	44.1	46.0	-1.9	188	1.0

Note :

1. Remark “---” means that the emissions level is too low to be measured.
2. The expanded uncertainty of the radiated emission tests is 3.53 dB.

#### 4.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

$$\text{Peak} = \text{Reading} + \text{Corrected Factor}$$

where

Corr. Factor = Antenna Factor + Cable Factor - Amplifier Gain (if any)

**4.6 Radiated Measurement Photos**



## **5 CONDUCTED EMISSION MEASUREMENT**

### **5.1 Standard Applicable**

This EUT is excused from investigation of conducted emission, for it is powered by DC only. According to §15.207 (d), measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

## **6 ANTENNA REQUIREMENT**

### **6.1 Standard Applicable**

According to §5.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### **6.2 Antenna Construction**

The antenna is permanently mounted on EUT, no consideration of replacement.



## 7 EMISSION BAND MEASUREMENT

### 7.1 Standard Applicable

According to 15.239(a), emissions from the intentional radiator shall be confined within a band 200kHz wide centered on the operating frequency. The 200 kHz band shall lie wholly within the frequency range of 88-108 MHz.

### 7.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 1 and measurement the turn on the EUT. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 10 kHz and 100kHz respectively with a convenient frequency span including 200kHz bandwidth of the emission.
4. Mark the bandwidth of 200kHz points and plot the graph on spectrum analyzer.
5. Repeat above procedures until all measured frequencies were complete.

### 7.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Amplifier	HP	8447D	2008/05/16	2009/05/16

### 7.4 Measurement Data

Test Date : Apr. 17, 2009      Temperature : 20 °C      Humidity : 65 %

***Test result:***

***The 26 dB bandwidth of 88.1 MHz = 162.0kHz < 200 kHz.***

***The 26 dB bandwidth of 91.1 MHz = 169.0kHz < 200 kHz.***

***The 200 kHz band lie wholly within the frequency range of 88-108 MHz.***

**Note :**

1. Bandwidth test was done with the EUT was playing DVD and the volume control was set to maximum. There is no user controlled function except frequency tuning.
2. Please see the following pages for Plotted Data.




\*RBW 10 kHz    Marker 1 [T1 ]  
VBW 30 kHz        51.70 dBμV  
\*SWT 100 ms       88.068000000 MHz

Ref 70 dBμV

Att 10 dB

1 PK  
VIEW



Center 88.1 MHz                      100 kHz/                      Span 1 MHz




\*RBW 10 kHz    Marker 1 [T1 ]  
VBW 30 kHz        51.41 dBµV  
\*SWT 100 ms       91.071200000 MHz

Ref 70 dBµV

Att 10 dB

1 PK  
VIEW



Center 91.1 MHz

180 kHz/

Span 1.8 MHz



