

# **FCC RF EXPOSURE REPORT**

**FCC ID: ATL-TSBOOM**

**Project No. : 1605C238**  
**Equipment : JUMBO LED Alarm Clock with wireless Shaker**  
**Model : TimeShaker Boom, TSBOOMzzyy (zz=power**  
**version, yy=color version)**  
**Applicant : iLuv Creative Technology**  
**Address : 2 Harbor Park Drive, Port Washington, NY**  
**11050, USA**

**According: : FCC Guidelines for Human Exposure IEEE**  
**C95.1**

**B T L I N C .**

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	Internal	N/A	0

**GENERAL CONCLUSION:**

Maximum measured transmitter power:

Field Strength (dBuV/m)	OutputPower (dBm)	Output Power (mW)	Limit (mW)
39.88	-55.42	0.0000	22

According to FCC KDB447498 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and  $\leq 50$  mm

The maximum measured output peak power of this EUT is 0.0000mW, less than 22mW at 5mm distance.

**Conclusion: No SAR evaluation required since transmitter power is below FCC threshold**