Applicant/Grantee Onkyo corporation						
FCC ID: ATM-BM875A						
Section 15.212 Modular Transmitters						
Request	for Modular Approval Requ	est for Limited Modular Approval				
	Requirements	EUT Conditions	Comply (Y/N)			
Single Modular Approval Requirements						
1	The radio elements of the modular	No have not RF shielding.	N			
	transmitter must have their own	Apply with limited module application				
	shielding. The physical crystal and					
	tuning capacitors may be located					
	external to the shielded radio elements.					
2	The modular transmitter must have	buffered modulation/data inputs is	Y			
	buffered modulation/data inputs (if such	included to the RF chip CSR8675				
	inputs are provided) to ensure that the					
	module will comply with Part 15					
	requirements under conditions of					
	excessive data rates or over-modulation.					
3	The modular transmitter must have its	No have not own power supply	N			
	own power supply regulation.	regulation.				
4	The modular transmitter must comply	A chip antenna is soldered on the	Y			
	with the antenna and transmission	module.				
	system requirements of Sections 15.203,					
	15.204(b) and 15.204(c). The antenna					
	must either be permanently attached or					
	employ a "unique" antenna coupler (at					
	all connections between the module and					
	the antenna, including the cable). The					
	"professional installation" provision of Section 15.203 is not applicable to					
	modules but can apply to limited					
	modular approvals under paragraph (b)					
	of this section.					
5	The modular transmitter must be tested	This is a limited module, installed on the	Y			
3	in a stand-alone configuration, <i>i.e.</i> , the	host to be tested.	1			
	module must not be inside another	End product information is as follows:				
	device during testing for compliance	Manufacturer: Onkyo corporation				
	with Part 15 requirements. Unless the	Model No: MCA1120				
	transmitter module will be battery					
	powered, it must comply with the AC					
	line conducted requirements found in					
	Section 15.207. AC or DC power lines					
	and data input/output lines connected to					
	the module must not contain ferrites,					
	unless they will be marketed with the					
	module (see Section 15.27(a)). The					
	length of these lines shall be the length					
	typical of actual use or, if that length is					
	unknown, at least 10 centimeters to					
	insure that there is no coupling between					
	the case of the module and supporting					

			1
	equipment. Any accessories, peripherals,		
	or support equipment connected to the		
	module during testing shall be		
	unmodified and commercially available		
	(see Section 15.31(i)).		
6	The modular transmitter must be	FCC ID is indicated by silk print on the	Y
	equipped with either a permanently	module	•
	affixed label or must be capable of	module	
	electronically displaying its FCC		
	identification number.		
	(A) If using a permanently affixed label, the		
	modular transmitter must be labeled with its own		
	FCC identification number, and, if the FCC		
	identification number is not visible when the		
	module is installed inside another device, then		
	the outside of the device into which the module is		
	installed must also display a label referring to		
	the enclosed module. This exterior label can use		
	wording such as the following: "Contains Transmitter Module		
	FCC ID: XYZMODEL1" or "Contains FCC ID:		
	XYZMODEL1." Any similar wording		
	that expresses the same meaning may be used.		
	The Grantee may either provide such a label, an		
	example of which must be included in the		
	application for equipment		
	authorization, or, must provide adequate		
	instructions along with the module which explain this requirement. In the latter case, a copy of		
	these instructions must be included in the		
	application for equipment authorization.		
	(B) If the modular transmitter uses an electronic		
	display of the FCC identification number, the		
	information must be readily accessible and		
	visible on the modular transmitter or on the		
	device in which it is installed. If the module is		
	installed inside another device, then the outside of the device into which the module is installed		
	must display a label referring to the enclosed		
	module. This exterior label can use wording such		
	as the following:		
	"Contains FCC certified transmitter module(s)."		
	Any similar wording that expresses the same		
	meaning may be used. The user manual must		
	include instructions on how to access the electronic display. A copy of these instructions		
	must be included in the application for		
	equipment authorization.		
7	The modular transmitter must comply	" Pass", corroborating document: refer to	Y
	with any specific rules or operating	completed product's user manual for the	
	requirements that	detail	
	ordinarily apply to a complete		
	transmitter and the manufacturer must		
	provide adequate instructions along with		
	the module to explain any such		
	- · ·		
	requirements. A copy of these instructions must be included in the		
	application for equipment authorization.		

8	The modular transmitter must comply	Pass the RF exposure requirements.	Y
	with any applicable RF exposure		
	requirements in its final configuration.		

A **limited modular approval** may be granted for single or split modular transmitters that do not comply with all of the above requirements, *e.g.*, shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.