

SAR Evaluation Report

Application No.: SZEM1907015844CR
Applicant: Onkyo Corporation
Address of Applicant: KOKUGIKAN FRONT BUILDING 1-10-5 Yokoami Sumida-ku, Tokyo, Japan.
Manufacturer: Onkyo Corporation
Address of Manufacturer: KOKUGIKAN FRONT BUILDING 1-10-5 Yokoami Sumida-ku, Tokyo, Japan.
Factory: Dongguan Tenji Industrial Co.,Ltd
Address of Factory: 7 Hai Yi Road, Chongtou Community, Chang an Town, Dongguan City, Guangdong Province, P.R.China


Equipment Under Test (EUT):
EUT Name: Wireless Stereo Headphones
Model No.: SE-E9TW *
 * Please refer to section 4.1 of this report which indicates which model was actually tested and which were electrically identical.

Trade Mark: Pioneer
FCC ID: ATMSEE9TW
Standards: 47 CFR Part 1.1307
 47 CFR Part 2.1093
 KDB447498D01 General RF Exposure Guidance v06

Date of Receipt: 2019-07-01
Date of Test: 2019-07-03 to 2019-07-08
Date of Issue: 2019-07-11

Test Result :	PASS*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.




Keny Xu
 EMC Laboratory Manager



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2019-07-11		Original

Authorized for issue by:			
			
		<hr/> Bill Chen /Project Engineer	
			
		<hr/> Eric Fu /Reviewer	



3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 GENERAL DESCRIPTION OF EUT	4
4.2 TEST LOCATION	5
4.3 TEST FACILITY	5
4.4 DEVIATION FROM STANDARDS	6
4.5 ABNORMALITIES FROM STANDARD CONDITIONS	6
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
5 SAR EVALUATION	7
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7
5.1.1 <i>Standard Requirement</i>	7
5.1.2 <i>Limits</i>	7
5.1.3 <i>EUT RF Exposure</i>	7-8



4 General Information

4.1 General Description of EUT

Power supply:	Left earphone: Rechargeable battery DC 3.7V 55mAh 0.2Wh (Charge by charge Box) Right earphone: Rechargeable battery DC 3.7V 55mAh 0.2Wh (Charge by charge Box)
For BT	
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.0(This test report is for classic mode.)
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Sample Type:	Portable production
Number of Channels:	79
Channel Spacing:	1MHz
Antenna Type:	Monopole
Antenna Gain:	Left earphone -4.8dBi Right earphone -5.43dBi
For BLE	
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.0(This test report is for BLE mode.)
Modulation Type:	GFSK
Sample Type:	Portable production
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	Monopole
Antenna Gain:	Left earphone -4.8dBi Right earphone -5.43dBi

Declaration of EUT Family Grouping:

Model No.: SE-E9TW

Only the sample with yellow-green was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for all the above model, with only difference on colour.



4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.



4.4 Deviation from Standards

None.

4.5 Abnormalities from Standard Conditions

None.

4.6 Other Information Requested by the Customer

None.



5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

For BT

Left earphone

The Max. power (including tune-up tolerance) is 3.04 dBm on the lowest channel 2.402 GHz (*)

3.04 dBm logarithmic terms convert to numeric result is nearly 2.01 mW

According to the formula. calculate the test exclusion thresholds:

$$\text{General RF Exposure} = \frac{(\text{Max. Power of channel, including tune-up tolerance, mW}) \cdot \sqrt{f(\text{GHz})}}{(\text{min. test separation distance, mm})}$$

$$\text{General RF Exposure} = (2.01 \text{ mW} / 5 \text{ mm}) \times \sqrt{2.402 \text{ GHz}} = 0.62 \quad (1)$$

SAR requirement:

$$S = 3.0 \quad (2)$$

(1) < (2)

So the SAR report is not required.

(*) Max. power refer to Report No.:SZEM190701584402



Left earphone

The Max. power (including tune-up tolerance) is 3.74 dBm on the lowest channel 2.402 GHz (*)
 3.74 dBm logarithmic terms convert to numeric result is nearly 2.37 mW
 According to the formula. calculate the test exclusion thresholds:

$$General\ RF\ Exposure = \frac{(Max.\ Power\ of\ channel,\ including\ tune\ -up\ tolerance,\ mW) * \sqrt{f\ (GHz)}}{(min.\ test\ separation\ distance,\ mm)}$$

$$General\ RF\ Exposure = (2.37\ mW / 5\ mm) * \sqrt{2.402\ GHz} = 0.73 \quad (1)$$

SAR requirement:

$$S = 3.0 \quad (2)$$

$$(1) < (2)$$

So the SAR report is not required.

(*) Max. power refer to Report No.:SZEM190701584402

For BLE

Right earphone

The Max. power (including tune-up tolerance) 2.84 dBm on the lowest channel 2.402 GHz (*)
 2.84 dBm logarithmic terms convert to numeric result is nearly 1.92 mW
 According to the formula. calculate the test exclusion thresholds:

$$[(max.\ power\ of\ channel,\ including\ tune\ -up\ tolerance,\ mW)/(min.\ test\ separation\ distance,\ n * \sqrt{f(GHz)})]$$

$$General\ RF\ Exposure = (1.92\ mW / 5\ mm) * \sqrt{2.402\ GHz} = 0.60 \quad (1)$$

SAR requirement:

$$S = 3.0 \quad (2)$$

$$(1) < (2)$$

So the SAR report is not required.

(*) Max. power refer to Report No.:SZEM190701584403

Right earphone

The Max. power (including tune-up tolerance) 2.89 dBm on the lowest channel 2.402 GHz (*)
 2.89 dBm logarithmic terms convert to numeric result is nearly 1.95 mW
 According to the formula. calculate the test exclusion thresholds:

$$[(max.\ power\ of\ channel,\ including\ tune\ -up\ tolerance,\ mW)/(min.\ test\ separation\ distance,\ n * \sqrt{f(GHz)})]$$

$$General\ RF\ Exposure = (1.95\ mW / 5\ mm) * \sqrt{2.402\ GHz} = 0.60 \quad (1)$$

SAR requirement:

$$S = 3.0 \quad (2)$$

$$(1) < (2)$$

So the SAR report is not required.

(*) Max. power refer to Report No.:SZEM190701584403

- End of the Report -

