



Global Product Certification
EMC-EMF Safety Approvals

Melbourne

176 Harrick Road
Keilor Park, Vic 3042
Tel: +61 3 9365 1000

Sydney

Unit 3/87 Station Road
Seven Hills, NSW 2147
Tel: +61 2 9624 2777

Email: emc-general@emctech.com.au

Web: www.emctech.com.au

47 CFR PART 2.1091

RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: MOBILE DEVICES

REPORT NUMBER: M2306030-2

STANDARD: 47 CFR § 2.1091

CUSTOMER: MESHED PTY LTD

DEVICE: N-COUNTER

MODEL: --

DATE OF ISSUE: 8 NOVEMBER 2023

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the customer or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



Accreditation No.5292

Accredited for compliance with ISO/IEC 17020.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection and proficiency testing scheme providers reports.

Except for the Certificate of Compliance, this document must only be reproduced in full.

REVISION TABLE

Version	Sec/Para Changed	Change Made	Date
1		Initial issue of document	8/11/2023

CONTENTS

1	Introduction.....	5
1.1	Laboratory Overview.....	4
1.2	Test Laboratory/Accreditations.....	5
2	Device Details.....	5
2.1	Transmitters Details.....	6
3	Limits For Maximum Permissible Exposure (MPE), §1.1310.....	6
4	Uncertainty	7
5	Assumptions in this Assessment.....	7
6	RF Exposure Calculations.....	7
7	Appendix A	8



Accreditation No.5292

Except for the Certificate of Compliance, this document must only be reproduced in full.

RADIOFREQUENCY RADIATION EXPOSURE EVALUATION REPORT – MPE

Device: n-Counter
Model Number: --
Manufacturer: Meshed Pty Ltd
Radio Module: 915 MHz ISM Radio module (Multi-Tech Systems, Inc., MTXDOT-NA1)
FCC ID: AU792U13A16858

Inspected for: Meshed Pty Ltd
Address: Suite 2, Level 4, 655 Pacific Highway, St. Leonards NSW 2065
Phone Number: +61 1300 637 433
Contact: Ashay Dhamdhare
Email: ashay@meshed.com.au

Standards: **447498 D01 General RF Exposure Guidance v06**
RF exposure procedures and equipment authorization policies for mobile and portable devices.

47 CFR § 2.1091

Radiofrequency radiation exposure evaluation: mobile devices (Transmitter is more than 20 cm from human body).

Result: Based on an assessment of the documentation provided and the declared separation distance from the human body under normal use, the n-Counter model-- complies with the RF exposure requirements of 47 CFR Part 2.1091. Refer to Report M2306030-2 for full details.

Assessment Date: 11 August 2023

Issue Date: 8 November 2023

Assessment Engineer: 
Ashish Nath

Authorised Signatory: 
Shabbir Ahmed
Technical Director

Issued by: EMC Technologies Pty. Ltd.,
176 Harrick Road, Keilor Park, VIC, 3042, Australia.

Phone: +61 3 9365 1000

E-mail: emc-general@emctech.com.au

Web: www.emctech.com.au

1 INTRODUCTION

This report is intended to demonstrate compliance of the n-counter model -- with the RF exposure requirements of 47 CFR Part 2.1091. Evaluation was performed in accordance with FCC KDB 447498 D01.

The test sample and information were provided by the customer.

1.1 Laboratory Overview

EMC Technologies Pty. Ltd. is an independently owned Australian company that is NATA accredited to ISO 17025 for both testing and calibration and ISO 17020 for Inspection. – **Accreditation Number 5292.**

1.2 Test Laboratory/Accreditations

Inspection was performed at EMC Technologies' laboratory in Keilor Park, Victoria Australia.

Table 1-1: *Accreditations for Conformity Assessment*

Country/Region	Body	
Australia/New Zealand	NATA	Accreditation Number: 5292
Europe	European Union	Notified Body Number: 0819
USA	FCC	Designation Number: AU0001 (Melb)
Canada	ISED Canada	Company Number: 3569B(Melb)
Japan	VCCI	Company Number: 785
Taiwan	BSMI	Lab Code SL2-IN-E-5001R

2 DEVICE DETAILS

(Information supplied by the Customer)

The nCounter is a people counting solution. It counts Wi-Fi probe requests to count the number of Wi-Fi enabled mobile phones in an area. It accumulates the counts over 10-minute intervals and transmits them using the LoRaWAN module to a LoRaWAN gateway.

Host Details

Manufacturer: Meshed Pty Ltd
Inspected Sample: n-Counter
Model Number: --
Distance From human body in normal use: Greater than 20cm

2.1 Transmitters Details

Transmitter parameters were provided by the customer and are shown below:

Table 2-1: Transmitter Parameters

Receiver #1	
Wireless Interface 1:	ESPRESSIF ESP-WROOM-02D 2.4 GHz Wi-Fi (Receiver only)
Operating Frequency:	2412 – 2462 MHz
Transmitter #1	
Wireless Interface 2:	915 MHz ISM Radio module (Multi-Tech Systems, Inc., MTXDOT-NA1)
Operating Frequency:	902 – 928 MHz
Max RF Output Power Level	19.4 dBm
Antenna Type:	¼-wave Monopole antenna (ANT-916-HETH)
Max Antenna gain:	6.4 dBi

3 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE), §1.1310

TABLE 1 - LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	* 100	6
3.0-30	1842/f	4.89/f	* 900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* 100	30
1.34-30	824/f	2.19/f	* 180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

4 UNCERTAINTY

EMC Technologies has evaluated the tools and methods used to perform Radiated Electromagnetic Field predictions.

The estimated inspection uncertainties for the test shown within this report are as follows:

Electromagnetic Modelling

30 MHz to 100GHz ±2.8 dB

The above expanded uncertainties are based on standard uncertainties multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

5 ASSUMPTIONS IN THIS ASSESSMENT

This assessment does not include accumulated RF fields from nearby sites/antennas or possible radio signal reflections or attenuation due to buildings or the general environment.

Antenna Parameters and power settings were supplied by the customer.

A 100% duty cycle is assumed.

The aperture of the radiating element assumed to be a point source in free space and far field conditions.

6 RF EXPOSURE CALCULATIONS

The reference level was evaluated at 20 cm to show compliance with the power density listed in Table 4 (Section3)

The following formula was used to calculate the power density at 20 cm:

$$S = \frac{P * G}{4\pi R^2}$$

$$S = \frac{EIRP}{4\pi R^2}$$

Where

(S): Power density (*mW/cm²*)

(P): Output power at antenna terminal (*mW*)

(G): Gain (ratio)

(R): Minimum test separation distance (*20 cm*)

Table 6-1: Calculations

Technology	Frequency Band (MHz)	Power	Gain	Duty Cycle	EIRP	EIRP	Flux Density at 20 cm	Flux Density limit	Percentage of the GP limit
		<i>dBm</i>	<i>dBi</i>	%	<i>dBm</i>	<i>mW</i>	<i>mW/cm²</i>	<i>mW/cm²</i>	%
915 MHz Transmitter	902	19.4	6.4	100%	25.8	380.2	0.075675	0.601333333	12.58%
Percentage of the GP limit for transmission at 20 cm									12.58%

7 APPENDIX A

Referenced Documents

Document	Comments
FCC 15.207 report no: MLTI0058.1	915 MHz transmitter output power
ANT-916-HETH Antenna Datasheet	915 MHz transmitter antenna gain

-- END OF THE REPORT --