

# 1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

---

## 1.1 General Information

### Client Information

Applicant: Modern Marketing Concepts, Inc.  
Address of applicant: 1220 E Oak, St. Louisville Kentucky United States 40204

Manufacturer: Shenzhen Jiaying Technology Holding Company Limited  
Address of manufacturer: No. 11, 11-1, Anye Road, Anliang village, Yuanshan Town, Longgang District, Shenzhen, China

### General Description of EUT:

Product Name: THE DINER TABLE TOP JUKEBOX  
Brand Name: CROSLEY  
Model No.: BT219  
Adding Model(s): CR1120A  
FCC ID: AUSCR1120A  
Rated Voltage: USB DC5V  
Battery Capacity: /  
Power Adapter#3: /

### Technical Characteristics of EUT:

Bluetooth Version: V5.0 (BR/EDR mode)  
Frequency Range: 2402-2480MHz  
RF Output Power: 4.15dBm (Conducted)  
Data Rate: 1Mbps, 2Mbps, 3Mbps  
Modulation: GFSK, Pi/4 DQPSK, 8DPSK  
Quantity of Channels: 79  
Channel Separation: 1MHz  
Type of Antenna: PCB Antenna  
Antenna Gain: -0.68dBi

## 1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

### (a) Limits for Occupational / Controlled Exposure

| Frequency range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                  | 6  |

|             |        |        |          |   |
|-------------|--------|--------|----------|---|
| 3.0-30      | 1842/f | 4.89/f | (900/f)* | 6 |
| 30-300      | 61.4   | 0.163  | 1.0      | 6 |
| 300-1500    | /      | /      | F/300    | 6 |
| 1500-100000 | /      | /      | 5        | 6 |

(b) Limits for General Population / Uncontrolled Exposure

| Frequency range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                  | 30   |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f)*                                | 30   |
| 30-300                | 27.5                              | 0.073                             | 0.2                                     | 30   |
| 300-1500              | /                                 | /                                 | F/1500                                  | 30   |
| 1500-100000           | /                                 | /                                 | 1                                       | 30   |

Note: f = frequency in MHz; \* = Plane-wave equivalents power density

### 1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

### 1.4 MPE Calculation Result

Maximum Tune-Up output power: 5 (dBm)

Maximum peak output power at antenna input terminal: 3.16(mW)

Prediction distance: >20(cm)

Prediction frequency: 2402 (MHz)

Antenna gain: -0.68 (dBi)

Directional gain (numeric gain): 0.86

The worst case is power density at prediction frequency at 20cm: 0.0005 (mw/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm<sup>2</sup>)

Result: Pass