

RF Exposure / SAR Statement

No. : 10006272S-A

Applicant : Clarion Co., Ltd.
Type of Equipment : Digital Wireless Camera System Camera With Transmitter
Model No. : CC-3500
FCC ID : AX2CC3500

Clarion Co., Ltd. declares that Model : Digital Wireless Camera System Camera With Transmitter complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091.

The "CC-3500" has 164.44 mW of conducted Peak Output power and 285.76 mW of EIRP.

This kind of equipment is below SAR Threshold (KDB447498 D01 v05)

The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "CC-3500" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 164.44 mW (Maximum peak output power)
G = 1.74 Numerical Antenna gain; equal 2.40 dBi
r = 20.0 cm

For: CC-3500

$$S = 0.05685 \text{ mW/cm}^2$$

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401