

## Prediction of MPE and ERP/ EIRP

The device is designed as module to be installed in other devices. This device is to be used only for fixed and mobile applications. If the final product after integration is intended for portable use, a new application and FCC is required.

The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all the persons and must not be co-located or operating in conjunction with any other antenna or transmitter.

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled Limits for Maximum Permissible Exposure (MPE) and Health Canada Safety Code 6, Limits for General Population/Uncontrolled Exposure:

Frequency Range (MHz)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
300 – 1500	f (MHz) /1500	30
1500 – 100.000	1.0	30

Based on the above table the limits are:

For 850 MHz frequency band device: 0.55 mW/cm<sup>2</sup>  
 For 1700 /1900 MHz frequency band device: 1 mW/cm<sup>2</sup>

**FCC § 2.1091 / IC RSS102, section 2.5.2**

The limit for 850 MHz mobile operations where no routine evaluation is required is: 1.5W ERP  
 The limit for 1700 / 1900 MHz mobile operations where no routine evaluation is required is: 3W EIRP

Max permissive power according to §24.232 and RSS133: 2W EIRP  
 Max permissive power according to §§22.913(a) and RSS132: 7W ERP

Using the equation from page 19 of OET Bulletin 65, Edition 97-01:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)  
 P = power input to the antenna (in appropriate units, e.g., mW)  
 G = power gain of the antenna in the direction of interest relative to an isotropic radiator  
 R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

## 850 MHz frequency band

Maximum output power considerations:

Mode	Maximum conducted output power (dBm)	Maximum conducted output power (W)	Duty cycle	Equivalent conducted output power (Maximum conducted output power x duty cycle) (mW)
GSM	33.5	2.239	26%	582
EDGE	27.5	0.562	26%	146
WCDMA	24.2	0.263	100%	263

P	Maximum power input to the antenna:	582	mW
R	Distance:	20	cm
S	MPE limit for uncontrolled exposure:	0.55	mW/cm <sup>2</sup>

G <sub>1</sub>	Antenna gain (dBi) to comply with MPE limits:	6.77	dBi
----------------	---	------	-----

ERP power limit according to §2.1091:	1.50	W ERP
---------------------------------------	------	-------

G <sub>2</sub>	Antenna gain (dBi) to comply with ERP limits:	6.25	dBi
----------------	---	------	-----

(ERP = Maximum conducted output power x Antenna gain / 1,64)

ERP power limit according to §22.913:	7.00	W ERP
---------------------------------------	------	-------

G <sub>3</sub>	Antenna gain (dBi) to comply with ERP limits:	7.09	dBi
----------------	---	------	-----

(ERP = Maximum conducted output power x Antenna gain / 1,64)

G <sub>850 MHz band</sub>	Min (G <sub>1</sub> , G <sub>2</sub> , G <sub>3</sub> )	7.09	dBi
---------------------------	---	------	-----

Therefore the maximum antenna gain for mobile operation to comply with MPE and ERP limits shall not exceed:

4.95 dBd

## 1900 MHz frequency band

Maximum output power considerations:

Mode	Maximum conducted output power (dBm)	Maximum conducted output power (W)	Duty cycle	Equivalent conducted output power (Maximum conducted output power x duty cycle) (mW)
GPRS	30	1.000	26%	260
EDGE	25.5	0.355	26%	92
WCDMA	24	0.251	100%	251

P	Maximum power input to the antenna:	260	mW
R	Distance:	20	cm
S	MPE limit for uncontrolled exposure:	1.00	mW/cm <sup>2</sup>

G <sub>1</sub>	Antenna gain (dBi) to comply with MPE limits:	<b>12.86</b>	dBi
----------------	---	--------------	-----

EIRP power limit according to §2.1091:	3.00	W EIRP
--	------	--------

G <sub>2</sub>	Antenna gain (dBi) to comply with EIRP limits:	<b>12.76</b>	dBi
(EIRP = Maximum conducted output power x Antenna gain )			

EIRP power limit according to §24.232	2.00	W EIRP
---------------------------------------	------	--------

G <sub>3</sub>	Antenna gain (dBi) to comply with EIRP limits:	<b>3.01</b>	dBi
(EIRP = Maximum conducted output power x Antenna gain )			

G <sub>1900 MHz band</sub>	Min (G <sub>1</sub> , G <sub>2</sub> , G <sub>3</sub> )	<b>3.01</b>	dBi
----------------------------	---	-------------	-----

Therefore the maximum antenna gain for mobile operation to comply with MPE and EIRP limits shall not exceed:

**3.01 dBi**

## 1700 MHz frequency band

### 1700 MHz frequency band

Maximum output power considerations:

Mode	Maximum conducted output power (dBm)	Maximum conducted output power (W)	Duty cycle	Equivalent conducted output power (Maximum conducted output power x duty cycle) (mW)
WCDMA	24.2	0.263	100%	263

P	Maximum power input to the antenna:	263	mW
R	Distance:	20	cm
S	MPE limit for uncontrolled exposure:	1.00	mW/cm <sup>2</sup>

G <sub>1</sub>	Antenna gain (dBi) to comply with MPE limits:	12.81	dBi
----------------	---	-------	-----

EIRP power limit according to §2.1091:	3.00	W EIRP
--	------	--------

G <sub>2</sub>	Antenna gain (dBi) to comply with EIRP limits:	12.71	dBi
(EIRP = Maximum conducted output power x Antenna gain )			

EIRP power limit according to §27.50	2.00	W ERP
--------------------------------------	------	-------

G <sub>3</sub>	Antenna gain (dBi) to comply with EIRP limits:	8.81	dBi
(EIRP = Maximum conducted output power x Antenna gain )			

G <sub>1900 MHz band</sub>	Min (G <sub>1</sub> , G <sub>2</sub> , G <sub>3</sub> )	8.81	dBi
----------------------------	---	------	-----

Therefore the maximum antenna gain for mobile operation to comply with MPE and EIRP limits shall not exceed:

8.81 dBi

p.o.

David Lang  
Testing Manager