

RF Exposure / SAR Statement

No. : 30DE0216-YK-B

Applicant : Clarion Co., Ltd.
Type of Equipment : Car audio
Model No. : PF-3302B-A
FCC ID : AX2PF3302

Clarion Co., Ltd. declares that Model : Car audio
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091.
The "PF-3302B-A" has 1.1 mW of conducted Peak Output power and 1.45 mW of EIRP.
This equipment is considered as a mobile device so that SAR testing is excluded.
The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "PF-3302B-A" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 1.10 mW (Maximum peak output power)
G = 1.31 Numerical Antenna gain; equal 1.18 dBi
r = 20.0 cm

For: PF-3302B-A

S = 0.00029 mW/cm²

UL Japan, Inc.

Yamakita EMC Lab.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011 Facsimile: +81 465 77 2112