

Exhibit 6

INDEX OF TEST RESULTS**Exhibit # Description**

6A	800 MHz band / Part 22 / AMPS : RF Power
6B	800 MHz band / Part 22 / AMPS : Modulation Characteristics
6C	800 MHz band / Part 22 / AMPS : Occupied Bandwidth
6D	800 MHz band / Part 22 / AMPS : Spurious Emissions (conducted)
6E	800 MHz band / Part 22 / AMPS : Spurious Emissions (radiated)
6F	800 MHz band / Part 22 / AMPS : Frequency Stability
6G	800 MHz band / Part 22 / DAMPS : RF Power
6H	800 MHz band / Part 22 / DAMPS : Modulation Characteristics
6I	800 MHz band / Part 22 / DAMPS : Occupied Bandwidth
6J	800 MHz band / Part 22 / DAMPS : Spurious Emissions (conducted)
6K	800 MHz band / Part 22 / DAMPS : Spurious Emissions (radiated)
6L	800 MHz band / Part 22 / DAMPS : Frequency Stability

Exhibit 6A1

800 MHz AMPS RF POWER OUTPUT

Para. 2.1046 (a) and 22.913 (a)

The RF power at the band center, measured at the antenna connector using a communications test set as the specified load, are plotted against supply voltage variations and temperature variations at the highest power level.


<u>Exhibit</u>	<u>Input Voltage</u>	<u>Temperature</u>	<u>P_o</u>	<u>Modulation (Freq)</u>	<u>Power Level</u>
6A2	6.0	Varied	0.355 W	Analog (800)	0 (CLASS 4)
6A3	6.0 Varied $\pm$ 15%	+25 C	0.355 W	Analog (800)	0 (CLASS 4)

Note: The 6V input voltage is varied $\pm$ 15%, even though the manufacturer's rated supply voltage is 5.2 VDC to 6.8 VDC. The manufacturer's specified temperature range is -40°C to $+70^{\circ}\text{C}$. The output power is calibrated at the center of the band at room temperature.

These measurements were made per EIA/TIA IS-137A using the following equipment:

Anritsu MT8801B	Radio Communication Analyzer
HP E3632A	DC Power Supply (2)
ESPEC Model SH-240	Temperature Chamber

The DM10 Transceiver has been designed as an OEM module for use by various OEM integrators. The transmitter section delivers up to 0.355 watts of output power to an RF connector designed for attachment to a customer-supplied cable and antenna. Since an antenna and cable are not provided to the customer, the substitution method per IS-137A of measuring effective radiated power data, and a comparison to SAR measurements, is not available.






Exhibit 6B1

800 MHz AMPS MODULATION CHARACTERISTICS

Para. 2.1047 (a), (b) and 22.915 (b)(1), (d)(1)

The frequency and amplitude response to audio inputs measured per TIA/EIA IS-137A are shown on the following:


Exhibit #


6B2	Transmit Audio Frequency Response	2.1047 (a)	IS-137A para. 3.3.1.2.2.2
6B3	Post Limiter Filter Attenuation	22.915 (d)(1)	IS-137A para. 3.3.1.2.2.2
6B4	Modulation Limiting vs. Input Voltage	2.1047 (b)	

NOTE: Exhibit 6B4 Modulation Limiting versus Input Signal – the plot includes the audio frequency (1800 Hz) that produced the highest level of deviation.

These measurements were made per TIA/EIA IS-137A using the following equipment:

HP8901B	Modulation Analyzer
HP8903B	Audio Analyzer
HP8904A	Multifunction Synthesizer
HP E3632A	DC Power Supply (2)








Exhibit 6C1

OCCUPIED BANDWIDTH

Per 2.1049 (c) (1) and 22.917 (d), the exhibits presented show the modulations that co-exist in a cellular system:

<u>Exhibit #</u>	<u>Description</u>	<u>Power Level</u>	Frequency (MHz)
6C2	Unmodulated Carrier	0, CLASS 4	836.52 MHz
6C3	SAT and Voice	0, CLASS 4	836.52 MHz
6C4	SAT and Signal Tone	0, CLASS 4	836.52 MHz
6C5	SAT and DTMF #3	0, CLASS 4	836.52 MHz
6C6	SAT and 10kb/s Wideband Data	0, CLASS 4	836.52 MHz

These measurements were made per EIA/TIA IS-137A using the following equipment:

Anritsu MT8801B	Radio Communication Analyzer
HP8593E	Spectrum Analyzer
HP E3632A	DC Power Supply (2)

Exhibit 6C2: Unmodulated Carrier. Class 4 Power Level 0 = 0.355 W
Carrier Frequency 836.52




Exhibit 6C3: CLASS 4 Power Level 0 = 0.355 W
Carrier Frequency 836.52 MHz, F3E Emission Mask
Voice Tone 2500Hz, SAT 6000Hz, Total Deviation 11000Hz




Exhibit 6C4: Class 4 Power Level 0 = 0.355 W
Carrier Frequency 836.52 MHz
SAT and Signaling Tone, F3E Emission Mask




Exhibit 6C5: Class 4 Power Level 0/2 = 0.355 W
Carrier Frequency 836.52 MHz
SAT and DTMF#3, F3E Emission Mask




Exhibit 6C6: Class 4 Power Level 0 = 0.355 W
Carrier Frequency 836.52 MHz
SAT and Wideband 10kb/s Digital data, F1D Emission Mask




Exhibit 6D1

800 MHz AMPS SPURIOUS EMISSIONS (CONDUCTED)

Per 2.1051 Conducted Spurious emissions were measured at the antenna connector with a spectrum analyzer per EIA/TIA IS-137A.


<u>EXHIBIT #</u>	<u>FREQUENCY</u>	<u>Output Power</u>
6D2	836.49 MHz	.355 W (CLASS 4 PL0)
6D3	836.49 MHz	.005 W (CLASS 4 PL7)

Note: The spectrum was examined through the 10th harmonic of the carrier at the highest and lowest power level at the center of the band. Measurements recorded are peak measurements.

These measurements were made per EIA/TIA IS-137A using the following equipment:

HP8593E	Spectrum Analyzer
HP E3632A	DC Power Supply (2)

Per 22.917 (f), the transmitter emissions in the base station transmit frequency range (869 – 894 MHz) have been verified to be attenuated below –80 dBm.






Exhibit 6E1

800 MHz AMPS SPURIOUS EMISSIONS (Radiated)

Per 2.1053 and 22.917 (e), field strength of spurious radiation was measured at Underwriters Laboratories Inc. Research Triangle Park, NC site. Underwriter Laboratories Inc. Research Triangle site is NVLAP and FCC registered. The measurement procedure is per EIA/TIA IS-137A conducted on a 3 meter test site. Results are shown on the following Exhibits.

Note: The spectrum was examined through the 10th harmonic of the carrier at the highest power level fat low, middle, and high ends of the band. The worst case plots is shown below. Measurements recorded are peak measurements.

<u>EXHIBIT</u>	<u>FREQUENCY</u>	<u>OUTPUT POWER</u>
6E2	824 MHz	0.355 W

The measurements were made per EIA/TIA IS-137A using the following equipment:

Receive Equipment:

<u>Item</u>	<u>Description</u>	<u>Manufacturer</u>
ATA033	52 ft Cable, N-N	UL
ATA034	52 ft Cable, N-N	UL
AT0020	Horn Antenna, 1-18 GHz	Electro-metrics
SAR001	EMI Receiver	Hewlett-Packard

For Substitution Calibration:

<u>Item</u>	<u>Description</u>	<u>Manufacturer</u>
FGR022	Signal Generator	Hewlett-Packard
ATA055	6 ft Cable, N-N	UL
AT0005	Horn Antenna, 1-18 GHz	Electro-metrics




EXHIBIT 6F1

800 MHz AMPS FREQUENCY STABILITY

Per 2.1055 (a)(1),(b),(d)(1)


Variation of output frequency as a result of varying voltage or temperature is shown in Exhibits 6F2 and 6F3.

<u>EXHIBIT #</u>	<u>Input Voltage</u>	<u>Temperature</u>	<u>Mode</u>	<u>Frequency</u>
6F2	6.0 V Varied $\pm$ 15%	+25 °C	Analog (CLASS 4)	836.49 MHz
6F3	6.0 VDC	Varied	Analog (CLASS 4)	836.49 MHz

Note: The 6V input voltage is varied $\pm$ 15%, even though the manufacturer's rated supply voltage is 5.2 VDC to 6.8 VDC. The manufacturer's specified temperature range is -40°C to $+70^{\circ}\text{C}$.

These measurements were made per EIA/TIA IS-137A using the following equipment:

Anritsu MT8801B	Radio Communication Analyzer
HP E3632A	DC Power Supply (2)
ESPEC Model SH-240	Temperature Chamber






Exhibit 6G1

800 MHz DAMPS RF POWER OUTPUT

Para. 2.1046 (a) and 22.913 (a)

The RF power at the band center, measured at the antenna connector using a communications test set as the specified load, are plotted against supply voltage variations and temperature variations at the highest power level.


<u>Exhibit</u>	<u>Input Voltage</u>	<u>Temperature</u>	<u>P_o</u>	<u>Modulation (Freq)</u>	<u>Power Level</u>
6G2	6.0	Varied	0.355 W	Digital (800)	0 (CLASS 4)
6G3	6.0 Varied $\pm$ 15%	+25 C	0.355 W	Digital (800)	0 (CLASS 4)

Note: The 6V input voltage is varied $\pm$ 15%, even though the manufacturer's rated supply voltage is 5.2 VDC to 6.8 VDC. The manufacturer's specified temperature range is -40°C to $+70^{\circ}\text{C}$. The output power is calibrated at the center of the band at room temperature.

These measurements were made per EIA/TIA IS-137A using the following equipment:

Anritsu MT8801B	Radio Communication Analyzer
HP E3632A	DC Power Supply (2)
ESPEC Model SH-240	Temperature Chamber

The DM20 Transceiver has been designed as an OEM module for use by various OEM integrators. Since an antenna and cable is not provided to the customer, the substitution method per IS-137A of measuring effective radiated power data is not available.






EXHIBIT 6H1

800 MHz: DAMPS MODULATION CHARACTERISTICS

Part 2.1047

Definition

The transceiver shall be capable of generating $\pi/4$ shifted differentially encoded quadrature phase shift keying signals. The transmitted signal is given by:

$$S(t) = \sum_n g(t-nT) \cos(\phi_n) \cos(\omega_c t) - \sum_n g(t-nT) \sin(\phi_n) \sin(\omega_c t)$$

where $g(t)$ is the pulse shaping function that corresponds to a square root raised cosine baseband filter with roll off factor of 0.35, ω_c is the radian carrier frequency, T is the symbol period, and ϕ_n is the absolute phase corresponding to the n th symbol interval. The symbol rate ($1/T$) is 24.3 k symbols /sec.

The modulation accuracy requirement is specified by setting limits on the RMS difference between the actual transmitted signal waveform and the ideal signal waveform. The ideal waveform is derived mathematically from the specification of modulation shown above. The specified requirement is error vector magnitude.

For this measurement, frequency accuracy shall meet the requirements of Section 3.1 prior to measurement.

The average carrier frequency error is the difference between the average carrier frequency of the actual transmitted waveform and the average signal waveform carrier frequency.

The ideal modulation is defined above. The definition is such that, observing an ideal transmitter through an ideal root raised-cosine receiver filter at the correct sampling instants one symbol apart would result in the sequence of values given by:

$$S(k) = S(k-1)e^{j\{\pi/4 + B(k)*\pi/2\}}$$

where $B(k) = 0, 1, 2, 3$ according to the following table:

X _k	Y _k	B(k)
0	0	0
0	1	1
1	1	2
1	0	3

In the forward channel, $S(k)$ forms part of a continuous data stream. In the reverse channel, the transit bursts from the mobile are truncated by power up and down ramping. In this case, $S(6)$ is the first sample that enters into demodulation, which yields the first two information bits by comparing $S(6)$ with $S(7)$. The last information bits lie in the comparison of $S(162)$ and $S(161)$.

The ideal transmit and receive filters in cascade form a raised cosine Nyquist filter having an impulse response going through zero at symbol period intervals, so there is no inter-symbol interference at the ideal sampling points. The ideal signal sampler therefore, take on one of the eight values defined above, at the output of the receive filter.

This section defines how the output signal from a transmitter is to be evaluated against the ideal signal.

Let $Z(k)$ be the complex vectors produced by observing the real transmitter through an ideal measuring receive filter at instants k , one symbol period apart. With $S(k)$ defined as above, the transmitter is modeled as:

$$Z(k) = [C_0 + C_1 * [S(k) + E(k)]] * W^k$$

where:

$$k = n/24.3\text{KHz}$$

$$dr = jda$$

$W = e^{dr}$ accounts for both a frequency offset giving "da" radians per symbol phase rotation and an amplitude changes of "dr" nepers per symbol:

C_0 is a constant origin offset representing quadrature modulator imbalance,
 C_1 is a complex constant representing the arbitrary phase and output power of the transmitter, and
 $E(k)$ is the residual vector error on sample $S(k)$

The sum square vector error is then:

$$\sum_{k=\text{MIN}}^{k=\text{MAX}} |E(k)|^2 \quad \sum_{k=\text{MIN}}^{k=\text{MAX}} |[Z(k) * W^{-C_0/C_1} - S(k)]|^2$$

C_0 , C_1 and W shall be chosen to minimize this expression and are then used to compute the individual vector errors $E(k)$ on each symbol. The symbol timing phase of the receiver output samples used to compute the vector error shall also be chosen to give the lowest value.

The values of MAX and MIN for the reverse channel (mobile station transmitter) are:

$$\begin{aligned} \text{MIN} &= 6 \\ \text{MAX} &= 162 \end{aligned}$$

The RMS vector error is then computed as the square root of the sum-square vector divided by the number of symbols in the slot, (157 in the reverse direction).

Method of Measurement

Connect the mobile station to the Standard Test Source and Modulation Accuracy Equipment. Modulate the Standard Test Source with pseudo-random Data Field bits. The mobile station shall transpond the Data Field bits using the TDMAON command. Use the Modulation Accuracy Measurement Equipment to measure the modulation accuracy of the mobile station.

Minimum Standard

The RMS vector error in any burst shall be less than 12.5%. In addition, the normalized error vector magnitude during the first 10 symbols (20 bits) of a burst following the ramp-up, must have an RMS value of less than 25% when averaged over 10 bursts within a 1 minute interval. The minimum standard for frequency offset is specified in section 3.1.2.2.3 of IS 137. The origin offset in any burst shall be less than -20 dBc.

Exhibit 6I1

800 MHz DAMPS OCCUPIED BANDWIDTH

Per 2.1049 (c) (1) and 22.917 (d), the exhibit presented shows the modulation that exists in a DAMPS cellular system:

<u>Exhibit #</u>	<u>Description</u>	<u>Power Level</u>	Frequency (MHz)
6I2	48.6 kb/s Wideband Data	0, CLASS 4	835.02 MHz

These measurements were made per EIA/TIA IS-137A using the following specialized test equipment with a measurement personality specific to this measurement:

HP8593E	Spectrum Analyzer
HP E3632A	DC Power Supply (2)

Exhibit 6I2: Class 4 Power Level 0 = 0.355 W (+25.5 dBm)
Carrier Frequency 835.02MHz, Wideband data 48.6 Kb/s





Exhibit 6J1

800 MHz DAMPS SPURIOUS EMISSIONS (CONDUCTED)

Per 2.1051 Conducted Spurious emissions were measured at the antenna connector with a spectrum analyzer per EIA/TIA IS-137A. The conducted spurious has been tested up to the 10th harmonic, reporting all spurious within 20 dB of the FCC limit.

<u>EXHIBIT #</u>	<u>FREQUENCY</u>	<u>Output Power</u>
6J2	836.49 MHz	.355 W (CLASS 4 PL0)
6J3	836.49 MHz	.0003 W (CLASS 4 PL10)


Note: The spectrum was examined through the 10th harmonic of the carrier at the highest and lowest power level for at the center of the band. Measurements recorded are peak measurements.

These measurements were made per EIA/TIA IS-137A using the following equipment:

HP8593E	Spectrum Analyzer
HP E3632A	DC Power Supply (2)

Per 22.917 (f), the transmitter emissions in the base station transmit frequency range (869 – 894 MHz) have been verified to be attenuated below –80 dBm.

Exhibit 6J2: Conducted Spurious Emissions - DAMPS
Carrier Frequency 836.49 MHz, Carrier Power 0.355 W






Exhibit 6K1

800 MHz DAMPS SPURIOUS EMISSIONS (Radiated)

Per 2.1053 and 22.917 (e), field strength of spurious radiation was measured at Underwriters Laboratories Inc. Research Triangle Park, NC site. Underwriter Laboratories Inc. Research Triangle site is NVLAP and FCC registered. The measurement procedure is per EIA/TIA IS-137A conducted on a 3 meter test site. Results are shown on the following Exhibits.

Note: The spectrum was examined through the 10th harmonic of the carrier at the highest power level for CLASS 4, at low, middle, and high ends of the band. The worst case plot is shown below. Measurements recorded are peak measurements.

<u>EXHIBIT</u>	<u>FREQUENCY</u>	<u>OUTPUT POWER</u>
6K2	824.04 MHz	0.355 W

The measurements were made per EIA/TIA IS-137A using the following equipment:

Receive Equipment:

<u>Item</u>	<u>Description</u>	<u>Manufacturer</u>
ATA033	52 ft Cable, N-N	UL
ATA034	52 ft Cable, N-N	UL
AT0020	Horn Antenna, 1-18 GHz	Electro-metrics
SAR001	EMI Receiver	Hewlett-Packard

For Substitution Calibration:

<u>Item</u>	<u>Description</u>	<u>Manufacturer</u>
FGR022	Signal Generator	Hewlett-Packard
ATA055	6 ft Cable, N-N	UL
AT0005	Horn Antenna, 1-18 GHz	Electro-metrics




EXHIBIT 6L1

800 MHz DAMPS FREQUENCY STABILITY

Per 2.1055 (a)(1),(b),(d)(1)

Variation of output frequency as a result of varying voltage or temperature is shown in Exhibits 6L2 and 6L3.

<u>EXHIBIT #</u>	<u>Input Voltage</u>	<u>Temperature</u>	<u>Mode</u>	<u>Frequency</u>
6L2	6.0 V Varied $\pm$ 15%	+25 °C	Digital (CLASS 4)	836.49 MHz
6L3	6.0 VDC	Varied	Digital (CLASS 4)	836.49 MHz

Note: The 6V input voltage is varied $\pm$ 15%, even though the manufacturer's rated supply voltage is 5.2 VDC to 6.8 VDC. The manufacturer's specified temperature range is -40°C to $+70^{\circ}\text{C}$.

These measurements were made per EIA/TIA IS-137A using the following equipment:

Anritsu MT8801B	Radio Communication Analyzer
HP E3632A	DC Power Supply (2)
ESPEC Model SH-240	Temperature Chamber

