



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR 352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

FCC
VHF PORTABLE PART 90
TEST REPORT

APPLICANT	VERTEX STANDARD USA, INC. 8000 WEST SUNRISE BLVD. FT. LAUDERDALE FL 33322 USA
FCC ID	AXI11283020
MODEL NUMBER	VX-261-D0-5
PRODUCT DESCRIPTION	UHF PORTABLE LAND MOBILE RADIO
STANDARD APPLIED	CFR 47 Part 90
DATE SAMPLE RECEIVED	12/3/2014
DATE TESTED	12/23/2014-12/26/2014
REPORT ISSUE DATE	12/26/2014
TESTED BY	Cory Leverett
APPROVED BY	Sid Sanders
TIMCO REPORT NO.	2220AUT14TestReport.docx
TEST RESULTS	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.

TABLE OF CONTENTS

GENERAL REMARKS	3
GENERAL INFORMATION.....	4
TEST REPORT SUMMARY.....	5
TEST PROCEDURE.....	6
RF POWER OUTPUT.....	7
MODULATION CHARACTERISTICS	8
VOICE MODULATED COMMUNICATION EQUIPMENT.....	10
OCCUPIED BANDWIDTH	12
SPURIOUS EMISSIONS AT ANTENNA TERMINALS (CONDUCTED)	15
FIELD STRENGTH OF SPURIOUS EMISSIONS.....	20
FREQUENCY STABILITY.....	23
TRANSIENT FREQUENCY BEHAVIOR.....	24
EQUIPMENT LIST.....	28

GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

Summary

The device under test does:

- fulfill the general approval requirements as identified in this test report
 not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025: 2005 requirements.

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669

Authorized Signatory Name:

Cory Leverett
Engineering Project Manager

Date: 12/26/2014



[Table of Contents](#)

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

GENERAL INFORMATION

EUT Specification

EUT Description	UHF PORTABLE LAND MOBILE RADIO
FCC ID	AXI11283020
Model Number	VX-261-D0-5
Operating Frequency	148-174MHz
Test Frequencies	150.8, 155.0, 162.05, 173.5MHz
No. of Channels	Programable for all legal Part 90 VHF channels
Type of Emission	11K0F3E
Modulation	FM
EUT Power Source	<input type="checkbox"/> 110–120Vac/50– 60Hz
	<input type="checkbox"/> DC Power 12V
	<input checked="" type="checkbox"/> Battery Operated Exclusively
Test Item	<input type="checkbox"/> Prototype
	<input checked="" type="checkbox"/> Pre-Production
	<input type="checkbox"/> Production
Type of Equipment	<input type="checkbox"/> Fixed
	<input checked="" type="checkbox"/> Mobile
	<input type="checkbox"/> Portable
Test Conditions	The temperature was 26°C with a relative humidity of 50%.
Revision History to the EUT	None
Test Exercise	The EUT was placed in continuous transmit mode.
Applicable Standards	ANSI/TIA 603-C:2004, FCC CFR 47 Part 90
Test Facility	Timco Engineering Inc. 849 NW State Road 45 Newberry, FL 32669 USA.

[Table of Contents](#)

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

TEST REPORT SUMMARY

Rule Part No.	Scope of Work	Status Pass/Fail/NA
Part 2.1033(c)(8) , Part 2.1046(a) , Part 90	RF Power Output	Pass
Part 2.1033(c)(4) Part 2.1047(a)(6)	Modulation Characteristics	Pass
2.1049(c) , 90.210(b) , 90.210(c) 90.210(d) , 90.210(e)	Emission Mask and Occupied Bandwidths	Pass
2.1051(a)	Antenna Conducted Emissions	Pass
2.1053 , Part 90	Field Strength Spurious Emissions	Pass
Part 2.1055 , Part 90.213	Frequency Stability	Pass
Part 90.214	Transient Frequency Behavior	Pass

[Table of Contents](#)

TEST PROCEDURE

Power Line Conducted Interference: The procedure used was ANSI/TIA 603-D:2010, using a 50uH LISN. Both lines were observed with the EUT transmitting. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

Bandwidth 20 dB: The measurements were made with the spectrum analyzer's resolution bandwidth (RBW) = 1 MHz and the video bandwidth (VBW) = 3 MHz and the span set as shown on plot.

Power Output: The RF power output was measured at the antenna feed point using a peak power meter.

Antenna Conducted Emissions: The RBW = 100 kHz, VBW = 300 kHz and the span set to 10.0 MHz and the spectrum was scanned from 30 MHz to the 10th harmonic of the fundamental. Above 1 GHz the resolution bandwidth was 1 MHz and the VBW = 3 MHz and the span to 50 MHz.

Radiation Interference: The test procedure used was ANSI/TIA 603-D:2010, using an Rohde & Schwarz – EMI test receiver. The bandwidth (RBW) of the spectrum receiver was 100 kHz up to 1 GHz and 1 MHz above 1 GHz with an appropriate sweep speed. The VBW above 1 GHz was 3 MHz. The analyzer was calibrated in dB above a microvolt at the output of the antenna.

[Table of Contents](#)

RF POWER OUTPUT


Rule Part No.: Part 2.1046(a), Part 90

Test Requirements: Manufacturer's Specification

Method of Measurement: RF power is measured by using a 50-ohm, resistive wattmeter to the RF output connector. With a nominal battery voltage (if battery operated), or a properly adjusted power supply (if not battery operated), and the transmitter properly adjusted the RF output measures:

For the device with a fixed or integral antenna, the RF power is measured as ERP. The substitution method was used. The RF output measures:

Test Setup Diagram:



Test Data: RF power of the EUT can be set at 5W to 25W.

OUTPUT POWER:

Tuned Frequency (MHz)	RF POWER (W)	
	HI	LOW
150.8	5	1
155.0	5	1
162.05	5	1
173.5	5	1

Part 2.1033 (C)(8) DC Input into the final amplifier

FOR HIGH POWER SETTING INPUT POWER: $(7.4)(1.3) = 9.62$ Watts

FOR LOW POWER SETTING INPUT POWER: $(7.4)(.3) = 2.22$ Watts

[Table of Contents](#)

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

MODULATION CHARACTERISTICS

Rule Part No.: Part 2.1047(a)(b)

Test Requirements:

Method of Measurement:

Part 2.1033(c)

Part 90.209

Part 90.207

Part 2.1033(c) (4) Type of Emission: 11K0F3E

$B_n = 2M + 2DK$

$M = 3000$

$D = 2500$


$K=1$

$B_n = 2(3000) + 2(2500) = 11.0k$

[Table of Contents](#)

Audio frequency response

The audio frequency response was measured in accordance with ANSI/TIA 603-D: 2010. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 – 5000Hz shall be submitted. The audio frequency response curve is shown below.




Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

VOICE MODULATED COMMUNICATION EQUIPMENT

Part 2.1047(a): For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter, or of all the circuitry installed between the modulation limiter and the modulated stage shall be submitted.



[Table of Contents](#)

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx


AUDIO INPUT VERSUS MODULATION

Rule Part No.: Part 2.1047(b) & 90

Test Requirements:

Method of Measurement: Modulation cannot exceed 100%, The audio input level needed for a particular percentage of modulation was measured in accordance with ANSI/TIA 603-D: 2010. The audio input curves versus modulation are shown below. Curves are provided for audio input frequencies of 300, 1000, and 3000 Hz.

Test data:



[Table of Contents](#)

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: V\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

OCCUPIED BANDWIDTH

Part 2.1049(c) EMISSION BANDWIDTH: Part 90.210(b) 25kHz Channel Spacing

Data in the plots show that on any frequency removed from the assigned frequency by more than 50%, but not more than 100%: At least 25dB. On any frequency removed from the assigned frequency by more than 100%, but not more than 250%: At least 35 dB. On any frequency removed from the assigned frequency by more than 250%, of the authorized bandwidth: At least $43 + 10\log(P)$ dB.

Part 90.210(c) 25 kHz Channel Spacing Not Equipped with a Low Pass Filter

For transmitters that are not equipped with an audio low pass filter pursuant to S90.211 (b), the power of any emission must be attenuated below the unmodulated carrier output power as follows; (1) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5 kHz but not more than 10 kHz: At least $83 \log(f_d/5)$ dB; (2) ON any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 10 kHz, but not more than 250% of the authorized bandwidth: At least $29 \log(f_d^2/11)$ dB or 50 dB, whichever is the lesser attenuation; (3) On any frequency removed from the center of the authorized bandwidth by more than 250% of the authorized bandwidth: At least $43 + 10 \log(P_0)$ dB.

Part 90.210(d) Emission Mask D - 12.5 kHz channel BW equipment.

For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27 (f_d - 2.88 \text{ kHz})$ dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10\log(P)$ dB or 70 dB, whichever is the lesser attenuation.

[Table of Contents](#)


Part 90.210(e) Emission Mask E – 6.25 kHz channel BW equipment.

For transmitters designed to operate with a 6.25 kHz bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 3.0 kHz removed from f_0 : Zero dB.
- (2) On any frequency from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 3.0 kHz but no more than 4.6 kHz: At least $30 + 16.67(f_d - 3.0 \text{ kHz})$ or $55 + 10 \text{ Log}(P)$ or 65, whichever us the lesser attenuation.
- (3) On any frequency removed from the center of the authorized bandwidth by more than 4.6kHz: At least $55 + 10\text{log}(P)$ dB or 65 dB, whichever is the lesser attenuation.

Method of Measurement: ANSI/TIA 603-D: 2010


Test Setup Diagram:



Test Data: See the plots below

OCCUPIED BANDWIDTH PLOTS: ANALOG
Part 90.210(D) Emission Mask D - 12.5 Khz Channel Bandwidth - ANALOG

99% Measured Bandwidth = 7.5 KHz



[Table of Contents](#)

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

SPURIOUS EMISSIONS AT ANTENNA TERMINALS (CONDUCTED)


Rule Part No.: Part 2.1051(a)

Requirements:

- 12.5 kHz Channel Spacing = $50 + 10 \log(5.0) = 57.0$ dBc (high power)
- 12.5 kHz Channel Spacing = $50 + 10 \log(1.0) = 50.0$ dBc (low power)

Method of Measurement: The carrier was modulated 100% using a 2500 Hz tone. The spectrum was scanned from the lowest frequency generated to at least the 10th harmonic of the fundamental. The measurements were made in accordance with standard ANSI/TIA 603-D: 2010.

Method of Measuring Conducted Spurious Emissions



Test Data: High Power Low end of Band

	dBm	dBm	Watts
Power Output	37	37	5
	Frequency	dBm	dBc
	150.8	37	0
	301.6	-45.63	82.63
	452.4	-64.81	101.81
	603.2	-85.32	122.32
	754	-82.64	119.64
	904.8	-88.34	125.34

[Table of Contents](#)

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

Test Data: High Power Middle of Band

	dBm	dBm	Watts
Power Output	37	37	5
	Frequency	dBm	dBc
	155	37	0
	310	-45.34	82.34
	465	-62.68	99.68
	620	-84.09	121.09
	775	-80.89	117.89
	930	-94.3	131.3

Test Data: High Power Middle of Band

	dBm	dBm	Watts
Power Output	37	37	5
	frequency	dBm	dBc
	162.05	37	0
	324.1	-45.75	82.75
	486.15	-62.62	99.62
	648.2	-76.26	113.26
	810.25	-80.71	117.71
	972.3	-88.01	125.01

[Table of Contents](#)

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

Test Data: High Power High End of Band

	dBm	dBm	Watts
Power Output	37	37	5
	frequency	dBm	dBc
	173.5	37	0
	347	-52.42	89.42
	520.5	-64.86	101.86
	694	-66.52	103.52
	867.5	-79.97	116.97

Test Data: Low Power Low end of Band

	dBm	dBm	Watts
Power Output	30	30	1
	Frequency	dBm	dBc
	150.8	30	0
	301.6	-49.41	79.41
	452.4	-79.39	109.39
	603.2	-90.31	120.31
	754	-95.23	125.23
	904.8	-95.68	125.68

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

Test Data: Low Power Middle of Band

	dBm	dBm	Watts
Power Output	30	30	1
	Frequency	dBm	dBc
	155	30	0
	310	-49.5	79.5
	465	-80.82	110.82
	620	-90.95	120.95
	775	-98.26	128.26
	930	-99.92	129.92

Test Data: Low Power Middle of Band

	Frequency	dBm	dBc
	162.05	30	0
	324.1	-51.43	81.43
	486.15	-82.61	112.61
	648.2	-88.22	118.22
	810.25	-95.43	125.43
	972.3	-99.76	129.76

[Table of Contents](#)

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

Test Data: low Power High End of Band

	dBm	dBm	Watts
Power Output	30	30	25
	Frequency	dBm	dBc
	173.5	30	0
	347	-52.42	82.42
	520.5	-65.62	95.62
	694	-66.52	96.52
	867.5	-78.66	108.66

Remarks: Emissions were checked to the tenth harmonic of each frequency tested, No Emissions found past 1000 MHz

RESULTS: PASS

[Table of Contents](#)

FIELD STRENGTH OF SPURIOUS EMISSIONS


Rule Parts. No.: Part 2.1053

Requirements:

$$12.5\text{kHz Channel Spacing} = 50 + 10\log(OP) = \text{dBc}$$

METHOD OF MEASUREMENT: The tabulated data shows the results of the radiated field strength emissions test. The spectrum was scanned from 30 MHz to at least the tenth harmonic of the fundamental. This test was conducted per ANSI/TIA 603-D: 2010 using the substitution method. Measurements were made at the test site of TIMCO ENGINEERING, INC. located at 849 NW State Road 45, Newberry, FL 32669.

Test Setup Diagram:



Test Data:

LOW POWER: Middle of the Band

Emission Frequency (MHz)	Power Mode	ERP Power Output (dBm)	ERP Power Output (Watts)	FCC Requirement dB	Bandwidth - BW - kHz
155.00	Lo	30.00	1.00	50.00	12.50
Emission Frequency (MHz)	Ant. Polarity		Below Carrier (dBc)	Margin	
310.00	H		91.42	41.42	
465.00	H		100.17	50.17	
620.00	H		93.27	43.27	
775.00	H		95.26	45.26	
930.00	H		90.31	40.31	
1,085.00	H		101.37	51.37	
1,240.00	H		99.36	49.36	
1,395.00	H		100.95	50.95	
1,550.00	H		101.28	51.28	

Emission Frequency (MHz)	Ant. Polarity	EUT Signal Reading	Signal Generator Reading	Coax Loss (dB)	Filter Insertion Loss	Substitution Antenna	ERP (dBm)	Below Carrier (dBc)	Margin
310.00	H	24.24	84.34	0.07	0.00	-1.25	-61.42	91.42	41.42
310.00	V	17.34	84.45	0.07	0.00	-1.25	-68.43	98.43	48.43
465.00	H	14.18	83.68	0.10	0.00	-0.57	-70.17	100.17	50.17
465.00	V	13.94	79.68	0.10	0.00	-0.57	-66.41	96.41	46.41
620.00	H	17.13	79.49	0.13	0.00	-0.77	-63.27	93.27	43.27
620.00	V	15.60	77.93	0.13	0.00	-0.77	-63.23	93.23	43.23
775.00	H	16.70	80.80	0.17	0.00	-1.00	-65.26	95.26	45.26
775.00	V	14.71	78.70	0.17	0.00	-1.00	-65.15	95.15	45.15
930.00	H	16.09	74.87	0.20	0.00	-1.32	-60.31	90.31	40.31
930.00	V	15.49	73.87	0.20	0.00	-1.32	-59.91	89.91	39.91

[Table of Contents](#)

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

Test Data:

HIGH POWER: Middle of the Band

Emission Frequency (MHz)	Power Mode	ERP Power Output (dBm)	ERP Power Output (Watts)	FCC Requirement dB	Bandwidth - BW - kHz
155.00	Hi	37.00	5.01	57.00	12.50
Emission Frequency (MHz)	Ant. Polarity		Below Carrier (dBc)	Margin	
310.00	H		101.43	44.43	
465.00	H		95.60	38.60	
620.00	H		96.45	39.45	
775.00	H		99.41	42.41	
930.00	H		86.06	29.06	
1,085.00	H		108.37	51.37	
1,240.00	H		106.36	49.36	
1,395.00	H		107.95	50.95	
1,550.00	H		108.28	51.28	

Emission Frequency (MHz)	Ant. Polarity	EUT Signal Reading	Signal Generator Reading	Coax Loss (dB)	Filter Insertion Loss	Substitution Antenna	ERP (dBm)	Below Carrier (dBc)	Margin
310.00	H	21.23	84.34	0.07	0.00	-1.25	-64.43	101.43	44.43
310.00	V	18.28	84.45	0.07	0.00	-1.25	-67.49	104.49	47.49
465.00	H	25.75	83.68	0.10	0.00	-0.57	-58.60	95.60	38.60
465.00	V	20.63	79.68	0.10	0.00	-0.57	-59.72	96.72	39.72
620.00	H	20.95	79.49	0.13	0.00	-0.77	-59.45	96.45	39.45
620.00	V	18.03	77.93	0.13	0.00	-0.77	-60.80	97.80	40.80
775.00	H	19.55	80.80	0.17	0.00	-1.00	-62.41	99.41	42.41
775.00	V	16.30	78.70	0.17	0.00	-1.00	-63.56	100.56	43.56
930.00	H	27.34	74.87	0.20	0.00	-1.32	-49.06	86.06	29.06
930.00	V	22.98	73.87	0.20	0.00	-1.32	-52.42	89.42	32.42

Remarks: Emissions were checked from 30 MHz to the tenth harmonic of each frequency tested, No Emissions found past 1000 MHz

RESULTS: PASS

[Table of Contents](#)

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

FREQUENCY STABILITY

Rule Parts. No.: Part 2.1055, Part 90.213

Requirements: Temperature range requirements: -30 to +50° C.
Voltage Variation +, -15%
±2.5 PPM

Method of Measurements: ANSI/TIA 603-D: 2010.

Test Data:

Temperature	Frequency MHz	PPM
25°C (reference)	173.499998	
-30°C	173.499926	-0.415
-20°C	173.49994	-0.334
-10°C	173.499948	-0.288
0°C	173.499955	-0.248
10°C	173.499981	-0.098
20°C	173.499992	-0.035
30°C	173.49999	-0.046
40°C	173.499982	-0.092
50°C	173.499976	-0.127
Battery Voltage	Frequency	PPM
-15%	173.500002	0.023
15%	173.499993	-0.029

Results: Pass

[Table of Contents](#)

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

TRANSIENT FREQUENCY BEHAVIOR

Part 90.214 Transient Frequency Behavior

REQUIREMENTS: Transmitters designed to operate in the 150-174 MHz and 421-512 MHz frequency bands must maintain transient frequencies within the maximum transient frequencies within the maximum frequency difference limits during the time intervals indicated:

Time Intervals	Maximum frequency difference	All Equipment	
		150-174 MHz	421-512 MHz

Transient Frequency Behavior for Equipment Designed to Operate on 25 kHz Channels

Time Intervals	Maximum frequency difference	150-174 MHz	421-512 MHz
t_1^4	± 25.0 kHz	5.0 ms	10.0 ms
t_2	± 12.5 kHz	20.0 ms	25.0 ms
t_3^4	± 25.0 kHz	5.0 ms	10.0 ms

Transient Frequency Behavior for Equipment Designed to Operate on 12.5 kHz Channels

Time Intervals	Maximum frequency difference	150-174 MHz	421-512 MHz
t_1^4	± 12.5 kHz	5.0 ms	10.0 ms
t_2	± 6.25 kHz	20.0 ms	25.0 ms
t_3^4	± 12.5 kHz	5.0 ms	10.0 ms


Transient Frequency Behavior for Equipment Designed to Operate on 6.25 kHz Channels

Time Intervals	Maximum frequency difference	150-174 MHz	421-512 MHz
t_1^4	± 6.25 kHz	5.0 ms	10.0 ms
t_2	± 3.125 kHz	20.0 ms	25.0 ms
t_3^4	± 6.25 kHz	5.0 ms	10.0 ms


[Table of Contents](#)

TEST PROCEEDURE: ANSI/TIA 603-D:2010, the levels were set as follows:

1. Using the variable attenuator the transmitter level was set to 40 dB below the test receivers maximum input level, then the transmitter was turned off.
2. With the transmitter off the signal generator was set 20dB below the level of the transmitter in the above step, this level will be maintained with the signal generator through-out the test.
3. Reduce the attenuation between the transmitter and the RF detector by 30 dB.
4. With the levels set as above, the transient frequency behavior was observed and recorded.



Test Data:



Results: Pass


[Table of Contents](#)

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

Test Data:



Results: Pass

[Table of Contents](#)

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx

EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
12 Volt Power Supply	Astron	RS-12A	9312779	NA	NA
DC Power Supply	HP	6286A	1744A03842	NA	NA
Antenna: Biconnical Chamber	Eaton Chamber	94455-1	1057	06/14/13	06/14/15
Antenna: Log-Periodic Chamber	Eaton	96005	1243	05/31/13	05/31/15
LISN (Primary)	Electro-Metrics	EM-7820	2682	02/26/13	02/26/15
DC Power Supply	HP	6264B	2032A04119	05/06/13	05/06/15
AC Voltmeter	HP	400FL	2213A14728	06/26/13	06/26/15
Digital Multimeter	Fluke	77	35053830	08/22/13	08/22/15
Audio Analyzer	HP	8903B	3011A13084	08/22/13	08/22/15
Frequency Counter Small Chamber	HP	5385A	3242A07460	06/16/13	06/16/15
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	12/31/13	12/31/15
Ant: Double-Ridged Horn/ETS Horn 1 Ch	ETS-Lindgren Chamber	3117	00035923	06/13/14	06/13/16
Audio Analyzer	HP	8903A	2336A03066	08/30/13	08/30/15
Temperature Chamber Small	Thermotron Corp.	S1.2 Mini Max	25-1420-09	08/20/14	08/20/16
EMI Test Receiver R & S ESIB 40 Screen Room	Rohde & Schwarz	ESIB 40	100274	08/12/14	08/12/16
Software: Field Strength Program	Timco	N/A	Version 4.0	NA	NA
Hygro-Thermometer	Extech	445703	0602	06/20/13	06/20/15
Signal Generator R & S SMIQ 02	Rohde & Schwarz	SMIQ02	DE24678	06/11/14	06/11/16
30 dB Attenuator	Narda	769-30	10267	03/15/13	03/15/15
EMI Test Receiver R & S ESU 40 Chamber	Rohde & Schwarz	ESU 40	100320	03/11/14	03/11/16
Signal Generator HP 8648C	HP	8648C	3623A02898	08/29/13	08/29/15

* EMI RECEIVER SOFTWARE VERSION

The receiver firmware used was version 4.43 Service Pack 3

Applicant: VERTEX STANDARD USA, INC.

FCC ID: AXI11283020

Report: \\VERTEX STANDARD USA\2220AUT14\2220AUT14TestReport.docx