



1601 North A.W. Grimes Blvd., Suite B

Round Rock, TX 78665

e-mail: info@ptitest.com

(512) 244-3371 Fax: (512) 244-1846

Statements Regarding MURS Requirements	
Paragraph Reference	Justification
§95.2725 MURS interference.	The device first listens for an idle channel before transmitting.
§95.2731 Permissible MURS uses.	The device only transmits locally pre-recorded voice messages, and optionally with standard sub-audible coding.
§95.2733 Prohibited MURS uses.	The receiving function is limited to testing for channel activity only. It cannot function as a booster or as a store-and-forward device.
§95.2741 MURS antenna height limit.	The antenna is internal to the device. The device is used within or mounted to a wall of the hosting structure. It is not designed to be mounted on a mast or tower. There is no external antenna connector.
§95.2749 MURS network connection.	The device has no capability to connect to the PSTN.
§95.2757 MURS duration of transmissions.	The device total storage capacity is 20 seconds and has minimum delays programmed to listen for channel activity. Consequently the maximum transmit time is limited by design.
§95.2761 MURS transmitter certification.	This model is exclusively programmed and sold as a MURS device.
§95.2763 MURS channels.	This model can be programmed to operate on the following channels: 151.820, 151.880, 151.940, 154.570, and 154.600 MHz

Signed:

Eric Lifsey
