

IDENTIFICATION LABEL

LOCATION

- See The Attached Photograph Or Sketch
- Back Of Radio
- Back Of Radio Under Belt Clip

TYPE

The label is a paper polyester film laminate with a pressure sensitive adhesive backing. The adhesive is a permanent type acrylic with a minimum peel strength of 40 oz/inch.

MARKINGS (TEXT)

- See The Attached Photograph
- Label Attached Below.
- See Attached Drawing.



GENERAL INFORMATION

1. Production Plans -- Pursuant 2.981 (c)

Quantity production is planned.

II. Application References -- Pursuant 2.1061

Reference is made to the following Motorola "Application References"

1. Portable Products and their application.
2. Portable Products Transmitter Modulations Methods.
3. Boynton Beach Antenna Range.

III. Data Submittal Procedure:

Data is supplied in accordance with Part 2, Sub-part J of the Commissions' rules.

Necessary Bandwidth Computation for 8K10F1E Emission Designator

The FCC Rule & Regulations Part 2, §2.202(b) defines *Necessary Bandwidth* as the minimum value of the occupied bandwidth sufficient to ensure that transmission of information at the rate and with the quality required for the system employed. §2.202(c) lists four methods of determining the necessary bandwidth, including the use of formulas in §2.202(g), and measurement in cases where the other methods of §2.202(c) do not apply. It is felt that while these formulas apply well to voice and many older digital modulation systems, the formulas do not apply to the high performance digital modulation employed in the system submitted for type acceptance because of difficulties determining representative values for the factors K and M. We have, therefore, used the measurements criteria of §2.202(c)(4).

The value cited, 8K10, is the bandwidth that contains 99% of the total transmitted power. The 99% value was chosen because §2.202(b) defines *Necessary Bandwidth* as the minimum value of the occupied bandwidth. In turn, §2.202(b) defines *Occupied Bandwidth* as the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5% of the total mean power radiated by a given emission, i.e., contains 99% of the total transmitted power.

IV. Applicable References:

Reference Type Acceptance FCC ID: AZ489FT4821
EIA/TIA-603 Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
FCC Federal Regulations Part 47 Sec. 2.983-2.999
FCC Federal Regulations Part 90 Sec.90.210

EXHIBIT 1a