

## General

This document is to describe the four types of internal Modems that are used to modulate data for radio transmission in Moscad\_L products.

This modems are in use with the P44 UHF 1 (FLN5923A) and UHF2 (FLN5922A) radios.

## DFM Modem



The Direct FM modulator produces a 3 level signal in the following principle:

A logic "1" is taken as the mid-level of the transmitted signal while the logic "0" takes values of the upper and lower levels alternately.

The transmitted signal passes through a low pass filter to produce a band-limited signal.

The bit rate is up to 4800 bps.

### DFM Modulation - Wave Form Example



The output data from the modem passes through a low pass filter so the final signal to the radio is in sinus shape with 350mV Pk-Pk.

(175mV Pk-Pk = 1 KHz deviation in the radio)

# FSK Modem


The FSK modulator produces a signal in the following principle:

A logic “0” produces a one period of a sine wave, which its frequency equals to the bit rate.


A logic “1” produces a half period of a sine wave, which its frequency equals to the half of the bit rate.

The bit rate is up to 2400 bps.

## FSK Modulation - Wave Form Example



## Transmitter bandwidth



# DPSK

DPSK is a standard v.22 1200 bits per second modem.

It is a Differential Phase Shift Key modulation on a 1200Hz carrier.

Every two bits in the stream data encoded as a phase change relative to the phase of the previous signal phase.



The data is entered to the encoded modem modulator after 17 bits pseudo random scrambler.

Phase changes:

Bits	Phase Change
00	+90
01	0
10	+180
11	270

The 3 DB Transmit frequency bandwidth is 900 Hz – 1500 Hz

Center frequency (carrier) is 1200 Hz +/- 1Hz




# COS


Cos is a 9600 bps, 3 level doabinary modem.

The basic operation of the modem is to transfer the data through a filter with a cosine shape. The shape reduces the frequency bandwidth of the transmitted signal to less than 4800 Hz.

Every transmitted bit is encoded and passes through 7 bits pseudo random encoder.



## COS Modulation - Wave Form Example



$$T = 1/9600 \text{ Sec}$$

## Transmitter bandwidth

