
TALKABOUT ® EMERGENCY PREPAREDNESS TWO-WAY **RADIO T48X Series**





MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners.

© 2015 and 2019 Motorola Solutions, Inc. All rights reserved.

For More Information

For further information, you may call Motorola Solutions at 1-800-448-6686 (Canada and U.S.), or visit us on the Internet at www.motorolasolutions.com/talkabout

Safety and General Information

Caution

Before using this radio, read this booklet which contains important operating instructions.

For information on product details, brochures, user manuals and approved accessories. Please refer to

Compliance with RF Exposure Standards

National and international regulations require manufacturers to comply with the RF energy exposure limits for portable two-way radios before they can be marketed. Your Motorola Solutions two-way radio is designed, manufactured, and tested to comply with all applicable national and international regulations for human exposure to radio frequency electromagnetic energy. RF Energy Exposure Awareness and Control Information and Operational Instructions for General Population and

Uncontrolled Environment Use For more information on what RF energy exposure is, see the

following websites:

- https://www.fcc.gov/
- http://www.who.int/peh-emf/project/en/ For additional information, see

https://www.motorolasolutions.com/en_us/about/ company overview/corporate-responsibility/governance-andpolicies/ elesscommunication-and-health-faqs.html.

FCC Licensing Information

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions. may cause harmful interference to radio communications However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna
- Increase the separation between the equipment and
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician

Operating Instructions

- Transmit no more than 50% of the time. To transmit (talk), press the Push-To-Talk (PTT) button. To receive calls, release the PTT button
- Hold the radio in a vertical position in front of the face with the microphone (and other parts of the radio including the antenna) at least 1 in. (2.5 cm) away from the nose or lips. Antenna should be kept away from the eye.
- When worn on the body, always place the radio in a Motorola Solutions-approved clip, holder, holster, case, or body harness for this product.

DO NOT hold the antenna when the radio is transmitting. · DO NOT use any portable radio that has a damaged antenna If a damaged antenna comes into contact with your skin, a minor burn can result. • To ensure continued compliance with applicable RF exposure

limits. use only Motorola Solutions-approved, supplied or replacement antennas, batteries, and accessories. For a list of Motorola Solutions-approved accessories please

refer to your user manual or visit www.motorolasolutions.com

Acoustic Safety

Exposure to loud noises from any source for extended periods of time may temporarily or permanently affect your hearing. The louder the volume of the radio, the sooner your hearing will be affected. Hearing damage from loud noise is sometimes undetectable at first, and can have a cumulative effect. To protect your hearing, follow these precautions:

- Use the lowest volume necessary to do your job
- Turn up the volume only if you are in noisy surroundings. · Turn down the volume before putting on a headset or
- headphones · Limit the amount of time you use a headset or headphones at
- high volume. · When using the radio without a headset or headphones, do not place the speaker of the radio directly against your ear.

Medical Devices

(BC)

If you use a personal medical device, such as a pacemaker or hearing aid, consult the manufacturer of your device to determine if it is adequately shielded from RF energy. Your physician may be able to assist you in obtaining this information

Operational Warnings

The following explains the operational warnings:

For Vehicle With Air Bags

Refer to vehicle manufacturer's manual prior to installation of electronic equipment to avoid nterference with air bag wiring.



DO NOT place a portable radio in the area over an air bag or in the air bag deployment area. Air bags inflate with great force. If a portable radio is WARNING placed in the air bag deployment area and the air bag inflates, the radio may be propelled with great force and cause serious injury to occupants of the

Potentially Explosive Atmospheres

Warning:

Use of a radio that is not intrinsically safe in a potentially explosive atmosphere could result in a serious injury, or death. You should only use a certified Intrinsically Safe radio in potentially explosive atmospheres.

Explosive atmospheres refer to hazard classified locations that may contain hazardous gas, vapors, dusts, such as fueling areas below decks on boats, fuel, or chemical transferor storage facilities, and areas where the air contains chemicals or particles such as grain,



metal powders. Areas with potentially explosive atmospheres are often, but not always, posted. Turn off your radio prior to entering any area with a potentially explosive atmosphere unless in is a radio type specifically certified for use in hazardous location areas.

DO NOT remove, install, or charge batteries in such areas, or remove or install antennas. Sparks n a potentially explosive atmosphere can cause an explosion or fire resulting in bodily injury or even death.

Blasting Caps and Blasting Areas



Warning: To avoid possible interference with blasting operations, turn off your radio when you are near electrical blasting caps, in a blasting area, or in areas posted: "Turn off two-way radio Obey all signs and instructions.

Batteries

- · Charge your battery using the approved Motorola Solutions charger.
- Use the battery in accordance with its water and/or dust Ingress Protection (IP) rating.
- · Do not discard your battery into a fire.
- Do not replace the battery in any area labeled "Hazardous
- Do not disassemble, crush, puncture, shred, or otherwise attempt to change the form of your battery.
- Do not dry a wet or damp battery with an appliance or heat source, such as a hair dryer or microwave oven.
- Do not allow conductive material such as iewelry, keys, or beaded chains to touch exposed battery terminals

Do Not Substitute Options or Accessories

The Motorola Solutions communications equipment certified as intrinsically safe by the approving agency (FM, UL, CSA, CENELEC) is tested as a complete system which consists of the listed agency approved portable, approved battery, and approved accessories or options, or both. This approved portable and battery combination must be strictly observed There must be no substitution of items, even if the substitute

has been previously approved with a different Motorola Solutions communications equipment unit. Approved configurations are listed by the approving agency (FM, UL, CSA. CENELEC). The Intrinsically Safe Approval Label affixed to radio refers to

the intrinsically safe classification of that radio product, and the approved batteries that can be used with that system. The manual PN referenced on the Intrinsically Safe Approval Label identifies the approved accessories and or options that can be used with that nortable radio unit Using a non-Motorola Solutions-intrinsically safe battery and/or accessory with the Motorola Solutions-approved radio unit will

European Union (EU) Waste of Electrical and Electronic Equipment (WEEE) Directive

void the intrinsically safe approval of that radio unit.

he European Union's WEEE directive requires that products sold into EU countries must have the crossed out trash bin label on the product (or the package in some cases). As defined by the WEEE directive, this cross-out trash bin label neans that customers and end-users in EU ountries should not dispose of electronic and electrical equipment or accessories in household waste. Customers or end-users in EU countries hould contact their local equipment supplier representative or service centre for information about the waste collection system in their country

Supplier's Declaration of Conformity

Supplier's Declaration of Conformity er FCC CFR 47 Part 2 Section 2.1077(a) Responsible Party Name: Motorola Solutions, Inc. Address: 500 West Monroe Street, Floors 39-44, hicago, IL 60661, nited States of America CHICAGO ILLINOIS US hone Number: 1-800-927-2744 ereby declares that the product: /lodel Name: T482 conforms to the following regulations: FCC Part 15, subpart B, section 15.107(a), 15.107(d),

Notice to Users (FCC and Industry Canada)

and section 15.109(a)

This device complies with Part 15 of the FCC rules and Industry Canada's license-exempt RSS's per the following conditions: This device may not cause harmful interference.

- This device must accept any interference received, including interference that may cause undesired operation.
- Changes or modifications made to this device, not expressly approved by Motorola Solutions, could void the authority of the user to operate this equipment

FCC Licensing Information

USA (FCC)/CANADA

According to FCC Part 95, FRS devices do not require a license. Use of Motorola radio in Canada is subject to the rules regulations in ISED RSS 210 and do not require a license.

Changes or modifications not expressly approved by Motorola Solutions may void the user authority granted by the FCC or ISED to operate this radio and should not be made. To comply with FCC or ISED requirements, transmitter adjustments should be made only by or under the supervision of a person certified as technically qualified to perform transmitter maintenance and repairs in the private land mobile and fixed services as certified by an organization representative of the user of those services. Replacement of any transmitter component (crystal, semiconductor, etc) not authorized by the FCC or ISED


equipment authorization for this radio could violate FCC or ISED

Note: Use of this radio outside the country where it was intended to be distributed is subject to government regulations and may be prohibited

Control Buttons



Display Screen Guide



Getting Started

Weatherproof

This radio is weatherproof to IP-54 standards. It is dust/ splashproof from any direction. The radio is resistant to water and rain splashes only when the battery cover, headset accessory port, and micro-USB ports are sealed. Open the battery compartment door or headset port cover only when the radio is dry. Use of a headset accessory should be in dry environments only.

The micro-USB adaptor is not waterproof. Do not expose to rain or snow. Charge the radios only in a dry location. Do not charge wet radios. The battery door must be tightly closed with the screw to maintain the weatherproof seal of the radio.

Installing the Batteries

Each radio can use either 1 NiMH rechargeable battery pack or 3 AA alkaline batteries and beeps when the batteries are low.

Installing the NiMH Rechargeable Battery Pack (Optional Accessory)

- Turn the radio off
- 2. With the back of the radio facing you, loosen the retaining screw on the battery door and open the cover
- Remove the NiMH battery pack from the clear plastic bag (do not disassemble or unwrap the battery pack).
- 4. Insert the NiMH battery pack with the diagram facing you (The ribbon should be underneath the battery pack and should wrap around the right side of the pack for easy
- 5. Close the battery cover and tighten the retaining screw on the battery cover

Installing the Three AA Alkaline Batteries

- 1. Turn the radio off.
- With the back of the radio facing you, lift the battery cover latch up and remove the cover.
- 3 Insert the three AA Alkaline batteries with + and polarity as shown inside. (The ribbon should be underneath the AA alkaline batteries and should wrap around the right side of the batteries).
- 4. Close the battery cover and tighten the retaining screw on the battery cover.

Radio Battery Meter

The radio battery icon shows the battery charge level, from full to empty _____. When the radio has one segment left, the radio chirps periodically or after releasing the PTT button (Low Battery Alert).

Removing Battery Door and Belt Clip

- 1. Use your thumb or index finger to unlatch the belt clip tab, use thumb on another hand to push up the belt clip.
- 2. Use a coin to unscrew the battery door screw lock.

Removing the NiMH Battery Pack

- 1 Turn the radio off
- 2. With the back of the radio facing you, loosen the retaining
- screw on the battery door and open the cover. 3. Remove the NiMH battery pack by pulling the ribbon attached to the radio.
- 4. Close the battery cover and tighten the retaining screw on the battery door

Removing the Three AA Alkaline Batteries

- 1. Turn the radio off.
- 2. With the back of the radio facing you, loosen the retaining screw on the battery door and open the cover 3. Gently remove each alkaline battery by easing each battery
- out individually 4. Close the battery cover and tighten the retaining screw on
- the battery door

- Exercise care when removing NiMH or AA batteries. Do not use sharp or conductive tools to remove either of these Remove the batteries before storing your radio for extended
- periods of time. Batteries corrode over time and may cause permanent damage to your radio.

Battery Capacity Maintenance

- 1. Charge the NiMH batteries once every 3 months when not in
- Before placing the radio in storage, remove the battery. Store the NiMH batteries in temperature between -20 °C to 35 °C and in low humidity. Avoid damp conditions and

Using the Micro-USB Charger

The micro-USB charger is a handy port that allows you to conveniently charge your NiMH battery pack.

- 1. Plug the micro-USB cable into the micro-USB charging port on your radio. Connect the other end of the micro-USE charger to wall power outlet
- 2. An empty battery will be fully charged in 14 hours.
- 3. The battery meter on LCD will move to indicate the battery is charging.


 When moving between hot and cold temperatures, do not. charge the NiMH battery pack until the battery temperature acclimates (usually about 20 minutes)

Using the Desk/Wall Stand

This stand allows for convenient placement during charging (on desk or hung on wall). Cable management can be achieved via cavity at bottom of stand

- Determine the required cable length.
- Place rolled up cable with cable tie into stand around the two latches following markings for correct orientation

Note: For alternate lengths, wrap cable around approximately 3 fingers for correct loop size



3. Assemble bottom cover on stand.

Quiet Charge

In order to ensure that your radio is always charged and on alert, we recommend that you leave the radio plugged in and turned on. The Quiet Charge feature allows you to disable the reception from regular two-way calls while still receiving weather alerts and receive and transmit emergency alerts To activate quiet charge

- 1. Press 9 times until **Q**⁴ appears on the display. The current setting will flash.
- 2. Press + or to select On or Off.
- 3. Press the PTT button or (a) to set.

Note: Turn Quiet Charge off when you want to have full two-way call functionality (receive all activity on your channel).

Attaching and Removing the Belt Clip

- Attach the belt clip to the Talkabout plate at the back of the radio until the clip clicks in place. 2. Attach the belt clip to pocket or belt strap until the clip clicks
- in place
- Pull the release tab on top of the belt clip to release the latch. 2. Push the belt clip with the other hand towards the top of the

Turning your Radio On and Off

Turn !!! clockwise to turn the radio on and counterclockwise to turn the radio off

- 1. In the ON position, the radio chirps and briefly shows all feature icons available on the radio
- 2. The display screen then shows the current channel, code and all features that are enabled. The radio is now in Two-Way mode

Setting the Volume

Press and hold (Figure 1) for three seconds while rotating (Figure 1) until you reach a comfortable listening level

- 1 Rotate Colockwise to increase the volume
- 2. Rotate Counterclockwise to decrease the volume. Do not hold the radio close to your ear. If the volume is set to an uncomfortable level, it could hurt your ear

Talking and Listening

To communicate, all radios in your group must be set to the same channel and Interference Eliminator Code. 1. To talk, press and hold the PTT button. When transmitting,

TW0-WAY icon blinks and Tx is shown. If it is a high power transmission, **H**i is shown. If it is a low power

transmission, **L0** is shown. 2. When you are finished talking, release the PTT button

3. When receiving, $\boxed{\text{TW0-WAY}}$ icon blinks and $\boxed{\textbf{Rx}}$ is shown. If it is a high power channel, **H**is shown. If it is a low power channel, **Lo** is shown.

For maximum clarity, hold the radio two to three inches away from your mouth and speak directly into the microphone. Do not cover the microphone while talking

Note: The use of an emergency two-way radio is best when other people in your community are using two-way radios as well. Talk to neighbors and friends nearby and suggest

Talk Range

Your radio is designed to maximize performance and improve transmission range. Do not use the radios closer than five feet

Power Boost

portion of the PTT button when talking. If you know your party is close by, you can conserve the energy of your battery by pushing the lower part of the PTT button to use less power Note: If you are on an FRS only channel (see "Channels and Frequencies") the radio will only use low power when either portion of the PTT button is pressed Power Boost is not applicable for model T400.

Monitor Button

Pressing and holding for three seconds allows you to listen to the volume level of the radio when you are not receiving. This allows you to adjust the volume, if necessary. You can also

press to check for activity on the current channel before you

To prevent accidental transmissions and save battery life, the radio emits a continuous warning tone and stops transmitting if you press the PTT button for 60 continuous seconds.

Mode Button

By pressing "mode" button, the user will be seamlessly switching between two-way, weather mode and FM mode. When radio is in two-way mode, **TW0-WAY** will be shown. When radio is in weather mode, **WEATHER** will be shown.

Corresponding setting and information will be shown on the

Selecting the Channel

Your radio has 22 channels. The channel is the frequency the radio uses to transmit. Channels 8-14 are FRS 0.5 watt only and all other channels are GMRS. (See the "Channels and Frequencies" table on overleaf for details)

1. With the radio on, press 1 time until the channel number starts to flash. When the radio is on a 0.5 watt channel

display shows **LO**. When the radio is on a 1.5 watts channel, display shows **Hi**. The current channel flashes.

2. Press + or - and select an unused or quiet channel. 3. Press the PTT button to save the channel setting or (a) to

continue set up.

Interference Eliminator Codes help minimize interference by blocking transmissions from unknown sources. Your radio has 121 Interference Eliminator Codes. Codes 1 – 38 are standard analog codes that appear on other FRS/GMRS radios. Codes 39 – 121 are additional digital codes added for superior interference protection. 0 is the off position, no analog or digita

1. Press (a) 2 times until the code starts to flash.

2. Press (+) or (-) to select the code.

You can set a different code for each channel using this procedure. An extended press of (+) or (-) allows you to scroll through the Interference Code rapidly so you can quickly reach

Note: On a radio that uses Interference Eliminator Codes, the code must be set to 0 to communicate with radios that do not have Interference Eliminator Codes. Select 0 for "no

your group so you can alert them that you want to talk. Your radio has 20 call tones from which to choose. To set a call tone

setting will flash.

3. Press the PTT button to set the new call tone or (a) to

Note: Setting the call to OFF disables the call tone feature

You can use the **ivox** feature to transmit hands-free without

the need for any headset accessories. Once **iVOX** is turned on,

channel and Interference Eliminator Code as your radio, press

Setting and Transmitting Call Tones Your radio can transmit different call tones to other radios in

1. Press 3 times until ② appears. The current call tone

2. Press (+) or (-) to change and hear the call tone.

to check in on each other when disaster strikes.

To boost your radio's power up to high power, press the top

Push-to-Talk Timeout Timer

Menu Options

Selecting the Interference Eliminator Code

codes are enabled

To set the code for a channel:

3. Press the **PTT** button to save the code setting or to continue set up.

tone, no code" on the display of your radio.

continue set up. To transmit your call tone to other radios set up to the same

Hands-Free Use Without Accessories (ivox)

the radio detects your voice and transmits when you speak into the internal microphone.

- 1. Press 4 times until **IVOX** appears on the display. The current setting will flash
- 2. Press \oplus or \bigcirc to select On or Off or set sensitivity L1, L2
- 3. Press the **PTT** button to set or (a) to continue set up.

You can transmit hands-free more reliable with the use of

Hands-Free Use with Accessories (vox)

optional headset accessories. Once VOX is turned on, the radio detects your voice and transmits when you speak Many accessories (sold separately) are available for your radio. For more information, visit our website at www.motorolasolutions.com/TalkaboutAccessories or call

1-800-448-6686

- 1. Turn the radio off and plug the **VOX** accessory into the accessory port.
- 2. Turn the radio on. **yox** shows on the display.
- 3. Adjust the volume appropriately by rotating $\{\cdot\}$. Lower the volume before placing the accessory on your head or in your
- 4. To turn off, simply remove accessory.

Note:

- There is a short delay between the time you start talking and when the radio transmits. There is a short delay before the transmission is completed.
- iVOX and VOX will not function when the radio is in FM mode.

Setting the Sensitivity Level When in vox Mode Adjusting the radio's sensitivity level helps minimize the

possibility of unintended noises triggering a transmission and helps the radio pick up soft voices. 1. Press (a) 4 times until **VOX** appears. The current setting

- (L1 L3) will flash.
- 2. Press + or to select the sensitivity level
- 3. Press the **PTT** button to set or (a) to continue set up. L3 = High Sensitivity for quiet environments
- L2 = Medium Sensitivity for most environments
- L1 = Low Sensitivity for noisy environments

Note: When you connect a headset, the radio is automatically set to the last chosen sensitivity level.

Setting the Extended Battery Save Level (♥)

This feature puts the radio into a low power "sleep" mode for cycle periods of 1, 2 or 3 seconds. The radio will briefly check for any channel activity after each sleep cycle. The sleep cycle repeats until a key is pressed or a call is received.

- 1. Press a 5 times until appears. The current setting (L0, L1. L2 or L3) will flash.
- 2. Press + or to select the battery save level.
- 3. Press the **PTT** button to set or (a) to continue set up.

L0 = Normal battery save mode

- L1 = 1 second extended battery save mode (low setting)
- L2 = 2 seconds extended battery save mode (mid setting) L3 = 3 seconds extended battery save mode (max setting)

- 1. Signals received during the sleep period will not be heard until after the timer period expires. The first 1 – 3 seconds of speech can be missed. Do not use (battery save) L1, L2 or L3 settings when immediate response may be required
- 2. Z, **VOX**, **iVOX** and **Q**_T modes are not available with extended battery save mode. Using **\(\sigma_{\text{, VOX}} \), iVOX** or enabling Q_T will necessarily disable the extended sleep cycle battery settings.
- 3 Maximum battery life sayings may be achieved only when usage is primarily in standby mode and very little TX or RX (talking or listening) use occurs. When RX or TX are often used, little or no battery life extension will occur.

Q₇ Noise Filtering

The \mathbf{Q}_T noise-filtering feature helps to ensure uninterrupted communication with other Motorola Solutions radios that have this feature. This feature also filters out unwanted transmissions from other radios. This is useful in places where there is heavy radio traffic, such as amusement parks or ski resorts.

Note: Q_T noise filtering is not available when the radio is scanning. Q_T noise filtering is not available when extended battery save is set to L1, L2 or L3. In consequence the \textbf{Q}_{T} will not appear in the Menu. You must set extended battery save to L0 in order to activate Q_⊤ noise filtering

To turn Q_T on or off

- 1. Press (6 times until Q_T displays. The current setting On/
- 2. Press + or to select On or Off.
- 3. Press the PTT button to set or (a) to continue set up.

To transmit to a radio that has Q_T noise filtering turned on: 1. Select the same channel and Interference Eliminator Code

- 2. Press (1) to send a call tone. This allows your voice to pass
- through the \mathbf{Q}_{T} noise filter on the receiving radio.
- Press the PTT button and speak normally.

Note: Without first pressing ②, your message will not be heard. After this, for a 30-second period, starting after the last transmission, all transmissions received on the selected channel and code will pass through the noise filter. When radio goes to idle. will need to be pressed again to allow communication to pass through

Keypad Tones

You may enable or disable the speaker key tones. You will hear the key tone each time a button is pushed.

- 1. Press 🖲 7 times until 🍱 appears. The current setting On/
- 2. Press either + or to turn On or Off.
- 3. Press the **PTT** button to confirm or to continue set up. Note: When the key tone feature is off, the following are not disabled:
- · Transmit timeout alert tone
- Call tone
- · Low battery alert tone or

The transmitted talk confirmation tone **Transmitting a Talk Confirmation Tone**

You can set your radio to transmit a unique tone when you finish transmitting. It is like saying "Roger" or "Over" to let others know

- 1. With the radio on, press (a) 8 times until the A appears. The current setting On/Off flashes.
- 2. Press + or to turn On or Off.
- 3. Press the **PTT** button to set or (a) to continue set up.

Special Features

Emergency Alert Mode

The Emergency Alert feature can be used to signal members in your group of your need for urgent help. T4XX series radios will operate in an automatic "hands-free" emergency control mode for a total of 30 seconds after activating the Emergency Alert. T4XX series radios in your group will automatically advance the speaker volume to the maximum setting and sound a warbling alert tone for 8 seconds. The alert tone is emitted from your own radio speaker and the receiving radios in your group. After the 8 second alert, any spoken words or incidental sounds at your end will be transmitted to the group for 22 seconds. For the 30 second duration of Emergency Alert mode, T4XX series radio controls and buttons will be locked to maximize reception of the

- 1. Press and hold the Emergency Alert button for 3 seconds. 2. Release the button the alert tone begins to sound. There is no need to continue to hold the Emergency Alert button or
- use PTT for your message to be transmitted. 3. After the alert tone ends you may speak into the microphone. Your voice or incidental sounds will be
- After 30 seconds your radio speaker will emit a Talk Confirmation Tone. Operation then returns to normal two-way mode

Note: All Motorola Talkabout EM, MJ, MR, MT, MU and T4XX series radios (except for model T400) are fully compatible with the Emergency Alert feature. Radios other than EM, MJ and MR series can receive the emergency alert signal, but will not respond with adjusted volume settings. locked controls or a warbling alert tone. Users of other radio models set to the same channel and Interference Fliminator Code will hear a steady tone for 8 seconds followed by the voice transmission for 22 seconds.

WARNING: The Emergency Alert feature should only be used in the event of an actual emergency Motorola Solutions is not responsible if there is no response to the emergency alert from the receiving group

Built-in LED Flashlight with Power Outage Function

Press the flashlight button to turn and keep the light on. The LED flashlight has a power outage function where the light is turned on automatically when power is cut. When the flashlight is turned on, press the flashlight button to turn it off. Note: If the flashlight is turned on automatically due to a power cut, the flashlight will turn off automatically after 30

Keypad Lock

To avoid accidentally changing your radio settings:

minutes to conserve battery power.

- 1. Press and hold until displays.
- When in lock mode, you can turn the radio on and off, adjust the volume, receive, transmit, send a call tone and monitor channels. All other functions are locked.
- 3. To unlock the radio, press and hold until is no longer displayed.

Scanning Channels

Use scan to search the 22 channels for transmissions from unknown parties, to find someone in your group who has accidentally changed channels or to quickly find unused channels for your own use.

There is a priority feature and 2 modes of scanning (basic and advanced) to make your search more effective. The basic scan mode uses the channel and code combinations for each of the 22 channels as you have set them (or with the default code

value of 1). The "Advanced Scan" mode will scan all channels for any and all codes, detect any code in use and use that code value temporarily for that channel

Priority is given to the "home channel", that is, the channel (and Interference Eliminator Code) your radio is set to when you start the scan. This means the initial channel (and code settings) is scanned more often than the other 21 channels and your radio will respond quickly to any activity occurring on the home channel as a priority.

To start Scanning.

- 1. Briefly press the key. The scan will appear in the display and the radio will begin to scroll through the channel and code combinations.
- 2. When the radio detects channel activity matching the channel and code combination, it stops scrolling and you can hear the transmission. 3. To respond and talk to the person transmitting, press the
- PTT button within five seconds after the end of the transmission.
- 4. The radio will resume scrolling through the channels five seconds after the end of any received activity.
- 5. To stop scanning, briefly press the (key) key.
- To start Advanced Scanning
- 1. Set the Interference Eliminator Code to "zero" or OFF.
- 2. Briefly press the key. The scan will appear in the display and the radio will begin to scroll through the channels. No Interference Eliminator Codes will filter what is
- 3. When the radio detects channel activity with ANY code (or NO code), it stops scrolling and you can hear the transmission. Any Interference Eliminator Code that may be
- in use by that party will be detected and displayed. To respond and talk to the person transmitting, press the PTT button within five seconds of the end of the transmission. The radio will transmit using the newly detected Interference Eliminator Code.
- 5. The radio will resume scrolling through the channels five seconds after the end of any received activity.
- 6. To stop scanning, briefly press the (Know).

Scanning Notes:

- 1. If you press the PTT button while the radio is scrolling through inactive channels, the transmission will be on the "home channel". Scanning will resume five seconds after the end of your transmission. You may press the key to stop scanning at any time.
- 2. If the radio stops on an undesired transmission, you may
- immediately resume the scan by briefly pressing (+) or (-) 3. If the radio repeatedly stops on an undesired transmission you may temporarily remove that channel from the scan list by pressing and holding (+) or (-) for three seconds. You may remove more than one channel in this way.
- 4. To restore the removed channel(s) to the scan list, turn the radio off and then turn back on, or exit and re-enter the scanning mode by pressing ().
- 5 You cannot remove the home channel from the scan list 6. In Advanced Scan, the detected code will only be used for one transmission. You must note that code, exit scan and set that detected code on that channel to permanently use the detected code

FM Receiver

Your radio can tune to receive FM frequencies ranges from 87.5 MHz to 108 MHz.

Entering FM Mode:

- 1. From Weather mode, press MODE to enter FM mode. The IMPADIO will be shown
- 2. The last set frequency will be displayed.
- Note: If you experience noise while listening to FM during charging, please move the radio around for a clearer reception. Call 1-800-448-6686 if difficulty continues.

Setting the FM Frequency:

In FM mode press (+) or (-) to change the frequency in 0.1 MHz increment. Long press will go to the next available FM

Note: While radio is in FM mode, it allows you to Tx and Rx using previous set two-way channel, as well as receiving weather alert (if it is turned on).

Transmitting a PTT call in FM Mode:

- 1. In FM mode, pressing the PTT button will switch radio to two-way mode. Two-way mode screen is shown and the TW0-WAY blinks.
- 2. Release the PTT button will return to FM mode screen and continue listen to FM channel.

Receiving Call in FM Mode.

1. In FM mode, any incoming call will switch radio to two-way mode. Two-way mode screen is shown and the TW0-WAY blinks.

2. When the call ended, radio will switch back to FM mode. FM

mode screen is shown Receiving Weather Alert in FM Mode:

. When receiving a Weather Alert Call, radio will switch to Weather Mode. Weather mode screen is shown and the !blinks until the mode is exited by you

2. You may stay in weather mode or press MODE to exit and return to FM mode

Note: When the weather channel is activated after receiving an alert, and no buttons are pressed for 5 minutes, the weather mode will automatically revert back to FM mode

Safety Whistle Belt Clip

To blow safety whistle:

- Take Belt Clip of Radio.
- 2. Ensure that mouth covers both holes on edge of whistle Belt Clip entirely

Weather Receiver

Your radio can tune in to broadcasts by the United States National Oceanic and Atmospheric Administration (NOAA) Weather Radio and Environment and Climate Change Canada (ECCC) Weather Radio. You can listen to a weather channel (see "Weather Channels and Frequencies" table for details) or set your radio to alert you to emergency weather broadcasts that interrupt routine broadcasts. When you listen to a weather channel, you cannot use your radio in scan mode or for two-way communications. Both NOAA and ECCC have transmitters located throughout the United States and Canada, respectively These transmitters broadcast watches, forecasts and other nformation 24 hours a day.

Note: NOAA weather radio stations are assigned to cover specific areas and service may be limited. Please check with your local weather office for frequency and details or visit www.weather.gov/nwr in the US to view the appropriate transmitter for your area. The use of the NOAA logo does not provide an endorsement or implied endorsement by the National Weather Service of NOAA, nor does the use of the Weatheradio logo provide an endorsement or implied endorsement by Environment and Climate Change Canada (ECCC).

Entering Weather Mode

1. From two-way mode, press MODE to enter weather mode

WEATHER

Setting the Weather Channel Your radio receives weather frequencies:

- 1. In weather mode, press (a) 1 time until weather channel
- 2. Press (+) or (-) to select the appropriate channel with good reception in your area
- 3. Press the PTT button to set or (a) to continue set up weather alert.

Setting the Weather Alert

Your radio can be set to respond to NOAA Weather Radio emergency messages. A special alarm tone sounds an alert and turns on the weather receiver to give you immediate weather

- and emergency information. 1. In weather mode, press (a) 2 times until (b)! displays.
- 2. Press (+) or (-) to select On/Off.
- 3. Press the PTT button or (a) to exit the weather menu set up.
- 4. Press MODE to return to two-way mode. If you activate Weather Alert and return to two-way mode ! will display. Note: When the weather channel is activated, either manually or after receiving an alert, and no buttons are pressed for 5 minutes, the weather mode will automatically revert

back to two-way mode In the United States, weather alert test is conducted by the National Weather Service on a weekly basis. This test is run every Wednesday somewhere between 10 a.m. and 1 p.m. If you are planning to use the radio at a fixed location in your

- house, we recommend to test at that location. 1. Find a location in your house where the weather channel is
- 2. Turn on the Weather Alert feature during the weekly test period. Leave the radio on in two-way mode during the test period. Ensure your radio is charged

If the radio successfully received the weekly test, you will hear the weather alert test message automatically turn on. If you did not receive the alert, move your radio to a different location in the house where the weather channel reception is better. For example, move your radio closer to a window. Repeat Step 2 if

Weather Channels and Frequencies

weather Channel	Frequency	Weather Channel	Frequency
WX1	162.550 MHz	WX7	162.525 MHz
WX2	162.400 MHz	WX8	161.650 MHz
WX3	162.475 MHz	WX9	161.775 MHz
WX4	162.425 MHz	WX10	161.750 MHz
WX5	162.450 MHz	WX11	162.000 MHz
WX6	162.500 MHz		
	WX1 WX2 WX3 WX4 WX5	WX1 162.550 MHz WX2 162.400 MHz WX3 162.475 MHz WX4 162.425 MHz WX5 162.450 MHz	WX1 162.550 MHz WX7 WX2 162.400 MHz WX8 WX3 162.475 MHz WX9 WX4 162.425 MHz WX10 WX5 162.450 MHz WX11

Channels and Frequencies

Channel	Frequency	Max Power Output	Channel	Frequency	Max Power Output
1	462.5625 MHz	2 W	12	467.6625 MHz	0.5 W
2	462.5875 MHz	2 W	13	467.6875 MHz	0.5 W
3	462.6125 MHz	2 W	14	467.7125 MHz	0.5 W
4	462.6375 MHz	2 W	15	462.5500 MHz	2 W
5	462.6625 MHz	2 W	16	462.5750 MHz	2 W
6	462.6875 MHz	2 W	17	462.6000 MHz	2 W
7	462.7125 MHz	2 W	18	462.6250 MHz	2 W
8	467.5625 MHz	0.5 W	19	462.6500 MHz	2 W
9	467.5875 MHz	0.5 W	20	462.6750 MHz	2 W
10	467.6125 MHz	0.5 W	21	462.7000 MHz	2 W
11	467.6375 MHz	0.5 W	22	462.7250 MHz	2 W

Remarks: Power refers to maximum allowable power as defined by FCC/ISED for each channel under FRS rules for USA and FRS/GMRS for Canada and is not a reflection of the power

Patent and Copyright Information

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license All other trademarks are the property of their respective owners. © 2015 and 2019 Motorola Solutions, Inc. All rights reserved.

Warranty

Consumer Two-Way Radio Products and Accessories purchased in the United States or

What Does this Warranty Cover?

Subject to the exclusions contained below, Motorola Solutions, Inc. ("Motorola") warrants the Motorola branded consumer two-way radios that operate via Family Radio Service or General Mobile Radio Service ("Products"), the Motorola branded or certified accessories sold for use with these Products ("Accessories") to be free from defects in materials and workmanship under normal consumer usage for the period(s) outlined below. This limited warranty is the exclusive remedy of a consumer, and applies as follows to new Products and Accessories and purchased by consumers in the United States or Canada, which are accompanied by this written

Who is Covered?

This warranty extends only to the first consumer purchaser, and is not transferable.

What will MOTOROLA SOLUTIONS, INC. do?

Motorola Solutions, Inc., at its option, will at no charge repair, replace or refund the purchase price of any Products or Accessories that do not conform to this warranty. We may use functionally equivalent reconditioned/ refurbished/ pre-owned or new Products or Accessories

What Other Limitations Are There?

Any Implied Warranties, Including Without Limitation

The implied warranties of merchantability and fitness for a particular purpose, shall be limited to the duration of this limited warranty, otherwise the repair, replacement, or refund as provided under this express limited warranty is the exclusive remedy of the consumers, and is provided in lieu of all other warranties, express or implied. In no event shall Motorola Solutions be liable, whether in contract or tort (including negligence) for damages in excess of the purchase price of the product or accessory, or for any indirect, incidental, special or consequential damages of any kind, or loss of revenue or profits, loss of business, loss of information or other financial loss arising out of or in connection with the ability or inability to use the products or accessories to the full extent these

damages may be disclaimed by law. Some states and jurisdictions do not allow the limitation or exclusion of incidental or consequential damages, or limitation on the length of an implied warranty, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state or from one jurisdiction to another.

Length Of Coverage

returned to the consumer, whichever is

	Products and Accessories as defined above, unless otherwise provided for below.	by the first consumer purchase of the product unless otherwise provided for below.		
	Batteries whose fully charged capacity falls below 80 % of their rated capacity and batteries that leak.	Ninety (90) days from the date of purchase by the first consumer purchaser of the product unless otherwise provided for below		
	Products and Accessories	The balance of the original warranty or for ninety (90) days from the date		

Normal Wear and Tear:

Accessories due to normal wear and tear.

Solutions

Periodic maintenance, repair and replacement of Products or

Exclusions From Warranty Coverage

Abuse & Misuse:

Defects or damage that result from: (a) improper operation, storage, misuse or abuse, accident or neglect, such as physical damage (cracks, scratches, etc.) to the surface of the Products and Accessories resulting from misuse; (b) contact with liquid, water, rain, extreme humidity or heavy perspiration sand, dirt or the like, extreme heat, or food; (c) use of the Products or Accessories for commercial purposes or subjecting the Product or Accessory to abnormal usage or conditions; or (d) other acts which are not the fault of Motorola

Use of Non-Motorola Solutions branded Products and

Defects or damage that result from the use of Non-Motorola Solutions branded or certified products, accessories, software or other peripheral equipment

Unauthorized Service or Modification:

Defects or damages resulting from service, testing, adjustment, installation, maintenance, alteration, or nodification in any way by someone other than Motorola Solutions or its authorized service centers

Altered Products:

Communication Services:

Products or Accessories with (a) serial numbers or date tags that have been removed, altered or obliterated; (b) broken seals or that show evidence of tampering; (c) mismatched board serial numbers; or (d) nonconforming or non-Motorola branded housings, or parts.

Defects, damages, or the failure of Products or Accessories

due to any communication service or signal you may subscribe to or use with the Products or Accessories.

How to Obtain Warranty Service or Other Information? To obtain service or information, please call USA and Canada Two-Way Radios 1-800-448-6686

www.motorolasolutions.com/talkabout

Please call the telephone number designated above for the

Product with which they are used. You will receive instructions on how to ship the Products of Accessories at your expense, to Motorola Solutions or a Motorola Solutions Authorized Repair Center. To obtain service you must include: (a) a copy of your receipt, bill of sale or other comparable proof of purchase; (b) a written description of the problem; (c) the name of your service provider, if applicable; (d) the name and location of the installation facility (if applicable) and, most importantly; (e) your address and telephone number.

For more information, please visit us at:



https://www.facebook.com/ MotorolaTalkaboutWalkieTalkies



www.motorolasolutions.com/talkabout