


MOTOROLA SOLUTIONS

**MS ISO/IEC 17025
TESTING
SMM No.0826**
DECLARATION OF COMPLIANCE SAR ASSESSMENT
Motorola Solutions Inc.
EME Test Laboratory

 Motorola Solutions Malaysia Sdn Bhd (Innoplex)
 Plot 2A, Medan Bayan Lepas
 Mukim 12 SWD 11900 Bayan Lepas Penang, Malaysia.

Date of Report: 4/3/2018
Report Revision: A

Responsible Engineer: Chang Chi Chern
Report Author: Chang Chi Chern
Assessment Date/s: 4/3/2018
Manufacturer: Motorola Solutions
DUT Description: OCW Earpiece PTT
TX mode(s): Bluetooth and Bluetooth Low Energy
Max. Power output: 2.5 mW
Tx Frequency Bands: 2402 - 2480 MHz
Signaling type: GFSK, $\Pi/4$ DQPSK, 8DPSK
Model(s) Certified: PMLN7851A
Classification: Occupational /Controlled
FCC ID: AZ489FT6020
IC: 109U-89FT6020
ISED Test Site registration: 109AK
FCC Test Firm Registration Number: 823256

Based on the information and the testing results provided herein, the undersigned certifies that when used as stated in the operating instructions supplied, said product complies with the national and international reference standards and guidelines listed in section 4.0 of this report. This report shall not be reproduced without written approval from an officially designated representative of the Motorola Solutions Inc EME Laboratory. I attest to the accuracy of the data and assume full responsibility for the completeness of these measurements. This reporting format is consistent with the suggested guidelines of the TIA TSB-150 December 2004. The results and statements contained in this report pertain only to the device(s) evaluated.

Tiong Nguk Ing
Deputy Technical Manager (Approved Signatory)
Approval Date: 4/16/2018

Table of Contents

1.0 Introduction..... 3
 2.0 Referenced Standards and Guidelines 3
 3.0 SAR Limits 4
 4.0 Description of Devices under Test (DUT)..... 4
 5.0 SAR Assessment at the Bluetooth band 5
 6.0 Results Summary 6

Report Revision History

Date	Revision	Comments
4/3/2018	A	Initial release

1.0 Introduction

This report details RF Exposure assessment for OCW Earpiece PTT model number PMLN7815A. This device classified as Occupational /Controlled.

2.0 Referenced Standards and Guidelines

This product is designed to comply with the following applicable national and international standards and guidelines.

- IEC62209-1 (2005) Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)
- Federal Communications Commission, “Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields”, OET Bulletin 65, FCC, Washington, D.C.: 1997.
- IEEE 1528 (2013), Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
- American National Standards Institute (ANSI) / Institute of Electrical and Electronics Engineers (IEEE) C95. 1-1992
- Institute of Electrical and Electronics Engineers (IEEE) C95.1-2005
- International Commission on Non-Ionizing Radiation Protection (ICNIRP) 1998
- Ministry of Health (Canada) Safety Code 6 (2015), Limits of Human Exposure to Radio frequency Electromagnetic Fields in the Frequency Range from 3 kHz to 300 GHz
- RSS-102 (Issue 5) – Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
- Australian Communications Authority Radio communications (Electromagnetic Radiation - Human Exposure) Standard (2014)
- ANATEL, Brazil Regulatory Authority, Resolution No. 303 of July 2, 2002 "Regulation of the limitation of exposure to electrical, magnetic, and electromagnetic fields in the radio frequency range between 9 kHz and 300 GHz." and “Attachment to resolution # 303 from July 2, 2002”
- IEC62209-2 Edition 1.0 2010-03, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz).
- FCC KDB – 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB – 865664 D02 RF Exposure Reporting v01r02
- FCC KDB – 447498 D01 General RF Exposure Guidance v06

3.0 SAR Limits

Table 1

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average - ANSI - (averaged over the whole body)	0.08	0.4
Spatial Peak - ANSI - (averaged over any 1-g of tissue)	1.6	8.0
Spatial Peak – ICNIRP/ANSI - (hands/wrists/feet/ankles averaged over 10-g)	4.0	20.0
Spatial Peak - ICNIRP - (Head and Trunk 10-g)	2.0	10.0

4.0 Description of Devices under Test (DUT)

This device incorporates a Class 2 Bluetooth device which is a Frequency Hopping Spread Spectrum (FHSS) technology and Bluetooth Low Energy intended to provide considerable reduce power consumption. Bluetooth LE operates at frequency spectrum 2.4 GHz to 2.480 GHz with GFSK schemes with employ 40 channels (20 MHz channel bandwidth). The maximum actual transmission duty cycle is imposed by the Bluetooth standard. The maximum duty cycle for BT is 60%.

Table 2 below summarized devices information.

Table 2

Technologies	Antenna Description	Frequency	Max Power (mW)
BT & BT LE	Internal chip antenna; -4.0 dBi gain	2402-2480 MHz	2.5

5.0 SAR Assessment at the Bluetooth band

5.1 FCC Requirement

Per guidelines in KDB 447498, the following formula was used to determine the test exclusion for standalone Bluetooth transmitter;

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{F_{\text{(GHz)}}}] = 0.47 \text{ W/kg}$, which is $\leq 3 \text{ W/kg}$ (1g)

Where:

Max. Power = 1.5 mW (2.5 mW*60% duty cycle)

Min. test separation distance = 5mm for actual test separation < 5mm

F(GHz) = 2.48 GHz

Per the result from the calculation above, SAR test is not required.

5.2 Industry Canada Requirement

Based on RSS-102 Issue 5, exemption limits for SAR evaluation for controlled devices at Bluetooth frequency band with separation distance $\leq 5\text{mm}$ is 20 mW.

Standalone Bluetooth transmitter operates at

Maximum conducted power:

= 2.5 mW * 60%

= 1.5 mW or 1.76 dBm

Equivalent isotropically radiated power (e.i.r.p):

= Maximum conducted power, dBm + Antenna gain, dBi

= 1.76 dBm - 4.0 dBi

= -2.24 dBm or 0.597 mW.

Output power level (higher of maximum conducted power or e.i.r.p), conducted power 1.5 mW is below the threshold power level 20 mW (at separation distance $\leq 5\text{mm}$).

Hence SAR test is not required.

6.0 Results Summary

Based on SAR assessments in section 5.0, SAR test is not required.