

	
<p>MOTOROLA PENANG ADV. COMM. LABORATORY Motorola Solutions Malaysia Sdn. Bhd. Innoplex Plot 2A Medan Bayan Lepas, Mukim 12, S.W.D. 11900 Bayan Lepas, Penang, Malaysia.</p>	<p>FCC / IC TEST REPORT Report Revision : Rev.A</p>
<p>Date/s Tested : 1-July-2017 - 2-July-2017 Report Issue Date : 3-July-2017 Manufacturer/Location : Motorola Solutions - Penang Requestor : Yee Teng Teoh Product Type : Portable Model Number : H92SDH9PW7AN Frequency Band : 2.402 - 2.480 GHz Rated / Max RF Output Power : 8.9 mWatts / 10 mWatts Applicant Name : Motorola Solution Malaysia Sdn Bhd Applicant Address : Innoplex Plot 2A, Medan Bayan Lepas, Mukim 12, S.W.D. 11900 Bayan Lepas, Penang, Malaysia FCC Registrations : 772092 IC Registrations : 109AK</p> <p>The equipment was tested accordance to the requirement listed below:</p> <p>(2.4GHz BT) Part 15C IC RSS 247 PASS</p> 	
<p>This report shall not be reproduced without written approval from an officially designated representative of the Motorola Penang Adv. Comm. Laboratory. The results and statements contained in this report pertain only to the device(s) evaluated.</p>	
<p>Prepared By:</p> <p>_____</p> <p>Jino Lim Test Personnel</p>	<p>Approved By:</p> <p>_____</p> <p>Goh Aik Hong Responsible Engineer</p>

Table of Contents

1.0. General Information.....	4
2.0. Summary of Test Results.....	5
3.0. Measurement Uncertainty	5
4.0. Equipment List.....	6
5.0. Test Mode Applicability and Test Channel Detail	7
6.0. Transmitter Test Parameters	8
6.1. Conducted RF Output Power (Peak).....	8
6.1.1. Test Setup.....	8
6.1.2. Test Limits:	8
6.1.3. Test Data:	8
6.2. 20dB Channel Bandwidth.....	12
6.2.1. Test Setup.....	12
6.2.2. Test Limits:	12
6.2.3. Test Data:	12
6.3. Band-edge Conducted Spurious Emission.....	16
6.3.1. Test Setup.....	16
6.3.2. Test Limits.....	16
6.3.3. Test Result.....	16
6.4. Dwell time on each channel.....	20
6.4.1. Test Setup.....	20
6.4.2. Test Limits:	20
6.4.3. Test Result.....	20
6.5. Number of hopping Frequency.....	26
6.5.1. Test Setup.....	26
6.5.2. Test Limits:	26
6.5.3. Test Result.....	26
6.6. Channel Separation	28
6.6.1. Test Setup.....	28
6.6.2. Test Limits:	28
6.6.3. Test Result.....	28
6.7. Conducted Spurious Emission	32
6.7.1. Test Setup.....	32
6.7.2. Test Limits:	32
6.7.3. Test Data:	32
6.8. Radiated Emission within restricted Bands	38
6.8.1. Test Setup.....	38
6.8.2. Test Limits:	39
6.8.3. Test Data:	40
6.9. AC Powerline Conducted Emission.....	41
6.9.1. Test Setup.....	41
6.9.2. Test Limits:	42
6.9.3. Test Result.....	42

REVISION HISTORY

Revision History	Description	Date	Originator
Rev. A	Initial Report	3-July-2017	Jino Lim

1.0. General Information

EUT Description:

Technologies	2.4GHz BT
TX Frequency range	2402MHz – 2480MHz
Modulation Type	GFSK, Pi/4 DQPSK, 8DPSK
Input/Output	RF Port
Connector type	PROGRAMMING, TEST & ALIGNMENT CABLE
Antenna type	ANTENNA, CHIP, GLONASS BT/GPS ANTENNA MODULE

Channel number and frequency information:

79 channels are provided to this EUT:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

The EUT contains following accessory devices and data cable:

Item	Brand	Model or P/N
IMPRES 3000 MAH, LI-ION HIGH CAPACITY BATTERY, LOW VOLTAGE, IP68.	MOTOROLA	PMNN4493
PROGRAMMING, TEST & ALIGNMENT CABLE	MOTOROLA	PMKN4013

General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, the EUT is to comply with the requirements of the following standards:

ANSI C63.10-2013

2.0. Summary of Test Results

FCC Clause	IC Clause	Test Item	Result	Remark
15.247 (b)(1)	RSS-247 5.1(2)	Conducted RF Output Power (Peak)	Pass	NA
15.247 (a)(1)	RSS-247 5.1(1) RSS-247 5.1(2)	(1) 20dB Channel Bandwidth (2) Channel Separation	Pass	NA
15.247(a)(1)(iii)	RSS-247 5.1(4)	Number of hopping Frequency used	Pass	NA
15.247(a)(1)(iii)	RSS-247 5.1(4)	Dwell time on each channel	Pass	NA
15.247 (d)	RSS-247 5.5	Band Edge Conducted Spurious Emission	Pass	NA
15.247 (d)	RSS-247 5.5	Conducted Spurious Emission	Pass	NA
15.205, 15.209, 15.247 (d)	RSS-247 5.5	Radiated Emission within Restricted Bands	Pass	NA
15.207	RSS-Gen 8.8	AC Powerline Conducted Emission	NA	Testing is not required, radio shall turn off during charging mode
15.203	-	Antenna Requirement	NA	Internal antenna is not accessible to the end-user

3.0. Measurement Uncertainty

Measurement	Frequency	Expanded Uncertainty (k=1.96) (±)
AC Power Line Conducted Spurious Emission	150KHz ~ 30MHz	3.43
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	5.01
	200MHz ~ 1000MHz	5.01
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	5.01
	18GHz ~ 25GHz	5.01

4.0. Equipment List

Bluetooth ATE # 1 (SW Version: Ate Main_3.1.9_R1)

Description	Model	Serial Number	Calibration Date	Calibration Due Date
SPECTRUM ANALYZER	E4445A	MY46181597	21-Dec-16	21-Dec-18
POWER SUPPLY	6652A	3541A02403	7-Sep-15	7-Sep-17
SPECTRUM ANALYZER	FSEK30	838495/014	29-Jun-16	29-Jun-18

5.0. Test Mode Applicability and Test Channel Detail

Radiated Emission Test (Above 1GHz)

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type
Test Mode	0 to 78	0,39,78	FHSS	GFSK, Pi/4 DQPSK,8DPSK

Radiated Emission Test (Below 1GHz)

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type
Test Mode	0 to 78	0,39,78	FHSS	GFSK, Pi/4 DQPSK,8DPSK

Power Line Conducted Emission Test

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type
Application Mode	0 to 78	AUTO	FHSS	AUTO

Antenna Port Conducted Measurement:

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).


Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type
Test Mode	0 to 78	0,39,78	FHSS	GFSK, Pi/4 DQPSK,8DPSK

6.0. Transmitter Test Parameters

6.1. Conducted RF Output Power (Peak)

6.1.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and set EUT to transmit maximum data rate with hopping disable.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = > 20 dB bandwidth
 - b. VBW = RBW
 - c. Detector mode = Peak
 - d. AMPLITUDE → Scale/Div = 10 dB
 - e. Trace = Max hold
 - f. Sweep = auto
- e) Measure the captured power within the band and recording the plot.
- f) Repeat above procedure with other different mode of operation.

6.1.2. Test Limits:



Normal Condition (25 ° C)
≤ 125mW (or 20.9dBm)

6.1.3. Test Data:


Test Conditions		Test Frequency (GHz)	Results	
Modulation	Voltage(V)		dBm	Status
GFSK	7.50	2.4020	9.48	Pass
		2.4410	9.42	Pass
		2.4800	9.23	Pass
Pi/4DQPSK	7.50	2.4020	6.93	Pass
		2.4410	6.82	Pass
		2.4800	6.58	Pass
8DPSK	7.50	2.4020	7.37	Pass
		2.4410	7.28	Pass
		2.4800	7.05	Pass

i. The Conducted RF Output Power test with result at low frequency, GFSK.

ii. The Conducted RF Output Power test with result at mid frequency, GFSK.





iii. The Conducted RF Output Power test with result at high frequency, GFSK.




i. The Conducted RF Output Power test with result at low frequency, Pi/4DQPSK.

ii. The Conducted RF Output Power test with result at mid frequency, Pi/4DQPSK.





iii. The Conducted RF Output Power test with result at high frequency, Pi/4DQPSK.




i. The Conducted RF Output Power test with result at low frequency, 8DPSK.

ii. The Conducted RF Output Power test with result at mid frequency, 8DPSK.




iii. The Conducted RF Output Power test with result at high frequency, 8DPSK.



6.2. 20dB Channel Bandwidth

6.2.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and set EUT to transmit maximum data rate with hopping disable.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 30 kHz
 - b. VBW = 100 kHz
 - c. SPAN = 3 MHz, center on test frequency
 - d. AMPLITUDE → Scale/Div = 10 dB
 - e. Detector mode = Peak
 - f. Trace = Max hold
 - g. Sweep = auto
- e) Measure the freq different of two frequencies that were attenuated 20dB from peak of the emission & record the frequency difference as the emission bandwidth.
- f) Save the plot result from spectrum analyzer screen.
- g) Repeat above procedure with other different mode of operation.

6.2.2. Test Limits:


Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

6.2.3. Test Data:

Test Conditions		Test Frequency TX (GHz)	Results (MHz)		
Modulation Type	Voltage(V)		20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Status
GFSK	7.50	2.4020	0.859	0.8416	Pass
		2.4410	0.858	0.8443	Pass
		2.4800	0.860	0.8426	Pass
Pi/4 DQPSK	7.50	2.4020	1.236	1.1677	Pass
		2.4410	1.235	1.1654	Pass
		2.4800	1.236	1.1652	Pass
8DPSK	7.50	2.4020	1.272	1.1762	Pass
		2.4410	1.264	1.1748	Pass
		2.4800	1.262	1.1753	Pass

i. The 20 dB BW & occupied bandwidth test with result at low frequency, GFSK.

ii. The 20 dB BW & occupied bandwidth test with result at mid frequency, GFSK.




iii. The 20 dB BW & occupied bandwidth test with result at high frequency, GFSK.




i. The 20 dB BW & occupied bandwidth test with result at low frequency, Pi/4 DQPSK.

ii. The 20 dB BW & occupied bandwidth test with result at mid frequency, Pi/4 DQPSK.




iii. The 20 dB BW & occupied bandwidth test with result at high frequency, Pi/4 DQPSK.




i. The 20 dB BW & occupied bandwidth test with result at low frequency, 8DPSK.

ii. The 20 dB BW & occupied bandwidth test with result at mid frequency, 8DPSK.




iii. The 20 dB BW & occupied bandwidth test with result at high frequency, 8DPSK.



6.3. Band-edge Conducted Spurious Emission

6.3.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and keep the EUT in hopping mode.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 100 kHz
 - b. VBW = 300 kHz
 - c. SPAN = 4 MHz (Low channel) or 6MHz(High Channel)
 - d. Detector mode = Peak
 - e. AMPLITUDE → Scale/Div = 10 dB
 - f. Trace = Max hold
 - g. Sweep = auto
- e) Measure the captured band edge emission result and recording the plot.
- f) Repeat above on EUT with hopping disable.
- g) Repeat above procedure with other different test frequency.


6.3.2. Test Limits

Normal Condition (25 ° C)
Shall be at least 20 dB below the peak power.

6.3.3. Test Result

Test Conditions		Hopping Method	Test Frequency(GHz)	Results	
Modulation	Voltage(V)			dB	Status
GFSK	7.50	Enabled (continuously)	2.4020	59.00	Pass
			2.4800	58.63	Pass
		Disabled (constantly)	2.4020	61.43	Pass
			2.4800	64.15	Pass
Pi/4 DQPSK	7.50	Enabled (continuously)	2.4020	56.47	Pass
			2.4800	59.97	Pass
		Disabled (constantly)	2.4020	51.14	Pass
			2.4800	59.80	Pass
8 DPSK	7.50	Enabled (continuously)	2.4020	50.66	Pass
			2.4800	59.51	Pass
		Disabled (constantly)	2.4020	46.58	Pass
			2.4800	56.88	Pass


i. The highest band edge emission at low carrier frequency with hopping function enabled, GFSK




ii. The highest band edge emission at high carrier frequency with hopping function enabled, GFSK



iii. The highest band edge emission at low carrier frequency with hopping function disabled, GFSK





iv. The highest band edge emission at high carrier frequency with hopping function disabled, GFSK





i. The highest band edge emission at low carrier frequency with hopping function enabled, Pi/4 DQPSK

ii. The highest band edge emission at high carrier frequency with hopping function enabled, Pi/4 DQPSK




iii. The highest band edge emission at low carrier frequency with hopping function disabled, Pi/4 DQPSK


iv. The highest band edge emission at high carrier frequency with hopping function disabled, Pi/4 DQPSK




i. The highest band edge emission at low carrier frequency with hopping function enabled, 8DPSK




ii. The highest band edge emission at high carrier frequency with hopping function enabled, 8DPSK



iii. The highest band edge emission at low carrier frequency with hopping function disabled, 8DPSK




iv. The highest band edge emission at high carrier frequency with hopping function disabled, 8DPSK



6.4. Dwell time on each channel

6.4.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and keep the EUT in hopping mode.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 100 kHz
 - b. VBW = 300 kHz
 - c. SPAN = Zero SPAN, center on hopping frequency
 - d. Detector mode = Peak
 - e. Trace = Max hold
 - f. Sweep time = 5second
 - g. Sweep = Single
- e) Measure dwell time for 1 transmission and save the plot.
- f) Calculate accumulate dwell time
- g) Repeat above procedure with other different mode of operation.

6.4.2. Test Limits:


Normal Condition (25 ° C)
≤ 400ms

6.4.3. Test Result


Test Conditions			Data Package	Results			
Modulation	Voltage (V)	Test Frequency (GHz)		Hops/s (a)	Dwell time in one transmission (b) (msec)	Total accumulate dwell time in 31.6s. (c) (msec)	Status
GFSK	7.50	2.4410	DH1	1600/(2*79)	0.401	128.32	Pass
			DH3	1600/(4*79)	1.658	265.28	Pass
			DH5	1600/(6*79)	2.907	310.08	Pass
Pi/4 DQPSK	7.50		DH1	1600/(2*79)	0.405	129.60	Pass
			DH3	1600/(4*79)	1.657	265.12	Pass
			DH5	1600/(6*79)	2.905	309.87	Pass
8 DPSK	7.50		DH1	1600/(2*79)	0.403	128.96	Pass
			DH3	1600/(4*79)	1.655	264.80	Pass
			DH5	1600/(6*79)	2.904	309.76	Pass

****Note:** Total dwell time (c) = (a) x (b) x 31.6s


i. Dwell Time at DH1, GFSK




ii. Dwell Time at DH3, GFSK




iii. Dwell Time at DH5, GFSK




iv. Dwell Time at DH1, PI/4DQPSK




v. Dwell Time at DH3, PI/4DQPSK




vi. Dwell Time at DH5, PI/4DQPSK




vii. Dwell Time at DH1, 8DQPSK



viii. Dwell Time at DH3, 8DQPSK




ix. Dwell Time at DH5, 8DQPSK



6.5. Number of hopping Frequency

6.5.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and keep the EUT in hopping mode.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 300 kHz
 - b. VBW = 300 kHz
 - c. Detector mode = Peak
 - d. Trace = Max hold
- e) Allow the trace to stabilized & save the plot result from spectrum analyzer screen.
- f) Count number of channel frequency in the operating.
- g) Repeat above procedure for other test frequency.


6.5.2. Test Limits:

Normal Condition (25 ° C)
≥ 15


6.5.3. Test Result

Test Conditions		Sweep Range (GHz)	Results	
Modulation	Voltage(V)		No. of Hopping Frequencies	Status
GFSK	7.50	2.4000-2.4835	79	Pass
Pi/4DQPSK	7.50	2.4000-2.4835	79	Pass
8DPSK	7.50	2.4000-2.4835	79	Pass


i. Number of Hopping Frequencies, GFSK



ii. Number of Hopping Frequencies, Pi/4 DQPSK




iii. Number of Hopping Frequencies, 8DPSK



6.6. Channel Separation

6.6.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and keep the EUT in hopping mode.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 300 kHz
 - b. VBW = 300 kHz
 - c. SPAN = 3 MHz, center on test frequency
 - d. AMPLITUDE → Scale/Div = 1 dB
 - e. Detector mode = Peak
 - f. Trace = Max hold
 - g. Sweep = auto
- e) Measure the frequency different of these two adjacent channels with marker delta function & record the measurement results.
- f) Repeat above procedure with other different mode of operation.

6.6.2. Test Limits:



Normal Condition (25 ° C)
≥ 2/3 of 20dB Bandwidth

6.6.3. Test Result


Test Conditions		Test Frequency (GHz)	Results			
Modulation	Voltage(V)		Test Data Adjacent Channel Separation (MHz)	20dB Bandwidth (MHz)	Min Limit = 2/3 of 20dB Bandwidth (kHz)	Status
GFSK	7.50	2.4020	0.978	0.859	572.667	Pass
		2.4410	1.000	0.858	572.000	Pass
		2.4800	1.000	0.860	573.333	Pass
Pi/4DQPSK	7.50	2.4020	0.973	1.236	824.000	Pass
		2.4410	0.983	1.235	823.333	Pass
		2.4800	1.001	1.236	824.000	Pass
8DPSK	7.50	2.4020	1.001	1.272	848.000	Pass
		2.4410	0.973	1.264	842.667	Pass
		2.4800	1.008	1.262	841.333	Pass

i. The Channel Separation test with result at low frequency, GFSK.

ii. The Channel Separation test with result at mid frequency, GFSK.





iii. The Channel Separation test with result at High frequency, GFSK.




i. The Channel Separation test with result at low frequency, PI/4DQPSK.

ii. The Channel Separation test with result at mid frequency, PI/4DQPSK.





iii. The Channel Separation test with result at High frequency, PI/4DQPSK.




i. The Channel Separation test with result at low frequency, 8DPSK.

ii. The Channel Separation test with result at mid frequency, 8DPSK.




iii. The Channel Separation test with result at High frequency, 8DPSK.



6.7. Conducted Spurious Emission

6.7.1. Test Setup



- a) Check and ensure the spectrum analyzer well calibrate.
- b) Turn on the EUT and set EUT to transmit maximum data rate with hopping disable.
- c) Connect EUT's antenna terminal to spectrum analyzer with a low loss cable.
- d) Setting of Spectrum analyzer :
 - a. RBW = 100 kHz
 - b. VBW = 300 kHz
 - c. SPAN = Cover until 10th harmonic
 - d. Detector mode = Peak
 - e. AMPLITUDE → Scale/Div = 10 dB
 - f. Trace = Max hold
 - g. Sweep = auto
- e) Measure the captured spurious emission result and recording the plot.
- f) Repeat above procedure with other different mode of operation.

6.7.2. Test Limits:


Normal Condition (25 ° C)
Shall be at least 20 dB below for peak power.

6.7.3. Test Data:

Test Conditions		Test Frequency (GHz)	Results
Modulation	Voltage(V)		Status
GFSK	7.50	2.4020	Pass
		2.4410	Pass
		2.4800	Pass
Pi/4DQPSK	7.50	2.4020	Pass
		2.4410	Pass
		2.4800	Pass
8DPSK	7.50	2.4020	Pass
		2.4410	Pass
		2.4800	Pass


GFSK Modulation:

- The high emission level within the assigned band at low carrier frequency.




Date: 01.JUL.2017 15:02:58

- The high emission level within the assigned band at mid carrier frequency.




Date: 02.JUL.2017 10:38:45

- Spurious emission measurement in 30MHz – 25GHz at low carrier frequency.




Date: 01.JUL.2017 15:03:58

- Spurious emission measurement in 30MHz – 25GHz at mid carrier frequency.




Date: 02.JUL.2017 10:39:44

• **The high emission level within the assigned band at high carrier frequency.**




• Spurious emission measurement in 30MHz – 25GHz at high carrier frequency.




Pi/4 DQPSK Modulation:


• **The high emission level within the assigned band at low carrier frequency.**




• Spurious emission measurement in 30MHz – 25GHz at low carrier frequency.




- The high emission level within the assigned band at mid carrier frequency.




- Spurious emission measurement in 30MHz – 25GHz at mid carrier frequency.



- The high emission level within the assigned band at high carrier frequency.




- Spurious emission measurement in 30MHz – 25GHz at high carrier frequency.




8DPSK Modulation:


- The high emission level within the assigned band at low carrier frequency.




- Spurious emission measurement in 30MHz – 25GHz at low carrier frequency.




- The high emission level within the assigned band at mid carrier frequency.




- Spurious emission measurement in 30MHz – 25GHz at mid carrier frequency.



• **The high emission level within the assigned band at high carrier frequency.**




• **Spurious emission measurement in 30MHz – 25GHz at high carrier frequency.**



6.8. Radiated Emission within restricted Bands

6.8.1. Test Setup



- The EUT is placed on the top of a rotating table 0.8m above the ground (<1GHz) and 1.5m above the ground (>1GHz) at a 3m semi-anechoic chamber. The table is rotated 360 degrees to determine the position of the highest radiation.
- The EUT is set 3m away from the interference-receiving antenna, which is mounted on the top of a variable-height antenna tower.
- The antenna is Bilog/Horn antenna depend on which frequency range uses, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT is arranged to its worst case and then the antenna is tuned to heights from 1m to 4m and the rotatable table is turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system is set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode is fall within the range of 10dB from the limit specified, the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. Otherwise, the testing could be stopped and the peak values of the EUT would be reported.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection at frequency below 1GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

6.8.2. Test Limits:

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

NOTE:


- a. The lower limit shall apply at the transition frequencies.
- b. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- c. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

6.8.3. Test Data:

Not Applicable.

6.9. AC Powerline Conducted Emission

6.9.1. Test Setup



- 1) Tests were conducted for both Receive and Transmit Mode of the EUT.
- 2) The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50uH of coupling impedance for the measuring instrument.
- 3) Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- 4) The frequency range from 150 kHz to 30MHz was measured.

6.9.2. Test Limits:

For AC Power Line Conducted Test Limit can be Class A or B depends on product classification.

**Limits for conducted disturbance at the mains ports
of class A ITE**

Frequency range MHz	Limits dB(μ V)	
	Quasi-peak	Average
0,15 to 0,50	79	66
0,50 to 30	73	60
NOTE The lower limit shall apply at the transition frequency.		

Table 1: Limits for Conducted Disturbance at the Mains Ports of Class A ITE.

**Limits for conducted disturbance at the mains ports
of class B ITE**

Frequency range MHz	Limits dB(μ V)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50
NOTE 1 The lower limit shall apply at the transition frequencies. NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.		

Table 2: Limits for Conducted Disturbance at the Mains Ports of Class B ITE

6.9.3. Test Result

Not Applicable. Testing is not required, radio shall turn off during charging mode