

 MOTOROLA SOLUTIONS	   <p>MS ISO/IEC 17025 TESTING</p> <p>SAMM No.0826 CERTIFICATE 2518.05</p>
---	---

DECLARATION OF COMPLIANCE SAR ASSESSMENT Part 1 of 4

<p align="center">Motorola Solutions Inc. EME Test Laboratory Motorola Solutions Malaysia Sdn Bhd (Innoplex) Plot 2A, Medan Bayan Lepas, Mukim 12 SWD 11900 Bayan Lepas Penang, Malaysia.</p>	<p>Date of Report: 4/10/2019 Report Revision: A</p>
---	--

<p>Responsible Engineer: Saw Sun Hock (EME Engineer) Report Author: Saw Sun Hock (EME Engineer) Test Personnel: Zarul, Azrii, Firdaus, Loh, Ammar, Naim, Zakwan, Bala Date/s Tested: 12/25/2018-12/31/2018, 1/2/2019-1/4/2019, 1/6/2019-2/8/2019, 2/10/2019-2/13/2019, 2/27/2019-2/28/2019, 3/4/2019, 3/6/2019, 3/13/2019-3/15/2019, 3/18/2019-3/19/2019</p> <p>Manufacturer: Motorola Solutions Inc. DUT Description: Handheld Portable – APX NEXT All-band Model 4.5 Test TX mode(s): FM; LTE; WLAN Max. Power output: Refer to Part 1 Table 3 Nominal Power: Refer to Part 1 Table 3 Tx Frequency Bands: Refer to Part 1 Table 3 Signaling type: FM, TDMA, SC-FDMA, FHSS, DSSS, OFDM and NFC Model(s) Tested: H55TGT9PW8AN (PNUW1100A) Model(s) Certified: H55TGT9PW8AN (PNUW1100A), H45KGT9PW8AN, H45UCT9PW8AN and H45XDT9PW8AN</p> <p>Serial Number(s): 437TUX0100, 437P1C0117, 437P1C0120, 437TUX0109, 437TUX0103, 437TUX0096, 437P1C0122</p> <p>Classification: Occupational/Controlled FCC ID: AZ489FT7199; LMR 150.8-173.4 MHz, 406.125-512 MHz, 769-775 MHz, 799-824 MHz, 851-869 MHz; LTE; WLAN 2.4 GH; WLAN 5GHZ, Bluetooth, NFC This report contains results that are immaterial for FCC equipment approval, which are clearly identified.</p> <p>IC: 109U-89FT7199; LMR 138-173.4 MHz, 406.125-430 MHz, 450-470 MHz, 769-775 MHz, 799-824 MHz, 851-869 MHz; LTE; WLAN 2.4 GH; WLAN 5GHZ, Bluetooth, NFC This report contains results that are immaterial for IC equipment approval, which are identified.</p> <p>ISED Test Site registration: 109AK FCC Test Firm Registration Number: 823256</p>	
---	--

The test results clearly demonstrate compliance with FCC Occupational/Controlled RF Exposure limits of 8 W/kg averaged over 1 gram per the requirements of FCC 47 CFR § 2.1093 and RSS-102 (Issue 5).

Based on the information and the testing results provided herein, the undersigned certifies that when used as stated in the operating instructions supplied, said product complies with the national and international reference standards and guidelines listed in section 4.0 of this report (no deviation from standard methods). This report shall not be reproduced without written approval from an officially designated representative of the Motorola Solutions Inc EME Laboratory. I attest to the accuracy of the data and assume full responsibility for the completeness of these measurements. This reporting format is consistent with the suggested guidelines of the TIA TSB-150 December 2004. The results and statements contained in this report pertain only to the device(s) evaluated.

<p align="center"><i>Tiong</i> Tiong Nguk Ing Deputy Technical Manager (Approved Signatory) Approval Date: 4/24/2019</p>	
--	--

Part 1 of 4

1.0 Introduction..... 4

2.0 FCC SAR Summary..... 4

3.0 Abbreviations / Definitions..... 5

4.0 Referenced Standards and Guidelines 5

5.0 SAR Limits 7

6.0 Description of Device Under Test (DUT) 7

7.0 Optional Accessories and Test Criteria 9

 7.1 Antennas 9

 7.2 Battery..... 10

 7.3 Body worn Accessories 11

 7.4 Audio Accessories 12

8.0 Description of Test System..... 13

 8.1 Descriptions of Robotics/Probes/Readout Electronics 14

 8.2 Description of Phantom(s)..... 14

 8.3 Description of Simulated Tissue..... 15

9.0 Additional Test Equipment..... 16

10.0 SAR Measurement System Validation and Verification 17

 10.1 System Validation..... 17

 10.2 System Verification 17

 10.3 Equivalent Tissue Test Results..... 18

11.0 Environmental Test Conditions 18

12.0 DUT Test Setup and Methodology..... 18

 12.1 Measurements 18

 12.2 DUT Configuration(s) 19

 12.3 DUT Positioning Procedures 19

 12.3.1 Body..... 19

 12.3.2 Head..... 19

 12.3.3 Face..... 20

 12.4 DUT Test Channels 20

 12.5 SAR Result Scaling Methodology..... 20

 12.6 DUT Test Plan 21

13.0 DUT Test Data..... 21

 13.1 Assessment at the LMR, LTE and WLAN bands..... 21

 13.2 Assessment at the Bluetooth band 21

 13.2.1 FCC Requirement 21

 13.2.2 ISED Canada Requirement..... 21

 13.3 Assessment at the NFC 22

14.0 Simultaneous Transmissions 23

 14.1 Simultaneous Transmission Exclusion for BT 23

 14.2 Simultaneous Transmission for LMR and WLAN 2.4 GHz 24

 14.3 Simultaneous Transmission for LMR and WLAN 5 GHz 25

 14.4 Simultaneous Transmission for LMR and LTE..... 27

15.0 Results Summary 38
 16.0 Measurement System Uncertainty 41

Part 2 of 4

System Validation for LMR3
 System Verification for LMR4
 Equivalent Tissue Test Result for LMR.....6
 DUT Test data for LMR.....13
 Variability Assessment97
 Shortened Scan Assessment98

Part 3 of 4

System Validation for LTE3
 System Verification for LTE.4
 Equivalent Tissue Test Result for LTE5
 DUT Test data for LTE9
 Variability Assessment55

Part 4 of 4

System Validation for WLAN.....2
 System Verification for WLAN.....3
 Equivalent Tissue Test Result for WLAN.....4
 DUT Test data for WLAN.....7
 Variability Assessment20

APPENDICES

- A Probe Calibration Certificates
- B Dipole Calibration Certificates
- C System Verification Check Scan
- D DUT Scans

Exhibit 7B

DUT, Body worn and Audio accessories photos

Report Revision History

Date	Revision	Comments
4/10/2019	A	Initial release

1.0 Introduction

This report details the utilization, test setup, test equipment, and test results of the Specific Absorption Rate (SAR) measurements performed at the Motorola Solutions Inc. EME Test Laboratory for handheld portable model number H55TGT9PW8AN (PNUW1100A). This device is classified as Occupational/Controlled.

2.0 FCC SAR Summary

Table 1

Equipment Class	Frequency band (MHz)	Max Calc at Body (W/kg)	Max Calc at Face (W/kg)
		1g-SAR	1g-SAR
TNF	150.8-173.4	1.24	1.19
	406.125-470	6.50	5.52
	450-512	6.08	4.48
	769-775	4.57	1.72
	799-824	5.41	2.37
	851-869	4.53	2.15
PCF	LTE B2	0.014	0.416
	LTE B4	0.033	0.325
	LTE B5	0.067	0.164
	LTE B12	0.034	0.160
	LTE B13	0.079	0.157
	LTE B14	0.098	0.186
	LTE B17	0.026	0.160
DTS	2.4 GHz	0.054	0.262
NII	5 GHz	0.057	1.183
*DXX	NFC	NA	NA
*DSS	BT	NA	NA
Highest Simultaneous Transmission SAR	Sum of SAR (W/kg)	6.60	5.58

*Results not required per KDB (refer to sections 13.2, 13.3 and 14.1)

3.0 Abbreviations / Definitions

BT: Bluetooth
CNR: Calibration Not Required
CW: Continuous Wave
DSS: Direct Spread Spectrum
DTS: Digital Transmission System
DUT: Device Under Test
DXX: Part 15 Low Power Communication Device Transmitter
EME: Electromagnetic Energy
FHSS: Frequency Hopping Spread Spectrum
FM: Frequency Modulation
LMR: Land Mobile Radio
LTE: Long Term Evolution
NA: Not Applicable
OFDM: Orthogonal Frequency Division Multiplexing
PCF: PCS Licensed Transmitter Held to Face
PSM: Public Safety Microphone
PTT: Push to Talk
QPSK: Quadrature Pulse Shift Key
RB: Resource Blocks
RSM: Remote Speaker Microphone
SAR: Specific Absorption Rate
TDMA: Time Division Multiple Access
TNF: Licensed Non-Broadcast Transmitter Held to Face
16QAM: 16 State Quadrature Amplitude Modulation

Audio accessories: These accessories allow communication while the DUT is worn on the body.

Body worn accessories: These accessories allow the DUT to be worn on the body of the user.

Maximum Power: Defined as the upper limit of the production line final test station.

4.0 Referenced Standards and Guidelines

This product is designed to comply with the following applicable national and international standards and guidelines.

- IEC62209-1 (2016) Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)
- Federal Communications Commission, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields", OET Bulletin 65, FCC, Washington, D.C.: 1997.

- IEEE 1528 (2013), Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
- American National Standards Institute (ANSI) / Institute of Electrical and Electronics Engineers (IEEE) C95. 1-1992
- Institute of Electrical and Electronics Engineers (IEEE) C95.1-2005
- International Commission on Non-Ionizing Radiation Protection (ICNIRP) 1998
- Ministry of Health (Canada) Safety Code 6 (2015), Limits of Human Exposure to Radio frequency Electromagnetic Fields in the Frequency Range from 3 kHz to 300 GHz
- RSS-102 (Issue 5) – Radio Frequency (RF) Exposure Compliance of Radio communication Apparatus (All Frequency Bands)
- Australian Communications Authority Radio communications (Electromagnetic Radiation - Human Exposure) Standard (2014)
- ANATEL, Brazil Regulatory Authority, Resolution No. 303 of July 2, 2002 "Regulation of the limitation of exposure to electrical, magnetic, and electromagnetic fields in the radio frequency range between 9 kHz and 300 GHz." and "Attachment to resolution # 303 from July 2, 2002"
- IEC62209-2 Edition 1.0 2010-03, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz).

- FCC KDB – 643646 D01 SAR Test for PTT Radios v01r03
- FCC KDB – 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB – 865664 D02 RF Exposure Reporting v01r02
- FCC KDB – 447498 D01 General RF Exposure Guidance v06
- FCC KDB – 941225 D05 SAR for LTE Devices v02r05
- FCC KDB – 248227 D01 802.11 Wi-Fi SAR v02r02

5.0 SAR Limits

Table 2

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average - ANSI - (averaged over the whole body)	0.08	0.4
Spatial Peak - ANSI - (averaged over any 1-g of tissue)	1.6	8.0
Spatial Peak – ICNIRP/ANSI - (hands/wrists/feet/ankles averaged over 10-g)	4.0	20.0
Spatial Peak - ICNIRP - (Head and Trunk 10-g)	2.0	10.0

6.0 Description of Device Under Test (DUT)

This portable device operates in the LMR bands using either frequency modulation (FM) with 100% transmit duty cycle or TDMA signals with maximum of 50% transmit duty cycle. For conservative assessment, FM signal was tested. It also contains LTE and WLAN technologies for data application, Bluetooth for short range wireless devices.

The LMR bands in this device operate in a half duplex system. A half duplex system only allows the user to transmit or receive. This device cannot transmit and receive simultaneously. The user must stop transmitting in order to receive a signal or listen for a response, regardless of PTT button or use of voice activated audio accessories. This type of operation, along with the RF safety booklet, which instructs the user to transmit no more than 50% of the time, justifies the use of 50% duty factor for this device.

This device also incorporates a Class 1 Bluetooth device which is a Frequency Hopping Spread Spectrum (FHSS) technology. The Bluetooth radio modem is used to wireless link audio accessories. The maximum actual transmission duty cycle is imposed by the Bluetooth standard. The maximum duty cycle for BT is 77.26%.

The intended operating positions are “at the face” with the DUT at least 2.5 cm from the mouth, and “at the body” by means of the offered body worn accessories. Body worn audio and PTT operation is accomplished by means of optional remote accessories that are connected to the radio. Operation at the body without an audio accessory attached is possible by means of BT accessories.

Table 3 below summarizes the technologies, bands, maximum duty cycles and maximum output powers. Maximum output powers are defined as upper limit of the production line final test station.

Table 3

Technologies	Tx Band (MHz)	Transmission	Duty Cycle (%)	Nominal Power (W)	Max Power (W)
LMR	136-174	FM	*50	6.00	6.60
LMR	380-470	FM	*50	5.00	5.70
LMR	450-520	FM	*50	5.00	5.70
LMR	762-776; 792-806	FM	*50	2.50	2.99
LMR	806-825; 851-870	FM	*50	3.00	3.60
LTE Band 2	1850-1910	QPSK, 16QAM	100	0.200	0.252
LTE Band 4	1710-1755	QPSK, 16QAM	100	0.200	0.252
LTE Band 5	824-849	QPSK, 16QAM	100	0.200	0.252
LTE Band 12	699-716	QPSK, 16QAM	100	0.200	0.252
LTE Band 13	777-787	QPSK, 16QAM	100	0.200	0.252
LTE Band 14	788-798	QPSK, 16QAM	100	0.200	0.252
LTE Band 17	704-716	QPSK, 16QAM	100	0.200	0.252
Bluetooth	2400-2485	FHSS	77.26	0.009	0.0115
Bluetooth LE	2400-2485	FHSS	62.68	0.009	0.0115
NFC	13.56	NFC	100	0.035	0.035
WLAN 802.11 b	2412-2462	DSSS	99.20	0.178	0.200
WLAN 802.11 g/n (20 MHz)	2412-2462	OFDM	94.90 (802.11g) 94.36 (802.11n)	0.033 (CH 1) / 0.150 (CH 2-11)	0.045 (CH 1) / 0.158 (CH 2-11)
WLAN 802.11 n (40 MHz)	2412-2462	OFDM	89.08	0.100 (CH 3) / 0.063 (CH 9) / 0.150 (Other channels)	0.126 (CH 3) / 0.079 (CH 9) / 0.158 (Other channels)
WLAN 802.11 a / n / ac (20 MHz)	5180-5825	OFDM	96.30 (802.11a) 95.59 (802.11 n /ac)	0.089 (CH 140) / 0.126 (other Channels)	0.126 (CH 140) / 0.158 (other Channels)
WLAN 802.11 n / ac (40 MHz)	5180-5825	OFDM	90.94	0.089 (CH 38, CH 102) 0.112 (CH 62) 0.126 (other Channels)	0.100 (CH 38, CH 102) / 0.126 (CH 62) / 0.158 (other Channels)

Table 3 Continued

Technologies	Tx Band (MHz)	Transmission	Duty Cycle (%)	Nominal Power (W)	Max Power (W)
WLAN 802.11 ac (80 MHz)	5180-5825	OFDM	80.27	0.063 (CH 42) 0.089 (CH 106) 0.100 (other Channels)	0.079 (CH 42) 0.100 (CH 106) 0.126 (other Channels)

Note - * includes 50% PTT operation

7.0 Optional Accessories and Test Criteria

This device is offered with optional accessories. All accessories were individually evaluated during the test plan creation as per the guidelines outlined in section 4.0 to assess compliance of this device. The following sections identify the test criteria and details for each accessory category. Refer to Exhibit 7B for the photos of the test configurations, antenna locations and accessories.

7.1 Antennas

There are optional removable antennas and internal LTE, WLAN/BT antennas offered for this product. The Table below lists their descriptions.

Table 4

Antenna No.	Antenna Models	Description	Selected for test	Tested
1	KT000026A01	All Band Antenna, ½ wave, -6d Bi (VHF), -1.5 dBi (UHF), -0.9 dBi (7/800MHz)	Yes	Yes
2	PMAD4088B	VHF Wideband Antenna, 136-174 MHz, 5/8 wave, -8.14 dBd	Yes	Yes
3	PMAD4094A	VHF Stubby Antenna, 147-160 MHz, ¼wave, -12.14dBd	Yes	Yes
4	PMAD4095A	VHF Stubby Antenna, 160-174MHz, ¼ wave, -12.14d Bd	Yes	Yes
5	PMAD4093A	VHF Stubby Antenna, 136-147MHz, ¼ wave, -12.14 dBd	Yes	Yes
6	PMAE4100A	UHF Stubby Antenna, 380-470MHz, ¼ wave, 0 dBi	Yes	Yes
7	PMAE4022B	UHF Whip Antenna, 380-480MHz, , ¼ wave, 0 dBi	Yes	Yes
8	PMAE4049A	UHF Whip Antenna, 450-527 MHz, , ¼ wave, 1.9 dBi	Yes	Yes
9	PMAE4102A	UHF Stubby Antenna, 450-527MHz, ¼ wave, 1.7 dBi	Yes	Yes
10	AN000296A01	7/800 Stubby Antenna, 760-870MHz, ¼ wave, -0.8 dBi	Yes	Yes
11	NAF5080A	7/800 Whip Antenna, 7/800MHz, ¼ wave, 0 dBi	Yes	Yes
12	PMAF4022A	7/800 Stubby Antenna, 7/800 MHz, ¼ wave, 0 dBi	Yes	Yes
13	PMAF4002A	7/800 PSM Antenna, 7/800MHz, ¼ wave, 0 dBi	Yes	Yes*

Table 4 Continued

Antenna No.	Antenna Models	Description	Selected for test	Tested
14	PMAE4065A	UHF GPS PSM Antenna, 380-520 MHz, ¼ wave, -2 dBd	Yes	Yes*
15	AN000304A01	LTE Antenna, 699-798 MHz, 824-849 MHz, 1710-2155MHz, ¼ wave, Band 4 (1.02 dBi), Band 2 (2.15 dBi), Band 12 (-3.18 dBi), Band 13 (-3.00 dBi), Band 14 (-3.52 dBi), Band 5 (-2.34 dBi), Band 17 (-3.65 dBi)	Yes	Yes
16	AN000304A03	WiFi/BT Antenna, 2400-2480 MHz, 5150-5850 MHz, ¼ wave, 2400 MHz (3.1 dBi), 2440 MHz (3.2 dBi), 2480 MHz (2.9 dBi), 5150MHz (2.8 dBi), 5500MHz (4.0 dBi) , 5850MHz (1.9 dBi)	Yes	Yes

Note - * For PSM only

7.2 Battery

There are four batteries offered for this product. The Table below lists their descriptions.

Table 5

Battery No.	Battery Models	Description	Selected for test	Tested	Comments
1	NNTN9087A	Standard Battery, IMPRES GEN2, Li-ion, IP68, 3800T	Yes	Yes	Default battery for body testing.
2	NNTN9089A	High Capacity Battery, IMPRES GEN2, Li-ion, 5650T	Yes	Yes	Default battery for face testing.
3	NNTN9088A	Standard Battery, IMPRES GEN2, Li-ion, IP68, 3800T	No	No	By Similarity to NNTN9087A (Only different label for UL)
4	NNTN9090A	High Capacity Battery, IMPRES GEN2, Li-ion, 5650T	No	No	By Similarity to NNTN9089A (Only different label for UL)

7.3 Body worn Accessories

All body worn accessories were considered. The Table below lists the body worn accessories, and body worn accessory descriptions.

Table 6

Body worn No.	Body worn Models	Description	Selected for test	Tested	Comments
1	PMLN7947A	Carry Accessory Holster	Yes	Yes	Test with NTN8266B and PMLN7965A
2	NTN8266B	Belt Clip Kit	Yes	Yes	Test with PMLN7947A, PMLN7948A and PMLN7964A
3	PMLN7948A	Hybrid Carry Case For Standard Capacity Battery	Yes	Yes	Test with NTN8266B, PMLN7965A, PMLN5407A, PMLN5408A and PMLN5409A. Compatible with battery NNTN9087A only.
4	PMLN7965A	3" Belt Clip	Yes	Yes	Test with PMLN7947A, PMLN7948A and PMLN7964A
5	PMLN5407A	2.5" Replacement Swivel Belt Loop	Yes	Yes	Test with PMLN7948A and PMLN7964A
6	PMLN5408A	2.75" Replacement Swivel Belt Loop	Yes	Yes	Test with PMLN7948A and PMLN7964A
7	PMLN5409A	3" Replacement Swivel Belt Loop	Yes	Yes	Test with PMLN7948A and PMLN7964A
8	PMLN7964A	Hybrid Carry Case For High Capacity Battery	Yes	Yes	Test with NTN8266B, PMLN7965A, PMLN5407A, PMLN5408A and PMLN5409A. Compatible with battery NNTN9089A only.
9	4205823V08	Belt clip for PSM	Yes	Yes*	Test with PMMN4059B, PMMN4060B and PMMN4061B

Note - * For PSM only

7.4 Audio Accessories

All audio accessories were considered. The Table below lists the offered audio accessories and their descriptions. Exhibit 7B illustrates photos of the tested audio accessories.

Table 7

Audio No.	Audio Acc. Models	Description	Selected for test	Tested	Comments
1	PMMN4123A	Audio Accessory-Remote Speaker Microphone, MC550	Yes	Yes*	Default Audio
2	NMN6274B	Audio Accessory-Remote Speaker Microphone, IMPRES XP RSM For APX With Dual Microphone Noise Suppression, 3.5mm THRD Jack	Yes	Yes*	
3	PMLN6129A	IMPRES 2 Wires With Translucent Tube - Black	Yes	Yes*	
4	PMMN4065A	IMPRES Remote Speaker Microphone IP57	Yes	Yes*	
5	BDN6783B	Audio Accessory adapter With PTT	Yes	Yes*	Test with RLN5312B
6	RLN5312B	CMRT Earpiece With Microphone and PTT - Black	Yes	Yes*	Test with BDN6783B
7	HMN4101B	IPRES Remote Speaker Microphone, No Display With Jack, No Channel	Yes	Yes*	
8	PMLN6852A	Next Gen Behind The Head Heavy Duty Headset - Gcai	Yes	Yes*	
9	PMMN4106D (Cable length 2.0 meter)	Fire Remote Speaker Microphone XE500 Model 1 Impact Green Color (2.0 meter cable)	Yes	Yes*	
10	PMMN4106D (Cable length 2.8 meter)	Fire Remote Speaker Microphone XE500 Model 1 Impact Green Color (2.8 meter cable)	Yes	Yes*	
11	PMMN4059B	Audio Accessory – Headset, PSM IP55 with 3.5mm Jack Receive 18 Inches	Yes	Yes	For PSM testing
12	PMMN4060B	Audio Accessory – Headset, PSM IP55 with 3.5mm Jack Receive 24 Inches	Yes	Yes	For PSM testing
13	PMMN4061B	Audio Accessory – Headset, PSM IP55 with 3.5mm Jack Receive 30 Inches	Yes	Yes	For PSM testing
11	NNTN8235A	SRX Remote Speaker Microphone IP57	No	No	By Similarity to NMN6274B
14	NNTN8236A	SRX IMPRES Remote Speaker Microphone	No	No	By Similarity to NMN6274B
15	PMLN6130A	IMPRES 2 Wires With Translucent Tube - Beige	No	No	By Similarity to PMLN6129A
16	PMLN6127A	IMPRES 2 Wires Surveillance - Black	No	No	By Similarity to PMLN6129A
17	PMMN4069A	IMPRES Remote Speaker Microphone, 3.5mm Jack, IP55	No	No	By Similarity to PMMN4065A
18	PMMN4099B	Remote Speaker Microphone IP68, 3.5mm, UL	No	No	By Similarity to PMMN4065A
19	PMMN4083A	IMPRES Large Remote Speaker Microphone, APX IP68 Delta - Gcai	No	No	By Similarity to PMMN4065A
20	PMMN4107D (2.0 meter)	Fire Remote Speaker Microphone XE500 Model 1.5 Impact Green Color (2.0 meter cable)	No	No	By Similarity to PMMN4106D (Cable length 2.0 meter)

Table 7 Continued

Audio No.	Audio Acc. Models	Description	Selected for test	Tested	Comments
21	PMMN4106CBLK (2.0 meter)	Fire Remote Speaker Microphone XE500 Model 1 Impact Black Color (2.0 meter cable)	No	No	By Similarity to PMMN4106D (Cable length 2.0 meter)
22	PMMN4107CBLK (2.0 meter)	Fire Remote Speaker Microphone XE500 Model 1.5 Impact Black Color (2.0 meter cable)	No	No	By Similarity to PMMN4106D (Cable length 2.0 meter)
23	PMMN4107D (2.8 meter)	Fire Remote Speaker Microphone XE500 Model 1.5 Impact Green Color (2.0 meter cable)	No	No	By Similarity to PMMN4106D (Cable length 2.8 meter)
24	PMMN4106CBLK (2.8 meter)	Fire Remote Speaker Microphone XE500 Model 1 Impact Black Color (2.0 meter cable)	No	No	By Similarity to PMMN4106D (Cable length 2.8 meter)
25	PMMN4107CBLK (2.8 meter)	Fire Remote Speaker Microphone XE500 Model 1.5 Impact Black Color (2.0 meter cable)	No	No	By Similarity to PMMN4106D (Cable length 2.8 meter)

Note - * Intended for test. Per KDB provision tests not required for VHF band.

8.0 Description of Test System



8.1 Descriptions of Robotics/Probes/Readout Electronics

Table 8

Dosimetric System type	System version	DAE type	Probe Type
Schmid & Partner Engineering AG SPEAG DASY 5	52.8.8.1222	DAE4	ES3DV3, EX3DV4 (E-Field)

The DASY5™ system is operated per the instructions in the DASY5™ Users Manual. The complete manual is available directly from SPEAG™. All measurement equipment used to assess SAR compliance was calibrated according to ISO/IEC 17025 A2LA guidelines. Section 9.0 presents additional test equipment information. Appendices B and C present the applicable calibration certificates. The E-field probe first scans a coarse grid over a large area inside the phantom in order to locate the interpolated maximum SAR distribution. After the coarse scan measurement, the probe is automatically moved to a position at the interpolated maximum. The subsequent scan can directly use this position as reference for the cube evaluations.

8.2 Description of Phantom(s)

Table 9

Phantom Type	Phantom(s) Used	Material Parameters	Phantom Dimensions LxWxD (mm)	Material Thickness (mm)	Support Structure Material	Loss Tangent (wood)
Triple Flat	NA	200MHz -6GHz; Er = 3-5, Loss Tangent = ≤0.05	280x175x175	2mm +/- 0.2mm	Wood	< 0.05
SAM	NA	300MHz -6GHz; Er = < 5, Loss Tangent = ≤0.05	Human Model			
Oval Flat	√	300MHz -6GHz; Er = 4+/- 1, Loss Tangent = ≤0.05	600x400x190			

8.3 Description of Simulated Tissue

The sugar based simulate tissue is produced by placing the correct measured amount of De-ionized water into a large container. Each of the dried ingredients are weighed and added to the water carefully to avoid clumping. If the solution has a high sugar concentration the water is pre-heated to aid in dissolving the ingredients. For Diacetin and similar type simulates, sugar and HEC ingredients are not needed. The solution is mixed thoroughly, covered, and allowed to sit overnight prior to use.

The simulated tissue mixture was mixed based on the Simulated Tissue Composition indicated in Table 10. During the daily testing of this product, the applicable mixture was used to measure the Di-electric parameters at each of the tested frequencies to verify that the Di-electric parameters were within the tolerance of the tissue specifications.

Simulated Tissue Composition (percent by mass)

Table 10

Ingredients	150MHz		450MHz		750MHz		835MHz	
	Head	Body	Head	Body	Head	Body	Head	Body
Sugar	55.4	49.7	56.0	46.5	57.0	46	57.0	44.9
Diacetin	0	0	0	0	0	0	NA	NA
De ionized - Water	38.35	46.2	39.1	50.53	40.12	51.8	40.45	53.06
Salt	5.15	3.00	3.8	1.87	1.78	1.1	1.45	0.94
HEC	1	1	1	1	1	1	1	1
Bact.	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1

Table 10 Continued

Ingredients	1750MHz		1900MHz		2450MHz		5GHz ⁽¹⁾	
	Head	Body	Head	Body	Head	Body	Head	Body
Sugar	NA	NA	NA	NA	NA	NA	NA	NA
Diacetin	51.5	35.0	51.5	34.5	51.0	34.5	NA	NA
De ionized - Water	47.82	64.35	48.03	64.97	48.75	65.20	NA	NA
Salt	0.58	0.55	0.37	0.43	0.15	0.20	NA	NA
HEC	NA	NA	NA	NA	NA	NA	NA	NA
Bact.	0.1	0.1	0.1	0.1	0.1	0.1	NA	NA

Note: (1) SPEAG provides Motorola proprietary stimulant ingredients for the 5GHz band.

9.0 Additional Test Equipment

The Table below lists additional test equipment used during the SAR assessment.

Table 11

Equipment Type	Model Number	Serial Number	Calibration Date	Calibration Due Date
Speag Probe	EX3DV4	7486	3/20/2018	3/20/2019
Speag Probe	ES3DV3	3122	4/18/2018	4/18/2019
Speag Probe	EX3DV4	3612	10/18/2018	10/18/2019
Speag Probe	EX3DV4	7519	10/19/2018	10/19/2019
Speag DAE	DAE4	1483	1/10/2019	1/10/2020
Speag DAE	DAE4	1488	3/9/2018	3/9/2019 *
Speag DAE	DAE4	850	3/7/2018	3/7/2019*
Speag DAE	DAE4	684	10/9/2018	10/9/2019
Speag DAE	DAE4	1294	10/16/2018	10/16/2019
Power Meter	E4418B	MY45107917	5/22/2017	5/22/2019
Power Meter	E4418B	GB40206480	9/16/2017	9/16/2019
Power Meter	E4419B	MY40330364	9/16/2017	9/16/2019
Power Meter	E4419B	MY45103725	5/22/2017	5/22/2019
Power Meter	E4418B	MY45100911	7/14/2017	7/14/2019
Power Sensor	E9301B	MY50290001	4/24/2018	4/24/2019
Power Sensor	E9301B	MY41495733	4/17/2018	4/17/2019
Power Sensor	E9301B	MY41495594	8/15/2018	8/15/2019
Power Sensor	8481B	MY41091170	4/23/2018	4/23/2019
Power Sensor	E9301B	MY50280001	7/5/2018	7/5/2019
Power Sensor	NRP-Z11	121252	2/6/2017	2/6/2019*
Amplifier Power	50W 1000A	14715	CNR	CNR
Amplifier Power	10WD1000	28782	CNR	CNR
Amplifier Power	5S1G4	313326	CNR	CNR
Amplifier Power	10W1000C	312859	CNR	CNR
Signal Generator	E4438C	MY44270302	3/8/2018	3/8/2019*
Signal Generator	E4438C	MY45091270	8/13/2018	8/13/2020
Bi-direction Coupler	3020A	41931	7/4/2018	7/4/2019
Bi-direction Coupler	3022	81640	9/15/2018	9/15/2019
Bi-direction Coupler	3022	77114	8/16/2018	8/16/2019
Bi-direction Coupler	3020A	40295	9/4/2018	9/4/2019
Temperature & Humidity Logger	TM320	12253047	10/30/2018	10/30/2019
Thermometer	HH806AU	080307	12/5/2018	12/5/2019
Thermometer	HH202A	35881	12/26/2018	12/26/2019
Wideband Radio Communication Tester	CMW500	153170	6/2/2017	6/2/2019
Temperature Probe	80PK-22	06032017	12/5/2018	12/5/2019
Temperature Probe	80PK-22	05032017	12/26/2018	12/26/2019
Network Analyzer	E5071B	MY42403218	9/6/2018	9/6/2019
Dielectric Probe Kit (DAK)	DAK-3.5	1120	5/15/2018	5/15/2019
Dielectric Probe Kit (DAK)	DAK-12	1051	5/15/2018	5/15/2019

Table 11 Continued

Equipment Type	Model Number	Serial Number	Calibration Date	Calibration Due Date
Speag Dipole	CLA150	4005	2/9/2018	2/9/2020
Speag Dipole	CLA150	4016	10/10/2018	10/10/2020
Speag Dipole	D450V3	1054	10/25/2017	10/25/2019
Speag Dipole	D450V3	1053	10/19/2018	10/19/2020
Speag Dipole	D900V2	1d025	3/7/2018	3/7/2020
Speag Dipole	D835V2	4d029	1/8/2018	1/8/2020
Speag Dipole	D2450V2	782	2/15/2017	2/15/2019*
Speag Dipole	D5GHzV2	1026	10/18/2018	10/18/2020
Speag Dipole	D750V3	1142	10/12/2017	10/12/2019
Speag Dipole	D1800V2	2d119	5/17/2018	5/17/2020
Speag Dipole	D1900V2	5d064	10/16/2018	10/16/2020

Note - * Equipment used for test dates prior to equipment calibration due date.

10.0 SAR Measurement System Validation and Verification

Calibration certificates of the probes and dipole are included in Appendix of the report.

10.1 System Validation

The SAR measurement system was validated according to procedures in KDB 865664. The validation status summary tables for respective technologies are references to the following parts of the report.

Part 2 for LMR (VHF, UHF1, UHF2, and 7/800)

Part 3 for LTE (Band 2, Band 4, Band 5, Band 12, Band 13, Band 14, and Band 17)

Part 4 for WLAN (2.4 GHz and 5 GHz)

10.2 System Verification

System check results and DASY plots for each day during the SAR assessment are included in Appendix of the report. System verification results are normalized to 1W and summarized in the follow parts of the report.

Part 2 for LMR (VHF, UHF1, UHF2, and 7/800)

Part 3 for LTE (Band 2, Band 4, Band 5, Band 12, Band 13, Band 14, and Band 17)

Part 4 for WLAN (2.4 GHz and 5 GHz)

10.3 Equivalent Tissue Test Results

Simulated tissue prepared for SAR measurements is measured daily and within 24 hours prior to actual SAR testing to verify that the tissue is within +/- 5% of target parameters at the center of the transmit band. This measurement is done using the applicable equipment indicated in section 9.0. Measured dielectric properties for simulated tissue are listed in the following parts of the report.

Part 2 for LMR (VHF, UHF1, UHF2, and 7/800)

Part 3 for LTE (Band 2, Band 4, Band 5, Band 12, Band 13, Band 14, and Band 17)

Part 4 for WLAN (2.4 GHz and 5 GHz)

11.0 Environmental Test Conditions

The EME Laboratory’s ambient environment is well controlled resulting in very stable simulated tissue temperature and therefore stable dielectric properties. Simulated tissue temperature is measured prior to each scan to insure it is within +/- 2°C of the temperature at which the dielectric properties were determined. The liquid depth within the phantom used for measurements was at least 15 cm. Additional precautions are routinely taken to ensure the stability of the simulated tissue such as covering the phantoms when scans are not actively in process in order to minimize evaporation. The lab environment is continuously monitored. The Table below presents the range and average environmental conditions during the SAR tests reported herein:

Table 15

	Target	Measured
Ambient Temperature	18 – 25 °C	Range: 21.3 – 23.4°C Avg. 22.0 °C
Tissue Temperature	18 – 25 °C	Range: 20.7-22.6°C Avg. 21.6°C

Relative humidity target range is a recommended target

The EME Lab RF environment uses a Spectrum Analyzer to monitor for extraneous large signal RF contaminants that could possibly affect the test results. If such unwanted signals are discovered the SAR scans are repeated.

12.0 DUT Test Setup and Methodology

12.1 Measurements

SAR measurements were performed using the DASY system described in section 8.0 using zoom scans. Oval flat phantoms filled with applicable simulated tissue were used for body and face testing.

The Table below includes the step sizes and resolution of area and zoom scans per KDB 865664 requirements.

Table 16

Description		≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface		5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location		30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}		≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
		When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
<p>Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.</p> <p>* When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.</p>			

12.2 DUT Configuration(s)

The DUT is a portable device operational at the body and face as described in section 6.0 while using the applicable accessories listed in section 7.0. All accessories listed in section 7.0 of this report were considered when implementing the guidelines specified in KDB 643646 D01 for LMR. KDB 941225 D05 was applied to LTE test configurations and KDB 248227 D01 applied to WLAN test configurations. CMW500 Communication Test set was used for LTE testing.

12.3 DUT Positioning Procedures

The positioning of the device for each body location is described below and illustrated in Exhibit 7b.

12.3.1 Body

The DUT was positioned in normal use configuration against the phantom with the offered body worn accessory as well as with and without the offered audio accessories as applicable.

12.3.2 Head

Not applicable.

12.3.3 Face

The DUT was positioned with its' front and back sides separated 2.5cm from the phantom.

12.4 DUT Test Channels

The number of test channels was determined by using the following IEEE 1528 equation. The use of this equation produces the same or more test channels compared to the FCC KDB 447498 number of test channels formula.

$$N_c = 2 * \text{roundup}[10 * (f_{\text{high}} - f_{\text{low}}) / f_c] + 1$$

Where

N_c = Number of channels

F_{high} = Upper channel

F_{low} = Lower channel

F_c = Center channel

12.5 SAR Result Scaling Methodology

The calculated 1-gram and 10-gram averaged SAR results indicated as “Max Calc. 1g-SAR” in the data Tables is determined by scaling the measured SAR to account for power leveling variations and drift. Appendix F includes a shortened scan to justify SAR scaling for drift. For this device the “Max Calc. 1g-SAR” is scaled using the following formula:

$$\text{Max_Calc} = \text{SAR_meas} \cdot 10^{\frac{-\text{Drift}}{10}} \cdot \frac{P_{\text{max}}}{P_{\text{int}}} \cdot \text{DC}$$

P_{max} = Maximum Power (W)

P_{int} = Initial Power (W)

Drift = DASY drift results (dB)

SAR_meas = Measured 1-g or 10-g Avg. SAR (W/kg)

DC = Transmission mode duty cycle in % where applicable

50% duty cycle is applied for PTT operation

Note: for conservative results, the following are applied:

If $P_{\text{int}} > P_{\text{max}}$, then $P_{\text{max}}/P_{\text{int}} = 1$.

Drift = 1 for positive drift

Additional SAR scaling was applied using the methodologies outlined in FCC KDB 865664 using tissue sensitivity values. SAR was scaled for conditions where the tissue permittivity was measured above the nominal target and for tissue conductivity that was measured below the nominal target. Negative or reduced SAR scaling is not permitted.

12.6 DUT Test Plan

The guidelines and requirements outlined in section 4.0 were used to assess compliance of this device. All modes of operation identified in section 6.0 were considered during the development of the test plan.

13.0 DUT Test Data

13.1 Assessment at the LMR, LTE and WLAN bands

Refer to following parts of the reports for SAR assessment results on respective technologies.

Part 2 for LMR (VHF, UHF1, UHF2, and 7/800)

Part 3 for LTE (Band 2, Band 4, Band 5, Band 12, Band 13, Band 14, and Band 17)

Part 4 for WLAN (2.4 GHz and 5 GHz)

13.2 Assessment at the Bluetooth band

13.2.1 FCC Requirement

Per guidelines in KDB 447498, the following formula was used to determine the test exclusion for standalone Bluetooth transmitter;

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{F_{(\text{GHz})}}] = 2.8 \text{ W/kg}$, which is $\leq 3 \text{ W/kg}$ (1g)

Where:

Max. Power = 8.89mW (11.5mW*77.26 % duty cycle)

Min. test separation distance = 5mm for actual test separation < 5mm

F(GHz) = 2.48 GHz

Per the result from the calculation above, the standalone SAR assessment was not required for Bluetooth band. Therefore, SAR results for Bluetooth are not reported herein.

13.2.2 ISED Canada Requirement

Based on RSS-102 Issue 5, exemption limits for SAR evaluation for controlled devices at Bluetooth frequency band with separation distance $\leq 5\text{mm}$ was 20 mW.

Standalone Bluetooth transmitter operates at

Maximum conducted power:

= 11.5 mW * 77.26 %

= 8.89 mW or 9.49 dBm

Equivalent isotropically radiated power (EIRP):
 = Maximum conducted power, dBm + Antenna gain, dBi
 = 9.49 dBm + 3.2 dBi
 = 12.69 dBm or 18.58 mW

Higher output power level, Equivalent isotropically radiated power (EIRP)
 18.58 mW was below the threshold power level 20 mW. Hence SAR test was not required for Bluetooth band.

13.3 Assessment at the NFC

Based on below calculation, SAR test exclusion power threshold at 13.56 MHz is 443 mW. Maximum power for NFC is 35 mW, hence SAR test was not required for NFC.

KDB 447498 4.3.1, b.1) for 100 MHz to 6 GHz and test separation distances > 50 mm, the 1-g test exclusion thresholds are determined by following:

For 100 MHz to 1500 MHz:

{[Power allowed at *numeric threshold* for 50 mm at 100 MHz] + [(test separation distance – 50 mm) · (f(MHz)/150)]} mW
 = **474.3 mW**

Where:

Power allowed at *numeric threshold* for 50 mm at 100 MHz = 474.3 mW

Test separation distance = 50 mm

KDB 447498 4.3.1, c.1) for below 100 MHz and test separation distances >50 mm and <200 mm,

Power threshold at the corresponding test separation distance at 100 MHz in step b) is multiply by [1+log (100/f (MHz))]

= 474.3 mW * [1+log (100/13.56 MHz)]

= **885.9 mW**

Where:

f (MHz)= 13.56 MHz

KDB 447498 4.3.1, c.2) for below 100 MHz and test separation distances ≤ 50 mm, Power threshold determined by equation in c) 1) is multiplied by ½

= 885.9 mW * 0.5

= **443.0 mW**

.

14.0 Simultaneous Transmissions

The Table below summarizes the simultaneous transmission conditions for this device.

Table 17

Exposure Conditions	Item	Capable Simultaneous Transmit Configurations
Body-Worn	1	LMR + WLAN 2.4 GHz
	2	LMR + WLAN 5 GHz
	3	LMR + BT
	4	LMR +LTE
Face	1	LMR + WLAN 2.4 GHz
	2	LMR + WLAN 5 GHz
	3	LMR + BT
	4	LMR +LTE

WLAN 2.4 GHz, 5GHz and Bluetooth share the same antenna, only one technology to transmit at a single time.

14.1 Simultaneous Transmission Exclusion for BT

Per guidelines in KDB 447498, the following formula was used to determine the test exclusion to an antenna that transmits simultaneously with other antennas for test distances $\leq 50\text{mm}$:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{F(\text{GHz})/X}] = 0.37 \text{ W/kg}$, which is $\leq 0.4 \text{ W/kg}$ (1g)

Where:

$X = 7.5$ for 1g-SAR; 18.75 for 10g

Max. Power = 8.89mW ($11.5\text{mW} * 77.26\%$ duty cycle)

Min. test separation distance = 5mm for actual test separation $< 5\text{mm}$

$F(\text{GHz}) = 2.48 \text{ GHz}$

Per the result from the calculation above, simultaneous exclusion is applied and therefore SAR results are not reported herein.

14.2 Simultaneous Transmission for LMR and WLAN 2.4 GHz

Table 18 (FCC)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	WLAN 2.4	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	WLAN 2.4 GHz	WLAN 2.4 GHz	WLAN 2.4 GHz	WLAN 2.4 GHz
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.036	0.65	6.54	6.12	5.45
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.054	0.68	5.62	5.40	5.42
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.031	0.62	6.15	5.17	5.22
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.78	5.15	0.043	1.28	5.40	4.82	5.19
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.038	0.43	3.14	2.95	2.84
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.037	0.33	2.84	2.83	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.044	0.40	2.92	2.52	3.46
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.030	0.61	4.86	4.77	3.28
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.028	0.46	4.23	4.38	3.05
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.010	0.43	2.52	2.28	1.53
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.012	0.37	2.56	1.91	1.82
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.026	0.42	2.64	2.28	1.87
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.262	1.02	3.40	2.61	2.46
	Face Back (display)	1.19	5.52	4.48	2.37	0.020	1.21	5.54	4.50	2.39

Table 19 (ISED)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	WLAN 2.4	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	WLAN 2.4 GHz	WLAN 2.4 GHz	WLAN 2.4 GHz	WLAN 2.4 GHz
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	5.43	5.41	0.036	0.65	6.54	5.47	5.45
	PMLN7947A w/ PMLN7965A	0.63	5.57	4.66	5.37	0.054	0.68	5.62	4.71	5.42
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.031	0.62	6.15	5.17	5.22
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.52	5.15	0.043	1.28	5.40	4.56	5.19
	PMLN7948A w/ PMLN5407A	0.39	3.10	1.65	2.80	0.038	0.43	3.14	1.69	2.84
	PMLN7948A w/ PMLN5408A	0.29	2.80	1.11	3.57	0.037	0.33	2.84	1.15	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	1.35	3.42	0.044	0.40	2.92	1.39	3.46
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.030	0.61	4.86	4.77	3.28
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.028	0.46	4.23	4.38	3.05
	PMLN7964A w/ PMLN5407A	0.42	2.51	1.3	1.52	0.010	0.43	2.52	1.31	1.53
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.1	1.81	0.012	0.37	2.56	1.11	1.82
	PMLN7964A w/ PMLN5409A	0.39	2.61	1.04	1.84	0.026	0.42	2.64	1.07	1.87
Face exposure	Face Front (non-display)	0.76	3.14	1.42	2.20	0.262	1.02	3.40	1.68	2.46
	Face Back (display)	1.19	5.52	2.85	2.37	0.020	1.21	5.54	2.87	2.39

Table 20 (Overall)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	WLAN 2.4	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	WLAN 2.4 GHz	WLAN 2.4 GHz	WLAN 2.4 GHz	WLAN 2.4 GHz
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.036	0.65	6.54	6.12	5.45
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.054	0.68	5.62	5.40	5.42
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.031	0.62	6.15	5.17	5.22
	PMLN7948A w/ PMLN7965A	1.64	5.36	4.78	5.15	0.043	1.68	5.40	4.82	5.19
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.038	0.43	3.14	2.95	2.84
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.037	0.33	2.84	2.83	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.044	0.40	2.92	2.52	3.46
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.030	0.61	4.86	4.77	3.28
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.028	0.46	4.23	4.38	3.05
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.010	0.43	2.52	2.28	1.53
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.012	0.37	2.56	1.91	1.82
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.026	0.42	2.64	2.28	1.87
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.262	1.02	3.40	2.61	2.46
	Face Back (display)	1.54	5.52	4.48	2.37	0.020	1.56	5.54	4.50	2.39

14.3 Simultaneous Transmission for LMR and WLAN 5 GHz

Table 21 (FCC)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	WLAN 5 GHz	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	WLAN 5 GHz	WLAN 5 GHz	WLAN 5 GHz	WLAN 5 GHz
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.041	0.65	6.54	6.12	5.45
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.051	0.68	5.62	5.40	5.42
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.038	0.63	6.16	5.18	5.23
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.78	5.15	0.023	1.26	5.38	4.80	5.17
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.030	0.42	3.13	2.94	2.83
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.036	0.33	2.84	2.83	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.046	0.41	2.93	2.53	3.47
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.057	0.64	4.89	4.80	3.31
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.028	0.46	4.23	4.38	3.05
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.028	0.45	2.54	2.30	1.55
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.031	0.39	2.58	1.93	1.84
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.025	0.42	2.64	2.28	1.87
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	1.183	1.94	4.32	3.53	3.38
	Face Back (display)	1.19	5.52	4.48	2.37	0.060	1.25	5.58	4.54	2.43

Table 22 (ISED)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	WLAN 5 GHz	VHF + WLAN 5 GHz	UHF1 + WLAN 5 GHz	UHF2 + WLAN 5 GHz	7/800 + WLAN 5 GHz
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)				
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	5.43	5.41	0.041	0.65	6.54	5.47	5.45
	PMLN7947A w/ PMLN7965A	0.63	5.57	4.66	5.37	0.051	0.68	5.62	4.71	5.42
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.038	0.63	6.16	5.18	5.23
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.52	5.15	0.023	1.26	5.38	4.54	5.17
	PMLN7948A w/ PMLN5407A	0.39	3.10	1.65	2.80	0.030	0.42	3.13	1.68	2.83
	PMLN7948A w/ PMLN5408A	0.29	2.80	1.11	3.57	0.036	0.33	2.84	1.15	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	1.35	3.42	0.046	0.41	2.93	1.40	3.47
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.057	0.64	4.89	4.80	3.31
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.028	0.46	4.23	4.38	3.05
	PMLN7964A w/ PMLN5407A	0.42	2.51	1.3	1.52	0.028	0.45	2.54	1.33	1.55
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.1	1.81	0.031	0.39	2.58	1.13	1.84
	PMLN7964A w/ PMLN5409A	0.39	2.61	1.04	1.84	0.025	0.42	2.64	1.07	1.87
Face exposure	Face Front (non-display)	0.76	3.14	1.42	2.20	1.183	1.94	4.32	2.60	3.38
	Face Back (display)	1.19	5.52	2.85	2.37	0.060	1.25	5.58	2.91	2.43

Table 23 (Overall)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	WLAN 5 GHz	VHF + WLAN 5 GHz	UHF1 + WLAN 5 GHz	UHF2 + WLAN 5 GHz	7/800 + WLAN 5 GHz
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)				
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.041	0.65	6.54	6.12	5.45
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.051	0.68	5.62	5.40	5.42
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.038	0.63	6.16	5.18	5.23
	PMLN7948A w/ PMLN7965A	1.64	5.36	4.78	5.15	0.023	1.66	5.38	4.80	5.17
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.030	0.42	3.13	2.94	2.83
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.036	0.33	2.84	2.83	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.046	0.41	2.93	2.53	3.47
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.057	0.64	4.89	4.80	3.31
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.028	0.46	4.23	4.38	3.05
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.028	0.45	2.54	2.30	1.55
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.031	0.39	2.58	1.93	1.84
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.025	0.42	2.64	2.28	1.87
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	1.183	1.94	4.32	3.53	3.38
	Face Back (display)	1.54	5.52	4.48	2.37	0.060	1.60	5.58	4.54	2.43

14.4 Simultaneous Transmission for LMR and LTE

Table 24 (FCC, LTE Band 12)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 12	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B12	LTE B12	LTE B12	LTE B12
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.034	0.64	6.53	6.11	5.44
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.028	0.66	5.60	5.38	5.40
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.013	0.60	6.13	5.15	5.20
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.78	5.15	0.013	1.25	5.37	4.79	5.16
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.007	0.40	3.11	2.92	2.81
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.006	0.30	2.81	2.80	3.58
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.004	0.36	2.88	2.48	3.42
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.017	0.60	4.85	4.76	3.27
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.016	0.45	4.22	4.37	3.04
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.004	0.42	2.51	2.27	1.52
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.004	0.36	2.55	1.90	1.81
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.006	0.40	2.62	2.26	1.85
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.160	0.92	3.30	2.51	2.36
	Face Back (display)	1.19	5.52	4.48	2.37	0.036	1.23	5.56	4.52	2.41

Table 25 (ISED, LTE Band 12)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 12	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B12	LTE B12	LTE B12	LTE B12
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	5.43	5.41	0.034	0.64	6.53	5.46	5.44
	PMLN7947A w/ PMLN7965A	0.63	5.57	4.66	5.37	0.028	0.66	5.60	4.69	5.40
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.013	0.60	6.13	5.15	5.20
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.52	5.15	0.013	1.25	5.37	4.53	5.16
	PMLN7948A w/ PMLN5407A	0.39	3.10	1.65	2.80	0.007	0.40	3.11	1.66	2.81
	PMLN7948A w/ PMLN5408A	0.29	2.80	1.11	3.57	0.006	0.30	2.81	1.12	3.58
	PMLN7948A w/ PMLN5409A	0.36	2.88	1.35	3.42	0.004	0.36	2.88	1.35	3.42
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.017	0.60	4.85	4.76	3.27
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.016	0.45	4.22	4.37	3.04
	PMLN7964A w/ PMLN5407A	0.42	2.51	1.3	1.52	0.004	0.42	2.51	1.30	1.52
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.1	1.81	0.004	0.36	2.55	1.10	1.81
	PMLN7964A w/ PMLN5409A	0.39	2.61	1.04	1.84	0.006	0.40	2.62	1.05	1.85
Face exposure	Face Front (non-display)	0.76	3.14	1.42	2.20	0.160	0.92	3.30	1.58	2.36
	Face Back (display)	1.19	5.52	2.85	2.37	0.036	1.23	5.56	2.89	2.41

Table 26 (Overall, LTE Band 12)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 12	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B12	LTE B12	LTE B12	LTE B12
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.034	0.64	6.53	6.11	5.44
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.028	0.66	5.60	5.38	5.40
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.013	0.60	6.13	5.15	5.20
	PMLN7948A w/ PMLN7965A	1.64	5.36	4.78	5.15	0.013	1.65	5.37	4.79	5.16
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.007	0.40	3.11	2.92	2.81
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.006	0.30	2.81	2.80	3.58
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.004	0.36	2.88	2.48	3.42
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.017	0.60	4.85	4.76	3.27
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.016	0.45	4.22	4.37	3.04
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.004	0.42	2.51	2.27	1.52
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.004	0.36	2.55	1.90	1.81
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.006	0.40	2.62	2.26	1.85
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.160	0.92	3.30	2.51	2.36
	Face Back (display)	1.54	5.52	4.48	2.37	0.036	1.58	5.56	4.52	2.41

Table 27 (FCC, LTE Band 13)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 13	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B13	LTE B13	LTE B13	LTE B13
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.079	0.69	6.58	6.16	5.49
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.078	0.71	5.65	5.43	5.45
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.050	0.64	6.17	5.19	5.24
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.78	5.15	0.049	1.29	5.41	4.83	5.20
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.032	0.42	3.13	2.94	2.83
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.037	0.33	2.84	2.83	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.038	0.40	2.92	2.52	3.46
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.041	0.62	4.87	4.78	3.29
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.038	0.47	4.24	4.39	3.06
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.024	0.44	2.53	2.29	1.54
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.027	0.39	2.58	1.93	1.84
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.022	0.41	2.63	2.27	1.86
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.157	0.92	3.30	2.51	2.36
	Face Back (display)	1.19	5.52	4.48	2.37	0.050	1.24	5.57	4.53	2.42

Table 28 (ISED, LTE Band 13)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 13	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B13	LTE B13	LTE B13	LTE B13
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	5.43	5.41	0.079	0.69	6.58	5.51	5.49
	PMLN7947A w/ PMLN7965A	0.63	5.57	4.66	5.37	0.078	0.71	5.65	4.74	5.45
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.050	0.64	6.17	5.19	5.24
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.52	5.15	0.049	1.29	5.41	4.57	5.20
	PMLN7948A w/ PMLN5407A	0.39	3.10	1.65	2.80	0.032	0.42	3.13	1.68	2.83
	PMLN7948A w/ PMLN5408A	0.29	2.80	1.11	3.57	0.037	0.33	2.84	1.15	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	1.35	3.42	0.038	0.40	2.92	1.39	3.46
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.041	0.62	4.87	4.78	3.29
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.038	0.47	4.24	4.39	3.06
	PMLN7964A w/ PMLN5407A	0.42	2.51	1.3	1.52	0.024	0.44	2.53	1.32	1.54
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.1	1.81	0.027	0.39	2.58	1.13	1.84
	PMLN7964A w/ PMLN5409A	0.39	2.61	1.04	1.84	0.022	0.41	2.63	1.06	1.86
Face exposure	Face Front (non-display)	0.76	3.14	1.42	2.20	0.157	0.92	3.30	1.58	2.36
	Face Back (display)	1.19	5.52	2.85	2.37	0.050	1.24	5.57	2.90	2.42

Table 29 (Overall, LTE Band 13)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 13	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B13	LTE B13	LTE B13	LTE B13
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.079	0.69	6.58	6.16	5.49
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.078	0.71	5.65	5.43	5.45
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.050	0.64	6.17	5.19	5.24
	PMLN7948A w/ PMLN7965A	1.64	5.36	4.78	5.15	0.049	1.69	5.41	4.83	5.20
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.032	0.42	3.13	2.94	2.83
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.037	0.33	2.84	2.83	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.038	0.40	2.92	2.52	3.46
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.041	0.62	4.87	4.78	3.29
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.038	0.47	4.24	4.39	3.06
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.024	0.44	2.53	2.29	1.54
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.027	0.39	2.58	1.93	1.84
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.022	0.41	2.63	2.27	1.86
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.157	0.92	3.30	2.51	2.36
	Face Back (display)	1.54	5.52	4.48	2.37	0.050	1.59	5.57	4.53	2.42

Table 30 (FCC, LTE Band 14)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 14	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B14	LTE B14	LTE B14	LTE B14
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.096	0.71	6.60	6.18	5.51
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.098	0.73	5.67	5.45	5.47
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.069	0.66	6.19	5.21	5.26
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.78	5.15	0.065	1.31	5.43	4.85	5.22
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.045	0.44	3.15	2.96	2.85
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.042	0.33	2.84	2.83	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.044	0.40	2.92	2.52	3.46
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.044	0.62	4.87	4.78	3.29
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.042	0.47	4.24	4.39	3.06
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.027	0.45	2.54	2.30	1.55
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.026	0.39	2.58	1.93	1.84
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.026	0.42	2.64	2.28	1.87
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.186	0.95	3.33	2.54	2.39
	Face Back (display)	1.19	5.52	4.48	2.37	0.063	1.25	5.58	4.54	2.43

Table 31 (ISED, LTE Band 14)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 14	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B14	LTE B14	LTE B14	LTE B14
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	5.43	5.41	0.096	0.71	6.60	5.53	5.51
	PMLN7947A w/ PMLN7965A	0.63	5.57	4.66	5.37	0.098	0.73	5.67	4.76	5.47
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.069	0.66	6.19	5.21	5.26
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.52	5.15	0.065	1.31	5.43	4.59	5.22
	PMLN7948A w/ PMLN5407A	0.39	3.10	1.65	2.80	0.045	0.44	3.15	1.70	2.85
	PMLN7948A w/ PMLN5408A	0.29	2.80	1.11	3.57	0.042	0.33	2.84	1.15	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	1.35	3.42	0.044	0.40	2.92	1.39	3.46
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.044	0.62	4.87	4.78	3.29
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.042	0.47	4.24	4.39	3.06
	PMLN7964A w/ PMLN5407A	0.42	2.51	1.3	1.52	0.027	0.45	2.54	1.33	1.55
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.1	1.81	0.026	0.39	2.58	1.13	1.84
	PMLN7964A w/ PMLN5409A	0.39	2.61	1.04	1.84	0.026	0.42	2.64	1.07	1.87
Face exposure	Face Front (non-display)	0.76	3.14	1.42	2.20	0.186	0.95	3.33	1.61	2.39
	Face Back (display)	1.19	5.52	2.85	2.37	0.063	1.25	5.58	2.91	2.43

Table 32 (Overall, LTE Band 14)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 14	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B14	LTE B14	LTE B14	LTE B14
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.096	0.71	6.60	6.18	5.51
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.098	0.73	5.67	5.45	5.47
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.069	0.66	6.19	5.21	5.26
	PMLN7948A w/ PMLN7965A	1.64	5.36	4.78	5.15	0.065	1.71	5.43	4.85	5.22
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.045	0.44	3.15	2.96	2.85
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.042	0.33	2.84	2.83	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.044	0.40	2.92	2.52	3.46
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.044	0.62	4.87	4.78	3.29
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.042	0.47	4.24	4.39	3.06
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.027	0.45	2.54	2.30	1.55
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.026	0.39	2.58	1.93	1.84
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.026	0.42	2.64	2.28	1.87
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.186	0.95	3.33	2.54	2.39
	Face Back (display)	1.54	5.52	4.48	2.37	0.063	1.60	5.58	4.54	2.43

Table 33 (FCC, LTE Band 17)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 17	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B17	LTE B17	LTE B17	LTE B17
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.026	0.64	6.53	6.11	5.44
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.017	0.65	5.59	5.37	5.39
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.007	0.60	6.13	5.15	5.20
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.78	5.15	0.006	1.25	5.37	4.79	5.16
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.004	0.39	3.10	2.91	2.80
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.006	0.30	2.81	2.80	3.58
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.005	0.37	2.89	2.49	3.43
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.012	0.59	4.84	4.75	3.26
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.009	0.44	4.21	4.36	3.03
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.007	0.43	2.52	2.28	1.53
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.006	0.37	2.56	1.91	1.82
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.004	0.39	2.61	2.25	1.84
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.160	0.92	3.30	2.51	2.36
	Face Back (display)	1.19	5.52	4.48	2.37	0.017	1.21	5.54	4.50	2.39

Table 34 (ISED, LTE Band 17)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 17	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B17	LTE B17	LTE B17	LTE B17
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	5.43	5.41	0.026	0.64	6.53	5.46	5.44
	PMLN7947A w/ PMLN7965A	0.63	5.57	4.66	5.37	0.017	0.65	5.59	4.68	5.39
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.007	0.60	6.13	5.15	5.20
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.52	5.15	0.006	1.25	5.37	4.53	5.16
	PMLN7948A w/ PMLN5407A	0.39	3.10	1.65	2.80	0.004	0.39	3.10	1.65	2.80
	PMLN7948A w/ PMLN5408A	0.29	2.80	1.11	3.57	0.006	0.30	2.81	1.12	3.58
	PMLN7948A w/ PMLN5409A	0.36	2.88	1.35	3.42	0.005	0.37	2.89	1.36	3.43
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.012	0.59	4.84	4.75	3.26
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.009	0.44	4.21	4.36	3.03
	PMLN7964A w/ PMLN5407A	0.42	2.51	1.3	1.52	0.007	0.43	2.52	1.31	1.53
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.1	1.81	0.006	0.37	2.56	1.11	1.82
	PMLN7964A w/ PMLN5409A	0.39	2.61	1.04	1.84	0.004	0.39	2.61	1.04	1.84
Face exposure	Face Front (non-display)	0.76	3.14	1.42	2.20	0.160	0.92	3.30	1.58	2.36
	Face Back (display)	1.19	5.52	2.85	2.37	0.017	1.21	5.54	2.87	2.39

Table 35 (Overall, LTE Band 17)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 17	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B17	LTE B17	LTE B17	LTE B17
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.026	0.64	6.53	6.11	5.44
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.017	0.65	5.59	5.37	5.39
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.007	0.60	6.13	5.15	5.20
	PMLN7948A w/ PMLN7965A	1.64	5.36	4.78	5.15	0.006	1.65	5.37	4.79	5.16
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.004	0.39	3.10	2.91	2.80
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.006	0.30	2.81	2.80	3.58
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.005	0.37	2.89	2.49	3.43
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.012	0.59	4.84	4.75	3.26
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.009	0.44	4.21	4.36	3.03
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.007	0.43	2.52	2.28	1.53
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.006	0.37	2.56	1.91	1.82
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.004	0.39	2.61	2.25	1.84
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.160	0.92	3.30	2.51	2.36
	Face Back (display)	1.54	5.52	4.48	2.37	0.017	1.56	5.54	4.50	2.39

Table 36 (FCC, LTE Band 5)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 5	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B5	LTE B5	LTE B5	LTE B5
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.067	0.68	6.57	6.15	5.48
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.067	0.70	5.64	5.42	5.44
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.067	0.66	6.19	5.21	5.26
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.78	5.15	0.065	1.31	5.43	4.85	5.22
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.043	0.43	3.14	2.95	2.84
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.041	0.33	2.84	2.83	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.041	0.40	2.92	2.52	3.46
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.044	0.62	4.87	4.78	3.29
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.045	0.48	4.25	4.40	3.07
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.023	0.44	2.53	2.29	1.54
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.024	0.38	2.57	1.92	1.83
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.024	0.41	2.63	2.27	1.86
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.164	0.92	3.30	2.51	2.36
	Face Back (display)	1.19	5.52	4.48	2.37	0.054	1.24	5.57	4.53	2.42

Table 37 (ISED, LTE Band 5)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 5	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B5	LTE B5	LTE B5	LTE B5
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	5.43	5.41	0.067	0.68	6.57	5.50	5.48
	PMLN7947A w/ PMLN7965A	0.63	5.57	4.66	5.37	0.067	0.70	5.64	4.73	5.44
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.067	0.66	6.19	5.21	5.26
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.52	5.15	0.065	1.31	5.43	4.59	5.22
	PMLN7948A w/ PMLN5407A	0.39	3.10	1.65	2.80	0.043	0.43	3.14	1.69	2.84
	PMLN7948A w/ PMLN5408A	0.29	2.80	1.11	3.57	0.041	0.33	2.84	1.15	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	1.35	3.42	0.041	0.40	2.92	1.39	3.46
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.044	0.62	4.87	4.78	3.29
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.045	0.48	4.25	4.40	3.07
	PMLN7964A w/ PMLN5407A	0.42	2.51	1.3	1.52	0.023	0.44	2.53	1.32	1.54
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.1	1.81	0.024	0.38	2.57	1.12	1.83
	PMLN7964A w/ PMLN5409A	0.39	2.61	1.04	1.84	0.024	0.41	2.63	1.06	1.86
Face exposure	Face Front (non-display)	0.76	3.14	1.42	2.20	0.164	0.92	3.30	1.58	2.36
	Face Back (display)	1.19	5.52	2.85	2.37	0.054	1.24	5.57	2.90	2.42

Table 38 (Overall, LTE Band 5)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 5	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B5	LTE B5	LTE B5	LTE B5
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.067	0.68	6.57	6.15	5.48
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.067	0.70	5.64	5.42	5.44
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.067	0.66	6.19	5.21	5.26
	PMLN7948A w/ PMLN7965A	1.64	5.36	4.78	5.15	0.065	1.71	5.43	4.85	5.22
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.043	0.43	3.14	2.95	2.84
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.041	0.33	2.84	2.83	3.61
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.041	0.40	2.92	2.52	3.46
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.044	0.62	4.87	4.78	3.29
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.045	0.48	4.25	4.40	3.07
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.023	0.44	2.53	2.29	1.54
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.024	0.38	2.57	1.92	1.83
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.024	0.41	2.63	2.27	1.86
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.164	0.92	3.30	2.51	2.36
	Face Back (display)	1.54	5.52	4.48	2.37	0.054	1.59	5.57	4.53	2.42

Table 39 (FCC, LTE Band 2)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 2	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B2	LTE B2	LTE B2	LTE B2
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.010	0.62	6.51	6.09	5.42
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.014	0.64	5.58	5.36	5.38
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.008	0.60	6.13	5.15	5.20
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.78	5.15	0.011	1.25	5.37	4.79	5.16
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.005	0.40	3.11	2.92	2.81
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.003	0.29	2.80	2.79	3.57
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.006	0.37	2.89	2.49	3.43
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.006	0.59	4.84	4.75	3.26
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.003	0.43	4.20	4.35	3.02
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.003	0.42	2.51	2.27	1.52
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.002	0.36	2.55	1.90	1.81
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.005	0.40	2.62	2.26	1.85
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.416	1.18	3.56	2.77	2.62
	Face Back (display)	1.19	5.52	4.48	2.37	0.005	1.20	5.53	4.49	2.38

Table 40 (ISED, LTE Band 2)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 2	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B2	LTE B2	LTE B2	LTE B2
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	5.43	5.41	0.010	0.62	6.51	5.44	5.42
	PMLN7947A w/ PMLN7965A	0.63	5.57	4.66	5.37	0.014	0.64	5.58	4.67	5.38
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.008	0.60	6.13	5.15	5.20
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.52	5.15	0.011	1.25	5.37	4.53	5.16
	PMLN7948A w/ PMLN5407A	0.39	3.10	1.65	2.80	0.005	0.40	3.11	1.66	2.81
	PMLN7948A w/ PMLN5408A	0.29	2.80	1.11	3.57	0.003	0.29	2.80	1.11	3.57
	PMLN7948A w/ PMLN5409A	0.36	2.88	1.35	3.42	0.006	0.37	2.89	1.36	3.43
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.006	0.59	4.84	4.75	3.26
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.003	0.43	4.20	4.35	3.02
	PMLN7964A w/ PMLN5407A	0.42	2.51	1.3	1.52	0.003	0.42	2.51	1.30	1.52
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.1	1.81	0.002	0.36	2.55	1.10	1.81
	PMLN7964A w/ PMLN5409A	0.39	2.61	1.04	1.84	0.005	0.40	2.62	1.05	1.85
Face exposure	Face Front (non-display)	0.76	3.14	1.42	2.20	0.416	1.18	3.56	1.84	2.62
	Face Back (display)	1.19	5.52	2.85	2.37	0.005	1.20	5.53	2.86	2.38

Table 41 (Overall, LTE Band 2)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 2	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B2	LTE B2	LTE B2	LTE B2
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.010	0.62	6.51	6.09	5.42
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.014	0.64	5.58	5.36	5.38
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.008	0.60	6.13	5.15	5.20
	PMLN7948A w/ PMLN7965A	1.64	5.36	4.78	5.15	0.011	1.65	5.37	4.79	5.16
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.005	0.40	3.11	2.92	2.81
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.003	0.29	2.80	2.79	3.57
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.006	0.37	2.89	2.49	3.43
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.006	0.59	4.84	4.75	3.26
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.003	0.43	4.20	4.35	3.02
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.003	0.42	2.51	2.27	1.52
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.002	0.36	2.55	1.90	1.81
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.005	0.40	2.62	2.26	1.85
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.416	1.18	3.56	2.77	2.62
	Face Back (display)	1.54	5.52	4.48	2.37	0.005	1.55	5.53	4.49	2.38

Table 42 (FCC, LTE Band 4)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 4	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B4	LTE B4	LTE B4	LTE B4
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.029	0.64	6.53	6.11	5.44
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.025	0.66	5.60	5.38	5.40
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.013	0.60	6.13	5.15	5.20
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.78	5.15	0.017	1.26	5.38	4.80	5.17
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.013	0.40	3.11	2.92	2.81
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.011	0.30	2.81	2.80	3.58
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.012	0.37	2.89	2.49	3.43
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.017	0.60	4.85	4.76	3.27
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.033	0.46	4.23	4.38	3.05
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.022	0.44	2.53	2.29	1.54
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.025	0.39	2.58	1.93	1.84
	PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.031	0.42	2.64	2.28	1.87
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.325	1.09	3.47	2.68	2.53
	Face Back (display)	1.19	5.52	4.48	2.37	0.006	1.20	5.53	4.49	2.38

Table 43 (ISED, LTE Band 4)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF	UHF R1	UHF R2	7/800	LTE Band 4	VHF +	UHF1 +	UHF2 +	7/800 +
		SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	SAR (W/kg)	LTE B4	LTE B4	LTE B4	LTE B4
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	5.43	5.41	0.029	0.64	6.53	5.46	5.44
	PMLN7947A w/ PMLN7965A	0.63	5.57	4.66	5.37	0.025	0.66	5.60	4.69	5.40
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.013	0.60	6.13	5.15	5.20
	PMLN7948A w/ PMLN7965A	1.24	5.36	4.52	5.15	0.017	1.26	5.38	4.54	5.17
	PMLN7948A w/ PMLN5407A	0.39	3.10	1.65	2.80	0.013	0.40	3.11	1.66	2.81
	PMLN7948A w/ PMLN5408A	0.29	2.80	1.11	3.57	0.011	0.30	2.81	1.12	3.58
	PMLN7948A w/ PMLN5409A	0.36	2.88	1.35	3.42	0.012	0.37	2.89	1.36	3.43
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.017	0.60	4.85	4.76	3.27
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.033	0.46	4.23	4.38	3.05
	PMLN7964A w/ PMLN5407A	0.42	2.51	1.3	1.52	0.022	0.44	2.53	1.32	1.54
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.1	1.81	0.025	0.39	2.58	1.13	1.84
	PMLN7964A w/ PMLN5409A	0.39	2.61	1.04	1.84	0.031	0.42	2.64	1.07	1.87
Face exposure	Face Front (non-display)	0.76	3.14	1.42	2.20	0.325	1.09	3.47	1.75	2.53
	Face Back (display)	1.19	5.52	2.85	2.37	0.006	1.20	5.53	2.86	2.38

Table 44 (Overall, LTE Band 4)

Exposure Conditions	Configurations	Standalone SAR					Sum of SAR			
		VHF SAR (W/kg)	UHF R1 SAR (W/kg)	UHF R2 SAR (W/kg)	7/800 SAR (W/kg)	LTE Band 4 SAR (W/kg)	VHF + LTE B4	UHF1 + LTE B4	UHF2 + LTE B4	7/800 + LTE B4
Body-worn exposure	PMLN7947A w/ NTN8266B	0.61	6.50	6.08	5.41	0.029	0.64	6.53	6.11	5.44
	PMLN7947A w/ PMLN7965A	0.63	5.57	5.35	5.37	0.025	0.66	5.60	5.38	5.40
	PMLN7948A w/ NTN8266B	0.59	6.12	5.14	5.19	0.013	0.60	6.13	5.15	5.20
	PMLN7948A w/ PMLN7965A	1.64	5.36	4.78	5.15	0.017	1.66	5.38	4.80	5.17
	PMLN7948A w/ PMLN5407A	0.39	3.10	2.91	2.80	0.013	0.40	3.11	2.92	2.81
	PMLN7948A w/ PMLN5408A	0.29	2.80	2.79	3.57	0.011	0.30	2.81	2.80	3.58
	PMLN7948A w/ PMLN5409A	0.36	2.88	2.48	3.42	0.012	0.37	2.89	2.49	3.43
	PMLN7964A w/ NTN8266B	0.58	4.83	4.74	3.25	0.017	0.60	4.85	4.76	3.27
	PMLN7964A w/ PMLN7965A	0.43	4.20	4.35	3.02	0.033	0.46	4.23	4.38	3.05
	PMLN7964A w/ PMLN5407A	0.42	2.51	2.27	1.52	0.022	0.44	2.53	2.29	1.54
	PMLN7964A w/ PMLN5408A	0.36	2.55	1.9	1.81	0.025	0.39	2.58	1.93	1.84
PMLN7964A w/ PMLN5409A	0.39	2.61	2.25	1.84	0.031	0.42	2.64	2.28	1.87	
Face exposure	Face Front (non-display)	0.76	3.14	2.35	2.20	0.325	1.09	3.47	2.68	2.53
	Face Back (display)	1.54	5.52	4.48	2.37	0.006	1.55	5.53	4.49	2.38

15.0 Results Summary

Based on the test guideline from section 4.0 and satisfying frequencies within FCC US bands and ISED Canada frequency bands, the highest Operational Maximum Calculated 1-g values found for this filing:

Table 45 (FCC)

Technologies	Frequency band (MHz)	Max Calc at Body (W/kg)	Max Calc at Face (W/kg)
		1g-SAR	1g-SAR
LMR	150.8-173.4	1.24	1.19
	406.125-470	6.50	5.52
	450-512	6.08	4.48
	769-775	4.57	1.72
	799-824	5.41	2.37
	851-869	4.53	2.15
LTE	LTE B2	0.014	0.416
	LTE B4	0.033	0.325
	LTE B5	0.067	0.164
	LTE B12	0.034	0.160
	LTE B13	0.079	0.157
	LTE B14	0.098	0.186
	LTE B17	0.026	0.160
WLAN	2.4 GHz	0.054	0.262
	5 GHz	0.057	1.183
Highest Simultaneous Transmission SAR	Sum of SAR (W/kg)	6.60	5.58

Table 46 (ISED)

Technologies	Frequency band (MHz)	Max Calc at Body (W/kg)	Max Calc at Face (W/kg)
		1g-SAR	1g-SAR
LMR	138-173.4	1.24	1.19
	406.125-430, 450-470	6.50	5.52
	450-470	5.43	2.85
	769-775	4.57	1.72
	799-824	5.41	2.37
	851-869	4.53	2.15
LTE	LTE B2	0.014	0.416
	LTE B4	0.033	0.325
	LTE B5	0.067	0.164
	LTE B12	0.034	0.160
	LTE B13	0.079	0.157
	LTE B14	0.098	0.186
	LTE B17	0.026	0.160
WLAN	2.4 GHz	0.054	0.262
	5 GHz	0.057	1.183
Highest Simultaneous Transmission SAR	Sum of SAR (W/kg)	6.60	5.58

Table 47 (Overall)

Technologies	Frequency band (MHz)	Max Calc at Body (W/kg)	Max Calc at Face (W/kg)
		1g-SAR	1g-SAR
LMR	136-174	1.64	1.54
	380-470	6.50	5.52
	450-520	6.08	4.48
	762-776	4.57	1.72
	792-825	5.41	2.37
	851-870	4.53	2.15
LTE	LTE B2	0.014	0.416
	LTE B4	0.033	0.325
	LTE B5	0.067	0.164
	LTE B12	0.034	0.160
	LTE B13	0.079	0.157
	LTE B14	0.098	0.186
	LTE B17	0.026	0.160
WLAN	2.4 GHz	0.054	0.262
	5 GHz	0.057	1.183
Highest Simultaneous Transmission SAR	Sum of SAR (W/kg)	6.60	5.58

The test results clearly demonstrate compliance with FCC Occupational/Controlled RF Exposure limits of 8.0 W/kg average over 1gram per the requirement of FCC 47 CFR § 2.1093 and ISED RSS-102 (Issue 5).

16.0 Measurement System Uncertainty

Uncertainty Budget for Device Under Test, for 150 MHz to 450 MHz

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e = f(d,k)</i>	<i>f</i>	<i>g</i>	<i>h = c x f / e</i>	<i>i = c x g / e</i>	<i>k</i>
Uncertainty Component	IEEE 1528 section	Tol. (± %)	Prob Dist	Div.	<i>c_i</i> (1 g)	<i>c_i</i> (10 g)	1 g <i>u_i</i> (±%)	10 g <i>u_i</i> (±%)	<i>v_i</i>
Measurement System									
Probe Calibration	E.2.1	6.7	N	1.00	1	1	6.7	6.7	∞
Axial Isotropy	E.2.2	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	E.2.2	9.6	R	1.73	0.707	0.707	3.9	3.9	∞
Boundary Effect	E.2.3	1.0	R	1.73	1	1	0.6	0.6	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	0.3	N	1.00	1	1	0.3	0.3	∞
Response Time	E.2.7	1.1	R	1.73	1	1	0.6	0.6	∞
Integration Time	E.2.8	1.1	R	1.73	1	1	0.6	0.6	∞
RF Ambient Conditions - Noise	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E.6.1	0.0	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mech. Tolerance	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning w.r.t Phantom	E.6.3	1.4	R	1.73	1	1	0.8	0.8	∞
Max. SAR Evaluation (ext., int., avg.)	E.5	3.4	R	1.73	1	1	2.0	2.0	∞
Test sample Related									
Test Sample Positioning	E.4.2	3.2	N	1.00	1	1	3.2	3.2	29
Device Holder Uncertainty	E.4.1	4.0	N	1.00	1	1	4.0	4.0	8
SAR drift	6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									
Phantom Uncertainty	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity (target)	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity (measurement)	E.3.3	3.3	N	1.00	0.64	0.43	2.1	1.4	∞
Liquid Permittivity (target)	E.3.2	5.0	R	1.73	0.6	0.49	1.7	1.4	∞
Liquid Permittivity (measurement)	E.3.3	1.9	N	1.00	0.6	0.49	1.1	0.9	∞
Combined Standard Uncertainty			RSS				12	11	482
Expanded Uncertainty (95% CONFIDENCE LEVEL)			<i>k</i> =2				23	23	

Notes for uncertainty budget Tables:

- a) Column headings *a-k* are given for reference.
- b) Tol. - tolerance in influence quantity.
- c) Prob. Dist. – Probability distribution
- d) N, R - normal, rectangular probability distributions
- e) Div. - divisor used to translate tolerance into normally distributed standard uncertainty
- f) *c_i* - sensitivity coefficient that should be applied to convert the variability of the uncertainty component into a variability of SAR.
- g) *u_i* – SAR uncertainty
- h) *v_i* - degrees of freedom for standard uncertainty and effective degrees of freedom for the expanded uncertainty

Uncertainty Budget for Device Under Test, for 750 MHz

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	$e = f(d,k)$	<i>f</i>	<i>g</i>	$h = c \times f / e$	$i = c \times g / e$	<i>k</i>
Uncertainty Component	IEEE 1528 section	Tol. (± %)	Prob Dist	Div.	c_i (1 g)	c_i (10 g)	1 g u_i (±%)	10 g u_i (±%)	v_i
Measurement System									
Probe Calibration	E.2.1	6.0	N	1.00	1	1	6.0	6.0	∞
Axial Isotropy	E.2.2	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	E.2.2	9.6	R	1.73	0.707	0.707	3.9	3.9	∞
Boundary Effect	E.2.3	1.0	R	1.73	1	1	0.6	0.6	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	0.3	N	1.00	1	1	0.3	0.3	∞
Response Time	E.2.7	1.1	R	1.73	1	1	0.6	0.6	∞
Integration Time	E.2.8	1.1	R	1.73	1	1	0.6	0.6	∞
RF Ambient Conditions - Noise	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E.6.1	0.0	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mech. Tolerance	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning w.r.t Phantom	E.6.3	1.4	R	1.73	1	1	0.8	0.8	∞
Max. SAR Evaluation (ext., int., avg.)	E.5	3.4	R	1.73	1	1	2.0	2.0	∞
Test sample Related									
Test Sample Positioning	E.4.2	3.2	N	1.00	1	1	3.2	3.2	29
Device Holder Uncertainty	E.4.1	4.0	N	1.00	1	1	4.0	4.0	8
SAR drift	6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									
Phantom Uncertainty	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity (target)	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity (measurement)	E.3.3	3.3	N	1.00	0.64	0.43	2.1	1.4	∞
Liquid Permittivity (target)	E.3.2	5.0	R	1.73	0.6	0.49	1.7	1.4	∞
Liquid Permittivity (measurement)	E.3.3	1.9	N	1.00	0.6	0.49	1.1	0.9	∞
Combined Standard Uncertainty			RSS				11	11	419
Expanded Uncertainty (95% CONFIDENCE LEVEL)			$k=2$				22	22	

Notes for uncertainty budget Tables:

- a) Column headings *a-k* are given for reference.
- b) Tol. - tolerance in influence quantity.
- c) Prob. Dist. – Probability distribution
- d) N, R - normal, rectangular probability distributions
- e) Div. - divisor used to translate tolerance into normally distributed standard uncertainty
- f) c_i - sensitivity coefficient that should be applied to convert the variability of the uncertainty component into a variability of SAR.
- g) u_i – SAR uncertainty
- h) v_i - degrees of freedom for standard uncertainty and effective degrees of freedom for the expanded uncertainty

Uncertainty Budget for Device Under Test, for 800 MHz to 3000 MHz

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	$e = f(d,k)$	<i>f</i>	<i>g</i>	$h = cxf/e$	$i = cxg/e$	<i>k</i>
Uncertainty Component	IEEE 1528 section	Tol. (± %)	Prob Dist	Div.	c_i (1 g)	c_i (10 g)	1 g u_i (±%)	10 g u_i (±%)	v_i
Measurement System									
Probe Calibration	E.2.1	6.0	N	1.00	1	1	6.0	6.0	∞
Axial Isotropy	E.2.2	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	E.2.2	9.6	R	1.73	0.707	0.707	3.9	3.9	∞
Boundary Effect	E.2.3	1.0	R	1.73	1	1	0.6	0.6	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	0.3	N	1.00	1	1	0.3	0.3	∞
Response Time	E.2.7	1.1	R	1.73	1	1	0.6	0.6	∞
Integration Time	E.2.8	1.1	R	1.73	1	1	0.6	0.6	∞
RF Ambient Conditions - Noise	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E.6.1	0.0	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mech. Tolerance	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning w.r.t Phantom	E.6.3	1.4	R	1.73	1	1	0.8	0.8	∞
Max. SAR Evaluation (ext., int., avg.)	E.5	3.4	R	1.73	1	1	2.0	2.0	∞
Test sample Related									
Test Sample Positioning	E.4.2	3.2	N	1.00	1	1	3.2	3.2	29
Device Holder Uncertainty	E.4.1	4.0	N	1.00	1	1	4.0	4.0	8
SAR drift	6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									
Phantom Uncertainty	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity (target)	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity (measurement)	E.3.3	3.3	N	1.00	0.64	0.43	2.1	1.4	∞
Liquid Permittivity (target)	E.3.2	5.0	R	1.73	0.6	0.49	1.7	1.4	∞
Liquid Permittivity (measurement)	E.3.3	1.9	N	1.00	0.6	0.49	1.1	0.9	∞
Combined Standard Uncertainty			RSS				11	11	419
Expanded Uncertainty (95% CONFIDENCE LEVEL)			$k=2$				22	22	

Notes for uncertainty budget Tables:

- a) Column headings *a-k* are given for reference.
- b) Tol. - tolerance in influence quantity.
- c) Prob. Dist. – Probability distribution
- d) N, R - normal, rectangular probability distributions
- e) Div. - divisor used to translate tolerance into normally distributed standard uncertainty
- f) c_i - sensitivity coefficient that should be applied to convert the variability of the uncertainty component into a variability of SAR.
- g) u_i – SAR uncertainty
- h) v_i - degrees of freedom for standard uncertainty and effective degrees of freedom for the expanded uncertainty

Uncertainty Budget for Device Under Test, for 5000 MHz to 5800 MHz

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e = f(d,k)</i>	<i>f</i>	<i>g</i>	<i>h = c x f / e</i>	<i>i = c x g / e</i>	<i>k</i>
Uncertainty Component	IEEE 1528 section	Tol. (± %)	Prob Dist	Div.	<i>c_i</i> (1 g)	<i>c_i</i> (10 g)	1 g <i>u_i</i> (±%)	10 g <i>u_i</i> (±%)	<i>v_i</i>
Measurement System									
Probe Calibration	E.2.1	6.6	N	1.00	1	1	6.6	6.6	∞
Axial Isotropy	E.2.2	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	E.2.2	9.6	R	1.73	0.707	0.707	3.9	3.9	∞
Boundary Effect	E.2.3	2.0	R	1.73	1	1	1.2	1.2	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	0.3	N	1.00	1	1	0.3	0.3	∞
Response Time	E.2.7	1.1	R	1.73	1	1	0.6	0.6	∞
Integration Time	E.2.8	1.1	R	1.73	1	1	0.6	0.6	∞
RF Ambient Conditions - Noise	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E.6.1	0.0	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mech. Tolerance	E.6.2	1.0	R	1.73	1	1	0.6	0.6	∞
Probe Positioning w.r.t Phantom	E.6.3	4.0	R	1.73	1	1	2.3	2.3	∞
Max. SAR Evaluation (ext., int., avg.)	E.5	2.1	R	1.73	1	1	1.2	1.2	∞
Test sample Related									
Test Sample Positioning	E.4.2	3.2	N	1.00	1	1	3.2	3.2	29
Device Holder Uncertainty	E.4.1	4.0	N	1.00	1	1	4.0	4.0	8
SAR drift	6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									
Phantom Uncertainty	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Dielectric Parameter Correction	--	1.4	N	1.00	1	0.79	1.4	1.1	∞
Liquid Conductivity (measurement)	E.3.3	3.3	N	1.00	0.64	0.43	2.1	1.4	∞
Liquid Permittivity (measurement)	E.3.3	1.9	N	1.00	0.6	0.49	1.1	0.9	∞
Combined Standard Uncertainty			RSS				11	11	465
Expanded Uncertainty (95% CONFIDENCE LEVEL)			<i>k</i> =2				23	23	

Notes for uncertainty budget Tables:

- a) Column headings *a-k* are given for reference.
- b) Tol. - tolerance in influence quantity.
- c) Prob. Dist. – Probability distribution
- d) N, R - normal, rectangular probability distributions
- e) Div. - divisor used to translate tolerance into normally distributed standard uncertainty
- f) *c_i* - sensitivity coefficient that should be applied to convert the variability of the uncertainty component into a variability of SAR.
- g) *u_i* – SAR uncertainty
- h) *v_i* - degrees of freedom for standard uncertainty and effective degrees of freedom for the expanded uncertainty

Uncertainty Budget for System Validation (dipole & flat phantom) for 150 MHz to 450 MHz

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e = f(d,k)</i>	<i>f</i>	<i>g</i>	<i>h = c x f / e</i>	<i>i = c x g / e</i>	<i>k</i>
Uncertainty Component	IEEE 1528 section	Tol. (± %)	Prob. Dist.	Div.	<i>c_i</i> (1 g)	<i>c_i</i> (10 g)	1 g <i>u_i</i> (±%)	10 g <i>u_i</i> (±%)	<i>v_i</i>
Measurement System									
Probe Calibration	E.2.1	6.7	N	1.00	1	1	6.7	6.7	∞
Axial Isotropy	E.2.2	4.7	R	1.73	1	1	2.7	2.7	∞
Spherical Isotropy	E.2.2	9.6	R	1.73	0	0	0.0	0.0	∞
Boundary Effect	E.2.3	1.0	R	1.73	1	1	0.6	0.6	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	0.3	N	1.00	1	1	0.3	0.3	∞
Response Time	E.2.7	1.1	R	1.73	1	1	0.6	0.6	∞
Integration Time	E.2.8	0.0	R	1.73	1	1	0.0	0.0	∞
RF Ambient Conditions - Noise	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E.6.1	0.0	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning w.r.t. Phantom	E.6.3	1.4	R	1.73	1	1	0.8	0.8	∞
Max. SAR Evaluation (ext., int., avg.)	E.5	3.4	R	1.73	1	1	2.0	2.0	∞
Dipole									
Dipole Axis to Liquid Distance	8, E.4.2	2.0	R	1.73	1	1	1.2	1.2	∞
Input Power and SAR Drift Measurement	8, 6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									
Phantom Uncertainty	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity (target)	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity (measurement)	E.3.3	3.3	R	1.73	0.64	0.43	1.2	0.8	∞
Liquid Permittivity (target)	E.3.2	5.0	R	1.73	0.6	0.49	1.7	1.4	∞
Liquid Permittivity (measurement)	E.3.3	1.9	R	1.73	0.6	0.49	0.6	0.5	∞
Combined Standard Uncertainty			RSS				10	9	99999
Expanded Uncertainty (95% CONFIDENCE LEVEL)			<i>k</i> =2				19	18	

Notes for uncertainty budget Tables:

- a) Column headings *a-k* are given for reference.
- b) Tol. - tolerance in influence quantity.
- c) Prob. Dist. – Probability distribution
- d) N, R - normal, rectangular probability distributions
- e) Div. - divisor used to translate tolerance into normally distributed standard uncertainty
- f) *c_i* - sensitivity coefficient that should be applied to convert the variability of the uncertainty component into a variability of SAR.
- g) *u_i* – SAR uncertainty
- h) *v_i* - degrees of freedom for standard uncertainty and effective degrees of freedom for the expanded uncertainty

Uncertainty Budget for System Validation (dipole & flat phantom) for 750 MHz

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e = f(d,k)</i>	<i>f</i>	<i>g</i>	<i>h = c x f / e</i>	<i>i = c x g / e</i>	<i>k</i>
Uncertainty Component	IEEE 1528 section	Tol. (± %)	Prob. Dist.	Div.	<i>c_i</i> (1 g)	<i>c_i</i> (10 g)	1 g <i>u_i</i> (±%)	10 g <i>u_i</i> (±%)	<i>v_i</i>
Measurement System									
Probe Calibration	E.2.1	6.0	N	1.00	1	1	6.0	6.0	∞
Axial Isotropy	E.2.2	4.7	R	1.73	1	1	2.7	2.7	∞
Spherical Isotropy	E.2.2	9.6	R	1.73	0	0	0.0	0.0	∞
Boundary Effect	E.2.3	1.0	R	1.73	1	1	0.6	0.6	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	0.3	N	1.00	1	1	0.3	0.3	∞
Response Time	E.2.7	1.1	R	1.73	1	1	0.6	0.6	∞
Integration Time	E.2.8	0.0	R	1.73	1	1	0.0	0.0	∞
RF Ambient Conditions - Noise	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E.6.1	0.0	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning w.r.t. Phantom	E.6.3	1.4	R	1.73	1	1	0.8	0.8	∞
Max. SAR Evaluation (ext., int., avg.)	E.5	3.4	R	1.73	1	1	2.0	2.0	∞
Dipole									
Dipole Axis to Liquid Distance	8, E.4.2	2.0	R	1.73	1	1	1.2	1.2	∞
Input Power and SAR Drift Measurement	8, 6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									
Phantom Uncertainty	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity (target)	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity (measurement)	E.3.3	3.3	R	1.73	0.64	0.43	1.2	0.8	∞
Liquid Permittivity (target)	E.3.2	5.0	R	1.73	0.6	0.49	1.7	1.4	∞
Liquid Permittivity (measurement)	E.3.3	1.9	R	1.73	0.6	0.49	0.6	0.5	∞
Combined Standard Uncertainty			RSS				9	9	99999
Expanded Uncertainty (95% CONFIDENCE LEVEL)			<i>k</i> =2				18	17	

Notes for uncertainty budget Tables:

- a) Column headings *a-k* are given for reference.
- b) Tol. - tolerance in influence quantity.
- c) Prob. Dist. – Probability distribution
- d) N, R - normal, rectangular probability distributions
- e) Div. - divisor used to translate tolerance into normally distributed standard uncertainty
- f) *c_i* - sensitivity coefficient that should be applied to convert the variability of the uncertainty component into a variability of SAR.
- g) *u_i* – SAR uncertainty
- h) *v_i* - degrees of freedom for standard uncertainty and effective degrees of freedom for the expanded uncertainty

Uncertainty Budget for System Validation (dipole & flat phantom) for 150 MHz to 450 MHz

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	$e = f(d,k)$	<i>f</i>	<i>g</i>	$h = c \times f / e$	$i = c \times g / e$	<i>k</i>
Uncertainty Component	IEEE 1528 section	Tol. (± %)	Prob. Dist.	Div.	c_i (1 g)	c_i (10 g)	1 g u_i (±%)	10 g u_i (±%)	v_i
Measurement System									
Probe Calibration	E.2.1	6.0	N	1.00	1	1	6.0	6.0	∞
Axial Isotropy	E.2.2	4.7	R	1.73	1	1	2.7	2.7	∞
Spherical Isotropy	E.2.2	9.6	R	1.73	0	0	0.0	0.0	∞
Boundary Effect	E.2.3	1.0	R	1.73	1	1	0.6	0.6	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	0.3	N	1.00	1	1	0.3	0.3	∞
Response Time	E.2.7	1.1	R	1.73	1	1	0.6	0.6	∞
Integration Time	E.2.8	0.0	R	1.73	1	1	0.0	0.0	∞
RF Ambient Conditions - Noise	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E.6.1	0.0	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning w.r.t. Phantom	E.6.3	1.4	R	1.73	1	1	0.8	0.8	∞
Max. SAR Evaluation (ext., int., avg.)	E.5	3.4	R	1.73	1	1	2.0	2.0	∞
Dipole									
Dipole Axis to Liquid Distance	8, E.4.2	2.0	R	1.73	1	1	1.2	1.2	∞
Input Power and SAR Drift Measurement	8, 6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									
Phantom Uncertainty	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity (target)	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity (measurement)	E.3.3	3.3	R	1.73	0.64	0.43	1.2	0.8	∞
Liquid Permittivity (target)	E.3.2	5.0	R	1.73	0.6	0.49	1.7	1.4	∞
Liquid Permittivity (measurement)	E.3.3	1.9	R	1.73	0.6	0.49	0.6	0.5	∞
Combined Standard Uncertainty			RSS				9	9	99999
Expanded Uncertainty (95% CONFIDENCE LEVEL)			$k=2$				18	17	

Notes for uncertainty budget Tables:

- a) Column headings *a-k* are given for reference.
- b) Tol. - tolerance in influence quantity.
- c) Prob. Dist. – Probability distribution
- d) N, R - normal, rectangular probability distributions
- e) Div. - divisor used to translate tolerance into normally distributed standard uncertainty
- f) c_i - sensitivity coefficient that should be applied to convert the variability of the uncertainty component into a variability of SAR.
- g) u_i – SAR uncertainty
- h) v_i - degrees of freedom for standard uncertainty and effective degrees of freedom for the expanded uncertainty

Uncertainty Budget for System Validation (dipole & flat phantom) for 5000 MHz to 5800 MHz

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e = f(d,k)</i>	<i>f</i>	<i>g</i>	<i>h = c x f / e</i>	<i>i = c x g / e</i>	<i>k</i>
Uncertainty Component	IEEE 1528 section	Tol. (± %)	Prob. Dist.	Div.	<i>c_i</i> (1 g)	<i>c_i</i> (10 g)	1 g <i>u_i</i> (±%)	10 g <i>u_i</i> (±%)	<i>v_i</i>
Measurement System									
Probe Calibration	E.2.1	6.6	N	1.00	1	1	6.6	6.6	∞
Axial Isotropy	E.2.2	4.7	R	1.73	1	1	2.7	2.7	∞
Spherical Isotropy	E.2.2	9.6	R	1.73	0	0	0.0	0.0	∞
Boundary Effect	E.2.3	2.0	R	1.73	1	1	1.2	1.2	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	0.3	N	1.00	1	1	0.3	0.3	∞
Response Time	E.2.7	1.1	R	1.73	1	1	0.6	0.6	∞
Integration Time	E.2.8	0.0	R	1.73	1	1	0.0	0.0	∞
RF Ambient Conditions - Noise	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E.6.1	0.0	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mechanical Tolerance	E.6.2	1.0	R	1.73	1	1	0.6	0.6	∞
Probe Positioning w.r.t. Phantom	E.6.3	4.0	R	1.73	1	1	2.3	2.3	∞
Max. SAR Evaluation (ext., int., avg.)	E.5	2.1	R	1.73	1	1	1.2	1.2	∞
Dipole									
Dipole Axis to Liquid Distance	8, E.4.2	2.0	R	1.73	1	1	1.2	1.2	∞
Input Power and SAR Drift Measurement	8, 6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									
Phantom Uncertainty	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Dielectric Parameter Correction	--	1.4	N	1.00	1	0.79	1.4	1.1	∞
Liquid Conductivity (measurement)	E.3.3	3.3	R	1.73	0.64	0.43	1.2	0.8	∞
Liquid Permittivity (measurement)	E.3.3	1.9	R	1.73	0.6	0.49	0.6	0.5	∞
Combined Standard Uncertainty							9	9	99999
Expanded Uncertainty (95% CONFIDENCE LEVEL)							19	18	

Notes for uncertainty budget Tables:

- a) Column headings *a-k* are given for reference.
- b) Tol. - tolerance in influence quantity.
- c) Prob. Dist. – Probability distribution
- d) N, R - normal, rectangular probability distributions
- e) Div. - divisor used to translate tolerance into normally distributed standard uncertainty
- f) *c_i* - sensitivity coefficient that should be applied to convert the variability of the uncertainty component into a variability of SAR.
- g) *u_i* – SAR uncertainty
- h) *v_i* - degrees of freedom for standard uncertainty and effective degrees of freedom for the expanded uncertainty