



BUREAU VERITAS

Test Report No.: RF2009WDG0079-2



TEST REPORT

Applicant	Motorola Solutions Inc.
Address	8000 West Sunrise Boulevard, Plantation, FL 33322, United States

Manufacturer or Supplier	Motorola Solutions
Address	16 Forth Street, Edinburgh, EH1 3LH, United Kingdom
Product	VB400
Brand Name	Motorola Solutions
Model	VB400
Additional Model & Model Difference	N/A
Date of tests	Sep. 08, 2020 ~ Oct. 19, 2020

The tests have been carried out according to the requirements of the following standard:

FCC Part 15, Subpart C, Section 15.247

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Lucas Chen
Project Engineer / EMC Department

Approved by Glyn He
Assistant Manager / EMC Department

Date: Dec. 08, 2020

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD 4

1 SUMMARY OF TEST RESULTS..... 5

2 MEASUREMENT UNCERTAINTY 5

3 GENERAL INFORMATION 6

3.1 GENERAL DESCRIPTION OF EUT..... 6

3.2 DESCRIPTION OF TEST MODES..... 8

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST 9

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... 9

3.3 DUTY CYCLE OF TEST SIGNAL11

3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS..... 12

3.5 DESCRIPTION OF SUPPORT UNITS..... 12

4 TEST TYPES AND RESULTS..... 13

4.1 RADIATED EMISSION MEASUREMENT 13

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT 13

4.1.2 TEST INSTRUMENTS..... 14

4.1.3 TEST PROCEDURES 15

4.1.4 DEVIATION FROM TEST STANDARD 16

4.1.5 TEST SETUP..... 16

4.1.6 EUT OPERATING CONDITIONS 17

4.1.7 TEST RESULTS 18

4.2 6DB BANDWIDTH MEASUREMENT..... 32

4.2.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT 32

4.2.2 TEST INSTRUMENTS..... 32

4.2.3 TEST PROCEDURE..... 32

4.2.4 DEVIATION FROM TEST STANDARD 33

4.2.5 TEST SETUP..... 33

4.2.6 EUT OPERATING CONDITIONS 33

4.2.7 TEST RESULTS 34

4.3 CONDUCTED OUTPUT POWER..... 39

4.3.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT 39

4.3.2 TEST SETUP..... 39

4.3.3 TEST INSTRUMENTS..... 39

4.3.4 TEST PROCEDURES 40

4.3.5 DEVIATION FROM TEST STANDARD 40

4.3.6 EUT OPERATING CONDITIONS 40



4.3.7 TEST RESULTS 41

4.4 POWER SPECTRAL DENSITY MEASUREMENT 43

4.4.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 43

4.4.2 TEST SETUP 43

4.4.3 TEST INSTRUMENTS 43

4.4.4 TEST PROCEDURE 43

4.4.5 DEVIATION FROM TEST STANDARD 43

4.4.6 EUT OPERATING CONDITION 44

4.4.7 TEST RESULTS 44

4.5 OUT OF BAND EMISSION MEASUREMENT 46

4.5.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT 46

4.5.2 TEST SETUP 46

4.5.3 TEST INSTRUMENTS 46

4.5.4 TEST PROCEDURE 46

4.5.5 DEVIATION FROM TEST STANDARD 47

4.5.6 EUT OPERATING CONDITION 47

4.5.7 TEST RESULTS 48

5 PHOTOGRAPHS OF THE TEST CONFIGURATION 54

**6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT
BY THE LAB 55**



BUREAU
VERITAS

Test Report No.: RF2009WDG0079-2

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF2009WDG0079-2	Original release	Dec. 08, 2020



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	N/A	Powered by Battery
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	9KHz ~ 30MHz	2.16dB
	30MHz ~ 1GMHz	3.60dB
	1GHz ~ 18GHz	4.82dB
	18GHz ~ 40GHz	5.00dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	VB400
MODEL NO.	VB400
ADDITIONAL NO.	N/A
FCC ID	AZ489FT7142
NOMINAL VOLTAGE	DC 3.8V Supplied by Li-ion Battery, DC 5V Charged by the Solo Docking Station
MODULATION TECHNOLOGY	DSSS, OFDM
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
OPERATING FREQUENCY	2412 ~ 2462MHz for 11b/g/n(HT20) 2422 ~ 2452MHz for 11n(HT40)
PEAK OUTPUT POWER	22.84dBm(Maximum)
ANTENNA TYPE	PCB Antenna, with 0.71dBi gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB cable : Shielded, detachable, 1.0m

NOTE:

1. The EUT incorporates a SISO function. Physically, the EUT provides 1 completed transmitter and 1 receiver.

MODULATION MODE	FUNCTION
802.11b	1TX
802.11g	1TX
802.11n (HT20)	1TX
802.11n (HT40)	1TX

2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
4. Please refer to the EUT photo document (Reference No.: 2009WDG0079) for detailed product photo.
5. When the EUT charging that wireless function can't working, the charging mode was tested in the FCC SDoc report.(report no.: FS2009WDG0079).



6. The EUT has two RF modules, specific RF functions are as follows:

Module	RF Function
Redpine RS9116	BT_EDR
	WIFI 2.4GHz
	WIFI 5GHz(Band 1,2)
MS50SF3_52832	BTLE



3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		



3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on X axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	-	√	Powered by Fully Battery with WIFI Link

Where **RE<1G**: Radiated Emission below 1GHz **RE≥1G**: Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1	DSSS	DBPSK	1.0

RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
-	802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	13.5



BANDEDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
-	802.11n HT20	1 to 11	1, 11	OFDM	BPSK	6.5
-	802.11n HT40	3 to 9	3, 9	OFDM	BPSK	13.5

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
-	802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	13.5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	23deg. C, 53%RH	DC 3.8V from Fully Battery	Vincent
RE≥1G	23deg. C, 53%RH	DC 3.8V from Fully Battery	Vincent
PLC	N/A	N/A	N/A
APCM	20deg. C, 55%RH	DC 3.8V from Fully Battery	Daniel



BUREAU VERITAS

Test Report No.: RF2009WDG0079-2


3.3 DUTY CYCLE OF TEST SIGNAL

802.11b: Duty cycle = 100%

802.11g: Duty cycle = 100%

802.11n (HT20): Duty cycle = 100%

802.11n (HT40): Duty cycle = 100%





3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 15.247 Meas Guidance v05r02

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together without other necessary accessories or support units.



4 TEST TYPES AND RESULTS

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTES:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Mar. 11,21
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Aug. 01,21
Active Loop Antenna (9KHz -30MHz)	SCHWARZBECK	FMZB 1519B	1519B-045	May 03,21
Amplifier (9KHz -1GHz)	Burgeon	BPA-530	100210	Apr. 18,21
Bilog Antenna (20MHz -2GHz)	Teseq	CBL 6111D	30643	Aug. 10, 21
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	Jul. 20, 21
Horn Antenna (18GHz -40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170242	May 04,21
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Feb. 09,21
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A
Broadband Preamplifier (1GHz~18GHz)	SCHWARZBECK	BBV9718	305	Apr. 18,21
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 08,20
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A

NOTES:

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 749762.



4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters (above 1GHz) and 0.8 meters (below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. For below 1GHz was used bilog antenna, and above 1GHz was used horn antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.
- g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTES:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes, the worst-case test configuration was reported on the file test setup photo.




4.1.4 DEVIATION FROM TEST STANDARD


No deviation.

4.1.5 TEST SETUP

Below 30MHz test setup




Below 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).



Above 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- Placed the EUT on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



4.1.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:


802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.00	18.61 QP	40.00	-21.39	1.00 H	235	28.71	-10.10
2	145.03	14.19 QP	43.50	-29.31	1.00 H	98	30.26	-16.07
3	297.37	17.65 QP	46.00	-28.35	1.00 H	114	30.44	-12.79
4	399.97	20.43 QP	46.00	-25.57	1.00 H	216	29.81	-9.38
5	494.79	21.71 QP	46.00	-24.29	1.00 H	59	29.53	-7.82
6	550.75	24.50 QP	46.00	-21.50	1.00 H	301	30.62	-6.12

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value






CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.00	19.42 QP	40.00	-20.58	1.00 V	152	29.52	-10.10
2	141.92	16.24 QP	43.50	-27.26	1.00 V	325	32.22	-15.98
3	350.22	18.18 QP	46.00	-27.82	1.00 V	251	28.85	-10.67
4	406.19	20.19 QP	46.00	-25.81	1.00 V	85	29.46	-9.27
5	477.69	21.86 QP	46.00	-24.14	1.00 V	112	30.00	-8.14
6	584.95	23.50 QP	46.00	-22.50	1.00 V	164	29.44	-5.94

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value





ABOVE 1GHZ DATA

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	43.75 PK	74.00	-30.25	1.00 H	0	41.46	2.29
2	2390.00	31.48 AV	54.00	-22.52	1.00 H	0	29.19	2.29
3	*2412.00	99.35 PK			1.00 H	0	96.91	2.44
4	*2412.00	95.45 AV			1.00 H	0	93.01	2.44
5	4824.00	51.59 PK	74.00	-22.41	1.00 H	0	46.47	5.12
6	4824.00	45.73 AV	54.00	-8.27	1.00 H	0	40.61	5.12
7	#7236.00	51.71 PK	74.00	-22.29	1.00 H	0	42.37	9.34
8	#7236.00	37.44 AV	54.00	-16.56	1.00 H	0	28.10	9.34

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	42.48 PK	74.00	-31.52	1.00 V	229	40.19	2.29
2	2390.00	30.38 AV	54.00	-23.62	1.00 V	229	28.09	2.29
3	*2412.00	96.31 PK			1.00 V	229	93.87	2.44
4	*2412.00	92.08 AV			1.00 V	229	89.64	2.44
5	4824.00	49.20 PK	74.00	-24.80	1.00 V	0	44.08	5.12
6	4824.00	40.11 AV	54.00	-13.89	1.00 V	0	34.99	5.12
7	#7236.00	51.48 PK	74.00	-22.52	1.00 V	0	42.14	9.34
8	#7236.00	36.77 AV	54.00	-17.23	1.00 V	0	27.43	9.34

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	100.82 PK			1.00 H	275	98.21	2.61
2	*2437.00	97.04 AV			1.00 H	275	94.43	2.61
3	4874.00	50.39 PK	74.00	-23.61	1.00 H	0	45.15	5.24
4	4874.00	41.06 AV	54.00	-12.94	1.00 H	0	35.82	5.24
5	7311.00	51.96 PK	74.00	-22.04	1.00 H	0	42.52	9.44
6	7311.00	37.84 AV	54.00	-16.16	1.00 H	0	28.40	9.44
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	93.95 PK			1.00 V	229	91.34	2.61
2	*2437.00	90.22 AV			1.00 V	229	87.61	2.61
3	4874.00	49.87 PK	74.00	-24.13	1.00 V	0	44.63	5.24
4	4874.00	40.36 AV	54.00	-13.64	1.00 V	0	35.12	5.24
5	7311.00	51.63 PK	74.00	-22.37	1.00 V	0	42.19	9.44
6	7311.00	37.35 AV	54.00	-16.65	1.00 V	0	27.91	9.44

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	100.76 PK			1.00 H	353	97.97	2.79
2	*2462.00	96.95 AV			1.00 H	353	94.16	2.79
3	2483.50	48.69 PK	74.00	-25.31	1.00 H	353	45.76	2.93
4	2483.50	34.51 AV	54.00	-19.49	1.00 H	353	31.58	2.93
5	4924.00	51.46 PK	74.00	-22.54	1.00 H	0	46.09	5.37
6	4924.00	46.13 AV	54.00	-7.87	1.00 H	0	40.76	5.37
7	7386.00	52.01 PK	74.00	-21.99	1.00 H	0	42.48	9.53
8	7386.00	38.34 AV	54.00	-15.66	1.00 H	0	28.81	9.53

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	94.49 PK			1.00 V	229	91.70	2.79
2	*2462.00	90.50 AV			1.00 V	229	87.71	2.79
3	2483.50	47.86 PK	74.00	-26.14	1.00 V	229	44.93	2.93
4	2483.50	35.19 AV	54.00	-18.81	1.00 V	229	32.26	2.93
5	4924.00	50.11 PK	74.00	-23.89	1.00 V	0	44.74	5.37
6	4924.00	40.57 AV	54.00	-13.43	1.00 V	0	35.20	5.37
7	7386.00	51.33 PK	74.00	-22.67	1.00 V	0	41.80	9.53
8	7386.00	37.14 AV	54.00	-16.86	1.00 V	0	27.61	9.53

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. "*" : Fundamental frequency.



802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.02 PK	74.00	-7.98	1.00 H	274	63.73	2.29
2	2390.00	49.10 AV	54.00	-4.90	1.00 H	274	46.81	2.29
3	*2412.00	104.63 PK			1.00 H	274	102.19	2.44
4	*2412.00	93.63 AV			1.00 H	274	91.19	2.44
5	4824.00	50.74 PK	74.00	-23.26	1.00 H	0	45.62	5.12
6	4824.00	45.36 AV	54.00	-8.64	1.00 H	0	40.24	5.12
7	#7236.00	52.01 PK	74.00	-21.99	1.00 H	0	42.67	9.34
8	#7236.00	38.31 AV	54.00	-15.69	1.00 H	0	28.97	9.34

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.03 PK	74.00	-17.97	1.00 V	121	53.74	2.29
2	2390.00	39.36 AV	54.00	-14.64	1.00 V	121	37.07	2.29
3	*2412.00	95.71 PK			1.00 V	121	93.27	2.44
4	*2412.00	84.61 AV			1.00 V	121	82.17	2.44
5	4824.00	49.36 PK	74.00	-24.64	1.00 V	0	44.24	5.12
6	4824.00	41.05 AV	54.00	-12.95	1.00 V	0	35.93	5.12
7	#7236.00	51.72 PK	74.00	-22.28	1.00 V	0	42.38	9.34
8	#7236.00	37.87 AV	54.00	-16.13	1.00 V	0	28.53	9.34

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	104.14 PK			1.00 H	304	101.53	2.61
2	*2437.00	93.05 AV			1.00 H	304	90.44	2.61
3	4874.00	51.85 PK	74.00	-22.15	1.00 H	0	46.61	5.24
4	4874.00	41.30 AV	54.00	-12.70	1.00 H	0	36.06	5.24
5	7311.00	52.10 PK	74.00	-21.90	1.00 H	0	42.66	9.44
6	7311.00	38.74 AV	54.00	-15.26	1.00 H	0	29.30	9.44
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	97.66 PK			1.00 V	230	95.05	2.61
2	*2437.00	86.43 AV			1.00 V	230	83.82	2.61
3	4874.00	50.23 PK	74.00	-23.77	1.00 V	0	44.99	5.24
4	4874.00	40.30 AV	54.00	-13.70	1.00 V	0	35.06	5.24
5	7311.00	51.47 PK	74.00	-22.53	1.00 V	0	42.03	9.44
6	7311.00	37.12 AV	54.00	-16.88	1.00 V	0	27.68	9.44

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	103.01 PK			1.00 H	353	100.22	2.79
2	*2462.00	91.79 AV			1.00 H	353	89.00	2.79
3	2483.50	62.75 PK	74.00	-11.25	1.00 H	353	59.82	2.93
4	2483.50	45.91 AV	54.00	-8.09	1.00 H	353	42.98	2.93
5	4924.00	52.74 PK	74.00	-21.26	1.00 H	0	47.37	5.37
6	4924.00	46.31 AV	54.00	-7.69	1.00 H	0	40.94	5.37
7	7386.00	52.83 PK	74.00	-21.17	1.00 H	0	43.30	9.53
8	7386.00	41.35 AV	54.00	-12.65	1.00 H	0	31.82	9.53

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	98.28 PK			1.00 V	229	95.49	2.79
2	*2462.00	86.72 AV			1.00 V	229	83.93	2.79
3	2483.50	54.25 PK	74.00	-19.75	1.00 V	229	51.32	2.93
4	2483.50	40.90 AV	54.00	-13.10	1.00 V	229	37.97	2.93
5	4924.00	51.54 PK	74.00	-22.46	1.00 V	0	46.17	5.37
6	4924.00	45.91 AV	54.00	-8.09	1.00 V	0	40.54	5.37
7	7386.00	51.71 PK	74.00	-22.29	1.00 V	0	42.18	9.53
8	7386.00	40.78 AV	54.00	-13.22	1.00 V	0	31.25	9.53

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



802.11n HT20

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.12 PK	74.00	-4.88	1.55 H	330	66.83	2.29
2	2390.00	50.61 AV	54.00	-3.39	1.55 H	330	48.32	2.29
3	*2412.00	105.67 PK			1.55 H	330	103.23	2.44
4	*2412.00	93.53 AV			1.55 H	330	91.09	2.44
5	4824.00	51.21 PK	74.00	-22.79	1.00 H	0	46.09	5.12
6	4824.00	45.57 AV	54.00	-8.43	1.00 H	0	40.45	5.12
7	#7236.00	51.06 PK	74.00	-22.94	1.00 H	0	41.72	9.34
8	#7236.00	40.04 AV	54.00	-13.96	1.00 H	0	30.70	9.34
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.43 PK	74.00	-15.57	1.00 V	99	56.14	2.29
2	2390.00	41.55 AV	54.00	-12.45	1.00 V	99	39.26	2.29
3	*2412.00	95.55 PK			1.00 V	99	93.11	2.44
4	*2412.00	83.62 AV			1.00 V	99	81.18	2.44
5	4824.00	51.07 PK	74.00	-22.93	1.00 V	0	45.95	5.12
6	4824.00	45.18 AV	54.00	-8.82	1.00 V	0	40.06	5.12
7	#7236.00	51.36 PK	74.00	-22.64	1.00 V	0	42.02	9.34
8	#7236.00	40.12 AV	54.00	-13.88	1.00 V	0	30.78	9.34

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	104.24 PK			2.17 H	275	101.63	2.61
2	*2437.00	91.57 AV			2.17 H	275	88.96	2.61
3	4874.00	51.27 PK	74.00	-22.73	1.00 H	0	46.03	5.24
4	4874.00	45.78 AV	54.00	-8.22	1.00 H	0	40.54	5.24
5	7311.00	51.01 PK	74.00	-22.99	1.00 H	0	41.57	9.44
6	7311.00	40.19 AV	54.00	-13.81	1.00 H	0	30.75	9.44
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	97.95 PK			2.09 V	229	95.34	2.61
2	*2437.00	85.72 AV			2.09 V	229	83.11	2.61
3	4874.00	51.37 PK	74.00	-22.63	1.00 V	0	46.13	5.24
4	4874.00	45.12 AV	54.00	-8.88	1.00 V	0	39.88	5.24
5	7311.00	51.57 PK	74.00	-22.43	1.00 V	0	42.13	9.44
6	7311.00	40.08 AV	54.00	-13.92	1.00 V	0	30.64	9.44

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	104.88 PK			1.92 H	347	102.09	2.79
2	*2462.00	92.62 AV			1.92 H	347	89.83	2.79
3	2483.50	62.54 PK	74.00	-11.46	1.92 H	347	59.61	2.93
4	2483.50	47.49 AV	54.00	-6.51	1.92 H	347	44.56	2.93
5	4924.00	51.62 PK	74.00	-22.38	1.00 H	0	46.25	5.37
6	4924.00	45.17 AV	54.00	-8.83	1.00 H	0	39.80	5.37
7	7386.00	51.07 PK	74.00	-22.93	1.00 H	0	41.54	9.53
8	7386.00	40.14 AV	54.00	-13.86	1.00 H	0	30.61	9.53

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	97.18 PK			1.60 V	123	94.39	2.79
2	*2462.00	84.92 AV			1.60 V	123	82.13	2.79
3	2483.50	54.80 PK	74.00	-19.20	1.60 V	123	51.87	2.93
4	2483.50	39.40 AV	54.00	-14.60	1.60 V	123	36.47	2.93
5	4924.00	51.24 PK	74.00	-22.76	1.00 V	0	45.87	5.37
6	4924.00	45.75 AV	54.00	-8.25	1.00 V	0	40.38	5.37
7	7386.00	51.71 PK	74.00	-22.29	1.00 V	0	42.18	9.53
8	7386.00	40.69 AV	54.00	-13.31	1.00 V	0	31.16	9.53

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. "*" : Fundamental frequency.



802.11n HT40

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	50.40 PK	74.00	-23.60	1.95 H	328	48.11	2.29
2	2390.00	37.94 AV	54.00	-16.06	1.95 H	328	35.65	2.29
3	*2422.00	91.05 PK			1.95 H	328	88.54	2.51
4	*2422.00	79.13 AV			1.95 H	328	76.62	2.51
5	4844.00	51.59 PK	74.00	-22.41	1.00 H	0	46.42	5.17
6	4844.00	45.17 AV	54.00	-8.83	1.00 H	0	40.00	5.17
7	7266.00	51.09 PK	74.00	-22.91	1.00 H	0	41.70	9.39
8	7266.00	40.14 AV	54.00	-13.86	1.00 H	0	30.75	9.39
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	45.73 PK	74.00	-28.27	1.73 V	230	43.44	2.29
2	2390.00	32.27 AV	54.00	-21.73	1.73 V	230	29.98	2.29
3	*2422.00	84.42 PK			1.73 V	230	81.91	2.51
4	*2422.00	71.80 AV			1.73 V	230	69.29	2.51
5	4844.00	51.07 PK	74.00	-22.93	1.00 V	0	45.90	5.17
6	4844.00	44.98 AV	54.00	-9.02	1.00 V	0	39.81	5.17
7	7266.00	51.34 PK	74.00	-22.66	1.00 V	0	41.95	9.39
8	7266.00	40.85 AV	54.00	-13.15	1.00 V	0	31.46	9.39

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	90.10 PK			2.16 H	275	87.49	2.61
2	*2437.00	77.75 AV			2.16 H	275	75.14	2.61
3	4874.00	51.64 PK	74.00	-22.36	1.00 H	0	46.40	5.24
4	4874.00	45.17 AV	54.00	-8.83	1.00 H	0	39.93	5.24
5	7311.00	51.09 PK	74.00	-22.91	1.00 H	0	41.65	9.44
6	7311.00	40.11 AV	54.00	-13.89	1.00 H	0	30.67	9.44
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	83.59 PK			1.45 V	229	80.98	2.61
2	*2437.00	70.62 AV			1.45 V	229	68.01	2.61
3	4874.00	50.18 PK	74.00	-23.82	1.00 V	0	44.94	5.24
4	4874.00	44.06 AV	54.00	-9.94	1.00 V	0	38.82	5.24
5	7311.00	51.19 PK	74.00	-22.81	1.00 V	0	41.75	9.44
6	7311.00	40.25 AV	54.00	-13.75	1.00 V	0	30.81	9.44

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	90.20 PK			1.90 H	347	87.48	2.72
2	*2452.00	77.79 AV			1.90 H	347	75.07	2.72
3	2483.50	45.89 PK	74.00	-28.11	1.90 H	347	42.96	2.93
4	2483.50	33.31 AV	54.00	-20.69	1.90 H	347	30.38	2.93
5	4904.00	51.18 PK	74.00	-22.82	1.00 H	0	45.86	5.32
6	4904.00	45.37 AV	54.00	-8.63	1.00 H	0	40.05	5.32
7	7356.00	51.21 PK	74.00	-22.79	1.00 H	0	41.72	9.49
8	7356.00	40.06 AV	54.00	-13.94	1.00 H	0	30.57	9.49

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	81.85 PK			1.01 V	81	79.13	2.72
2	*2452.00	69.12 AV			1.01 V	81	66.40	2.72
3	2483.50	43.54 PK	74.00	-30.46	1.01 V	81	40.61	2.93
4	2483.50	31.11 AV	54.00	-22.89	1.01 V	81	28.18	2.93
5	4904.00	50.87 PK	74.00	-23.13	1.00 V	0	45.55	5.32
6	4904.00	45.16 AV	54.00	-8.84	1.00 V	0	39.84	5.32
7	7356.00	51.66 PK	74.00	-22.34	1.00 V	0	42.17	9.49
8	7356.00	40.16 AV	54.00	-13.84	1.00 V	0	30.67	9.49

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



4.2 6dB BANDWIDTH MEASUREMENT

4.2.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	Jun. 12,21
Power Sensor	Keysight	U2021XA	MY55060018	Jun. 12,21
Power Meter	Anritsu	ML2495A	1139001	Mar. 11,21
Power Sensor	Anritsu	MA2411B	1531155	Mar. 11,21
Digital Multimeter	FLUKE	15B	A1220010DG	Oct.16, 21
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Nov. 14,20
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 08,20
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Aug. 01,21
Signal Generator	Agilent	N5183A	MY50140980	Dec. 06,20
Agile Signal Generator	Agilent	8645A	Agilent	Oct.26, 20
Spectrum Analyzer	Keysight	N9020A	MY55400499	Mar. 11,21
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Dec. 06, 20
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Jul. 05, 21
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A
DC Source	Keysight	E3642A	MY56146098	N/A

NOTES:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.2.3 TEST PROCEDURE


1. Set resolution bandwidth (RBW) = 100KHz
2. Set the video bandwidth (VBW) ≥ 3 x RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



4.2.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.2.7 TEST RESULTS

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	8.55	0.5	PASS
6	2437	8.11	0.5	PASS
11	2462	8.11	0.5	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.63	0.5	PASS
6	2437	16.50	0.5	PASS
11	2462	16.61	0.5	PASS

802.11n HT20

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.79	0.5	PASS
6	2437	17.77	0.5	PASS
11	2462	17.70	0.5	PASS

802.11n HT40

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
3	2422	36.54	0.5	PASS
6	2437	36.54	0.5	PASS
9	2452	36.55	0.5	PASS




BUREAU VERITAS


Test Report No.: RF2009WDG0079-2

SPECTRUM PLOT OF 6dB BANDWIDTH


802.11b_CH1



802.11b_CH6




802.11b_CH11





BUREAU VERITAS

Test Report No.: RF2009WDG0079-2



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch


No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province, 523942, People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



BUREAU VERITAS

Test Report No.: RF2009WDG0079-2



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch


No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province, 523942, People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



BUREAU VERITAS

Test Report No.: RF2009WDG0079-2



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province, 523942, People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com




4.3 CONDUCTED OUTPUT POWER

4.3.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm).

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	Jun. 12,21
Power Sensor	Keysight	U2021XA	MY55060018	Jun. 12,21
Power Meter	Anritsu	ML2495A	1139001	Mar. 11,21
Power Sensor	Anritsu	MA2411B	1531155	Mar. 11,21
Digital Multimeter	FLUKE	15B	A1220010DG	Oct.16, 21
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Nov. 14,20
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 08,20
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Aug. 01,21
Signal Generator	Agilent	N5183A	MY50140980	Dec. 06,20
Agile Signal Generator	Agilent	8645A	Agilent	Oct.26, 20
Spectrum Analyzer	Keysight	N9020A	MY55400499	Mar. 11,21
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Dec. 06, 20
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Jul. 05, 21
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A
DC Source	Keysight	E3642A	MY56146098	N/A

NOTES:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



4.3.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A peak power meter was used to read the response of the peak power sensor. Record the peak power level.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.3.7 TEST RESULTS

MAXIMUM PEAK OUTPUT POWER

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
1	2412	16.00	39.811	1	PASS
6	2437	17.78	59.979	1	PASS
11	2462	16.07	40.458	1	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
1	2412	16.89	48.865	1	PASS
6	2437	22.84	192.309	1	PASS
11	2462	18.58	72.111	1	PASS

802.11n HT20

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
1	2412	17.95	62.373	1	PASS
6	2437	22.56	180.302	1	PASS
11	2462	20.01	100.231	1	PASS

802.11n HT40

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
3	2422	11.78	15.066	1	PASS
6	2437	10.61	11.508	1	PASS
9	2452	10.12	10.28	1	PASS



AVERAGE OUTPUT POWER (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)
1	2412	13.67	23.281
6	2437	14.47	27.990
11	2462	12.49	17.742

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)
1	2412	9.17	8.260
6	2437	15.13	32.584
11	2462	10.89	12.274

802.11n HT20

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)
1	2412	9.43	8.770
6	2437	13.86	24.322
11	2462	10.80	12.023

802.11n HT40

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)
3	2422	2.71	1.866
6	2437	2.36	1.722
9	2452	1.61	1.449




4.4 POWER SPECTRAL DENSITY MEASUREMENT

4.4.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.4.4 TEST PROCEDURE

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to 1.5 times the DTS bandwidth.
- c) Set RBW to: 3KHz
- d) Set VBW $\geq 3 \times$ RBW.
- e) Detector = peak
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times$ span/RBW.
- g) Sweep time = auto couple.
- h) Use the peak marker function to determine the maximum amplitude level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.



4.4.6 EUT OPERATING CONDITION

Same as item 4.3.6.

4.4.7 TEST RESULTS

802.11b

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-8.46	8.00	PASS
6	2437	-5.90	8.00	PASS
11	2462	-9.74	8.00	PASS

802.11g

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-15.80	8.00	PASS
6	2437	-11.06	8.00	PASS
11	2462	-13.70	8.00	PASS

802.11n HT20

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-16.62	8.00	PASS
6	2437	-12.15	8.00	PASS
11	2462	-13.20	8.00	PASS


802.11n HT40

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
3	2422	-25.47	8.00	PASS
6	2437	-27.01	8.00	PASS
9	2452	-27.44	8.00	PASS



**BUREAU
VERITAS**

Test Report No.: RF2009WDG0079-2



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942, People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



4.5 OUT OF BAND EMISSION MEASUREMENT

4.5.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.5.4 TEST PROCEDURE

Measurement Procedure - Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



Measurement Procedure –Unwanted Emission Level

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

Same as item 4.3.6




BUREAU VERITAS

Test Report No.: RF2009WDG0079-2

4.5.7 TEST RESULTS

802.11b






BUREAU VERITAS


Test Report No.: RF2009WDG0079-2

802.11g


CH 1



CH 6



CH 11



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province, 523942, People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com





BUREAU VERITAS



Test Report No.: RF2009WDG0079-2

802.11n HT20



CH 1



CH 6



CH 11







BUREAU VERITAS



Test Report No.: RF2009WDG0079-2

802.11n HT40



CH 3



CH 6



CH 9







BUREAU VERITAS

Test Report No.: RF2009WDG0079-2


802.11b



802.11g



802.11n HT20






**BUREAU
VERITAS**

Test Report No.: RF2009WDG0079-2

802.11n HT40



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



**BUREAU
VERITAS**

Test Report No.: RF2009WDG0079-2

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



**BUREAU
VERITAS**

Test Report No.: RF2009WDG0079-2

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---