

 MOTOROLA SOLUTIONS	    SMM 826 CERTIFICATE 2518.05
---	--

Exhibit 7B: SAR Test Report Photographs

Motorola Solutions Inc
EME Test Laboratory
Motorola Solutions Malaysia Sdn Bhd
Plot 2A, Medan Bayan Lepas
Mukim 12 SWD 11900 Bayan Lepas Penang, Malaysia.



Saw Sun Hock (Approved Signatory)
Approval Date: 09/27/2022

Report Revision History

Date	Revision	Comments
09/27/2022	A	Initial release

1.0 Highest SAR Test Position per body location

1.1 Body

DUT with antenna PMAF4010A with offered battery PMNN4809A and body worn HLN6022A against the phantom without an audio accessory attached. Same configurations offered to other antennas and batteries.



Antenna kit #	Separation Distances (mm)		
	@ bottom surface of the DUT	@ antenna's base	@ antenna's tip
PMAF4009A	0	20	25
PMAF4010A	0	20	25
PMAF4011A	0	20	16
PMAF4012A	0	20	28

(*) Depending on applicable offered battery

1.2 Face

Front of DUT w/ antenna PMAF4011A with offered battery PMNN4810A separated 2.5cm from the phantom without an audio accessory attached. Same configurations offered to other antennas and batteries.



Antenna kit #	Separation Distances (mm)		
	@ bottom surface of the DUT	@ antenna's base	@ antenna's tip
PMAF4009A	30	42	55
PMAF4010A	30	42	50
PMAF4011A	30	42	56
PMAF4012A	30	42	53

1.3 Head
Not applicable.

1.4 Hand
Not applicable

2.0 Other SAR tested positions at the body

2.1 Body worn

DUT with antenna PMAF4010A with offered battery PMNN4807A and body worn PMLN4615A against the phantom without an audio accessory attached. Same configurations offered to other antennas and batteries.



Antenna kit #	Separation Distances (mm)		
	@ bottom surface of the DUT	@ antenna's base	@ antenna's tip
PMAF4009A	6	29	43
PMAF4010A	6	29	43
PMAF4011A	6	29	49
PMAF4012A	6	29	47

(*) Depending on applicable offered battery

DUT with antenna PMAF4010A with offered battery PMNN4807A and body worn PMLN7008A against the phantom without an audio accessory attached. Same configurations offered to other antennas and batteries.



Antenna kit #	Separation Distances (mm)		
	@ bottom surface of the DUT	@ antenna's base	@ antenna's tip
PMAF4009A	7	30	43
PMAF4010A	7	30	45
PMAF4011A	7	30	49
PMAF4012A	7	30	50

(*) Depending on applicable offered battery

DUT with antenna PMAF4012A with offered battery PMNN4809A and body worn PMLN8302A w/o belt loop w/ NTN5243A against the phantom without an audio accessory attached. Same configurations offered to other antennas and batteries.



Antenna kit #	Separation Distances (mm)		
	@ bottom surface of the DUT	@ antenna's base	@ antenna's tip
PMAF4009A	0	40	63
PMAF4010A	0	40	62
PMAF4011A	0	40	70
PMAF4012A	0	40	71

(*) Depending on applicable offered battery

DUT with antenna PMAF4010A with offered battery PMNN4807A and body worn PMLN8304A w/ NTN5243A against the phantom without an audio accessory attached Same configurations offered to other antennas and batteries.



Antenna kit #	Separation Distances (mm)		
	@ bottom surface of the DUT	@ antenna's base	@ antenna's tip
PMAF4009A	0	56	97
PMAF4010A	0	56	88
PMAF4011A	0	56	110
PMAF4012A	0	56	96

(*) Depending on applicable offered battery

DUT with antenna PMAF4009A with offered battery PMNN4807A and body worn PMLN8302A w/o belt loop w/ RLN6487A w/ RLN6488A against the phantom without an audio accessory attached Same configurations offered to other antennas and batteries.



Antenna kit #	Separation Distances (mm)		
	@ bottom surface of the DUT	@ antenna's base	@ antenna's tip
PMAF4009A	0	40	55
PMAF4010A	0	40	59
PMAF4011A	0	40	67
PMAF4012A	0	40	68

(*) Depending on applicable offered battery

2.2 Front Side against phantom

Not applicable.

2.3 Back side against phantom

Not applicable.

2.4 Front 2.5cm separation

Not applicable

2.5 Antenna 2.5cm separation

Not applicable

2.6 Back 2.5cm separation

Not applicable

Other SAR tested positions at the face

2.7 Back of DUT at 2.5cm separation

Not applicable

2.8 Front of DUT at 2.5cm separation
 Refer to section 1.2

3.0 Other SAR tested positions at the head

3.1 Left ear touch
 Not applicable.

3.2 Left ear tilt
 Not applicable.

3.3 Right ear touch
 Not applicable.

3.4 Right ear tilt
 Not applicable.

4.0 Other SAR tested positions at the hand

4.1 Left side
 Not applicable.

4.2 Right side
 Not applicable.

4.3 Top side
 Not applicable.

4.4 Bottom side
 Not applicable.

4.5 Back side
 Not applicable.

5.0 DUT and Accessory Photos

The purpose of these photos is to illustrate the tested accessories. Refer to Part 1 of 2, section 7.0 for additional details on the offered accessories.

5.1 Antenna dimension and photo(s):

Antenna Kit #	Physical Length (mm)	Electrical Length
PMAF4009A	120	¼ wave
PMAF4010A	112	¼ wave
PMAF4011A	164	¼ wave
PMAF4012A	140	¼ wave



From bottom to top: PMAF4009A, PMAF4010A, PMAF4011A, PMAF4012A



5.2 Body worn accessories



PMLN7008A
DUT Side View

PMLN7008A
DUT Back View



PMLN4651A
DUT Side View

PMLN4651A
DUT Back View



PMLN7008A



PMLN4651A



**PMLN8302 with NTN5243A
(Front view)**



**PMLN8302 with NTN5243A
(Side view)**



**PMLN8304 with NTN5243A
(Front View)**



**PMLN8304 with NTN5243A
(Side View)**



**PMLN8302 with RLN6487A +
RLN6488A (Front View)**



**PMLN8302 with RLN6487A +
RLN6488A (Side View)**



HLN6602 Chest pack

5.3 Battery accessories:



PMNN4810A



PMNN4809A



PMNN4808A



PMNN4807A

5.3 Audio accessories



PMMN4128A



PMLN8297A & PMLN8265A



PMLN8337A



PMLN8343A



PMLN8295A



PMLN8086A

5.4 DUT Dimensions

VHF

	Height (mm)	Width (mm)	Depth (mm)
Radio only (w/o battery)	134	63.8	35.5
Radio with battery PMNN4807A	134	63.8	41.0
Radio with battery PMNN4808A	134	63.8	46.5
Radio with battery PMNN4809A	134	63.8	41.0
Radio with battery PMNN4810A	134	63.8	46.5

For illustration purposes only - the following figure reflects the location of the device's dimensions.



Note: H = Height; W = Width; D = Depth

$$W1 = (\text{Width @ Top}) / (\text{Width @ PTT})$$

$$D2 = (\text{Depth @ Bottom}) / (\text{Depth @ PTT})$$