



MOTOROLA SOLUTIONS



TESTING CERT # 2518.01

DECLARATION OF COMPLIANCE: MPE ASSESSMENT Part 2 of 2

EME Test Laboratory 8000 West Sunrise Blvd Fort Lauderdale, FL. 33322	Date of Report: January 13, 2012 Report Revision: O Report ID: SR9340 MPE MC rpt APX7500 UHF R1 & UHF R2 Rev O 01132012
---	---

Responsible Engineer: Stephen C. Whalen (Principal Staff EME Test Engineer) *SCW 1/13/12*
Report author: Stephen C. Whalen (Principal Staff EME Test Engineer)
Date(s) Tested: UHFR2 - 11/12/2010 & 1/28/2011
Manufacturer/Location: Motorola Solutions, Schaumburg, IL
Date submitted for test: 05/31/2011
DUT Description: APX7500 Dual Band UHF R1 15W (380 - 470MHz) & UHF R2 15W (450-520MHz) Motorcycle Mount Option
Test TX mode(s): CW
Max. Power output: 18W
TX Frequency Bands: 380-470MHz & 450-520MHz
Signaling type: Analog, APCO 25, and TDMA 1:2 (F2)
Model(s) Tested M30SSS9PW1AN (FCC ID AZ492FT4896) with G67 motorcycle option
Model(s) Certified: M30TSS9PW1AN (MHUE1002A) with G67 motorcycle option
Serial Number(s): QMKNJ030
Classification: Occupational/Controlled Environment
FCC ID: AZ492FT4904
 Part 22 & 90 UHF R1 (406.1-470MHz) & UHF R2 (450-512MHz)
 Results outside FCC bands are not applicable for FCC compliance demonstration.

Based on the information and the testing results provided herein, the undersigned certifies that when used as stated in the operating instructions supplied, said product complies with the national and international reference standards and guidelines listed in section 3.0 of this report. This report shall not be reproduced without written approval from an officially designated representative of the Motorola Solutions Inc. EME Laboratory.

I attest to the accuracy of the data and assume full responsibility for the completeness of these measurements.
 This reporting format is consistent with the suggested guidelines of the TIA TSB-159 April 2006
 The results and statements contained in this report pertain only to the device(s) evaluated herein.

Kim Anhellina
FOR Deanna Zakharia

EME Lab Senior Resource Manager and
Laboratory Director

Approval Date: *1/18/2012*

Certification Date:

Certification No.:

Document Revision History

Date	Revision	Comments
1/13/2012	O	Initial release

Part 1 of 2: MPE Assessment for 380-470MHz
Part 2 of 2: MPE Assessment for 450-520MHz

Part 2 of 2

Table of Contents

1.0	Introduction.....	4
2.0	Abbreviations / Definitions.....	4
3.0	Referenced Standards and Guidelines	4
4.0	Power Density Limits	5
5.0	N _c Test Channels.....	6
6.0	Measurement Equipment	6
7.0	Measurement System Uncertainty Levels	6
8.0	Product and System Description.....	7
9.0	Additional Options and Accessories.....	7
10.0	Test Set-Up Description.....	7
11.0	Method of Measurement for motorcycle mounted antenna(s).....	8
11.1	Bystander vehicle MPE measurements	8
11.2	Operator vehicle MPE measurements	8
12.0	MPE Calculations	9
13.0	Antenna Summary	10
14.0	Test Results Summary	10
15.0	Conclusion	11
	Appendix A - Illustration of Antenna Location and Test Distances.....	12
	Appendix B - Probe Calibration Certificates.....	14
	Appendix C - Photos of Assessed Antennas.....	19
	Appendix D – MPE Measurement Results	20

1.0 Introduction

This report details the test setup, test equipment and test results of Maximum Permissible Exposure (MPE) performed at Motorola Solutions' outside test site for product model M30TSS9PW1AN (MHUE1002A) with G67 motorcycle option.

2.0 Abbreviations / Definitions

APCO: Association of Public-Safety Communications Officials
BS: Bystander
C4FM: Compatible 4-Level Frequency Modulation
CNR: Calibration Not Required
CQPSK: Compatible Quadrature Phase Shift Keying
CW: Continuous Wave
DUT: Device Under Test
EME: Electromagnetic Energy
F2: 2 slot Time Division Multiple Access
FM: Frequency Modulation
MPE: Maximum Permissible Exposure
NA: Not Applicable
OP: Operator
PTT: Push to Talk
TDMA: Time Division Multiple Access

3.0 Referenced Standards and Guidelines

This product is designed to comply with the following applicable national and international standards and guidelines.

- United States Federal Communications Commission, Code of Federal Regulations; Rule Part 47CFR § 1.1310, § 2.1091 (d) and § 2.1093 for RF Exposure, where applicable.
- Federal Communications Commission, “Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields”, OET Bulletin 65, Supplement C (Edition 01-01), FCC, Washington, D.C.: June 2001.
- American National Standards Institute (ANSI) / Institute of Electrical and Electronics Engineers (IEEE) C95. 1-1999
- American National Standards Institute (ANSI) / Institute of Electrical and Electronics Engineers (IEEE) C95. 1-1992. Specific to FCC rules and regulations.
- Institute of Electrical and Electronics Engineers (IEEE) C95.1-2005
- Institute of Electrical and Electronics Engineers (IEEE) C95.3-2002
- International Commission on Non-Ionizing Radiation Protection (ICNIRP) 1998

4.0 Power Density Limits

Table 1 – Occupational / Controlled Exposure Limits

Frequency Range (MHz)	FCC OET Bulletin 65 Supplement C	ICNIRP	IEEE C95.1 1992/1999	IEEE C95.1 2005
	mW/cm ²	W/m ²	mW/cm ²	W/m ²
30 - 300	1.0			
10 - 400		10.0		
100 - 300			1.0	10.0
300 - 1,500	f/300			
300 - 3,000			f/300	f/30
400 - 2,000		f/40		
1,500 - 15,000				
1,500 - 100,000	5.0			
2,000 - 300,000		50.0		
3,000 - 300,000			10.0	100.0

Table 2 – General Population / Uncontrolled Exposure Limits

Frequency Range (MHz)	FCC OET Bulletin 65 Supplement C	ICNIRP	IEEE C95.1 1992/1999	IEEE C95.1 2005
	mW/cm ²	W/m ²	mW/cm ²	W/m ²
30 - 300	0.2			
10 - 400		2.0		
100 - 300			0.2	
100 - 400				2.0
300 - 1,500	f/1,500			
400 - 2,000		f/200		f/200
300 - 15,000			f/1,500	
1,500 - 15,000				
1,500 - 100,000	1.0			
2,000 - 100,000				10.0
2,000 - 300,000		10.0		

5.0 N_c Test Channels

The number of test channels are determined by using Equation 1 below. This equation is available in FCC's KDB 447498. The test channels are appropriately spaced across the antenna's frequency range.

Equation 1 – Number of test channels

$$N_c = \text{Round} \{ [100(f_{\text{high}} - f_{\text{low}})/f_c]^{0.5} \times (f_c / 100)^{0.2} \}$$

where N_c is the number of test channels, f_{high} and f_{low} are the highest and lowest frequencies within the transmission band, f_c is the mid-band frequency, and frequencies are in MHz.

6.0 Measurement Equipment

Table 3 - Equipment

Equipment Type	Model #	SN	Calibration Date	Calibration Due Date
Motorcycle	2005 Kawasaki KZ1000	NA	NA	NA
Survey Meter Probe – E-Field	ETS Model HI-2200 ETS Model E100	00086887 00126277	07/15/2010	07/15/2011

E-field measurements are in mW/cm².

7.0 Measurement System Uncertainty Levels

Table 4 - Uncertainty Budget for Near Field Probe Measurements

	Tol. (± %)	Prob. Dist.	Divisor	u_i (±%)	v_i
Measurement System					
Probe Calibration	6.0	N	1.00	6.0	∞
Survey Meter Calibration	3.0	N	1.00	3.0	∞
Hemispherical Isotropy	8.0	R	1.73	4.6	∞
Linearity	5.0	R	1.73	2.9	∞
Pulse Response	1.0	R	1.73	0.6	∞
RF Ambient Noise	3.0	R	1.73	1.7	∞
RF Reflections	8.0	R	1.73	4.6	∞
Probe Positioning	10.0	R	1.73	5.8	∞
Test sample Related					
Antenna Positioning	3.0	N	1.00	3.0	∞
Power drift	5.0	R	1.73	2.9	∞
Combined Standard Uncertainty		RSS		12.2	∞
Expanded Uncertainty (95% CONFIDENCE LEVEL)		$k=2$		24	

8.0 Product and System Description

Model M30TSS9PW1AN (MHUE1002A) with G67 motorcycle option is a mobile transceiver that utilizes analog, APCO 25 & F2 digital two-way radio communications. The analog modulation scheme uses Frequency Modulation (FM). APCO 25 & F2 digital modes use C4FM of CQPSK family of modulation (Compatible 4-Level Frequency Modulation of Compatible Quadrature Phase Shift Keying). F2 is a TDMA 1:2 protocol that allocates portions of the RF signal by dividing time into two slots (2 slots TDMA). Transmission from a unit or base station is accommodated in time-slot lengths of 30 milliseconds and frame lengths of 60 milliseconds. This product supports voice in analog mode, and both voice and data modes in digital mode.

The maximum duty cycle for TDMA is 1:2 (50%) and is controlled by software. The FM signal is continuous. However, because of hand shaking or Push-To-Talk (PTT) between users and/or base stations a conservative 50% duty cycle is applied. The TDMA mode was not tested because its duty cycle is inherently 50% and would include an additional 50% duty cycle for PTT.

The intended use of the radio is PTT while the device is properly installed on a motorcycle.

This device will be marketed to and used by employees solely for work-related operations, such as public safety agencies, e.g. police, fire and emergency medical. User training is the responsibility of these agencies which can be expected to employ the usage instructions, safety information and operational cautions set forth in the user's manual, instructional sessions or other means.

Accordingly this product is classified as Occupational/Controlled Exposure. However, in accordance with FCC requirements, the bystanders are evaluated to the General Population/ Uncontrolled Exposure Limits, and the operator is evaluated to the Occupational/Controlled Exposure Limits.

(Note that "Bystanders" as used herein are people other than operator)

9.0 Additional Options and Accessories

Refer to Table 5 for complete list of tested antennas.

10.0 Test Set-Up Description

Assessments were performed with mobile radio installed on the test vehicle while engine was at idle, at the specified distances and test locations indicated in section 11.0 and Appendix A.

All antennas described in Table 5 were considered in order to develop the test plan for this product. Antennas were installed and tested per their defined test channels.

11.0 Method of Measurement for motorcycle mounted antenna(s)

11.1 Bystander vehicle MPE measurements

Antenna is located at the rear of the test vehicle. Refer to Appendix A for antenna location with respect to the bystander.

MPE measurements for bystander (BS) conditions are determined by taking the average of (10) measurements in a 2m vertical line for the bystander test location indicated in Appendix A with 20cm height increments, with antenna to probe sensor separation distance of 60cm directly behind the vehicle. The separation distance used for testing is defined from the antenna where as the RF safety booklet defines the same distance from the vehicle body to ensure that the assessment is applicable to other vehicles. The measurement probe is positioned orthogonal to antenna (typically parallel to ground with a vertically mounted antenna) and aimed directly at the antenna's axis. These measurements are representative of persons other than the operator standing next to the vehicle.

11.2 Operator vehicle MPE measurements

Antenna is located at the rear of the test vehicle. Refer to Appendix A for antenna location with respect to the operator.

MPE measurements for operator (OP) conditions are determined by taking the average of the (3) measurements (Head, Chest and Lower Trunk) at the standard test distance of 30cm from the operators' seat area.

The measurement probe is oriented parallel (horizontal) to the ground and positioned above the motorcycle operator's seat. The probe head is pointed towards the back of the vehicle and aimed directly at the antenna's axis while maintaining a twenty (20) centimeter separation distance between the probe sensor and reradiating structures. These (3) measurements are representative of the operator.

Note; Motorola Solutions' weather proof enclosures provide 30cm separation distance from the antenna to the enclosure's edge. Refer to the installation manual for universal mounting options.

12.0 MPE Calculations

The final MPE results for this mobile radio are presented in section 14.0 Tables 6 & 7. These results are based on 50% duty cycle for PTT.

Below is an explanation of how the MPE results are calculated. Refer to Appendix D for MPE measurement results and calculations.

Bystander -10 measurements are averaged over the body (*Avg_over_body*).

Operator - 3 measurements are averaged over the body (*Avg_over_body*).

The Average over Body test methodology is consistent with IEEE/ANSI C95.3-2002 guidelines.

Therefore;

Equation 2 – Power Density Calculation (*Calc._P.D.*)

$$\text{Calc._P.D.} = (\text{Avg_over_body}) * (\text{probe_frequency_cal_factor}) * (\text{duty_cycle})$$

Note 1: The highest “average” cal factors from the calibration certificates were selected for the applicable frequency range. Linear interpretation was used to determine “probe_frequency_cal_factor” for the specific test frequencies.

Note 2: The E-field probe calibration certificate’s frequency cal factors were determined by measuring V/m. The survey meter’s results were measured in power density (mW/cm^2) and therefore the “probe_frequency_cal_factor” was squared in equation 2 to account for these results.

Note 3: The H-field probe calibration certificate’s frequency cal factors were determined by measuring A/m. The survey meter’s results were measured in A/m and therefore the “Avg_over_body” A/m results were converted to power density (mW/cm^2) using the equation 3. H-field measurements are only applicable to frequencies below 300MHz.

Equation 3 – Converting A/m to mW/cm^2

$$\text{mW/cm}^2 = (\text{A/m})^2 * 37.699$$

Equation 4 – Power Density Maximum Calculation

$$\text{Max_Calc._P.D.} = \text{P.D._calc} * \frac{\text{max_output_power}}{\text{initial_output_power}}$$

Note 4: For initial output power > max_output_power; max_output_power / initial output power = 1

13.0 Antenna Summary

Table 5 below summarizes the tested antennas and their descriptions, overlap of FCC bands, number of test channels per FCC KDB 447498 (FCC N_c) and actual number of tested channels (Actual N_c). This information was used to determine the test configurations presented in this report.

Table 5

#	Antenna Model	Frequency Range (MHz)	Physical Length (cm)	Gain (dBi)	Remarks	Overlap FCC Bands	FCC N_c	Actual N_c
1	HAE6033A	450-482	15.0	2.15	1/4 wave, wire	450-482	4	4
2	HAE6034A	482-520	14.0	2.15	1/4 wave, wire	482-512	3	6
3	HAE6035A	450 - 512	8.3	2.15	1/4 wave, cylinder	450-512	5	5

14.0 Test Results Summary

The following tables below summarize the MPE results for each test configuration: test positions (BS-Bystander, OP-Operator), E/H field measurements, antenna model & freq. range, maximum output power, initial power, TX frequency, max calculated power density results, applicable FCC/IEEE/ICNIRP specification limits and % of the applicable specification limits.

Table 6 - Bystander MPE assessment to General Population / Uncontrolled Exposure Limits

Test Position	E/H field	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm^2)	FCC Limit	% To Spec Limit	ICNIRP Limit	% To Spec Limit
BS	E	HAE6033A, 450-482MHz	18	17.4	450.0125	0.08	0.30	28	0.23	37
				17.4	460.0000	0.08	0.31	25	0.23	34
				17.2	471.0000	0.07	0.31	24	0.24	31
				17.5	481.9875	0.08	0.32	26	0.24	34
		HAE6034A, 482-512MHz	18	17.5	482.0125	0.08	0.32	25	0.24	33
				17.5	497.0000	0.10	0.33	29	0.25	39
				17.6	511.9875	0.09	0.34	25	0.26	34
				17.3	512.0125	0.09	0.34	26	0.26	34
				17.4	516.0125	0.09	0.34	25	0.26	33
				17.3	519.9875	0.08	0.35	23	0.26	31
		HAE6035A, 450 - 512MHz	18	17.4	450.0125	0.08	0.30	26	0.23	35
				17.4	465.5000	0.08	0.31	26	0.23	35
				17.5	481.0125	0.07	0.32	22	0.24	29
				17.5	496.5000	0.07	0.33	21	0.25	28
				17.6	511.9875	0.07	0.34	21	0.26	28

Table 7 - Operator MPE assessment to Occupational / Controlled Exposure Limits

Test Position	E/H field	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm^2)	FCC Limit	% To Spec Limit	ICNIRP Limit	% To Spec Limit
OP	E	HAE6033A, 450-482MHz	18	17.4	450.0125	0.35	1.50	24	1.13	31
				17.4	460.0000	0.40	1.53	26	1.15	34
				17.2	471.0000	0.38	1.57	24	1.18	33
				17.5	481.9875	0.40	1.61	25	1.20	33
		HAE6034A, 482-512MHz	18							
				17.5	482.0125	0.39	1.61	24	1.21	32
				17.5	497.0000	0.33	1.66	20	1.24	27
				17.6	511.9875	0.41	1.71	24	1.28	32
				17.3	512.0125	0.42	1.71	24	1.28	33
				17.4	516.0125	0.43	1.72	25	1.29	33
				17.3	519.9875	0.42	1.73	24	1.30	32
		HAE6035A, 450 - 512MHz	18							
				17.4	450.0125	0.36	1.50	24	1.13	32
				17.4	465.5000	0.44	1.55	28	1.16	37
				17.5	481.0125	0.42	1.60	26	1.20	35
				17.5	496.5000	0.32	1.66	19	1.24	26
				17.6	511.9875	0.37	1.71	22	1.28	29

15.0 Conclusion

The assessments for this device were performed with an output power range as indicated in section 14.0 Tables 6 & 7. The maximum allowable output power is equal to the upper limit of the final test factory transmit power specification of 18W. The highest power density results for the mobile device scaled to the maximum allowable power output are indicated in Table 8 for operator and bystander to the vehicle.

Table 8: Maximum MPE RF Exposure Summary


Designator	Frequency (MHz)	Operator (mW/cm ²)	Bystander (mW/cm ²)
Overall	450-520	0.44	0.10
FCC	450-512	0.44	0.10

These MPE results herein demonstrate compliance to the FCC/IEEE/ICNIRP Occupational/Controlled Exposure limit. FCC rules require compliance for Bystanders to the FCC General Population/Uncontrolled limits.

Appendix A - Illustration of Antenna Location and Test Distances


Bystander Illustration

Meter - Probe



Operator Illustration

Meter - Probe



Note that the Lower Trunk measurement distance (45cm) from the antenna is to achieve 20cm distance from reradiating objects.

Appendix B - Probe Calibration Certificates



Cert I.D.: 79630



An ESCO Technologies Company
1301 Arrow Point Drive
Cedar Park, Texas 78613
(512) 531-6498



Certificate of Calibration Conformance

Page 1 of 4

The instrument identified below has been individually calibrated in compliance with the following standard(s):

IEEE 1309 - 2005, Institute of Electrical and Electronics Engineers, Standard for Calibration of Electromagnetic Field Sensors and Probes, Excluding Antennas from 9 kHz to 40 GHz

CALIBRATION
BY **AS** DATE **7-15-10**
DUE **7-15-11** ID **S19628**

Environment: Laboratory MTE is maintained in a temperature controlled environment with ambient conditions from 18 to 28 C, relative humidity less than 90%. The instrument under test has been calibrated in a suitable environment using an EMCO TEM Cell 5101C, GTEM! 5305 and an RF Shielded EMC Chamber which is conducive to maintaining accurate and reliable measurement quality.

Manufacturer:	ETS-Lindgren	Operating Range:	100kHz - 5GHz
Model Number:	E100	Instrument Type:	Isotropic Probe > 1 GHz
Serial Number/ ID:	00126277	Date Code:	
Tracking Number:	S000019628	Alternate ID:	
Date Completed:	15-Jul-10	Customer:	AGILENT/MOTOROLA (FL)
Test Type:	Standard Field, Field Strength		
Calibration Uncertainty:	Std Field Method k=2, (95% Confidence Level)	10kHz - 18000 MHz, +/-0.7 dB, 26.5GHz - 40GHz, +/- 0.95 dB	

Test Remarks: Replaced broken probe head sn 00083370 with sn 00126277. Provided customer specified frequencies.

Calibration Traceability: All Measuring and Test Equipment (M/TE) identified below are traceable to the National Institute for Standards and Technology (NIST). Calibration Laboratory and Quality System controls are compliant with ISO/IEC 17025-2005.

Standards and Equipment Used:

Make / Model / Name / S/N / Recall Date

**Condition of Instrument
Upon Receipt:**

Hewlett Packard	437B	HP Power Meter	3125U12370	15-Jun-11	INOP
Fluke	6060B	RF Signal Generator	5690204	15-Jun-11	
Marconi	2022	Signal Generator	119019/077	25-Sep-10	On Release:
Agilent	E4419B	Power Meter	MY45104171	16-Jun-11	In Tolerance to Internal Quality Standards
Rohde & Schwarz	857.8008.02	Power Meter NRV	100451	11-Mar-11	
Hewlett Packard	83620B	Signal Generator	3722A00541	25-Sep-10	

Alan Schifferdecker
Calibration Completed By
Alan Schifferdecker, Calibration Technician

Richard Goodlow
Attested and Issued on 15-Jul-10
Richard Goodlow, Calibration Supervisor

This document provides traceability of measurements to recognized national standards using controlled processes at the ETS-Lindgren Calibration Laboratory. Uncertainties listed are derived from the methods described by NIST Tech Note 1297. This certificate and report may not be reproduced, except in full, without the written approval of ETS-Lindgren Calibration Laboratory in accordance with ISO/IEC 17025-2005. QAF 1127 (06/07)



Frequency Response Calibration Factors
 Model E100 Serial Number 00126277
 Date of Calibration 14 Jul 2010

Frequency (MHz)	Applied V/m	Probe Reading			Correction Factor			
		X	Y	Z	X	Y	Z	Avg
1.00	7.99	6.73	6.65	6.64	1.19	1.20	1.20	1.20
1.00	19.86	16.88	16.46	16.75	1.18	1.21	1.19	1.19
1.00	69.83	58.57	57.16	57.94	1.19	1.22	1.21	1.21
1.00	124.10	104.33	101.84	103.29	1.19	1.22	1.20	1.20
15.00	7.98	7.87	7.89	7.76	1.01	1.01	1.03	1.02
15.00	20.02	19.90	19.66	19.57	1.01	1.02	1.02	1.02
15.00	69.73	68.75	68.03	67.93	1.01	1.02	1.03	1.02
15.00	125.10	123.58	122.44	121.98	1.01	1.02	1.03	1.02
30.00	7.98	8.00	8.02	7.92	1.00	0.99	1.01	1.00
30.00	20.13	20.26	20.02	19.95	0.99	1.01	1.01	1.00
30.00	70.33	69.96	69.20	69.16	1.01	1.02	1.02	1.01
30.00	125.54	125.61	124.27	124.22	1.00	1.01	1.01	1.01
75.00	8.00	8.02	8.09	7.92	1.00	0.99	1.01	1.00
75.00	19.99	20.13	19.98	19.76	0.99	1.00	1.01	1.00
75.00	70.36	69.86	69.30	68.86	1.01	1.02	1.02	1.01
75.00	125.15	125.40	124.63	123.68	1.00	1.00	1.01	1.00
100.00	7.96	7.97	8.01	7.88	1.00	0.99	1.01	1.00
100.00	19.88	19.91	19.74	19.61	1.00	1.01	1.01	1.01
100.00	69.57	69.51	68.99	68.72	1.00	1.01	1.01	1.01
100.00	124.96	124.36	123.49	122.96	1.00	1.01	1.02	1.01
150.00	8.01	8.06	8.15	7.96	0.99	0.98	1.01	0.99
150.00	19.95	20.28	20.15	19.91	0.98	0.99	1.00	0.99
150.00	69.89	69.62	69.33	68.78	1.00	1.01	1.02	1.01
150.00	124.33	125.18	124.63	123.79	0.99	1.00	1.00	1.00
200.00	8.00	8.45	8.63	8.33	0.95	0.93	0.96	0.95
200.00	20.01	21.13	21.27	20.72	0.95	0.94	0.97	0.95
200.00	69.87	73.33	73.78	72.18	0.95	0.95	0.97	0.96
200.00	124.17	129.74	130.72	127.78	0.96	0.95	0.97	0.96
250.00	8.01	8.19	8.12	8.13	0.98	0.99	0.99	0.98
250.00	20.01	20.51	20.01	20.27	0.98	1.00	0.99	0.99
250.00	69.83	71.26	69.62	70.60	0.98	1.00	0.99	0.99
250.00	125.43	127.92	125.29	127.07	0.98	1.00	0.99	0.99
300.00	8.01	8.15	8.10	8.06	0.98	0.99	0.99	0.99
300.00	19.94	20.39	20.06	20.16	0.98	0.99	0.99	0.99
300.00	69.60	70.46	69.32	69.88	0.99	1.00	1.00	1.00
300.00	125.08	126.92	124.75	125.61	0.99	1.00	1.00	0.99
400.00	8.02	8.14	8.13	8.06	0.98	0.99	0.99	0.99
400.00	19.87	20.24	19.93	19.94	0.98	1.00	1.00	0.99
400.00	69.66	70.49	69.46	69.77	0.99	1.00	1.00	1.00
400.00	124.99	127.20	125.29	125.73	0.98	1.00	0.99	0.99
500.00	8.04	8.01	8.13	7.92	1.00	0.99	1.02	1.00
500.00	19.98	19.97	19.95	19.63	1.00	1.00	1.02	1.01
500.00	70.28	69.96	69.96	69.11	1.00	1.00	1.02	1.01
500.00	124.86	124.41	124.25	122.86	1.00	1.00	1.02	1.01
600.00	8.00	7.72	7.73	7.65	1.04	1.04	1.05	1.04
600.00	19.95	19.30	19.03	19.07	1.03	1.05	1.05	1.04
600.00	69.83	67.03	64.80	65.25	1.04	1.08	1.07	1.06
600.00	125.49	121.42	119.78	120.36	1.03	1.05	1.04	1.04




Frequency Response Calibration Factors
Model E100 Serial Number 00126277
Date of Calibration 14 Jul 2010

Frequency (MHz)	Applied Vm	Probe Reading			Correction Factor			
		X	Y	Z	X	Y	Z	Avg
700.00	8.06	7.63	7.53	7.57	1.06	1.07	1.06	1.06
700.00	20.05	18.94	18.46	18.74	1.06	1.09	1.07	1.07
700.00	70.48	66.13	64.14	65.29	1.07	1.10	1.08	1.08
700.00	124.23	117.32	114.56	116.78	1.06	1.08	1.06	1.07
800.00	7.97	7.37	7.39	7.27	1.08	1.08	1.10	1.09
800.00	19.93	18.50	18.31	18.29	1.08	1.09	1.09	1.09
800.00	69.90	64.64	64.92	64.77	1.08	1.08	1.08	1.08
800.00	124.55	115.81	114.68	114.76	1.08	1.09	1.09	1.08
900.00	8.01	7.85	7.93	7.71	1.02	1.01	1.04	1.02
900.00	19.90	19.74	19.73	19.30	1.01	1.01	1.03	1.02
900.00	70.29	69.02	68.60	67.71	1.02	1.02	1.04	1.03
900.00	124.72	123.49	122.93	121.00	1.01	1.01	1.03	1.02
1000.00	8.00	8.16	8.06	8.08	0.98	0.99	0.99	0.99
1000.00	19.91	20.37	19.74	20.07	0.98	1.01	0.99	0.99
1000.00	69.79	70.93	68.52	69.98	0.98	1.02	1.00	1.00
1000.00	124.52	127.44	123.83	125.80	0.98	1.01	0.99	0.99
2000.00	20.07	19.68	19.26	19.58	1.02	1.04	1.03	1.03
2450.00	20.02	19.58	19.47	18.99	1.02	1.03	1.05	1.03
3000.00	19.99	20.23	18.92	20.34	0.99	1.06	0.98	1.01
3500.00	20.03	20.44	20.24	20.40	0.98	0.99	0.98	0.98
4000.00	20.47	20.59	19.87	20.88	0.99	1.03	0.98	1.00
5000.00	20.07	14.70	15.34	16.37	1.37	1.31	1.23	1.30
5500.00	19.74	15.36	15.43	14.11	1.28	1.28	1.40	1.32
6000.00	19.94	13.34	15.14	14.53	1.49	1.32	1.37	1.39



PROBE ROTATIONAL RESPONSE

Model E100
S/N 00126277
Date 15-Jul-2010
Time 19:04:45
Variation 0.75 dB



- Isotropic response measured in a 20 V/m field at 400 MHz

Appendix C - Photos of Assessed Antennas

(Refer to Exhibit 7B)

Appendix D – MPE Measurement Results

MPE measurement data for Bystander

D.U.T. Info.							Probe Info.		Test Pos.	Bystander (BS) Positions										DUT Max. TX Factor	Avg. over Body (mW/ cm^2)	Calc. P.D. (mW/ cm^2)	Max Calc. P.D. (mW/ cm^2)	
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm					
MC	HAE6033A, 450-482MHz	2.15	450.0125	18	17.4	CW	E	1.01	BS	0.06	0.07	0.08	0.13	0.27	0.34	0.29	0.19	0.10	0.06	0.5	0.159	0.08	0.08	
MC	HAE6033A, 450-482MHz	2.15	460	18	17.4	CW	E	1.01	BS	0.08	0.09	0.08	0.13	0.26	0.31	0.25	0.16	0.09	0.04	0.5	0.149	0.08	0.08	
MC	HAE6033A, 450-482MHz	2.15	471	18	17.2	CW	E	1.01	BS	0.08	0.08	0.06	0.13	0.26	0.30	0.23	0.14	0.08	0.04	0.5	0.140	0.07	0.07	
MC	HAE6033A, 450-482MHz	2.15	481.9875	18	17.5	CW	E	1.02	BS	0.08	0.07	0.05	0.14	0.29	0.34	0.28	0.17	0.10	0.06	0.5	0.158	0.08	0.08	
MC	HAE6034A, 482-512MHz	2.15	482.0125	18	17.5	CW	E	1.02	BS	0.08	0.07	0.06	0.15	0.27	0.32	0.26	0.16	0.10	0.06	0.5	0.153	0.08	0.08	
MC	HAE6034A, 482-512MHz	2.15	497	18	17.5	CW	E	1.02	BS	0.05	0.03	0.04	0.18	0.34	0.39	0.33	0.23	0.16	0.09	0.5	0.184	0.09	0.10	
MC	HAE6034A, 482-512MHz	2.15	511.9875	18	17.6	CW	E	1.03	BS	0.07	0.03	0.06	0.20	0.32	0.34	0.27	0.17	0.11	0.07	0.5	0.164	0.08	0.09	
MC	HAE6034A, 482-512MHz	2.15	512.0125	18	17.3	CW	E	1.03	BS	0.07	0.03	0.06	0.20	0.31	0.34	0.26	0.18	0.11	0.07	0.5	0.163	0.08	0.09	
MC	HAE6034A, 482-512MHz	2.15	516.0125	18	17.4	CW	E	1.04	BS	0.06	0.04	0.07	0.21	0.30	0.34	0.24	0.17	0.10	0.06	0.5	0.159	0.08	0.09	
MC	HAE6034A, 482-512MHz	2.15	519.9875	18	17.3	CW	E	1.04	BS	0.07	0.05	0.07	0.20	0.31	0.32	0.22	0.13	0.08	0.05	0.5	0.150	0.08	0.08	
MC	HAE6035A, 450 - 512MHz	2.15	450.0125	18	17.4	CW	E	1.01	BS	0.08	0.08	0.10	0.12	0.26	0.30	0.27	0.17	0.09	0.05	0.5	0.152	0.08	0.08	
MC	HAE6035A, 450 - 512MHz	2.15	465.5	18	17.4	CW	E	1.01	BS	0.10	0.12	0.09	0.13	0.30	0.32	0.24	0.13	0.07	0.04	0.5	0.154	0.08	0.08	
MC	HAE6035A, 450 - 512MHz	2.15	481.0125	18	17.5	CW	E	1.02	BS	0.11	0.11	0.06	0.13	0.24	0.27	0.19	0.12	0.07	0.05	0.5	0.135	0.07	0.07	
MC	HAE6035A, 450 - 512MHz	2.15	496.5	18	17.5	CW	E	1.02	BS	0.10	0.07	0.04	0.13	0.26	0.25	0.19	0.13	0.10	0.07	0.5	0.134	0.07	0.07	
MC	HAE6035A, 450 - 512MHz	2.15	511.9875	18	17.6	CW	E	1.03	BS	0.08	0.04	0.04	0.16	0.25	0.27	0.20	0.14	0.09	0.07	0.5	0.134	0.07	0.07	

MPE calculations are defined in section 12.0.

MPE measurement data for Operator

D.U.T. Info.							Probe Info.		Test Pos.	Operator (MC) Positions			DUT Max. TX Factor	Avg. over Body (mW/ cm^2)	Calc. P.D. (mW/ cm^2)	Max Calc. P.D. (mW/ cm^2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Head	Chest	Lower Trunk				
	HAE6033A, 450-482MHz	2.15	450.0125	18	17.4	CW	E	1.01	OP	0.34	1.05	0.64	0.5	0.677	0.34	0.35
MC	HAE6033A, 450-482MHz	2.15	460	18	17.4	CW	E	1.01	OP	0.42	1.11	0.74	0.5	0.757	0.38	0.40
MC	HAE6033A, 450-482MHz	2.15	471	18	17.2	CW	E	1.01	OP	0.38	1.05	0.75	0.5	0.727	0.37	0.38
MC	HAE6033A, 450-482MHz	2.15	481.9875	18	17.5	CW	E	1.02	OP	0.44	1.14	0.70	0.5	0.760	0.39	0.40
MC	HAE6034A, 482-512MHz	2.15	482.0125	18	17.5	CW	E	1.02	OP	0.44	1.09	0.69	0.5	0.740	0.38	0.39
MC	HAE6034A, 482-512MHz	2.15	497	18	17.5	CW	E	1.02	OP	0.38	1.01	0.51	0.5	0.633	0.32	0.33
MC	HAE6034A, 482-512MHz	2.15	511.9875	18	17.6	CW	E	1.03	OP	0.47	1.19	0.68	0.5	0.780	0.40	0.41
MC	HAE6034A, 482-512MHz	2.15	512.0125	18	17.3	CW	E	1.03	OP	0.46	1.18	0.69	0.5	0.777	0.40	0.42
MC	HAE6034A, 482-512MHz	2.15	516.0125	18	17.4	CW	E	1.04	OP	0.45	1.23	0.73	0.5	0.803	0.42	0.43
MC	HAE6034A, 482-512MHz	2.15	519.9875	18	17.3	CW	E	1.04	OP	0.44	1.22	0.68	0.5	0.780	0.41	0.42
MC	HAE6035A, 450 - 512MHz	2.15	450.0125	18	17.4	CW	E	1.01	OP	0.36	0.99	0.72	0.5	0.690	0.35	0.36
MC	HAE6035A, 450 - 512MHz	2.15	465.5	18	17.4	CW	E	1.01	OP	0.48	1.18	0.84	0.5	0.833	0.42	0.44
MC	HAE6035A, 450 - 512MHz	2.15	481.0125	18	17.5	CW	E	1.02	OP	0.50	1.20	0.71	0.5	0.803	0.41	0.42
MC	HAE6035A, 450 - 512MHz	2.15	496.5	18	17.5	CW	E	1.02	OP	0.40	0.98	0.47	0.5	0.617	0.31	0.32
MC	HAE6035A, 450 - 512MHz	2.15	511.9875	18	17.6	CW	E	1.03	OP	0.44	1.08	0.59	0.5	0.703	0.36	0.37

MPE calculations are defined in section 12.0.