



DECLARATION OF COMPLIANCE: MPE ASSESSMENT PCII Report Part 2 of 2

<p>Motorola Solutions Inc. EME Test Laboratory Motorola Solutions Malaysia Sdn Bhd Plot 2A, Medan Bayan Lepas, Mukim 12 SWD 11900 Bayan Lepas Penang, Malaysia.</p>	<p>Date of Report: 4/23/2020 Report Revision: B</p>
---	--

<p>Responsible Engineer: Report author: Date(s) Tested: Manufacturer: Date submitted for test: DUT Description: Test TX mode(s): Max. Power output: TX Frequency Bands: Signaling type: Model(s) Tested: Model(s) Certified: Serial Number(s): Classification: Applicant Name: Applicant Address: FCC ID: IC:</p>	<p>Saw Sun Hock (EME Engineer) Saw Sun Hock (EME Engineer) 2/17/2017-3/17/2017; 4/23/2019 - 4/24/2019, 5/7/2019, 5/9/2019, 5/13/2019 - 5/14/2019, 5/29/2019 Futurecom Systems Group (DVR), Motorola Solutions. Inc (Mobile) 01/13/2017; 04/12/2019 APX6500 7/800 MHz: Multiple HW Encryption WiFi Interoperability Data Modem Tethering via WiFi or Cable Companion Device: DVR VHF (136-174 MHz), Digital Vehicular Repeater CW APX6500 7/800 MHz: 36W (762-805 MHz), 42W (806-870 MHz); 11.22 mW (Bluetooth); 6.3 mW (Bluetooth LE); 39.8 mW (WLAN 2.4GHz 802.11b), 15.8 mW (WLAN 2.4GHz 802.11g), 12.6mW (WLAN 2.4GHz 802.11n); 15.8mW (WLAN 5GHz 802.11a/n/ac) Companion Device: 6W (DVR VHF) APX6500 7/800 MHz: 762-806 MHz; 806-870 MHz; WLAN 2412-2462 MHz; WLAN 5180-5825 MHz; BT 2402-2480 MHz Companion Device: 136-174 MHz FM, TDMA, FHSS (Bluetooth), 802.11b/g/n (WLAN 2.4 GHz), 802.11 a/n/ac (WLAN 5 GHz) APX6500 7/800 MHz: M25URS9PW1BN (PMUF1969A) Companion Device: MOBEXCOM DVRS VHF (DQPMDVR3000P) M25URS9PW1BN (PMUF1969A), MOBEXCOM DVRS VHF (DQPMDVR3000P) 471TVF3314 (APX6500 7/800 MHz) , 16082232 (DVR VHF) Occupational/Controlled Environment Motorola Solutions Inc. 8000 West Sunrise Boulevard, Fort Lauderdale, Florida 33322 APX6500 7/800 MHz: AZ492FT7124 (769-775 MHz, 799-824 MHz, 851-869 MHz, 2402-2480 MHz, 2412-2462 MHz; 5180-5825 MHz) Companion Device: LO6-DVRSVHF (150.8-173.4MHz) This report contains results that are immaterial for FCC equipment approval, which are clearly identified. APX6500 7/800 MHz: 109U-92FT7124 Companion Device: 2098-DVRSVHF This report contains results that are immaterial for ISED Canada equipment approval, which are clearly identified.</p>
--	---


The MPE results clearly demonstrate compliance with FCC Occupational/Controlled RF Exposure limits. FCC rules require compliance for Passengers and Bystanders to the FCC General Population/Uncontrolled limits.

Based on the information and the testing results provided herein, the undersigned certifies that when used as stated in the operating instructions supplied, said product complies with the national and international reference standards and guidelines listed in section 4.0 of this report (no deviation from standard methods). This report shall not be reproduced without written approval from an officially designated representative of the Motorola Solutions Inc. EME Laboratory.

I attest to the accuracy of the data and assume full responsibility for the completeness of these measurements.

This reporting format is consistent with the suggested guidelines of the TIA TSB-159 April 2006

The results and statements contained in this report pertain only to the device(s) evaluated herein.

<p style="text-align: center;">  Tiong Nguk Ing Deputy Technical Manager (Approved Signatory) Approval Date: 4/23/2020 </p>	
--	--

Appendix D – MPE Test Results Summary for APX6500 7/800MHz

Table D.1

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS1	E	1	HAF4013A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.04	0.51	8.4	0.24	17.5
						35.2	769.0125	0.04	0.51	8.4	0.25	17.5
						35.0	772.0000	0.05	0.51	9.2	0.25	19.1
						34.9	774.9875	0.04	0.52	8.2	0.25	17.1
						34.6	794.0125	0.05	0.53	9.3	0.25	19.6
					35.5	799.0125	0.05	0.53	9.6	0.25	20.3	
					42	42.0	811.5000	0.04	0.54	7.3	0.25	15.6
						40.8	823.9875	0.04	0.55	6.8	0.26	14.5
						41.8	851.0125	0.03	0.57	5.1	0.26	11.0
						41.1	860.5000	0.04	0.57	6.9	0.27	14.8
41.1	868.9875	0.03	0.58	5.4		0.27	11.8					
Roof	BS2	E	1	HAF4013A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.03	0.51	5.9	0.24	12.2
						35.2	769.0125	0.03	0.51	5.9	0.25	12.2
						35.0	772.0000	0.03	0.51	5.9	0.25	12.3
						34.9	774.9875	0.03	0.52	5.2	0.25	11.0
						34.6	794.0125	0.03	0.53	5.2	0.25	10.9
					35.5	799.0125	0.03	0.53	4.9	0.25	10.4	
					42	42.0	811.5000	0.02	0.54	4.4	0.25	9.3
						40.8	823.9875	0.03	0.55	5.4	0.26	11.6
						41.8	851.0125	0.03	0.57	5.0	0.26	10.7
						41.1	860.5000	0.03	0.57	5.7	0.27	12.3
41.1	868.9875	0.03	0.58	4.5		0.27	9.7					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS3	E	1	HAF4013A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	2.3	0.24	4.8
						35.2	769.0125	0.01	0.51	2.3	0.25	4.8
						35.0	772.0000	0.01	0.51	2.2	0.25	4.7
						34.9	774.9875	0.01	0.52	1.9	0.25	4.1
						34.6	794.0125	0.02	0.53	2.9	0.25	6.2
					35.5	799.0125	0.02	0.53	2.8	0.25	6.0	
					42	42.0	811.5000	0.01	0.54	2.5	0.25	5.2
						40.8	823.9875	0.02	0.55	2.9	0.26	6.1
						41.8	851.0125	0.01	0.57	2.3	0.26	5.1
						41.1	860.5000	0.01	0.57	2.3	0.27	4.9
41.1	868.9875	0.01	0.58	2.5		0.27	5.4					
Roof	BS4	E	1	HAF4013A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	1.4	0.24	2.9
						35.2	769.0125	0.01	0.51	1.4	0.25	2.9
						35.0	772.0000	0.01	0.51	1.3	0.25	2.7
						34.9	774.9875	0.01	0.52	1.3	0.25	2.8
						34.6	794.0125	0.01	0.53	1.2	0.25	2.5
					35.5	799.0125	0.01	0.53	1.2	0.25	2.4	
					42	42.0	811.5000	0.01	0.54	1.0	0.25	2.1
						40.8	823.9875	0.01	0.55	1.2	0.26	2.6
						41.8	851.0125	0.01	0.57	1.1	0.26	2.3
						41.1	860.5000	0.01	0.57	1.4	0.27	3.1
41.1	868.9875	0.01	0.58	1.1		0.27	2.5					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS5	E	1	HAF4013A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	1.1	0.24	2.2
						35.2	769.0125	0.01	0.51	1.1	0.25	2.2
						35.0	772.0000	0.01	0.51	1.4	0.25	2.9
						34.9	774.9875	0.01	0.52	1.4	0.25	3.0
						34.6	794.0125	0.01	0.53	1.5	0.25	3.1
					35.5	799.0125	0.01	0.53	1.9	0.25	3.9	
					42	42.0	811.5000	0.01	0.54	1.8	0.25	3.9
						40.8	823.9875	0.01	0.55	1.0	0.26	2.2
						41.8	851.0125	0.004	0.57	0.7	0.26	1.6
						41.1	860.5000	0.01	0.57	0.9	0.27	1.9
41.1	868.9875	0.004	0.58	0.7		0.27	1.5					
Roof	BS1	E	2	HAF4014A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.03	0.51	5.8	0.24	12.1
						35.2	769.0125	0.03	0.51	5.8	0.25	12.1
						35.0	772.0000	0.03	0.51	6.6	0.25	13.7
						34.9	774.9875	0.03	0.52	6.2	0.25	13.0
						34.6	794.0125	0.05	0.53	8.7	0.25	18.4
					35.5	799.0125	0.05	0.53	9.7	0.25	20.5	
					42	42.0	811.5000	0.04	0.54	7.9	0.25	16.8
						40.8	823.9875	0.04	0.55	6.7	0.26	14.4
						41.8	851.0125	0.02	0.57	4.1	0.26	8.9
						41.1	860.5000	0.03	0.57	5.0	0.27	10.8
41.1	868.9875	0.03	0.58	4.4		0.27	9.6					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS2	E	2	HAF4014A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.02	0.51	3.5	0.24	7.2
						35.2	769.0125	0.02	0.51	3.3	0.25	7.0
						35.0	772.0000	0.02	0.51	3.6	0.25	7.6
						34.9	774.9875	0.02	0.52	3.8	0.25	8.0
						34.6	794.0125	0.02	0.53	3.9	0.25	8.2
					35.5	799.0125	0.02	0.53	4.0	0.25	8.4	
					42	42.0	811.5000	0.02	0.54	3.6	0.25	7.7
						40.8	823.9875	0.03	0.55	5.3	0.26	11.2
						41.8	851.0125	0.03	0.57	4.7	0.26	10.1
						41.1	860.5000	0.03	0.57	5.1	0.27	11.1
41.1	868.9875	0.02	0.58	3.7		0.27	8.1					
Roof	BS3	E	2	HAF4014A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	1.4	0.24	2.9
						35.2	769.0125	0.01	0.51	1.4	0.25	2.9
						35.0	772.0000	0.01	0.51	1.4	0.25	3.0
						34.9	774.9875	0.01	0.52	1.3	0.25	2.6
						34.6	794.0125	0.02	0.53	3.4	0.25	7.2
					35.5	799.0125	0.02	0.53	3.4	0.25	7.2	
					42	42.0	811.5000	0.02	0.54	4.6	0.25	9.8
						40.8	823.9875	0.02	0.55	4.2	0.26	8.9
						41.8	851.0125	0.02	0.57	3.9	0.26	8.4
						41.1	860.5000	0.02	0.57	3.0	0.27	6.5
41.1	868.9875	0.02	0.58	3.7		0.27	8.1					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS4	E	2	HAF4014A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.004	0.51	0.9	0.24	1.8
						35.2	769.0125	0.004	0.51	0.9	0.25	1.8
						35.0	772.0000	0.004	0.51	0.8	0.25	1.8
						34.9	774.9875	0.01	0.52	1.2	0.25	2.5
						34.6	794.0125	0.01	0.53	1.4	0.25	3.0
					35.5	799.0125	0.01	0.53	1.3	0.25	2.7	
					42	42.0	811.5000	0.01	0.54	1.3	0.25	2.8
						40.8	823.9875	0.01	0.55	1.7	0.26	3.7
						41.8	851.0125	0.01	0.57	2.1	0.26	4.6
						41.1	860.5000	0.01	0.57	2.4	0.27	5.2
41.1	868.9875	0.01	0.58	1.8		0.27	3.8					
Roof	BS5	E	2	HAF4014A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.004	0.51	0.8	0.24	1.8
						35.2	769.0125	0.004	0.51	0.8	0.25	1.7
						35.0	772.0000	0.01	0.51	1.3	0.25	2.7
						34.9	774.9875	0.01	0.52	1.3	0.25	2.8
						34.6	794.0125	0.01	0.53	1.8	0.25	3.8
					35.5	799.0125	0.01	0.53	2.7	0.25	5.6	
					42	42.0	811.5000	0.01	0.54	2.2	0.25	4.7
						40.8	823.9875	0.01	0.55	2.2	0.26	4.6
						41.8	851.0125	0.01	0.57	1.4	0.26	3.0
						41.1	860.5000	0.01	0.57	1.4	0.27	2.9
41.1	868.9875	0.01	0.58	1.3		0.27	2.8					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS1	E	3	HAF4016A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.04	0.51	8.2	0.24	17.1
						35.2	769.0125	0.04	0.51	8.1	0.25	16.9
						35.0	772.0000	0.04	0.51	8.1	0.25	17.0
						34.9	774.9875	0.04	0.52	8.0	0.25	16.8
						34.6	794.0125	0.05	0.53	9.2	0.25	19.4
					35.5	799.0125	0.05	0.53	9.7	0.25	20.5	
					42	42.0	811.5000	0.04	0.54	7.4	0.25	15.6
						40.8	823.9875	0.04	0.55	6.8	0.26	14.5
						41.8	851.0125	0.03	0.57	4.6	0.26	9.9
						41.1	860.5000	0.04	0.57	6.2	0.27	13.5
41.1	868.9875	0.03	0.58	4.9		0.27	10.6					
Roof	BS2	E	3	HAF4016A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.03	0.51	5.6	0.24	11.7
						35.2	769.0125	0.03	0.51	5.6	0.25	11.7
						35.0	772.0000	0.03	0.51	5.6	0.25	11.7
						34.9	774.9875	0.03	0.52	5.0	0.25	10.5
						34.6	794.0125	0.03	0.53	5.0	0.25	10.6
					35.5	799.0125	0.03	0.53	4.7	0.25	10.0	
					42	42.0	811.5000	0.02	0.54	3.9	0.25	8.4
						40.8	823.9875	0.03	0.55	5.0	0.26	10.7
						41.8	851.0125	0.02	0.57	4.1	0.26	8.9
						41.1	860.5000	0.03	0.57	4.8	0.27	10.3
41.1	868.9875	0.02	0.58	3.7		0.27	8.0					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS3	E	3	HAF4016A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	2.4	0.24	5.0
						35.2	769.0125	0.01	0.51	2.4	0.25	5.0
						35.0	772.0000	0.01	0.51	2.4	0.25	5.0
						34.9	774.9875	0.01	0.52	2.1	0.25	4.5
						34.6	794.0125	0.02	0.53	2.9	0.25	6.2
					35.5	799.0125	0.01	0.53	2.7	0.25	5.8	
					42	42.0	811.5000	0.01	0.54	2.5	0.25	5.3
						40.8	823.9875	0.02	0.55	3.0	0.26	6.3
						41.8	851.0125	0.01	0.57	2.1	0.26	4.6
						41.1	860.5000	0.01	0.57	2.4	0.27	5.1
41.1	868.9875	0.01	0.58	2.5		0.27	5.3					
Roof	BS4	E	3	HAF4016A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	1.5	0.24	3.1
						35.2	769.0125	0.01	0.51	1.5	0.25	3.0
						35.0	772.0000	0.01	0.51	1.3	0.25	2.8
						34.9	774.9875	0.01	0.52	1.5	0.25	3.0
						34.6	794.0125	0.01	0.53	1.2	0.25	2.5
					35.5	799.0125	0.01	0.53	1.2	0.25	2.6	
					42	42.0	811.5000	0.005	0.54	0.9	0.25	2.0
						40.8	823.9875	0.01	0.55	1.1	0.26	2.4
						41.8	851.0125	0.01	0.57	1.1	0.26	2.3
						41.1	860.5000	0.01	0.57	1.3	0.27	2.9
41.1	868.9875	0.01	0.58	1.1		0.27	2.4					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS5	E	3	HAF4016A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	1.4	0.24	3.0
						35.2	769.0125	0.01	0.51	1.4	0.25	2.9
						35.0	772.0000	0.01	0.51	1.9	0.25	3.9
						34.9	774.9875	0.01	0.52	1.9	0.25	3.9
						34.6	794.0125	0.01	0.53	1.7	0.25	3.5
					35.5	799.0125	0.01	0.53	2.1	0.25	4.5	
					42	42.0	811.5000	0.01	0.54	1.4	0.25	3.1
						40.8	823.9875	0.01	0.55	1.3	0.26	2.8
						41.8	851.0125	0.004	0.57	0.8	0.26	1.6
						41.1	860.5000	0.01	0.57	0.9	0.27	2.0
41.1	868.9875	0.004	0.58	0.7		0.27	1.6					
Roof	BS1	E	4	HAF4017A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.05	0.51	9.2	0.24	19.2
						35.2	769.0125	0.05	0.51	9.2	0.25	19.1
						35.0	772.0000	0.05	0.51	10.2	0.25	21.4
						34.9	774.9875	0.05	0.52	9.2	0.25	19.2
						34.6	794.0125	0.06	0.53	11.4	0.25	24.1
					35.5	799.0125	0.07	0.53	12.2	0.25	25.8	
					42	42.0	811.5000	0.05	0.54	8.4	0.25	17.8
						40.8	823.9875	0.04	0.55	8.0	0.26	17.0
						41.8	851.0125	0.02	0.57	4.3	0.26	9.3
						41.1	860.5000	0.04	0.57	6.2	0.27	13.4
41.1	868.9875	0.03	0.58	4.4		0.27	9.6					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS2	E	4	HAF4017A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.04	0.51	7.5	0.24	15.6
						35.2	769.0125	0.04	0.51	7.4	0.25	15.4
						35.0	772.0000	0.04	0.51	7.4	0.25	15.5
						34.9	774.9875	0.04	0.52	6.9	0.25	14.3
						34.6	794.0125	0.03	0.53	6.3	0.25	13.2
					35.5	799.0125	0.03	0.53	6.2	0.25	13.1	
					42	42.0	811.5000	0.03	0.54	4.8	0.25	10.2
						40.8	823.9875	0.04	0.55	6.5	0.26	14.0
						41.8	851.0125	0.03	0.57	4.6	0.26	10.0
						41.1	860.5000	0.03	0.57	5.9	0.27	12.7
41.1	868.9875	0.02	0.58	4.1		0.27	9.0					
Roof	BS3	E	4	HAF4017A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.02	0.51	4.2	0.24	8.7
						35.2	769.0125	0.02	0.51	4.2	0.25	8.9
						35.0	772.0000	0.02	0.51	4.0	0.25	8.3
						34.9	774.9875	0.02	0.52	3.6	0.25	7.6
						34.6	794.0125	0.03	0.53	5.1	0.25	10.8
					35.5	799.0125	0.02	0.53	4.7	0.25	9.9	
					42	42.0	811.5000	0.02	0.54	4.1	0.25	8.6
						40.8	823.9875	0.03	0.55	4.9	0.26	10.4
						41.8	851.0125	0.02	0.57	3.1	0.26	6.7
						41.1	860.5000	0.02	0.57	3.6	0.27	7.7
41.1	868.9875	0.02	0.58	3.2		0.27	7.0					

Table D.1 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	BS4	E	4	HAF4017A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	2.9	0.24	6.1
						35.2	769.0125	0.01	0.51	2.9	0.25	6.0
						35.0	772.0000	0.01	0.51	2.6	0.25	5.4
						34.9	774.9875	0.02	0.52	2.9	0.25	6.1
						34.6	794.0125	0.01	0.53	2.7	0.25	5.7
					35.5	799.0125	0.01	0.53	2.7	0.25	5.8	
					42	42.0	811.5000	0.01	0.54	1.6	0.25	3.4
						40.8	823.9875	0.01	0.55	2.0	0.26	4.3
						41.8	851.0125	0.01	0.57	1.7	0.26	3.6
						41.1	860.5000	0.01	0.57	2.2	0.27	4.7
41.1	868.9875	0.01	0.58	1.7		0.27	3.6					
Roof	BS5	E	4	HAF4017A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	2.6	0.24	5.3
						35.2	769.0125	0.01	0.51	2.6	0.25	5.4
						35.0	772.0000	0.02	0.51	3.6	0.25	7.5
						34.9	774.9875	0.02	0.52	3.4	0.25	7.2
						34.6	794.0125	0.02	0.53	3.0	0.25	6.4
					35.5	799.0125	0.02	0.53	3.8	0.25	8.0	
					42	42.0	811.5000	0.01	0.54	2.5	0.25	5.3
						40.8	823.9875	0.01	0.55	2.5	0.26	5.3
						41.8	851.0125	0.01	0.57	1.2	0.26	2.6
						41.1	860.5000	0.01	0.57	1.5	0.27	3.2
41.1	868.9875	0.01	0.58	1.2		0.27	2.7					

Table D.2

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Passenger

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	PB	E	1	HAF4013A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.02	0.51	3.2	0.24	6.7
						35.2	769.0125	0.02	0.51	3.2	0.25	6.6
						35.0	772.0000	0.02	0.51	3.5	0.25	7.4
						34.9	774.9875	0.02	0.52	3.6	0.25	7.4
						34.6	794.0125	0.02	0.53	3.3	0.25	7.0
					35.5	799.0125	0.02	0.53	2.9	0.25	6.2	
					42	42.0	811.5000	0.01	0.54	2.5	0.25	5.2
						40.8	823.9875	0.02	0.55	2.9	0.26	6.1
						41.8	851.0125	0.01	0.57	1.2	0.26	2.7
						41.1	860.5000	0.01	0.57	1.8	0.27	3.9
41.1	868.9875	0.01	0.58	1.4		0.27	3.1					
Roof	PB	E	2	HAF4014A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.001	0.51	0.3	0.24	0.6
						35.2	769.0125	0.002	0.51	0.3	0.25	0.6
						35.0	772.0000	0.001	0.51	0.3	0.25	0.6
						34.9	774.9875	0.001	0.52	0.2	0.25	0.5
						34.6	794.0125	0.004	0.53	0.8	0.25	1.6
					35.5	799.0125	0.01	0.53	1.0	0.25	2.2	
					42	42.0	811.5000	0.01	0.54	1.9	0.25	4.1
						40.8	823.9875	0.01	0.55	2.3	0.26	5.0
						41.8	851.0125	0.01	0.57	1.9	0.26	4.0
						41.1	860.5000	0.01	0.57	1.3	0.27	2.8
41.1	868.9875	0.01	0.58	1.8		0.27	4.0					

Table D.2 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Passenger

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	PB	E	3	HAF4016A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.02	0.51	3.1	0.24	6.5
						35.2	769.0125	0.02	0.51	3.5	0.25	7.3
						35.0	772.0000	0.02	0.51	3.3	0.25	6.8
						34.9	774.9875	0.02	0.52	3.3	0.25	6.8
						34.6	794.0125	0.02	0.53	3.6	0.25	7.6
					35.5	799.0125	0.02	0.53	2.9	0.25	6.2	
					42	42.0	811.5000	0.01	0.54	2.2	0.25	4.6
						40.8	823.9875	0.02	0.55	3.4	0.26	7.2
						41.8	851.0125	0.01	0.57	1.6	0.26	3.5
						41.1	860.5000	0.01	0.57	1.5	0.27	3.3
41.1	868.9875	0.01	0.58	1.6		0.27	3.4					
Roof	PB	E	4	HAF4017A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.03	0.51	5.8	0.24	12.1
						35.2	769.0125	0.03	0.51	5.2	0.25	10.9
						35.0	772.0000	0.03	0.51	5.5	0.25	11.5
						34.9	774.9875	0.03	0.52	5.5	0.25	11.6
						34.6	794.0125	0.03	0.53	5.4	0.25	11.3
					35.5	799.0125	0.03	0.53	5.0	0.25	10.6	
					42	42.0	811.5000	0.02	0.54	3.8	0.25	8.1
						40.8	823.9875	0.02	0.55	3.9	0.26	8.4
						41.8	851.0125	0.01	0.57	2.1	0.26	4.6
						41.1	860.5000	0.02	0.57	3.3	0.27	7.2
41.1	868.9875	0.01	0.58	2.0		0.27	4.4					

Table D.2 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Passenger

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	PF	E	1	HAF4013A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	1.7	0.24	3.4
						35.2	769.0125	0.01	0.51	2.0	0.25	4.1
						35.0	772.0000	0.01	0.51	1.8	0.25	3.9
						34.9	774.9875	0.01	0.52	1.9	0.25	4.1
						34.6	794.0125	0.01	0.53	1.4	0.25	3.0
					35.5	799.0125	0.01	0.53	1.3	0.25	2.7	
					42	42.0	811.5000	0.01	0.54	1.4	0.25	3.0
						40.8	823.9875	0.01	0.55	1.8	0.26	3.9
						41.8	851.0125	0.01	0.57	1.5	0.26	3.2
						41.1	860.5000	0.01	0.57	1.6	0.27	3.4
41.1	868.9875	0.01	0.58	1.3		0.27	2.8					
Roof	PF	E	2	HAF4014A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.002	0.51	0.3	0.24	0.6
						35.2	769.0125	0.002	0.51	0.3	0.25	0.7
						35.0	772.0000	0.002	0.51	0.4	0.25	0.8
						34.9	774.9875	0.002	0.52	0.3	0.25	0.6
						34.6	794.0125	0.003	0.53	0.6	0.25	1.2
					35.5	799.0125	0.004	0.53	0.7	0.25	1.4	
					42	42.0	811.5000	0.01	0.54	1.1	0.25	2.4
						40.8	823.9875	0.01	0.55	1.5	0.26	3.2
						41.8	851.0125	0.01	0.57	2.0	0.26	4.4
						41.1	860.5000	0.01	0.57	1.8	0.27	4.0
41.1	868.9875	0.01	0.58	1.4		0.27	3.1					

Table D.2 (Continued)

MPE assessment for APX6500 7/800MHz - roof mounted antenna – Passenger

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Roof	PF	E	3	HAF4016A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.01	0.51	1.8	0.24	3.7
						35.2	769.0125	0.01	0.51	1.9	0.25	4.0
						35.0	772.0000	0.01	0.51	1.4	0.25	3.0
						34.9	774.9875	0.01	0.52	1.6	0.25	3.4
						34.6	794.0125	0.01	0.53	1.3	0.25	2.8
					35.5	799.0125	0.01	0.53	1.3	0.25	2.8	
					42	42.0	811.5000	0.01	0.54	1.4	0.25	3.0
						40.8	823.9875	0.01	0.55	1.9	0.26	4.1
						41.8	851.0125	0.01	0.57	1.4	0.26	3.1
						41.1	860.5000	0.01	0.57	1.4	0.27	3.1
41.1	868.9875	0.01	0.58	1.2		0.27	2.5					
Roof	PF	E	4	HAF4017A, 1/4 Wave, (762-870MHz)	36	35.2	762.0125	0.02	0.51	3.5	0.24	7.4
						35.2	769.0125	0.02	0.51	3.4	0.25	7.2
						35.0	772.0000	0.02	0.51	3.3	0.25	6.9
						34.9	774.9875	0.01	0.52	2.8	0.25	5.9
						34.6	794.0125	0.01	0.53	2.8	0.25	5.9
					35.5	799.0125	0.01	0.53	2.3	0.25	4.8	
					42	42.0	811.5000	0.01	0.54	2.1	0.25	4.4
						40.8	823.9875	0.02	0.55	3.0	0.26	6.4
						41.8	851.0125	0.01	0.57	2.1	0.26	4.5
						41.1	860.5000	0.01	0.57	2.0	0.27	4.3
41.1	868.9875	0.01	0.58	1.5		0.27	3.3					

Table D.3
APX6500 7/800MHz MPE Results for FCC

Note:

Blue fonts: Frequencies not regulated by FCC.

Pmax (W)
36, 52

Pinitial (W)

FCCLimit (mW/cm²)

35.2	35.2	35.0	34.9	34.6	35.5	42.0	40.8	41.8	41.1	41.1
0.51	0.51	0.51	0.52	0.53	0.53	0.54	0.55	0.57	0.57	0.58

Table	Test Post.	Trunk / Roof	E/H Field	Antenna No.	F1	F2	F3	F4	F5	F6	F7	F8	F9	F10	F11
					762.0125	769.0125	772.0000	774.9875	794.0125	799.0125	811.5000	823.9875	851.0125	860.5000	868.9875
D.1	BS1	Roof	E	1	0.04	0.04	0.05	0.04	0.05	0.05	0.04	0.04	0.03	0.04	0.03
D.1	BS2	Roof	E	1	0.03	0.03	0.03	0.03	0.03	0.03	0.02	0.03	0.03	0.03	0.03
D.1	BS3	Roof	E	1	0.01	0.01	0.01	0.01	0.02	0.02	0.01	0.02	0.01	0.01	0.01
D.1	BS4	Roof	E	1	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
D.1	BS5	Roof	E	1	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.004	0.01	0.004
D.1	BS1	Roof	E	2	0.03	0.03	0.03	0.03	0.05	0.05	0.04	0.04	0.02	0.03	0.03
D.1	BS2	Roof	E	2	0.02	0.02	0.02	0.02	0.02	0.02	0.02	0.03	0.03	0.03	0.02
D.1	BS3	Roof	E	2	0.01	0.01	0.01	0.01	0.02	0.02	0.02	0.02	0.02	0.02	0.02
D.1	BS4	Roof	E	2	0.004	0.004	0.004	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
D.1	BS5	Roof	E	2	0.004	0.004	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
D.1	BS1	Roof	E	3	0.04	0.04	0.04	0.04	0.05	0.05	0.04	0.04	0.03	0.04	0.03
D.1	BS2	Roof	E	3	0.03	0.03	0.03	0.03	0.03	0.03	0.02	0.03	0.02	0.03	0.02
D.1	BS3	Roof	E	3	0.01	0.01	0.01	0.01	0.02	0.01	0.01	0.02	0.01	0.01	0.01
D.1	BS4	Roof	E	3	0.01	0.01	0.01	0.01	0.01	0.01	0.005	0.01	0.01	0.01	0.01
D.1	BS5	Roof	E	3	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.004	0.01	0.004
D.1	BS1	Roof	E	4	0.05	0.05	0.05	0.05	0.06	0.07	0.05	0.04	0.02	0.04	0.03
D.1	BS2	Roof	E	4	0.04	0.04	0.04	0.04	0.03	0.03	0.03	0.04	0.03	0.03	0.02
D.1	BS3	Roof	E	4	0.02	0.02	0.02	0.02	0.03	0.02	0.02	0.03	0.02	0.02	0.02
D.1	BS4	Roof	E	4	0.01	0.01	0.01	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.01
D.1	BS5	Roof	E	4	0.01	0.01	0.02	0.02	0.02	0.02	0.01	0.01	0.01	0.01	0.01
D.2	PB	Roof	E	1	0.02	0.02	0.02	0.02	0.02	0.02	0.01	0.02	0.01	0.01	0.01
D.2	PB	Roof	E	2	0.001	0.002	0.001	0.001	0.004	0.01	0.01	0.01	0.01	0.01	0.01
D.2	PB	Roof	E	3	0.02	0.02	0.02	0.02	0.02	0.02	0.01	0.02	0.01	0.01	0.01
D.2	PB	Roof	E	4	0.03	0.03	0.03	0.03	0.03	0.03	0.02	0.02	0.01	0.02	0.01
D.2	PF	Roof	E	1	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
D.2	PF	Roof	E	2	0.002	0.002	0.002	0.002	0.003	0.004	0.01	0.01	0.01	0.01	0.01
D.2	PF	Roof	E	3	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
D.2	PF	Roof	E	4	0.02	0.02	0.02	0.01	0.01	0.01	0.01	0.02	0.01	0.01	0.01

Appendix E – MPE Test Results Summary for Companion Device (DVR VHF)

Table E.1

MPE assessment for DVR VHF - trunk mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk/ Roof	Test Post.	E/H Field	Antenn a No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Trunk	BS1	E	9	HAD4006A, 1/4 Wave (136- 144MHz)	6.0	5.82	140.0000	0.013	0.20	6.5	0.13	10.1
						5.83	144.0000	0.012	0.20	6.1	0.13	9.5
Trunk	BS1	H	9	HAD4006A, 1/4 Wave (136- 144MHz)	6.0	5.82	140.0000	0.012	0.20	5.8	0.13	9.0
						5.83	144.0000	0.010	0.20	5.1	0.13	7.9
Trunk	BS2	E	9	HAD4006A, 1/4 Wave (136- 144MHz)	6.0	5.82	140.0000	0.020	0.20	10.0	0.13	15.5
						5.83	144.0000	0.015	0.20	7.3	0.13	11.4
Trunk	BS2	H	9	HAD4006A, 1/4 Wave (136- 144MHz)	6.0	5.82	140.0000	0.019	0.20	9.6	0.13	14.8
						5.83	144.0000	0.019	0.20	9.5	0.13	14.8
Trunk	BS3	E	9	HAD4006A, 1/4 Wave (136- 144MHz)	6.0	5.82	140.0000	0.029	0.20	14.7	0.13	22.8
						5.83	144.0000	0.026	0.20	13.2	0.13	20.4
Trunk	BS3	H	9	HAD4006A, 1/4 Wave (136- 144MHz)	6.0	5.82	140.0000	0.023	0.20	11.6	0.13	18.0
						5.83	144.0000	0.015	0.20	7.6	0.13	11.8
Trunk	BS4	E	9	HAD4006A, 1/4 Wave (136- 144MHz)	6.0	5.82	140.0000	0.027	0.20	13.7	0.13	21.3
						5.83	144.0000	0.025	0.20	12.5	0.13	19.4
Trunk	BS4	H	9	HAD4006A, 1/4 Wave (136- 144MHz)	6.0	5.82	140.0000	0.022	0.20	11.1	0.13	17.1
						5.83	144.0000	0.017	0.20	8.6	0.13	13.3
Trunk	BS5	E	9	HAD4006A, 1/4 Wave (136- 144MHz)	6.0	5.82	140.0000	0.019	0.20	9.7	0.13	15.1
						5.83	144.0000	0.021	0.20	10.4	0.13	16.2
Trunk	BS5	H	9	HAD4006A, 1/4 Wave (136- 144MHz)	6.0	5.82	140.0000	0.018	0.20	9.1	0.13	14.1
						5.83	144.0000	0.019	0.20	9.3	0.13	14.3
Trunk	BS1	E	10	HAD4007A, 1/4 Wave (144- 150.8MHz)	6.0	5.83	144.0000	0.015	0.20	7.5	0.13	11.6
						5.81	150.8000	0.006	0.20	3.1	0.13	4.7
Trunk	BS1	H	10	HAD4007A, 1/4 Wave (144- 150.8MHz)	6.0	5.83	144.0000	0.010	0.20	5.1	0.13	7.9
						5.81	150.8000	0.012	0.20	5.9	0.13	9.1
Trunk	BS2	E	10	HAD4007A, 1/4 Wave (144- 150.8MHz)	6.0	5.83	144.0000	0.017	0.20	8.5	0.13	13.1
						5.81	150.8000	0.012	0.20	5.8	0.13	9.0

Table E.1 (Continued)

MPE assessment for DVR VHF - trunk mounted antenna – Bystander

Note:

Blue fonts: Frequencies not regulated by FCC.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Trunk	BS2	H	10	HAD4007A, 1/4 Wave (144-150.8MHz)	6.0	5.83	144.0000	0.018	0.20	8.8	0.13	13.7
						5.81	150.8000	0.015	0.20	7.3	0.13	11.4
Trunk	BS3	E	10	HAD4007A, 1/4 Wave (144-150.8MHz)	6.0	5.83	144.0000	0.028	0.20	13.9	0.13	21.5
						5.81	150.8000	0.029	0.20	14.7	0.13	22.8
Trunk	BS3	H	10	HAD4007A, 1/4 Wave (144-150.8MHz)	6.0	5.83	144.0000	0.016	0.20	8.0	0.13	12.3
						5.81	150.8000	0.024	0.20	11.8	0.13	18.3
Trunk	BS4	E	10	HAD4007A, 1/4 Wave (144-150.8MHz)	6.0	5.83	144.0000	0.027	0.20	13.5	0.13	20.9
						5.81	150.8000	0.034	0.20	17.1	0.13	26.5
Trunk	BS4	H	10	HAD4007A, 1/4 Wave (144-150.8MHz)	6.0	5.83	144.0000	0.017	0.20	8.5	0.13	13.2
						5.81	150.8000	0.027	0.20	13.4	0.13	20.8
Trunk	BS5	E	10	HAD4007A, 1/4 Wave (144-150.8MHz)	6.0	5.83	144.0000	0.022	0.20	11.0	0.13	17.0
						5.81	150.8000	0.015	0.20	7.6	0.13	11.7
Trunk	BS5	H	10	HAD4007A, 1/4 Wave (144-150.8MHz)	6.0	5.83	144.0000	0.019	0.20	9.4	0.13	14.6
						5.81	150.8000	0.019	0.20	9.7	0.13	15.1
Trunk	BS1	E	11	HAD4008A, 1/4 Wave (150.8-162MHz)	6.0	5.81	150.8000	0.007	0.20	3.4	0.13	5.2
						5.92	156.4000	0.005	0.20	2.6	0.13	4.0
						5.88	162.0000	0.005	0.20	2.3	0.13	3.5
Trunk	BS1	H	11	HAD4008A, 1/4 Wave (150.8-162MHz)	6.0	5.81	150.8000	0.012	0.20	6.0	0.13	9.3
						5.92	156.4000	0.011	0.20	5.3	0.13	8.2
						5.88	162.0000	0.013	0.20	6.4	0.13	9.9
Trunk	BS2	E	11	HAD4008A, 1/4 Wave (150.8-162MHz)	6.0	5.81	150.8000	0.011	0.20	5.6	0.13	8.6
						5.92	156.4000	0.016	0.20	8.2	0.13	12.7
						5.88	162.0000	0.022	0.20	10.9	0.13	16.8
Trunk	BS2	H	11	HAD4008A, 1/4 Wave (150.8-162MHz)	6.0	5.81	150.8000	0.013	0.20	6.7	0.13	10.5
						5.92	156.4000	0.015	0.20	7.5	0.13	11.6
						5.88	162.0000	0.017	0.20	8.7	0.13	13.6

Table E.1 (Continued)

MPE assessment for DVR VHF - trunk mounted antenna – Bystander

Notes:

Results in bold font are configurations with highest percentage of limits.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Trunk	BS3	E	11	HAD4008A, 1/4 Wave (150.8-162MHz)	6.0	5.81	150.8000	0.027	0.20	13.4	0.13	20.8
						5.92	156.4000	0.035	0.20	17.3	0.13	26.8
						5.88	162.0000	0.042	0.20	21.0	0.13	32.5
Trunk	BS3	H	11	HAD4008A, 1/4 Wave (150.8-162MHz)	6.0	5.81	150.8000	0.021	0.20	10.6	0.13	16.4
						5.92	156.4000	0.016	0.20	8.2	0.13	12.7
						5.88	162.0000	0.027	0.20	13.7	0.13	21.2
Trunk	BS4	E	11	HAD4008A, 1/4 Wave (150.8-162MHz)	6.0	5.81	150.8000	0.030	0.20	15.1	0.13	23.3
						5.92	156.4000	0.028	0.20	13.8	0.13	21.4
						5.88	162.0000	0.041	0.20	20.5	0.13	31.7
Trunk	BS4	H	11	HAD4008A, 1/4 Wave (150.8-162MHz)	6.0	5.81	150.8000	0.027	0.20	13.4	0.13	20.8
						5.92	156.4000	0.023	0.20	11.5	0.13	17.8
						5.88	162.0000	0.029	0.20	14.7	0.13	22.7
Trunk	BS5	E	11	HAD4008A, 1/4 Wave (150.8-162MHz)	6.0	5.81	150.8000	0.014	0.20	6.9	0.13	10.7
						5.92	156.4000	0.020	0.20	9.8	0.13	15.2
						5.88	162.0000	0.020	0.20	10.0	0.13	15.6
Trunk	BS5	H	11	HAD4008A, 1/4 Wave (150.8-162MHz)	6.0	5.81	150.8000	0.019	0.20	9.5	0.13	14.7
						5.92	156.4000	0.021	0.20	10.7	0.13	16.6
						5.88	162.0000	0.022	0.20	10.9	0.13	16.9
Trunk	BS1	E	12	HAD4009A, 1/4 Wave (162-174MHz)	6.0	5.88	162.0000	0.005	0.20	2.5	0.13	3.9
						5.95	167.7000	0.004	0.20	1.8	0.13	2.8
						5.91	173.4000	0.007	0.20	3.4	0.13	5.2
Trunk	BS1	H	12	HAD4009A, 1/4 Wave (162-174MHz)	6.0	5.88	162.0000	0.010	0.20	5.1	0.13	7.9
						5.95	167.7000	0.010	0.20	5.2	0.13	8.0
						5.91	173.4000	0.011	0.20	5.5	0.13	8.5
Trunk	BS2	E	12	HAD4009A, 1/4 Wave (162-174MHz)	6.0	5.88	162.0000	0.015	0.20	7.4	0.13	11.4
						5.95	167.7000	0.019	0.20	9.4	0.13	14.6
						5.91	173.4000	0.014	0.20	6.8	0.13	10.5

Table E.1 (Continued)

MPE assessment for DVR VHF - trunk mounted antenna - Bystander

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Trunk	BS2	H	12	HAD4009A, 1/4 Wave (162-174MHz)	6.0	5.88	162.0000	0.015	0.20	7.5	0.13	11.6
						5.95	167.7000	0.013	0.20	6.4	0.13	9.9
						5.91	173.4000	0.013	0.20	6.5	0.13	10.1
Trunk	BS3	E	12	HAD4009A, 1/4 Wave (162-174MHz)	6.0	5.88	162.0000	0.029	0.20	14.7	0.13	22.8
						5.95	167.7000	0.040	0.20	19.9	0.13	30.8
						5.91	173.4000	0.033	0.20	16.3	0.13	25.2
Trunk	BS3	H	12	HAD4009A, 1/4 Wave (162-174MHz)	6.0	5.88	162.0000	0.020	0.20	9.9	0.13	15.4
						5.95	167.7000	0.027	0.20	13.5	0.13	21.0
						5.91	173.4000	0.026	0.20	13.0	0.13	20.1
Trunk	BS4	E	12	HAD4009A, 1/4 Wave (162-174MHz)	6.0	5.88	162.0000	0.029	0.20	14.3	0.13	22.2
						5.95	167.7000	0.041	0.20	20.3	0.13	31.4
						5.91	173.4000	0.034	0.20	17.0	0.13	26.3
Trunk	BS4	H	12	HAD4009A, 1/4 Wave (162-174MHz)	6.0	5.88	162.0000	0.020	0.20	10.2	0.13	15.8
						5.95	167.7000	0.031	0.20	15.4	0.13	23.9
						5.91	173.4000	0.031	0.20	15.5	0.13	24.0
Trunk	BS5	E	12	HAD4009A, 1/4 Wave (162-174MHz)	6.0	5.88	162.0000	0.014	0.20	7.0	0.13	10.9
						5.95	167.7000	0.020	0.20	10.2	0.13	15.8
						5.91	173.4000	0.012	0.20	6.2	0.13	9.6
Trunk	BS5	H	12	HAD4009A, 1/4 Wave (162-174MHz)	6.0	5.88	162.0000	0.017	0.20	8.3	0.13	12.8
						5.95	167.7000	0.019	0.20	9.4	0.13	14.5
						5.91	173.4000	0.016	0.20	8.2	0.13	12.8

Table E.2

MPE assessment for DVR VHF– trunk mounted antenna – Passenger

Notes:

Blue fonts: Frequencies not regulated by FCC.

Results in bold font are configurations with highest percentage of limits.

Trunk / Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Trunk	PB	E	9	HAD4006A, 1/4 Wave (136-144MHz)	6.0	5.82	140.0000	0.196	0.20	97.8	0.13	151.5
						5.83	144.0000	0.168	0.20	83.8	0.13	129.8
Trunk	PB	H	9	HAD4006A, 1/4 Wave (136-144MHz)	6.0	5.82	140.0000	0.111	0.20	55.4	0.13	85.8
						5.83	144.0000	0.093	0.20	46.6	0.13	72.2
Trunk	PB	E	10	HAD4007A, 1/4 Wave (144-150.8MHz)	6.0	5.83	144.0000	0.146	0.20	73.0	0.13	113.0
						5.81	150.8000	0.103	0.20	51.4	0.13	79.7
Trunk	PB	H	10	HAD4007A, 1/4 Wave (144-150.8MHz)	6.0	5.83	144.0000	0.074	0.20	37.2	0.13	57.6
						5.81	150.8000	0.096	0.20	47.9	0.13	74.2
Trunk	PB	E	11	HAD4008A, 1/4 Wave (150.8-162MHz)	6.0	5.81	150.8000	0.098	0.20	49.0	0.13	75.9
						5.92	156.4000	0.137	0.20	68.4	0.13	106.0
						5.88	162.0000	0.230	0.20	114.8	0.13	177.9
Trunk	PB	H	11	HAD4008A, 1/4 Wave (150.8-162MHz)	6.0	5.81	150.8000	0.076	0.20	37.8	0.13	58.6
						5.92	156.4000	0.142	0.20	71.2	0.13	110.3
						5.88	162.0000	0.175	0.20	87.3	0.13	135.2
Trunk	PB	E	12	HAD4009A, 1/4 Wave (162-174MHz)	6.0	5.88	162.0000	0.172	0.20	86.2	0.13	133.6
						5.95	167.7000	0.161	0.20	80.3	0.13	124.4
						5.91	173.4000	0.185	0.20	92.3	0.13	143.0
Trunk	PB	H	12	HAD4009A, 1/4 Wave (162-174MHz)	6.0	5.88	162.0000	0.119	0.20	59.5	0.13	92.2
						5.95	167.7000	0.159	0.20	79.3	0.13	122.9
						5.91	173.4000	0.093	0.20	46.5	0.13	72.0

Table E.2 (Continued)

MPE assessment for DVR VHF– trunk mounted antenna – Passenger

Notes:

Blue fonts: Frequencies not regulated by FCC.

Results in bold font are configurations with highest percentage of limits.

Trunk/ Roof	Test Post.	E/H Field	Antenna No.	Antenna Model	Max Pwr (W)	Initial Pwr (W)	Tx Freq (MHz)	Max Calc. P.D. (mW/cm ²)	FCC Limit	% To FCC Spec Limit	ISED Limit	% To ISED Spec Limit
Trunk	PF	E	9	HAD4006A, 1/4 Wave (136-144MHz)	6.0	5.82	140.0000	0.014	0.20	7.2	0.13	11.1
						5.83	144.0000	0.018	0.20	9.1	0.13	14.1
Trunk	PF	H	9	HAD4006A, 1/4 Wave (136-144MHz)	6.0	5.82	140.0000	0.021	0.20	10.7	0.13	16.6
						5.83	144.0000	0.024	0.20	12.1	0.13	18.7
Trunk	PF	E	10	HAD4007A, 1/4 Wave (144-150.8MHz)	6.0	5.83	144.0000	0.021	0.20	10.3	0.13	16.0
						5.81	150.8000	0.023	0.20	11.4	0.13	17.7
Trunk	PF	H	10	HAD4007A, 1/4 Wave (144-150.8MHz)	6.0	5.83	144.0000	0.025	0.20	12.3	0.13	19.1
						5.81	150.8000	0.029	0.20	14.5	0.13	22.4
Trunk	PF	E	11	HAD4008A, 1/4 Wave (150.8-162MHz)	6.0	5.81	150.8000	0.025	0.20	12.3	0.13	19.0
						5.92	156.4000	0.033	0.20	16.5	0.13	25.6
						5.88	162.0000	0.033	0.20	16.5	0.13	25.5
Trunk	PF	H	11	HAD4008A, 1/4 Wave (150.8-162MHz)	6.0	5.81	150.8000	0.028	0.20	13.9	0.13	21.5
						5.92	156.4000	0.036	0.20	18.0	0.13	27.8
						5.88	162.0000	0.035	0.20	17.4	0.13	27.0
Trunk	PF	E	12	HAD4009A, 1/4 Wave (162-174MHz)	6.0	5.88	162.0000	0.023	0.20	11.6	0.13	18.0
						5.95	167.7000	0.024	0.20	12.2	0.13	18.9
						5.91	173.4000	0.027	0.20	13.5	0.13	20.9
Trunk	PF	H	12	HAD4009A, 1/4 Wave (162-174MHz)	6.0	5.88	162.0000	0.028	0.20	14.0	0.13	21.6
						5.95	167.7000	0.033	0.20	16.5	0.13	25.6
						5.91	173.4000	0.021	0.20	10.6	0.13	16.4

Table E.3
DVR VHF MPE Results for FCC

Note:
Blue fonts: Frequencies not regulated by FCC.

Pmax (W)	6	Pinitial (W)	5.82	5.83	5.81	5.92	5.88	5.95	5.91
			FCCLimit (mW/cm ²)	0.20	0.20	0.20	0.20	0.20	0.20

Table	Test Post.	Angle	Trunk / Roof	E/H Field	Antenna No.	f1	f2	f3	f4	f5	f6	f7
						140.0000	144.0000	150.8000	156.4000	162.0000	167.7000	173.4000
E.1	BS1		Trunk	E	9	0.013	0.012					
E.1	BS1		Trunk	H	9	0.012	0.010					
E.1	BS2		Trunk	E	9	0.020	0.015					
E.1	BS2		Trunk	H	9	0.019	0.019					
E.1	BS3		Trunk	E	9	0.029	0.026					
E.1	BS3		Trunk	H	9	0.023	0.015					
E.1	BS4		Trunk	E	9	0.027	0.025					
E.1	BS4		Trunk	H	9	0.022	0.017					
E.1	BS5		Trunk	E	9	0.019	0.021					
E.1	BS5		Trunk	H	9	0.018	0.019					
E.1	BS1		Trunk	E	10		0.015	0.006				
E.1	BS1		Trunk	H	10		0.010	0.012				
E.1	BS2		Trunk	E	10		0.017	0.012				
E.1	BS2		Trunk	H	10		0.018	0.015				
E.1	BS3		Trunk	E	10		0.028	0.029				
E.1	BS3		Trunk	H	10		0.016	0.024				
E.1	BS4		Trunk	E	10		0.027	0.034				
E.1	BS4		Trunk	H	10		0.017	0.027				
E.1	BS5		Trunk	E	10		0.022	0.015				
E.1	BS5		Trunk	H	10		0.019	0.019				
E.1	BS1		Trunk	E	11			0.007	0.005	0.005		
E.1	BS1		Trunk	H	11			0.012	0.011	0.013		
E.1	BS2		Trunk	E	11			0.011	0.016	0.022		
E.1	BS2		Trunk	H	11			0.013	0.015	0.017		
E.1	BS3		Trunk	E	11			0.027	0.035	0.042		
E.1	BS3		Trunk	H	11			0.021	0.016	0.027		
E.1	BS4		Trunk	E	11			0.030	0.028	0.041		
E.1	BS4		Trunk	H	11			0.027	0.023	0.029		
E.1	BS5		Trunk	E	11			0.014	0.020	0.020		
E.1	BS5		Trunk	H	11			0.019	0.021	0.022		
E.1	BS1		Trunk	E	12					0.005	0.004	0.007
E.1	BS1		Trunk	H	12					0.010	0.010	0.011
E.1	BS2		Trunk	E	12					0.015	0.019	0.014
E.1	BS2		Trunk	H	12					0.015	0.013	0.013
E.1	BS3		Trunk	E	12					0.029	0.040	0.033
E.1	BS3		Trunk	H	12					0.020	0.027	0.026
E.1	BS4		Trunk	E	12					0.029	0.041	0.034
E.1	BS4		Trunk	H	12					0.020	0.031	0.031
E.1	BS5		Trunk	E	12					0.014	0.020	0.012
E.1	BS5		Trunk	H	12					0.017	0.019	0.016

Table E.3 (Continued)
DVR VHF MPE Results for FCC

Note:

Blue fonts: Frequencies not regulated by FCC.

Pmax (W)	6	Pinitial (W)	5.82	5.83	5.81	5.92	5.88	5.95	5.91
		FCCLimit (mW/cm ²)	0.20	0.20	0.20	0.20	0.20	0.20	0.54

Table	Test Post.	Angle	Trunk / Roof	E/H Field	Antenna No.	f1	f2	f3	f4	f5	f6	f7
						140.0000	144.0000	150.8000	156.4000	162.0000	167.7000	173.4000
E.2	PB		Trunk	E	9	0.196	0.168					
E.2	PB		Trunk	H	9	0.011	0.093					
E.2	PB		Trunk	E	10		0.146	0.103				
E.2	PB		Trunk	H	10		0.074	0.096				
E.2	PB		Trunk	E	11			0.098	0.137	0.230		
E.2	PB		Trunk	H	11			0.076	0.142	0.175		
E.2	PB		Trunk	E	12					0.172	0.161	0.185
E.2	PB		Trunk	H	12					0.119	0.159	0.093
E.2	PF		Trunk	E	9	0.014	0.018					
E.2	PF		Trunk	H	9	0.021	0.024					
E.2	PF		Trunk	E	10		0.021	0.023				
E.2	PF		Trunk	H	10		0.025	0.029				
E.2	PF		Trunk	E	11			0.025	0.033	0.033		
E.2	PF		Trunk	H	11			0.028	0.036	0.035		
E.2	PF		Trunk	E	12					0.023	0.024	0.027
E.2	PF		Trunk	H	12					0.028	0.033	0.021

Appendix F – MPE Test Results Summary for APX6500 7/800MHz

Table F.1

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS1	0.0030	0.0120	0.0110	0.0130	0.0210	0.0450	0.0780	0.2120	0.2480	0.2030	0.5	0.083	0.04	0.04
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS1	0.0030	0.0120	0.0110	0.0130	0.0220	0.0440	0.0780	0.2110	0.2500	0.2060	0.5	0.084	0.04	0.04
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS1	0.0030	0.0090	0.0070	0.0110	0.0200	0.0610	0.0990	0.2360	0.2640	0.2170	0.5	0.092	0.05	0.05
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS1	0.0030	0.0070	0.0060	0.0170	0.0190	0.0570	0.0900	0.2200	0.2300	0.1800	0.5	0.082	0.04	0.04
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS1	0.0050	0.0060	0.0100	0.0120	0.0120	0.0440	0.0810	0.2700	0.3100	0.1980	0.5	0.095	0.05	0.05
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS1	0.0040	0.0060	0.0080	0.0100	0.0180	0.0560	0.1110	0.2660	0.3240	0.2050	0.5	0.101	0.05	0.05
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS1	0.0020	0.0070	0.0090	0.0120	0.0110	0.0280	0.0890	0.2080	0.2460	0.1770	0.5	0.079	0.04	0.04
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS1	0.0020	0.0040	0.0050	0.0080	0.0080	0.0300	0.0740	0.1660	0.2280	0.1890	0.5	0.072	0.04	0.04
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS1	0.0010	0.0020	0.0050	0.0110	0.0250	0.0280	0.0300	0.1040	0.1770	0.1760	0.5	0.058	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS1	0.0040	0.0030	0.0040	0.0120	0.0220	0.0390	0.0560	0.1670	0.2170	0.2180	0.5	0.077	0.04	0.04
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS1	0.0030	0.0040	0.0080	0.0150	0.0180	0.0150	0.0480	0.1440	0.1830	0.1550	0.5	0.062	0.03	0.03

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS2	0.0020	0.0010	0.0080	0.0130	0.0260	0.0310	0.0670	0.1090	0.1590	0.1750	0.5	0.058	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS2	0.0020	0.0010	0.0080	0.0130	0.0260	0.0300	0.0670	0.1110	0.1610	0.1750	0.5	0.059	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS2	0.0010	0.0030	0.0090	0.0180	0.0250	0.0260	0.0650	0.1260	0.1820	0.1410	0.5	0.059	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS2	0.0000	0.0040	0.0080	0.0130	0.0160	0.0230	0.0520	0.0930	0.1800	0.1410	0.5	0.052	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS2	0.0000	0.0090	0.0080	0.0150	0.0240	0.0200	0.0400	0.0850	0.1480	0.1790	0.5	0.053	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS2	0.0010	0.0060	0.0060	0.0140	0.0280	0.0200	0.0480	0.0940	0.1510	0.1510	0.5	0.052	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS2	0.0010	0.0030	0.0030	0.0070	0.0180	0.0210	0.0450	0.0900	0.1250	0.1560	0.5	0.047	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS2	0.0010	0.0020	0.0030	0.0080	0.0140	0.0230	0.0660	0.1400	0.1660	0.1470	0.5	0.058	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS2	0.0010	0.0030	0.0080	0.0090	0.0090	0.0390	0.0620	0.1250	0.1520	0.1350	0.5	0.056	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS2	0.0010	0.0020	0.0060	0.0110	0.0060	0.0280	0.0530	0.1600	0.2010	0.1470	0.5	0.064	0.03	0.03
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS2	0.0000	0.0010	0.0020	0.0050	0.0100	0.0320	0.0560	0.1180	0.1440	0.1210	0.5	0.051	0.03	0.03

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS3	0.0050	0.0090	0.0110	0.0160	0.0100	0.0070	0.0290	0.0410	0.0430	0.0630	0.5	0.023	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS3	0.0050	0.0100	0.0110	0.0150	0.0110	0.0070	0.0280	0.0410	0.0430	0.0620	0.5	0.023	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS3	0.0060	0.0070	0.0120	0.0130	0.0140	0.0080	0.0210	0.0310	0.0390	0.0760	0.5	0.022	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS3	0.0020	0.0050	0.0110	0.0110	0.0140	0.0110	0.0280	0.0300	0.0330	0.0510	0.5	0.019	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS3	0.0020	0.0080	0.0080	0.0090	0.0100	0.0160	0.0390	0.0560	0.0770	0.0760	0.5	0.030	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS3	0.0020	0.0030	0.0060	0.0060	0.0060	0.0150	0.0420	0.0490	0.0720	0.0980	0.5	0.030	0.01	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS3	0.0030	0.0050	0.0060	0.0060	0.0090	0.0120	0.0330	0.0460	0.0630	0.0820	0.5	0.027	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS3	0.0040	0.0070	0.0100	0.0100	0.0140	0.0170	0.0340	0.0570	0.0710	0.0770	0.5	0.031	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS3	0.0030	0.0030	0.0080	0.0130	0.0080	0.0130	0.0310	0.0420	0.0730	0.0630	0.5	0.026	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS3	0.0030	0.0040	0.0070	0.0180	0.0170	0.0160	0.0280	0.0310	0.0580	0.0630	0.5	0.025	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS3	0.0020	0.0040	0.0080	0.0150	0.0120	0.0120	0.0260	0.0310	0.0650	0.0950	0.5	0.028	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS4	0.0030	0.0060	0.0050	0.0100	0.0110	0.0090	0.0080	0.0240	0.0320	0.0330	0.5	0.014	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS4	0.0030	0.0060	0.0050	0.0100	0.0110	0.0090	0.0080	0.0230	0.0330	0.0320	0.5	0.014	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS4	0.0020	0.0050	0.0070	0.0090	0.0100	0.0110	0.0120	0.0230	0.0250	0.0260	0.5	0.013	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS4	0.0030	0.0040	0.0040	0.0090	0.0100	0.0110	0.0120	0.0230	0.0300	0.0300	0.5	0.013	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS4	0.0020	0.0040	0.0040	0.0060	0.0110	0.0120	0.0100	0.0180	0.0230	0.0300	0.5	0.012	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS4	0.0010	0.0060	0.0020	0.0090	0.0100	0.0090	0.0090	0.0260	0.0250	0.0240	0.5	0.012	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS4	0.0010	0.0030	0.0020	0.0050	0.0090	0.0070	0.0110	0.0240	0.0190	0.0260	0.5	0.011	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS4	0.0020	0.0040	0.0040	0.0070	0.0090	0.0050	0.0120	0.0330	0.0270	0.0260	0.5	0.013	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS4	0.0020	0.0030	0.0020	0.0040	0.0100	0.0080	0.0100	0.0270	0.0260	0.0250	0.5	0.012	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS4	0.0020	0.0020	0.0000	0.0040	0.0100	0.0140	0.0130	0.0320	0.0370	0.0400	0.5	0.016	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS4	0.0010	0.0030	0.0040	0.0070	0.0090	0.0080	0.0150	0.0300	0.0240	0.0240	0.5	0.013	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS5	0.0000	0.0030	0.0030	0.0030	0.0060	0.0070	0.0100	0.0230	0.0330	0.0190	0.5	0.011	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS5	0.0000	0.0030	0.0030	0.0030	0.0060	0.0070	0.0100	0.0230	0.0340	0.0180	0.5	0.011	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS5	0.0010	0.0020	0.0010	0.0030	0.0080	0.0130	0.0130	0.0210	0.0450	0.0330	0.5	0.014	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS5	0.0020	0.0010	0.0020	0.0080	0.0130	0.0140	0.0130	0.0170	0.0390	0.0360	0.5	0.014	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS5	0.0010	0.0010	0.0010	0.0050	0.0120	0.0160	0.0140	0.0320	0.0400	0.0290	0.5	0.015	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS5	0.0000	0.0010	0.0020	0.0050	0.0120	0.0180	0.0210	0.0470	0.0540	0.0350	0.5	0.019	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS5	0.0000	0.0010	0.0020	0.0050	0.0120	0.0180	0.0210	0.0470	0.0540	0.0350	0.5	0.020	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS5	0.0000	0.0010	0.0020	0.0090	0.0130	0.0110	0.0090	0.0210	0.0260	0.0180	0.5	0.011	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS5	0.0020	0.0010	0.0010	0.0060	0.0090	0.0110	0.0070	0.0130	0.0170	0.0140	0.5	0.008	0.00	0.00
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS5	0.0010	0.0000	0.0000	0.0040	0.0070	0.0120	0.0050	0.0160	0.0310	0.0190	0.5	0.010	0.00	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS5	0.0010	0.0000	0.0010	0.0030	0.0040	0.0060	0.0060	0.0170	0.0220	0.0150	0.5	0.008	0.00	0.00

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS1	0.0000	0.0000	0.0000	0.0000	0.0040	0.0000	0.0070	0.0830	0.2440	0.2470	0.5	0.058	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS1	0.0000	0.0000	0.0000	0.0000	0.0040	0.0010	0.0070	0.0820	0.2460	0.2480	0.5	0.058	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS1	0.0000	0.0000	0.0000	0.0000	0.0020	0.0010	0.0130	0.1020	0.2690	0.2780	0.5	0.066	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS1	0.0000	0.0000	0.0000	0.0010	0.0010	0.0020	0.0170	0.1170	0.2600	0.2320	0.5	0.062	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS1	0.0000	0.0010	0.0010	0.0010	0.0040	0.0110	0.0540	0.2500	0.3200	0.2500	0.5	0.089	0.04	0.05
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS1	0.0010	0.0000	0.0000	0.0030	0.0020	0.0130	0.0710	0.2790	0.3750	0.2780	0.5	0.102	0.05	0.05
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS1	0.0010	0.0010	0.0010	0.0060	0.0060	0.0130	0.0790	0.2440	0.2760	0.2250	0.5	0.086	0.04	0.04
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS1	0.0010	0.0020	0.0020	0.0050	0.0100	0.0320	0.1000	0.1990	0.2000	0.1570	0.5	0.072	0.04	0.04
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS1	0.0030	0.0030	0.0100	0.0080	0.0300	0.0380	0.0480	0.1250	0.0870	0.1010	0.5	0.047	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS1	0.0060	0.0030	0.0040	0.0130	0.0190	0.0390	0.0730	0.1460	0.1080	0.1280	0.5	0.056	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS1	0.0020	0.0020	0.0080	0.0150	0.0300	0.0290	0.0600	0.1390	0.0920	0.1070	0.5	0.050	0.03	0.03

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS2	0.0000	0.0000	0.0000	0.0000	0.0000	0.0020	0.0100	0.0380	0.1130	0.1870	0.5	0.034	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS2	0.0000	0.0000	0.0000	0.0000	0.0000	0.0020	0.0090	0.0370	0.1100	0.1820	0.5	0.034	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS2	0.0000	0.0000	0.0000	0.0010	0.0010	0.0030	0.0130	0.0560	0.1300	0.1620	0.5	0.036	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS2	0.0000	0.0000	0.0000	0.0010	0.0020	0.0030	0.0160	0.0590	0.1400	0.1650	0.5	0.038	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS2	0.0000	0.0010	0.0020	0.0030	0.0090	0.0140	0.0360	0.0730	0.1220	0.1380	0.5	0.040	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS2	0.0000	0.0020	0.0020	0.0050	0.0150	0.0140	0.0330	0.0860	0.1420	0.1200	0.5	0.042	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS2	0.0000	0.0010	0.0020	0.0030	0.0090	0.0160	0.0490	0.0900	0.1260	0.0930	0.5	0.039	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS2	0.0000	0.0030	0.0050	0.0060	0.0100	0.0250	0.0730	0.1430	0.1730	0.1150	0.5	0.056	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS2	0.0010	0.0010	0.0030	0.0100	0.0070	0.0380	0.0910	0.1660	0.1160	0.0820	0.5	0.053	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS2	0.0010	0.0020	0.0030	0.0100	0.0070	0.0330	0.0950	0.1890	0.1280	0.0870	0.5	0.058	0.03	0.03
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS2	0.0000	0.0020	0.0090	0.0040	0.0110	0.0400	0.0760	0.1320	0.0820	0.0500	0.5	0.042	0.02	0.02

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS3	0.0000	0.0000	0.0000	0.0020	0.0010	0.0030	0.0120	0.0230	0.0380	0.0610	0.5	0.014	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS3	0.0000	0.0000	0.0000	0.0020	0.0010	0.0030	0.0120	0.0230	0.0390	0.0590	0.5	0.014	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS3	0.0000	0.0000	0.0000	0.0010	0.0000	0.0030	0.0110	0.0220	0.0420	0.0640	0.5	0.014	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS3	0.0010	0.0010	0.0020	0.0020	0.0030	0.0040	0.0110	0.0190	0.0350	0.0490	0.5	0.013	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS3	0.0010	0.0040	0.0050	0.0060	0.0060	0.0130	0.0460	0.0820	0.1090	0.0790	0.5	0.035	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS3	0.0010	0.0030	0.0050	0.0060	0.0070	0.0180	0.0490	0.0690	0.1080	0.0940	0.5	0.036	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS3	0.0020	0.0040	0.0100	0.0080	0.0180	0.0320	0.0660	0.0990	0.1500	0.1060	0.5	0.050	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS3	0.0030	0.0030	0.0090	0.0120	0.0180	0.0380	0.0910	0.0900	0.1110	0.0630	0.5	0.044	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS3	0.0030	0.0060	0.0140	0.0340	0.0210	0.0260	0.0820	0.0970	0.0950	0.0510	0.5	0.044	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS3	0.0050	0.0040	0.0100	0.0190	0.0310	0.0330	0.0580	0.0580	0.0700	0.0370	0.5	0.034	0.02	0.02
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS3	0.0030	0.0040	0.0110	0.0190	0.0220	0.0370	0.0680	0.0790	0.1140	0.0510	0.5	0.043	0.02	0.02

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS4	0.0010	0.0000	0.0010	0.0000	0.0010	0.0010	0.0050	0.0160	0.0260	0.0360	0.5	0.009	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS4	0.0010	0.0000	0.0000	0.0000	0.0010	0.0010	0.0050	0.0160	0.0270	0.0370	0.5	0.009	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS4	0.0010	0.0010	0.0020	0.0020	0.0010	0.0020	0.0070	0.0150	0.0200	0.0350	0.5	0.009	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS4	0.0010	0.0020	0.0010	0.0050	0.0070	0.0090	0.0130	0.0190	0.0240	0.0390	0.5	0.012	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS4	0.0020	0.0030	0.0030	0.0070	0.0110	0.0130	0.0160	0.0260	0.0280	0.0370	0.5	0.015	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS4	0.0010	0.0040	0.0020	0.0040	0.0100	0.0110	0.0180	0.0250	0.0270	0.0300	0.5	0.013	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS4	0.0030	0.0040	0.0040	0.0050	0.0100	0.0090	0.0150	0.0320	0.0280	0.0330	0.5	0.014	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS4	0.0010	0.0020	0.0040	0.0070	0.0070	0.0060	0.0230	0.0520	0.0400	0.0410	0.5	0.019	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS4	0.0020	0.0060	0.0020	0.0110	0.0180	0.0150	0.0360	0.0690	0.0360	0.0400	0.5	0.024	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS4	0.0010	0.0030	0.0030	0.0090	0.0180	0.0230	0.0430	0.0710	0.0430	0.0480	0.5	0.027	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS4	0.0020	0.0030	0.0020	0.0090	0.0130	0.0150	0.0310	0.0530	0.0340	0.0310	0.5	0.020	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS5	0.0000	0.0000	0.0010	0.0010	0.0010	0.0010	0.0080	0.0230	0.0250	0.0250	0.5	0.008	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35	CW	E	0.99	BS5	0.0000	0.0000	0.0010	0.0010	0.0000	0.0020	0.0080	0.0220	0.0250	0.0250	0.5	0.008	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS5	0.0000	0.0000	0.0010	0.0010	0.0020	0.0060	0.0150	0.0300	0.0390	0.0380	0.5	0.013	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS5	0.0000	0.0020	0.0010	0.0020	0.0070	0.0130	0.0170	0.0250	0.0340	0.0330	0.5	0.013	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS5	0.0020	0.0010	0.0000	0.0050	0.0120	0.0160	0.0210	0.0530	0.0430	0.0300	0.5	0.018	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS5	0.0010	0.0000	0.0020	0.0080	0.0150	0.0230	0.0390	0.0760	0.0650	0.0500	0.5	0.028	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS5	0.0000	0.0000	0.0020	0.0090	0.0160	0.0200	0.0270	0.0650	0.0550	0.0430	0.5	0.024	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS5	0.0020	0.0010	0.0050	0.0170	0.0220	0.0220	0.0230	0.0540	0.0460	0.0350	0.5	0.023	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS5	0.0020	0.0020	0.0070	0.0130	0.0110	0.0150	0.0130	0.0360	0.0330	0.0220	0.5	0.016	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS5	0.0020	0.0030	0.0050	0.0080	0.0120	0.0150	0.0160	0.0380	0.0280	0.0200	0.5	0.015	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS5	0.0010	0.0030	0.0040	0.0100	0.0100	0.0140	0.0160	0.0380	0.0260	0.0190	0.5	0.015	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	762.0125	36.0	35	CW	E	0.98	BS1	0.0030	0.0130	0.0100	0.0140	0.0220	0.0440	0.0770	0.1980	0.2460	0.2000	0.5	0.081	0.04	0.04
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	769.0125	36	35.2	CW	E	0.99	BS1	0.0030	0.0130	0.0100	0.0140	0.0220	0.0450	0.0760	0.1960	0.2450	0.1990	0.5	0.081	0.04	0.04
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	772.0000	36.0	35	CW	E	0.99	BS1	0.0030	0.0130	0.0100	0.0140	0.0220	0.0450	0.0760	0.1960	0.2450	0.1990	0.5	0.081	0.04	0.04
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	774.9875	36.0	35	CW	E	0.99	BS1	0.0020	0.0070	0.0050	0.0170	0.0200	0.0580	0.0860	0.2170	0.2240	0.1760	0.5	0.080	0.04	0.04
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	794.0125	36.0	35	CW	E	1.00	BS1	0.0060	0.0050	0.0110	0.0130	0.0120	0.0400	0.0810	0.2690	0.3020	0.2020	0.5	0.094	0.05	0.05
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	799.0125	36.0	36	CW	E	1.00	BS1	0.0030	0.0060	0.0090	0.0110	0.0160	0.0560	0.1190	0.2750	0.3200	0.2060	0.5	0.102	0.05	0.05
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	811.5000	42.0	42	CW	E	1.01	BS1	0.0020	0.0060	0.0090	0.0130	0.0110	0.0270	0.0910	0.2070	0.2480	0.1760	0.5	0.080	0.04	0.04
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	823.9875	42.0	41	CW	E	1.01	BS1	0.0020	0.0040	0.0060	0.0090	0.0070	0.0320	0.0800	0.1670	0.2290	0.1770	0.5	0.072	0.04	0.04
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	851.0125	42.0	42	CW	E	1.03	BS1	0.0010	0.0010	0.0050	0.0110	0.0240	0.0300	0.0270	0.0970	0.1560	0.1510	0.5	0.052	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	860.5000	42.0	41	CW	E	1.04	BS1	0.0040	0.0030	0.0040	0.0120	0.0220	0.0410	0.0490	0.1540	0.1940	0.1930	0.5	0.070	0.04	0.04
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	868.9875	42.0	41	CW	E	1.04	BS1	0.0030	0.0030	0.0060	0.0130	0.0170	0.0130	0.0410	0.1260	0.1700	0.1420	0.5	0.056	0.03	0.03

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	762.0125	36.0	35	CW	E	0.98	BS2	0.0020	0.0010	0.0060	0.0130	0.0250	0.0320	0.0670	0.1050	0.1520	0.1630	0.5	0.056	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	769.0125	36	35.2	CW	E	0.99	BS2	0.0020	0.0010	0.0060	0.0120	0.0260	0.0340	0.0660	0.1070	0.1520	0.1640	0.5	0.056	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	772.0000	36.0	35	CW	E	0.99	BS2	0.0010	0.0030	0.0080	0.0180	0.0270	0.0280	0.0600	0.1190	0.1760	0.1280	0.5	0.056	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	774.9875	36.0	35	CW	E	0.99	BS2	0.0000	0.0040	0.0080	0.0120	0.0160	0.0220	0.0490	0.0940	0.1750	0.1300	0.5	0.050	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	794.0125	36.0	35	CW	E	1.00	BS2	0.0000	0.0080	0.0090	0.0170	0.0250	0.0190	0.0420	0.0800	0.1360	0.1750	0.5	0.051	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	799.0125	36.0	36	CW	E	1.00	BS2	0.0010	0.0060	0.0080	0.0150	0.0270	0.0170	0.0460	0.0910	0.1460	0.1420	0.5	0.050	0.02	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	811.5000	42.0	42	CW	E	1.01	BS2	0.0010	0.0030	0.0030	0.0090	0.0160	0.0160	0.0410	0.0810	0.1140	0.1400	0.5	0.043	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	823.9875	42.0	41	CW	E	1.01	BS2	0.0010	0.0030	0.0020	0.0070	0.0110	0.0250	0.0630	0.1300	0.1540	0.1310	0.5	0.053	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	851.0125	42.0	42	CW	E	1.03	BS2	0.0010	0.0020	0.0060	0.0070	0.0070	0.0330	0.0550	0.1040	0.1230	0.1150	0.5	0.047	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	860.5000	42.0	41	CW	E	1.04	BS2	0.0000	0.0020	0.0040	0.0090	0.0050	0.0250	0.0480	0.1360	0.1700	0.1170	0.5	0.053	0.03	0.03
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	868.9875	42.0	41	CW	E	1.04	BS2	0.0000	0.0000	0.0020	0.0030	0.0100	0.0280	0.0480	0.0900	0.1180	0.1020	0.5	0.042	0.02	0.02

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)
APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	762.0125	36.0	35	CW	E	0.98	BS3	0.0060	0.0100	0.0110	0.0160	0.0110	0.0070	0.0280	0.0440	0.0470	0.0630	0.5	0.024	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	769.0125	36	35.2	CW	E	0.99	BS3	0.0060	0.0100	0.0110	0.0150	0.0110	0.0060	0.0280	0.0440	0.0470	0.0630	0.5	0.024	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	772.0000	36.0	35	CW	E	0.99	BS3	0.0080	0.0080	0.0110	0.0120	0.0130	0.0060	0.0230	0.0350	0.0460	0.0790	0.5	0.024	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	774.9875	36.0	35	CW	E	0.99	BS3	0.0040	0.0040	0.0130	0.0130	0.0140	0.0100	0.0310	0.0340	0.0380	0.0560	0.5	0.021	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	794.0125	36.0	35	CW	E	1.00	BS3	0.0030	0.0080	0.0120	0.0100	0.0100	0.0170	0.0360	0.0550	0.0760	0.0720	0.5	0.030	0.01	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	799.0125	36.0	36	CW	E	1.00	BS3	0.0030	0.0040	0.0070	0.0050	0.0080	0.0160	0.0380	0.0460	0.0690	0.0920	0.5	0.029	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	811.5000	42.0	42	CW	E	1.01	BS3	0.0040	0.0050	0.0070	0.0060	0.0060	0.0120	0.0360	0.0510	0.0650	0.0750	0.5	0.027	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	823.9875	42.0	41	CW	E	1.01	BS3	0.0030	0.0070	0.0090	0.0100	0.0130	0.0180	0.0410	0.0590	0.0740	0.0770	0.5	0.032	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	851.0125	42.0	42	CW	E	1.03	BS3	0.0030	0.0040	0.0080	0.0130	0.0100	0.0110	0.0280	0.0360	0.0620	0.0590	0.5	0.024	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	860.5000	42.0	41	CW	E	1.04	BS3	0.0030	0.0060	0.0080	0.0170	0.0160	0.0150	0.0300	0.0350	0.0600	0.0660	0.5	0.027	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	868.9875	42.0	41	CW	E	1.04	BS3	0.0020	0.0040	0.0070	0.0130	0.0100	0.0120	0.0290	0.0330	0.0640	0.0940	0.5	0.028	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	762.0125	36.0	35	CW	E	0.98	BS4	0.0030	0.0070	0.0050	0.0110	0.0130	0.0090	0.0090	0.0250	0.0330	0.0330	0.5	0.015	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	769.0125	36	35.2	CW	E	0.99	BS4	0.0030	0.0070	0.0050	0.0110	0.0120	0.0100	0.0080	0.0250	0.0330	0.0340	0.5	0.015	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	772.0000	36.0	35	CW	E	0.99	BS4	0.0020	0.0050	0.0070	0.0100	0.0120	0.0110	0.0120	0.0230	0.0250	0.0280	0.5	0.013	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	774.9875	36.0	35	CW	E	0.99	BS4	0.0030	0.0040	0.0040	0.0100	0.0110	0.0110	0.0120	0.0260	0.0330	0.0330	0.5	0.015	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	794.0125	36.0	35	CW	E	1.00	BS4	0.0020	0.0040	0.0040	0.0070	0.0120	0.0120	0.0100	0.0190	0.0210	0.0320	0.5	0.012	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	799.0125	36.0	36	CW	E	1.00	BS4	0.0020	0.0070	0.0030	0.0100	0.0110	0.0090	0.0100	0.0270	0.0250	0.0250	0.5	0.013	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	811.5000	42.0	42	CW	E	1.01	BS4	0.0010	0.0020	0.0020	0.0040	0.0080	0.0050	0.0100	0.0240	0.0180	0.0250	0.5	0.010	0.00	0.00
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	823.9875	42.0	41	CW	E	1.01	BS4	0.0020	0.0040	0.0040	0.0060	0.0070	0.0050	0.0120	0.0280	0.0240	0.0240	0.5	0.012	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	851.0125	42.0	42	CW	E	1.03	BS4	0.0010	0.0030	0.0010	0.0050	0.0110	0.0090	0.0110	0.0290	0.0240	0.0240	0.5	0.012	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	860.5000	42.0	41	CW	E	1.04	BS4	0.0010	0.0020	0.0000	0.0030	0.0090	0.0120	0.0110	0.0310	0.0370	0.0390	0.5	0.015	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	868.9875	42.0	41	CW	E	1.04	BS4	0.0010	0.0020	0.0040	0.0070	0.0090	0.0070	0.0140	0.0290	0.0230	0.0220	0.5	0.012	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	762.0125	36.0	35	CW	E	0.98	BS5	0.0010	0.0040	0.0050	0.0030	0.0070	0.0100	0.0130	0.0320	0.0440	0.0250	0.5	0.014	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	769.0125	36	35.2	CW	E	0.99	BS5	0.0010	0.0040	0.0040	0.0030	0.0070	0.0100	0.0130	0.0320	0.0420	0.0240	0.5	0.014	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	772.0000	36.0	35	CW	E	0.99	BS5	0.0010	0.0040	0.0020	0.0040	0.0120	0.0160	0.0170	0.0310	0.0570	0.0450	0.5	0.019	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	774.9875	36.0	35	CW	E	0.99	BS5	0.0030	0.0030	0.0030	0.0100	0.0150	0.0180	0.0160	0.0230	0.0490	0.0490	0.5	0.019	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	794.0125	36.0	35	CW	E	1.00	BS5	0.0020	0.0010	0.0010	0.0070	0.0130	0.0180	0.0150	0.0360	0.0470	0.0300	0.5	0.017	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	799.0125	36.0	36	CW	E	1.00	BS5	0.0000	0.0010	0.0020	0.0070	0.0150	0.0200	0.0230	0.0540	0.0620	0.0400	0.5	0.022	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	811.5000	42.0	42	CW	E	1.01	BS5	0.0010	0.0000	0.0030	0.0100	0.0150	0.0150	0.0140	0.0370	0.0400	0.0200	0.5	0.016	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	823.9875	42.0	41	CW	E	1.01	BS5	0.0010	0.0020	0.0030	0.0110	0.0140	0.0140	0.0110	0.0250	0.0320	0.0240	0.5	0.014	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	851.0125	42.0	42	CW	E	1.03	BS5	0.0020	0.0010	0.0020	0.0060	0.0090	0.0110	0.0060	0.0140	0.0180	0.0140	0.5	0.009	0.00	0.00
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	860.5000	42.0	41	CW	E	1.04	BS5	0.0000	0.0010	0.0000	0.0040	0.0060	0.0120	0.0060	0.0170	0.0350	0.0190	0.5	0.010	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	868.9875	42.0	41	CW	E	1.04	BS5	0.0010	0.0000	0.0010	0.0030	0.0050	0.0070	0.0060	0.0180	0.0220	0.0170	0.5	0.008	0.00	0.00

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS1	0.0040	0.0160	0.0150	0.0270	0.0390	0.0920	0.1520	0.2960	0.2290	0.0590	0.5	0.091	0.05	0.05
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36	35.2	CW	E	0.99	BS1	0.0040	0.0160	0.0150	0.0270	0.0400	0.0920	0.1530	0.2930	0.2290	0.0600	0.5	0.092	0.05	0.05
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS1	0.0040	0.0180	0.0120	0.0210	0.0340	0.1170	0.1850	0.3320	0.2420	0.0700	0.5	0.102	0.05	0.05
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS1	0.0050	0.0150	0.0100	0.0230	0.0340	0.1070	0.1600	0.3280	0.2010	0.0470	0.5	0.092	0.05	0.05
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS1	0.0100	0.0110	0.0180	0.0250	0.0250	0.0740	0.1720	0.4320	0.3160	0.0830	0.5	0.116	0.06	0.06
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS1	0.0070	0.0100	0.0130	0.0190	0.0230	0.0870	0.2260	0.4670	0.3340	0.0970	0.5	0.128	0.06	0.07
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS1	0.0030	0.0090	0.0130	0.0190	0.0180	0.0420	0.1570	0.3250	0.2410	0.0760	0.5	0.091	0.05	0.05
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS1	0.0040	0.0060	0.0090	0.0130	0.0140	0.0620	0.1560	0.2680	0.2240	0.0850	0.5	0.085	0.04	0.04
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS1	0.0020	0.0020	0.0070	0.0110	0.0350	0.0470	0.0480	0.1320	0.1320	0.0550	0.5	0.049	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS1	0.0060	0.0030	0.0050	0.0150	0.0310	0.0620	0.0830	0.2020	0.1860	0.0780	0.5	0.070	0.03	0.04
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS1	0.0030	0.0030	0.0070	0.0160	0.0230	0.0220	0.0600	0.1620	0.1330	0.0520	0.5	0.050	0.03	0.03

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS2	0.0010	0.0030	0.0140	0.0200	0.0490	0.0640	0.1250	0.1990	0.1880	0.0930	0.5	0.074	0.04	0.04
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36	35.2	CW	E	0.99	BS2	0.0010	0.0030	0.0140	0.0200	0.0480	0.0640	0.1250	0.1980	0.1860	0.0900	0.5	0.074	0.04	0.04
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS2	0.0020	0.0050	0.0130	0.0300	0.0490	0.0600	0.1190	0.1990	0.2050	0.0690	0.5	0.074	0.04	0.04
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS2	0.0000	0.0040	0.0140	0.0220	0.0330	0.0490	0.1040	0.1850	0.2040	0.0790	0.5	0.069	0.03	0.04
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS2	0.0000	0.0110	0.0150	0.0260	0.0480	0.0410	0.0830	0.1390	0.1630	0.1150	0.5	0.064	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS2	0.0010	0.0100	0.0140	0.0250	0.0480	0.0330	0.0910	0.1690	0.1680	0.0910	0.5	0.065	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS2	0.0010	0.0040	0.0060	0.0120	0.0240	0.0320	0.0760	0.1350	0.1400	0.0860	0.5	0.052	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS2	0.0010	0.0050	0.0070	0.0130	0.0180	0.0460	0.1160	0.2080	0.1940	0.0810	0.5	0.070	0.03	0.04
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS2	0.0010	0.0030	0.0080	0.0110	0.0090	0.0470	0.0880	0.1530	0.1320	0.0570	0.5	0.052	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS2	0.0010	0.0020	0.0050	0.0150	0.0080	0.0390	0.0900	0.2170	0.1870	0.0700	0.5	0.066	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS2	0.0000	0.0010	0.0050	0.0040	0.0140	0.0420	0.0760	0.1370	0.1180	0.0530	0.5	0.047	0.02	0.02

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.		Test Pos.	MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS3	0.0130	0.0200	0.0250	0.0320	0.0220	0.0170	0.0590	0.0800	0.0830	0.0730	0.5	0.042	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36	35.2	CW	E	0.99	BS3	0.0130	0.0200	0.0240	0.0310	0.0230	0.0170	0.0600	0.0830	0.0860	0.0740	0.5	0.043	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS3	0.0130	0.0160	0.0240	0.0260	0.0250	0.0170	0.0520	0.0630	0.0730	0.0920	0.5	0.040	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS3	0.0080	0.0090	0.0250	0.0250	0.0230	0.0220	0.0680	0.0670	0.0560	0.0660	0.5	0.037	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS3	0.0060	0.0120	0.0220	0.0160	0.0160	0.0350	0.0830	0.1110	0.1310	0.0900	0.5	0.052	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS3	0.0060	0.0100	0.0150	0.0110	0.0180	0.0350	0.0800	0.0910	0.1120	0.1130	0.5	0.049	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS3	0.0060	0.0080	0.0120	0.0120	0.0130	0.0280	0.0740	0.0890	0.1090	0.0850	0.5	0.044	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS3	0.0050	0.0100	0.0160	0.0200	0.0270	0.0400	0.0800	0.1020	0.1220	0.0900	0.5	0.052	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS3	0.0040	0.0060	0.0140	0.0220	0.0210	0.0210	0.0500	0.0580	0.0840	0.0590	0.5	0.035	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS3	0.0040	0.0080	0.0140	0.0240	0.0250	0.0270	0.0580	0.0610	0.0900	0.0760	0.5	0.040	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS3	0.0030	0.0050	0.0110	0.0170	0.0160	0.0240	0.0480	0.0540	0.0910	0.0840	0.5	0.037	0.02	0.02

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS4	0.0090	0.0110	0.0130	0.0220	0.0310	0.0250	0.0250	0.0550	0.0570	0.0470	0.5	0.029	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36	35.2	CW	E	0.99	BS4	0.0090	0.0110	0.0110	0.0220	0.0310	0.0240	0.0250	0.0530	0.0570	0.0470	0.5	0.029	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS4	0.0070	0.0110	0.0130	0.0160	0.0260	0.0270	0.0300	0.0480	0.0450	0.0390	0.5	0.026	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS4	0.0070	0.0140	0.0120	0.0170	0.0260	0.0270	0.0320	0.0610	0.0530	0.0450	0.5	0.029	0.01	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS4	0.0060	0.0110	0.0100	0.0230	0.0270	0.0200	0.0270	0.0540	0.0530	0.0470	0.5	0.028	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS4	0.0060	0.0130	0.0120	0.0220	0.0250	0.0230	0.0270	0.0540	0.0540	0.0510	0.5	0.029	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS4	0.0030	0.0070	0.0040	0.0110	0.0180	0.0130	0.0230	0.0400	0.0260	0.0260	0.5	0.017	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS4	0.0050	0.0070	0.0040	0.0100	0.0170	0.0100	0.0250	0.0470	0.0400	0.0450	0.5	0.021	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS4	0.0020	0.0060	0.0020	0.0070	0.0170	0.0110	0.0220	0.0480	0.0330	0.0340	0.5	0.019	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS4	0.0020	0.0040	0.0030	0.0050	0.0100	0.0160	0.0340	0.0650	0.0500	0.0480	0.5	0.025	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS4	0.0020	0.0050	0.0030	0.0080	0.0160	0.0140	0.0240	0.0440	0.0330	0.0340	0.5	0.019	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.1 (Continued)

APX6500 7/800MHz - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35	CW	E	0.98	BS5	0.0030	0.0080	0.0090	0.0100	0.0150	0.0180	0.0230	0.0620	0.0760	0.0340	0.5	0.025	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36	35.2	CW	E	0.99	BS5	0.0030	0.0090	0.0090	0.0090	0.0140	0.0190	0.0240	0.0650	0.0770	0.0340	0.5	0.026	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35	CW	E	0.99	BS5	0.0030	0.0090	0.0060	0.0120	0.0220	0.0310	0.0330	0.0720	0.1120	0.0630	0.5	0.036	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	35	CW	E	0.99	BS5	0.0060	0.0100	0.0070	0.0200	0.0310	0.0350	0.0260	0.0550	0.0940	0.0630	0.5	0.034	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	35	CW	E	1.00	BS5	0.0040	0.0030	0.0040	0.0180	0.0280	0.0330	0.0310	0.0770	0.0770	0.0340	0.5	0.031	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	36	CW	E	1.00	BS5	0.0010	0.0020	0.0050	0.0170	0.0300	0.0410	0.0440	0.1070	0.1050	0.0460	0.5	0.040	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42	CW	E	1.01	BS5	0.0020	0.0010	0.0050	0.0170	0.0240	0.0270	0.0270	0.0700	0.0650	0.0280	0.5	0.027	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	41	CW	E	1.01	BS5	0.0020	0.0030	0.0070	0.0190	0.0280	0.0300	0.0220	0.0500	0.0620	0.0360	0.5	0.026	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	42	CW	E	1.03	BS5	0.0050	0.0020	0.0050	0.0150	0.0130	0.0140	0.0090	0.0250	0.0300	0.0150	0.5	0.014	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41	CW	E	1.04	BS5	0.0030	0.0010	0.0030	0.0080	0.0110	0.0180	0.0130	0.0340	0.0460	0.0220	0.5	0.016	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41	CW	E	1.04	BS5	0.0020	0.0010	0.0030	0.0060	0.0090	0.0130	0.0140	0.0330	0.0340	0.0210	0.5	0.014	0.01	0.01

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table F.2

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35.2	CW	E	0.98	PB	0.036	0.024	0.038	0.5	0.032	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35.2	CW	E	0.99	PB	0.033	0.026	0.038	0.5	0.032	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35.0	CW	E	0.99	PB	0.035	0.031	0.041	0.5	0.035	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	34.9	CW	E	0.99	PB	0.036	0.035	0.037	0.5	0.036	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	34.6	CW	E	1.00	PB	0.042	0.036	0.024	0.5	0.034	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	35.5	CW	E	1.00	PB	0.034	0.033	0.025	0.5	0.031	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42.0	CW	E	1.01	PB	0.024	0.031	0.024	0.5	0.027	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	40.8	CW	E	1.01	PB	0.024	0.015	0.052	0.5	0.031	0.02	0.02
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	41.8	CW	E	1.03	PB	0.016	0.012	0.013	0.5	0.014	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41.1	CW	E	1.04	PB	0.021	0.022	0.016	0.5	0.020	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41.1	CW	E	1.04	PB	0.016	0.018	0.013	0.5	0.016	0.01	0.01

Notes:

MPE calculations are defined in section 15.0

Blue fonts: Frequencies not regulated by FCC.

Table F.2 (Continued)

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35.2	CW	E	0.98	PB	0.002	0.004	0.002	0.5	0.003	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35.2	CW	E	0.99	PB	0.002	0.004	0.003	0.5	0.003	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35.0	CW	E	0.99	PB	0.002	0.003	0.003	0.5	0.003	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	34.9	CW	E	0.99	PB	0.002	0.003	0.002	0.5	0.002	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	34.6	CW	E	1.00	PB	0.013	0.005	0.005	0.5	0.008	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	35.5	CW	E	1.00	PB	0.01	0.013	0.01	0.5	0.011	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42.0	CW	E	1.01	PB	0.018	0.027	0.017	0.5	0.021	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	40.8	CW	E	1.01	PB	0.018	0.013	0.043	0.5	0.025	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	41.8	CW	E	1.03	PB	0.024	0.015	0.022	0.5	0.021	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41.1	CW	E	1.04	PB	0.012	0.016	0.014	0.5	0.015	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41.1	CW	E	1.04	PB	0.028	0.017	0.015	0.5	0.021	0.01	0.01

Notes:

MPE calculations are defined in section 15.0

Blue fonts: Frequencies not regulated by FCC.

Table F.2 (Continued)

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	762.0125	36.0	35.2	CW	E	0.98	PB	0.037	0.031	0.027	0.5	0.031	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	769.0125	36.0	35.2	CW	E	0.99	PB	0.04	0.027	0.04	0.5	0.035	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	772.0000	36.0	35.0	CW	E	0.99	PB	0.033	0.027	0.039	0.5	0.033	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	774.9875	36.0	34.9	CW	E	0.99	PB	0.035	0.022	0.042	0.5	0.033	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	794.0125	36.0	34.6	CW	E	1.00	PB	0.046	0.034	0.031	0.5	0.037	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	799.0125	36.0	35.5	CW	E	1.00	PB	0.035	0.03	0.028	0.5	0.031	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	811.5000	42.0	42.0	CW	E	1.01	PB	0.02	0.026	0.024	0.5	0.023	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	823.9875	42.0	40.8	CW	E	1.01	PB	0.022	0.017	0.067	0.5	0.036	0.02	0.02
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	851.0125	42.0	41.8	CW	E	1.03	PB	0.022	0.015	0.016	0.5	0.018	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	860.5000	42.0	41.1	CW	E	1.04	PB	0.02	0.019	0.01	0.5	0.017	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	868.9875	42.0	41.1	CW	E	1.04	PB	0.025	0.014	0.012	0.5	0.018	0.01	0.01

Notes:

MPE calculations are defined in section 15.0

Blue fonts: Frequencies not regulated by FCC.

Table F.2 (Continued)

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35.2	CW	E	0.98	PB	0.066	0.04	0.07	0.5	0.058	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35.2	CW	E	0.99	PB	0.066	0.041	0.052	0.5	0.052	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35.0	CW	E	0.99	PB	0.054	0.04	0.073	0.5	0.055	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	34.9	CW	E	0.99	PB	0.055	0.041	0.072	0.5	0.055	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	34.6	CW	E	1.00	PB	0.053	0.058	0.053	0.5	0.055	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	35.5	CW	E	1.00	PB	0.06	0.053	0.045	0.5	0.053	0.03	0.03
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42.0	CW	E	1.01	PB	0.039	0.043	0.041	0.5	0.041	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	40.8	CW	E	1.01	PB	0.055	0.029	0.040	0.5	0.042	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	41.8	CW	E	1.03	PB	0.035	0.019	0.016	0.5	0.024	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41.1	CW	E	1.04	PB	0.040	0.043	0.025	0.5	0.037	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41.1	CW	E	1.04	PB	0.03	0.018	0.018	0.5	0.023	0.01	0.01

Notes:

MPE calculations are defined in section 15.0

Blue fonts: Frequencies not regulated by FCC.

Table F.2 (Continued)

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35.2	CW	E	0.98	PF	0.014	0.019	0.017	0.5	0.016	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35.2	CW	E	0.99	PF	0.016	0.025	0.019	0.5	0.020	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35.0	CW	E	0.99	PF	0.011	0.028	0.017	0.5	0.018	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	34.9	CW	E	0.99	PF	0.018	0.029	0.012	0.5	0.019	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	34.6	CW	E	1.00	PF	0.011	0.025	0.008	0.5	0.015	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	35.5	CW	E	1.00	PF	0.018	0.012	0.01	0.5	0.013	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42.0	CW	E	1.01	PF	0.013	0.018	0.015	0.5	0.015	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	40.8	CW	E	1.01	PF	0.024	0.017	0.017	0.5	0.020	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	41.8	CW	E	1.03	PF	0.02	0.016	0.013	0.5	0.017	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41.1	CW	E	1.04	PF	0.014	0.018	0.019	0.5	0.018	0.01	0.01
Roof	HAF4013A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41.1	CW	E	1.04	PF	0.018	0.014	0.01	0.5	0.015	0.01	0.01

Notes:

MPE calculations are defined in section 15.0

Blue fonts: Frequencies not regulated by FCC.

Table F.2 (Continued)

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35.2	CW	E	0.98	PF	0.002	0.004	0.003	0.5	0.003	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35.2	CW	E	0.99	PF	0.003	0.004	0.003	0.5	0.003	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35.0	CW	E	0.99	PF	0.004	0.004	0.003	0.5	0.004	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	34.9	CW	E	0.99	PF	0.004	0.003	0.002	0.5	0.003	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	34.6	CW	E	1.00	PF	0.006	0.008	0.004	0.5	0.006	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	35.5	CW	E	1.00	PF	0.004	0.010	0.007	0.5	0.007	0.00	0.00
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42.0	CW	E	1.01	PF	0.009	0.019	0.009	0.5	0.012	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	40.8	CW	E	1.01	PF	0.023	0.010	0.014	0.5	0.016	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	41.8	CW	E	1.03	PF	0.029	0.030	0.008	0.5	0.023	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41.1	CW	E	1.04	PF	0.020	0.025	0.015	0.5	0.021	0.01	0.01
Roof	HAF4014A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41.1	CW	E	1.04	PF	0.021	0.014	0.011	0.5	0.016	0.01	0.01

Notes:

MPE calculations are defined in section 15.0

Blue fonts: Frequencies not regulated by FCC.

Table F.2 (Continued)

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	762.0125	36.0	35.2	CW	E	0.98	PF	0.015	0.022	0.017	0.5	0.018	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	769.0125	36.0	35.2	CW	E	0.99	PF	0.017	0.024	0.018	0.5	0.019	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	772.0000	36.0	35.0	CW	E	0.99	PF	0.013	0.016	0.014	0.5	0.014	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	774.9875	36.0	34.9	CW	E	0.99	PF	0.01	0.026	0.013	0.5	0.016	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	794.0125	36.0	34.6	CW	E	1.00	PF	0.013	0.021	0.007	0.5	0.014	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	799.0125	36.0	35.5	CW	E	1.00	PF	0.016	0.016	0.01	0.5	0.014	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	811.5000	42.0	42.0	CW	E	1.01	PF	0.01	0.025	0.011	0.5	0.015	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	823.9875	42.0	40.8	CW	E	1.01	PF	0.023	0.018	0.019	0.5	0.020	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	851.0125	42.0	41.8	CW	E	1.03	PF	0.021	0.016	0.01	0.5	0.016	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	860.5000	42.0	41.1	CW	E	1.04	PF	0.017	0.016	0.014	0.5	0.016	0.01	0.01
Roof	HAF4016A, 1/4 Wave, (762-870MHz)	2.15	868.9875	42.0	41.1	CW	E	1.04	PF	0.016	0.014	0.008	0.5	0.013	0.01	0.01

Notes:

MPE calculations are defined in section 15.0

Blue fonts: Frequencies not regulated by FCC.

Table F.2 (Continued)

APX6500 7/800MHz - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	762.0125	36.0	35.2	CW	E	0.98	PF	0.032	0.042	0.033	0.5	0.035	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	769.0125	36.0	35.2	CW	E	0.99	PF	0.033	0.038	0.034	0.5	0.035	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	772.0000	36.0	35.0	CW	E	0.99	PF	0.029	0.038	0.033	0.5	0.033	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	774.9875	36.0	34.9	CW	E	0.99	PF	0.016	0.049	0.021	0.5	0.028	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	794.0125	36.0	34.6	CW	E	1.00	PF	0.026	0.044	0.015	0.5	0.028	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	799.0125	36.0	35.5	CW	E	1.00	PF	0.026	0.027	0.019	0.5	0.024	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	811.5000	42.0	42.0	CW	E	1.01	PF	0.014	0.035	0.018	0.5	0.022	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	823.9875	42.0	40.8	CW	E	1.01	PF	0.046	0.028	0.021	0.5	0.032	0.02	0.02
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	851.0125	42.0	41.8	CW	E	1.03	PF	0.034	0.024	0.011	0.5	0.024	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	860.5000	42.0	41.1	CW	E	1.04	PF	0.022	0.026	0.016	0.5	0.022	0.01	0.01
Roof	HAF4017A, 1/4 Wave, (762-870MHz)	5.15	868.9875	42.0	41.1	CW	E	1.04	PF	0.021	0.017	0.011	0.5	0.017	0.01	0.01

Notes:

MPE calculations are defined in section 15.0

Blue fonts: Frequencies not regulated by FCC.

Appendix G – MPE Test Results Summary for Companion Device (DVR UHF)

Table G.1

DVR VHF - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.		Test Pos.	MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)	
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Bystander (BS) Positions														
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm					
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	140.0000	6.00	5.82	CW	E	1.02	BS1	0.006	0.009	0.013	0.013	0.013	0.014	0.014	0.014	0.014	0.014	0.014	1.0	0.012	0.01	0.013
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	144.0000	6.00	5.83	CW	E	1.02	BS1	0.008	0.008	0.009	0.01	0.012	0.014	0.014	0.014	0.014	0.014	0.014	1.0	0.012	0.01	0.012
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	140.0000	6.00	5.82	CW	E	1.02	BS2	0.007	0.011	0.014	0.016	0.022	0.024	0.024	0.024	0.024	0.024	0.024	1.0	0.019	0.02	0.020
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	144.0000	6.00	5.83	CW	E	1.02	BS2	0.005	0.008	0.011	0.014	0.017	0.017	0.017	0.017	0.017	0.017	0.017	1.0	0.014	0.01	0.015
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	140.0000	6.00	5.82	CW	E	1.02	BS3	0.009	0.012	0.02	0.025	0.03	0.032	0.038	0.038	0.038	0.038	0.038	1.0	0.028	0.03	0.029
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	144.0000	6.00	5.83	CW	E	1.02	BS3	0.007	0.011	0.014	0.018	0.026	0.031	0.036	0.036	0.036	0.036	0.036	1.0	0.025	0.03	0.026
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	140.0000	6.00	5.82	CW	E	1.02	BS4	0.012	0.019	0.022	0.024	0.025	0.027	0.033	0.0333	0.033	0.033	0.033	1.0	0.026	0.03	0.027
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	144.0000	6.00	5.83	CW	E	1.02	BS4	0.01	0.017	0.02	0.02	0.021	0.027	0.031	0.031	0.031	0.031	0.031	1.0	0.024	0.02	0.025
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	140.0000	6.00	5.82	CW	E	1.02	BS5	0.01	0.01	0.01	0.014	0.016	0.021	0.026	0.026	0.026	0.026	0.026	1.0	0.019	0.02	0.019
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	144.0000	6.00	5.83	CW	E	1.02	BS5	0.015	0.015	0.015	0.015	0.019	0.024	0.024	0.024	0.024	0.024	0.024	1.0	0.020	0.02	0.021

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table G.1 (Continued)
DVR VHF - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements											DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions														
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm					
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	144.0000	6.00	5.83	CW	E	1.02	BS1	0.006	0.007	0.009	0.013	0.018	0.018	0.018	0.018	0.018	0.018	0.018	1.0	0.014	0.01	0.015
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	150.8000	6.00	5.81	CW	E	1.02	BS1	0.002	0.004	0.005	0.006	0.006	0.007	0.007	0.007	0.007	0.007	0.007	1.0	0.006	0.01	0.006
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	144.0000	6.00	5.83	CW	E	1.02	BS2	0.006	0.009	0.012	0.017	0.018	0.019	0.02	0.02	0.02	0.02	0.02	1.0	0.016	0.02	0.017
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	150.8000	6.00	5.81	CW	E	1.02	BS2	0.002	0.005	0.006	0.009	0.013	0.015	0.015	0.015	0.015	0.015	0.015	1.0	0.011	0.01	0.012
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	144.0000	6.00	5.83	CW	E	1.02	BS3	0.007	0.013	0.018	0.019	0.031	0.033	0.036	0.036	0.036	0.036	0.036	1.0	0.027	0.03	0.028
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	150.8000	6.00	5.81	CW	E	1.02	BS3	0.007	0.012	0.017	0.019	0.03	0.035	0.04	0.04	0.04	0.04	0.04	1.0	0.028	0.03	0.029
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	144.0000	6.00	5.83	CW	E	1.02	BS4	0.013	0.019	0.022	0.024	0.026	0.029	0.031	0.031	0.031	0.031	0.031	1.0	0.026	0.03	0.027
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	150.8000	6.00	5.81	CW	E	1.02	BS4	0.013	0.013	0.024	0.025	0.03	0.044	0.044	0.044	0.044	0.044	0.044	1.0	0.033	0.03	0.034
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	144.0000	6.00	5.83	CW	E	1.02	BS5	0.014	0.016	0.016	0.016	0.018	0.025	0.026	0.026	0.026	0.026	0.026	1.0	0.021	0.02	0.022
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	150.8000	6.00	5.81	CW	E	1.02	BS5	0.008	0.008	0.009	0.009	0.015	0.019	0.019	0.019	0.019	0.019	0.019	1.0	0.014	0.01	0.015

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table G.1 (Continued)
DVR VHF - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.		Test Pos.	MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	150.8000	6.00	5.81	CW	E	1.02	BS1	0.003	0.003	0.006	0.007	0.007	0.007	0.007	0.007	0.008	0.009	1.0	0.006	0.01	0.007
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	156.4000	6.00	5.92	CW	E	1.02	BS1	0.003	0.004	0.005	0.005	0.005	0.005	0.005	0.006	0.006	0.006	1.0	0.005	0.01	0.005
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	162.0000	6.00	5.88	CW	E	1.02	BS1	0.003	0.004	0.004	0.004	0.004	0.005	0.005	0.005	0.005	0.005	1.0	0.004	0.00	0.005
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	150.8000	6.00	5.81	CW	E	1.02	BS2	0.002	0.006	0.007	0.01	0.012	0.013	0.014	0.014	0.014	0.014	1.0	0.011	0.01	0.011
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	156.4000	6.00	5.92	CW	E	1.02	BS2	0.005	0.009	0.01	0.017	0.017	0.02	0.02	0.02	0.02	0.02	1.0	0.016	0.02	0.016
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	162.0000	6.00	5.88	CW	E	1.02	BS2	0.006	0.009	0.011	0.021	0.027	0.027	0.027	0.027	0.027	0.027	1.0	0.021	0.02	0.022
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	150.8000	6.00	5.81	CW	E	1.02	BS3	0.006	0.011	0.017	0.018	0.027	0.032	0.036	0.036	0.036	0.036	1.0	0.026	0.03	0.027
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	156.4000	6.00	5.92	CW	E	1.02	BS3	0.009	0.016	0.021	0.021	0.028	0.044	0.049	0.049	0.049	0.049	1.0	0.034	0.03	0.035
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	162.0000	6.00	5.88	CW	E	1.02	BS3	0.014	0.021	0.027	0.031	0.051	0.051	0.052	0.052	0.052	0.052	1.0	0.040	0.041	0.042
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	150.8000	6.00	5.81	CW	E	1.02	BS4	0.012	0.018	0.021	0.022	0.025	0.032	0.039	0.039	0.039	0.039	1.0	0.029	0.03	0.030
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	156.4000	6.00	5.92	CW	E	1.02	BS4	0.011	0.017	0.021	0.023	0.029	0.03	0.034	0.034	0.034	0.034	1.0	0.027	0.03	0.028
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	162.0000	6.00	5.88	CW	E	1.02	BS4	0.016	0.025	0.03	0.031	0.038	0.049	0.051	0.051	0.051	0.051	1.0	0.039	0.04	0.041

MPE calculations are defined in section 15.0.

Table G.1 (Continued)
DVR VHF - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.		Test Pos.	MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	150.8000	6.00	5.81	CW	E	1.02	BS5	0.007	0.007	0.007	0.007	0.013	0.018	0.018	0.018	0.018	0.018	1.0	0.013	0.01	0.014
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	156.4000	6.00	5.92	CW	E	1.02	BS5	0.01	0.01	0.011	0.011	0.018	0.026	0.026	0.026	0.026	0.026	1.0	0.019	0.02	0.020
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	162.0000	6.00	5.88	CW	E	1.02	BS5	0.01	0.01	0.01	0.012	0.021	0.026	0.026	0.026	0.026	0.026	1.0	0.019	0.02	0.020
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	162.0000	6.00	5.88	CW	E	1.02	BS1	0.004	0.004	0.005	0.005	0.005	0.005	0.005	0.005	0.005	0.005	1.0	0.005	0.00	0.005
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	167.7000	6.00	5.95	CW	E	1.01	BS1	0.002	0.003	0.003	0.004	0.004	0.004	0.004	0.004	0.004	0.004	1.0	0.004	0.00	0.004
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	173.4000	6.00	5.91	CW	E	1.01	BS1	0.005	0.005	0.005	0.005	0.006	0.008	0.008	0.008	0.008	0.008	1.0	0.007	0.01	0.007
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	162.0000	6.00	5.88	CW	E	1.02	BS2	0.005	0.011	0.011	0.011	0.016	0.016	0.018	0.018	0.018	0.018	1.0	0.014	0.01	0.015
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	167.7000	6.00	5.95	CW	E	1.01	BS2	0.005	0.008	0.01	0.014	0.02	0.024	0.026	0.026	0.026	0.026	1.0	0.019	0.02	0.019
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	173.4000	6.00	5.91	CW	E	1.01	BS2	0.005	0.006	0.008	0.01	0.015	0.016	0.018	0.018	0.018	0.018	1.0	0.013	0.01	0.014
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	162.0000	6.00	5.88	CW	E	1.02	BS3	0.012	0.015	0.018	0.02	0.028	0.038	0.038	0.038	0.038	0.038	1.0	0.028	0.03	0.029
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	167.7000	6.00	5.95	CW	E	1.01	BS3	0.01	0.02	0.025	0.036	0.036	0.048	0.053	0.054	0.054	0.054	1.0	0.039	0.04	0.040
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	173.4000	6.00	5.91	CW	E	1.01	BS3	0.012	0.017	0.02	0.021	0.037	0.038	0.043	0.043	0.043	0.043	1.0	0.032	0.03	0.033

MPE calculations are defined in section 15.0.

Table G.1 (Continued)
DVR VHF - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	162.0000	6.00	5.88	CW	E	1.02	BS4	0.011	0.017	0.021	0.021	0.024	0.033	0.037	0.037	0.037	0.037	1.0	0.028	0.03	0.029
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	167.7000	6.00	5.95	CW	E	1.01	BS4	0.017	0.026	0.032	0.032	0.041	0.05	0.05	0.05	0.05	0.05	1.0	0.040	0.04	0.041
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	173.4000	6.00	5.91	CW	E	1.01	BS4	0.021	0.021	0.023	0.024	0.033	0.041	0.042	0.042	0.042	0.042	1.0	0.033	0.03	0.034
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	162.0000	6.00	5.88	CW	E	1.02	BS5	0.006	0.006	0.007	0.007	0.012	0.013	0.021	0.021	0.021	0.021	1.0	0.014	0.01	0.014
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	167.7000	6.00	5.95	CW	E	1.01	BS5	0.01	0.01	0.01	0.014	0.021	0.027	0.027	0.027	0.027	0.027	1.0	0.020	0.02	0.020
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	173.4000	6.00	5.91	CW	E	1.01	BS5	0.005	0.006	0.006	0.008	0.016	0.016	0.016	0.016	0.016	0.016	1.0	0.012	0.01	0.012

MPE calculations are defined in section 15.0.

Table G1 (Continued)

DVR VHF - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
(2) Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	140.0000	6.00	5.82	CW	H	0.88	BS1	0.016	0.016	0.016	0.017	0.018	0.019	0.019	0.023	0.026	0.026	1.0	0.020	0.01	0.012
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	144.0000	6.00	5.83	CW	H	0.87	BS1	0.016	0.016	0.016	0.016	0.017	0.017	0.018	0.021	0.024	0.025	1.0	0.019	0.01	0.010
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	140.0000	6.00	5.82	CW	H	0.88	BS2	0.02	0.02	0.021	0.021	0.023	0.026	0.028	0.028	0.031	0.034	1.0	0.025	0.02	0.019
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	144.0000	6.00	5.83	CW	H	0.87	BS2	0.019	0.02	0.021	0.021	0.024	0.026	0.029	0.03	0.032	0.033	1.0	0.026	0.02	0.019
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	140.0000	6.00	5.82	CW	H	0.88	BS3	0.022	0.022	0.023	0.025	0.026	0.029	0.031	0.034	0.033	0.033	1.0	0.028	0.02	0.023
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	144.0000	6.00	5.83	CW	H	0.87	BS3	0.016	0.018	0.018	0.021	0.021	0.023	0.025	0.027	0.029	0.03	1.0	0.023	0.01	0.015
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	140.0000	6.00	5.82	CW	H	0.88	BS4	0.021	0.021	0.021	0.022	0.024	0.028	0.032	0.033	0.034	0.035	1.0	0.027	0.02	0.022
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	144.0000	6.00	5.83	CW	H	0.87	BS4	0.019	0.019	0.019	0.02	0.022	0.025	0.028	0.028	0.029	0.033	1.0	0.024	0.02	0.017
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	140.0000	6.00	5.82	CW	H	0.88	BS5	0.019	0.019	0.019	0.02	0.024	0.026	0.03	0.03	0.03	0.029	1.0	0.025	0.02	0.018
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	144.0000	6.00	5.83	CW	H	0.87	BS5	0.02	0.02	0.02	0.022	0.025	0.028	0.029	0.03	0.029	0.028	1.0	0.025	0.02	0.019

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table G.1 (Continued)
DVR VHF - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.		Test Pos.	MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
⁽²⁾ Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	144.0000	6.00	5.83	CW	H	0.87	BS1	0.016	0.017	0.017	0.017	0.017	0.017	0.018	0.02	0.023	0.024	1.0	0.019	0.01	0.010
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	150.8000	6.00	5.81	CW	H	0.87	BS1	0.016	0.017	0.017	0.017	0.018	0.019	0.021	0.023	0.026	0.026	1.0	0.020	0.01	0.012
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	144.0000	6.00	5.83	CW	H	0.87	BS2	0.018	0.019	0.02	0.021	0.024	0.025	0.027	0.029	0.03	0.032	1.0	0.025	0.02	0.018
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	150.8000	6.00	5.81	CW	H	0.87	BS2	0.018	0.018	0.019	0.02	0.021	0.022	0.024	0.025	0.027	0.029	1.0	0.022	0.01	0.015
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	144.0000	6.00	5.83	CW	H	0.87	BS3	0.017	0.018	0.02	0.022	0.022	0.024	0.025	0.028	0.029	0.028	1.0	0.023	0.02	0.016
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	150.8000	6.00	5.81	CW	H	0.87	BS3	0.024	0.024	0.025	0.026	0.026	0.028	0.03	0.034	0.034	0.032	1.0	0.028	0.02	0.024
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	144.0000	6.00	5.83	CW	H	0.87	BS4	0.018	0.018	0.018	0.02	0.022	0.026	0.028	0.029	0.029	0.033	1.0	0.024	0.02	0.017
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	150.8000	6.00	5.81	CW	H	0.87	BS4	0.026	0.026	0.026	0.026	0.026	0.031	0.034	0.035	0.035	0.037	1.0	0.030	0.03	0.027
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	144.0000	6.00	5.83	CW	H	0.87	BS5	0.02	0.02	0.02	0.023	0.026	0.028	0.03	0.031	0.028	0.027	1.0	0.025	0.02	0.019
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	150.8000	6.00	5.81	CW	H	0.87	BS5	0.022	0.022	0.022	0.023	0.027	0.028	0.029	0.029	0.028	0.027	1.0	0.026	0.02	0.019

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table G.1 (Continued)
DVR VHF - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
⁽²⁾ Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	150.8000	6.00	5.81	CW	H	0.87	BS1	0.016	0.016	0.016	0.018	0.018	0.02	0.02	0.025	0.027	0.026	1.0	0.020	0.01	0.012
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	156.4000	6.00	5.92	CW	H	0.86	BS1	0.017	0.017	0.017	0.017	0.018	0.019	0.02	0.022	0.023	0.023	1.0	0.019	0.01	0.011
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	162.0000	6.00	5.88	CW	H	0.86	BS1	0.017	0.019	0.019	0.02	0.02	0.021	0.021	0.023	0.026	0.026	1.0	0.021	0.01	0.013
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	150.8000	6.00	5.81	CW	H	0.87	BS2	0.017	0.018	0.018	0.019	0.02	0.02	0.022	0.025	0.027	0.028	1.0	0.021	0.01	0.013
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	156.4000	6.00	5.92	CW	H	0.86	BS2	0.018	0.02	0.02	0.021	0.023	0.023	0.024	0.026	0.027	0.028	1.0	0.023	0.01	0.015
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	162.0000	6.00	5.88	CW	H	0.86	BS2	0.02	0.02	0.02	0.021	0.025	0.025	0.027	0.03	0.03	0.03	1.0	0.025	0.02	0.017
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	150.8000	6.00	5.81	CW	H	0.87	BS3	0.022	0.023	0.024	0.025	0.025	0.027	0.029	0.031	0.031	0.031	1.0	0.027	0.02	0.021
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	156.4000	6.00	5.92	CW	H	0.86	BS3	0.022	0.022	0.023	0.024	0.024	0.024	0.024	0.026	0.026	0.026	1.0	0.024	0.02	0.016
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	162.0000	6.00	5.88	CW	H	0.86	BS3	0.026	0.027	0.027	0.03	0.03	0.033	0.034	0.035	0.035	0.033	1.0	0.031	0.03	0.027
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	150.8000	6.00	5.81	CW	H	0.87	BS4	0.025	0.025	0.025	0.026	0.027	0.031	0.033	0.035	0.036	0.039	1.0	0.030	0.03	0.027
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	156.4000	6.00	5.92	CW	H	0.86	BS4	0.025	0.026	0.026	0.026	0.026	0.03	0.031	0.032	0.032	0.031	1.0	0.029	0.02	0.023
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	162.0000	6.00	5.88	CW	H	0.86	BS4	0.028	0.028	0.028	0.028	0.03	0.034	0.036	0.036	0.036	0.037	1.0	0.032	0.03	0.029

MPE calculations are defined in section 15.0.

Table G.1 (Continued)
DVR VHF - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.			MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
(2)Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	150.8000	6.00	5.81	CW	H	0.87	BS5	0.021	0.021	0.021	0.023	0.026	0.027	0.029	0.029	0.029	0.028	1.0	0.025	0.02	0.019
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	156.4000	6.00	5.92	CW	H	0.86	BS5	0.023	0.023	0.023	0.025	0.028	0.03	0.031	0.031	0.031	0.03	1.0	0.028	0.02	0.021
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	162.0000	6.00	5.88	CW	H	0.86	BS5	0.022	0.022	0.022	0.025	0.029	0.03	0.032	0.032	0.032	0.031	1.0	0.028	0.02	0.022
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	162.0000	6.00	5.88	CW	H	0.86	BS1	0.017	0.017	0.017	0.017	0.017	0.018	0.019	0.021	0.023	0.023	1.0	0.019	0.01	0.010
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	167.7000	6.00	5.95	CW	H	0.85	BS1	0.016	0.016	0.016	0.018	0.018	0.02	0.021	0.023	0.026	0.02	1.0	0.019	0.01	0.010
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	173.4000	6.00	5.91	CW	H	0.84	BS1	0.016	0.016	0.016	0.017	0.019	0.021	0.022	0.024	0.025	0.026	1.0	0.020	0.01	0.011
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	162.0000	6.00	5.88	CW	H	0.86	BS2	0.016	0.016	0.018	0.019	0.022	0.023	0.025	0.026	0.034	0.03	1.0	0.023	0.01	0.015
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	167.7000	6.00	5.95	CW	H	0.85	BS2	0.016	0.017	0.018	0.017	0.02	0.022	0.024	0.026	0.029	0.027	1.0	0.022	0.01	0.013
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	173.4000	6.00	5.91	CW	H	0.84	BS2	0.017	0.018	0.018	0.019	0.021	0.023	0.024	0.026	0.028	0.026	1.0	0.022	0.01	0.013
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	162.0000	6.00	5.88	CW	H	0.86	BS3	0.022	0.022	0.024	0.025	0.026	0.028	0.029	0.031	0.029	0.028	1.0	0.026	0.02	0.020
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	167.7000	6.00	5.95	CW	H	0.85	BS3	0.026	0.028	0.029	0.03	0.03	0.032	0.033	0.036	0.036	0.034	1.0	0.031	0.03	0.027
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	173.4000	6.00	5.91	CW	H	0.84	BS3	0.025	0.028	0.028	0.029	0.03	0.032	0.034	0.034	0.035	0.035	1.0	0.031	0.03	0.026

MPE calculations are defined in section 15.0.

Table G.1 (Continued)
DVR VHF - MPE measurement data for Bystander

D.U.T. Info.							Probe Info.		Test Pos.	MPE Measurements										DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)
⁽²⁾ Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Bystander (BS) Positions													
										20 cm	40 cm	60 cm	80 cm	100 cm	120 cm	140 cm	160 cm	180 cm	200 cm				
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	162.0000	6.00	5.88	CW	H	0.86	BS4	0.023	0.023	0.023	0.024	0.025	0.028	0.03	0.03	0.03	0.032	1.0	0.027	0.02	0.020
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	167.7000	6.00	5.95	CW	H	0.85	BS4	0.028	0.028	0.028	0.03	0.032	0.037	0.038	0.038	0.038	0.038	1.0	0.034	0.03	0.031
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	173.4000	6.00	5.91	CW	H	0.84	BS4	0.028	0.029	0.029	0.03	0.033	0.036	0.038	0.038	0.039	0.039	1.0	0.034	0.03	0.031
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	162.0000	6.00	5.88	CW	H	0.86	BS5	0.02	0.02	0.02	0.021	0.024	0.026	0.027	0.027	0.028	0.028	1.0	0.024	0.02	0.017
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	167.7000	6.00	5.95	CW	H	0.85	BS5	0.021	0.021	0.021	0.024	0.029	0.029	0.03	0.03	0.028	0.028	1.0	0.026	0.02	0.019
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	173.4000	6.00	5.91	CW	H	0.84	BS5	0.02	0.02	0.02	0.023	0.027	0.027	0.028	0.028	0.028	0.026	1.0	0.025	0.02	0.016

MPE calculations are defined in section 15.0.

Table G.2
DVR VHF - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.		MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm ²)	Calc. P.D. (mW/cm ²)	Max Calc. P.D. (mW/cm ²)	
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3					Lower Trunk/ Bottom 1/3
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	140.0000	6.00	5.82	CW	E	1.02	PB	0.28	0.164	0.114	1.0	0.186	0.19	0.196
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	144.0000	6.00	5.83	CW	E	1.02	PB	0.181	0.166	0.132	1.0	0.160	0.16	0.168
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	144.0000	6.00	5.83	CW	E	1.02	PB	0.141	0.153	0.123	1.0	0.139	0.14	0.146
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	150.8000	6.00	5.81	CW	E	1.02	PB	0.131	0.098	0.064	1.0	0.098	0.10	0.103
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	150.8000	6.00	5.81	CW	E	1.02	PB	0.106	0.09	0.083	1.0	0.093	0.09	0.098
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	156.4000	6.00	5.92	CW	E	1.02	PB	0.153	0.137	0.107	1.0	0.132	0.13	0.137
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	162.0000	6.00	5.88	CW	E	1.02	PB	0.202	0.254	0.206	1.0	0.221	0.225	0.230
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	162.0000	6.00	5.88	CW	E	1.02	PB	0.147	0.185	0.165	1.0	0.166	0.17	0.172
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	167.7000	6.00	5.95	CW	E	1.01	PB	0.11	0.194	0.169	1.0	0.158	0.16	0.161
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	173.4000	6.00	5.91	CW	E	1.01	PB	0.158	0.197	0.185	1.0	0.180	0.18	0.185

Notes:

MPE calculations are defined in section 15.0
Blue fonts: Frequencies not regulated by FCC.

Table G.2 (Continued)
DVR VHF - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.		Test Pos.	MPE Measurements Passenger/Operator (MC) Positions			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor		Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	140.0000	6.00	5.82	CW	H	0.88		PB	0.068	0.057				
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	144.0000	6.00	5.83	CW	H	0.87	PB	0.055	0.067	0.047	1.0	0.056	0.09	0.093
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	144.0000	6.00	5.83	CW	H	0.87	PB	0.05	0.055	0.046	1.0	0.050	0.07	0.074
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	150.8000	6.00	5.81	CW	H	0.87	PB	0.056	0.067	0.048	1.0	0.057	0.09	0.096
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	150.8000	6.00	5.81	CW	H	0.87	PB	0.054	0.052	0.046	1.0	0.051	0.07	0.076
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	156.4000	6.00	5.92	CW	H	0.86	PB	0.065	0.088	0.06	1.0	0.071	0.14	0.142
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	162.0000	6.00	5.88	CW	H	0.86	PB	0.068	0.081	0.086	1.0	0.078	0.17	0.175
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	162.0000	6.00	5.88	CW	H	0.86	PB	0.059	0.067	0.068	1.0	0.065	0.12	0.119
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	167.7000	6.00	5.95	CW	H	0.85	PB	0.064	0.078	0.086	1.0	0.076	0.16	0.159
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	173.4000	6.00	5.91	CW	H	0.84	PB	0.05	0.064	0.062	1.0	0.059	0.09	0.093

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table G.2 (Continued)
DVR VHF - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	140.0000	6.00	5.82	CW	E	1.02	PF	0.011	0.015	0.015	1.0	0.014	0.01	0.014
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	144.0000	6.00	5.83	CW	E	1.02	PF	0.015	0.015	0.022	1.0	0.017	0.02	0.018
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	144.0000	6.00	5.83	CW	E	1.02	PF	0.017	0.016	0.026	1.0	0.020	0.02	0.021
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	150.8000	6.00	5.81	CW	E	1.02	PF	0.023	0.023	0.019	1.0	0.022	0.02	0.023
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	150.8000	6.00	5.81	CW	E	1.02	PF	0.023	0.023	0.024	1.0	0.023	0.02	0.025
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	156.4000	6.00	5.92	CW	E	1.02	PF	0.031	0.031	0.034	1.0	0.032	0.03	0.033
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	162.0000	6.00	5.88	CW	E	1.02	PF	0.027	0.03	0.038	1.0	0.032	0.03	0.033
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	162.0000	6.00	5.88	CW	E	1.02	PF	0.018	0.022	0.027	1.0	0.022	0.02	0.023
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	167.7000	6.00	5.95	CW	E	1.01	PF	0.014	0.023	0.035	1.0	0.024	0.02	0.024
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	173.4000	6.00	5.91	CW	E	1.01	PF	0.012	0.022	0.045	1.0	0.026	0.03	0.027

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.

Table G.2 (Continued)
DVR VHF - MPE measurement data for Passenger

D.U.T. Info.							Probe Info.			MPE Measurements			DUT Max. TX Factor	Avg. over Body (mW/cm2)	Calc. P.D. (mW/cm2)	Max Calc. P.D. (mW/cm2)
Ant Loc.	Ant. Model/ Desc.	Ant. Gain (dBi)	Tx Freq (MHz)	Max Pwr (W)	Initial Pwr (W)	Test Mode	E/H Field	Probe Cal. Factor	Test Pos.	Passenger/Operator (MC) Positions						
										Head/ Top 1/3	Chest/ Middle 1/3	Lower Trunk/ Bottom 1/3				
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	140.0000	6.00	5.82	CW	H	0.88	PF	0.03	0.028	0.022	1.0	0.027	0.02	0.021
Trunk	HAD4006A, 1/4 Wave (136-144MHz)	2.15	144.0000	6.00	5.83	CW	H	0.87	PF	0.031	0.03	0.025	1.0	0.029	0.02	0.024
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	144.0000	6.00	5.83	CW	H	0.87	PF	0.031	0.031	0.025	1.0	0.029	0.02	0.025
Trunk	HAD4007A, 1/4 Wave (144-150.8MHz)	2.15	150.8000	6.00	5.81	CW	H	0.87	PF	0.032	0.033	0.029	1.0	0.031	0.03	0.029
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	150.8000	6.00	5.81	CW	H	0.87	PF	0.033	0.033	0.026	1.0	0.031	0.03	0.028
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	156.4000	6.00	5.92	CW	H	0.86	PF	0.039	0.037	0.031	1.0	0.036	0.04	0.036
Trunk	HAD4008A, 1/4 Wave (150.8-162MHz)	2.15	162.0000	6.00	5.88	CW	H	0.86	PF	0.038	0.036	0.031	1.0	0.035	0.03	0.035
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	162.0000	6.00	5.88	CW	H	0.86	PF	0.032	0.033	0.029	1.0	0.031	0.03	0.028
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	167.7000	6.00	5.95	CW	H	0.85	PF	0.032	0.034	0.038	1.0	0.035	0.03	0.033
Trunk	HAD4009A, 1/4 Wave (162-174MHz)	2.15	173.4000	6.00	5.91	CW	H	0.84	PF	0.023	0.03	0.031	1.0	0.028	0.02	0.021

Notes:

MPE calculations are defined in section 15.0
 Blue fonts: Frequencies not regulated by FCC.