



SAR TEST REPORT

Test Report No. : 31GE0277-HO-01-A-R01

Applicant : CANON INC.
Type of Equipment : **Wireless Module (Platform: Wireless File transmitter)**
/with Host device: Digital camera
Model No. : CH9-1225 (Platform: DS585882)
Test Standard : FCC 47CFR §2.1093,
Supplement C (Edition 01-01) to OET Bulletin 65
Test Result : **Complied**
Maximum SAR(1g) Value : **0.31 W/kg** (2462MHz, IEEE 802.11b, 1Mbps(DBPSK/DSSS) / 2412-2462 MHz band) (DTS)
0.70 W/kg (5190MHz, IEEE 802.11n(40HT), MCS0(BPSK/OFDM) / 5180-5320MHz band) (NII)

*. Body-touch & Portable device. SAR limit was for general population/uncontrolled exposure, and considered on the multi-platform (SAR(1g) : <0.8 W/kg).


1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by any agency of the Federal Government.
6. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.

Date of test: July 19, 20 and 21, 2011(for SAR test)

Test engineer:


Hiroshi Naka
Engineer of WiSE Japan, UL Verification Service

Approved by:


Toyokazu Imamura
Leader of WiSE Japan, UL Verification Service

- The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.
 There is no testing item of "Non-accreditation".



CONTENTS	PAGE
SECTION 1: Customer information	3
SECTION 2: Equipment under test (EUT).....	3
SECTION 3: Test specification, procedures and results.....	4
3.1 Test specification	4
3.2 Exposure limit	4
3.3 Procedure and result.....	4
3.4 Test location	4
3.5 Confirmation before SAR testing	5
3.6 Confirmation after SAR testing.....	6
3.7 Measurement procedure	6
3.8 Test setup of EUT	6
SECTION 4: Operation of EUT during testing.....	7
4.1 Operating modes for SAR testing	7
SECTION 5: Uncertainty assessment.....	8
SECTION 6: Confirmation before testing.....	9
6.1 Assessment for the conducted power of EUT / Correction of the power at EMC test and at SAR test.....	9
SECTION 7: Measurement results.....	12
7.1 SAR for 2412-2462 MHz band.....	12
7.2 SAR for 5180-5320 MHz band (W52/53 band).....	13
7.3 SAR for 5745-5825 MHz band (W58 band)	14

Contents of appendixes

APPENDIX 1: Photographs of test setup	15
Appendix 1-1 Photograph of EUT and antenna position	15
Appendix 1-2 Photograph of test setup	17
APPENDIX 2: SAR Measurement data	20
Appendix 2-1 Evaluation procedure	20
Appendix 2-2 Measurement data (Body liquid) / 2.4GHz band	21
Appendix 2-3 Measurement data (Body liquid) / W52/53 band.....	33
Appendix 2-4 Measurement data (Body liquid) / W58 band.....	46
APPENDIX 3: Test instruments	55
Appendix 3-1 Equipment used	55
Appendix 3-2 Dosimetry assessment setup	56
Appendix 3-3 Configuration and peripherals.....	57
Appendix 3-4 System components.....	57
Appendix 3-5 Test system specification	58
Appendix 3-6 Simulated tissues composition	58
Appendix 3-7 Simulated tissues parameter confirmation	59
Appendix 3-8 System validation data	59
Appendix 3-9 Validation measurement data	60
Appendix 3-10 Validation uncertainty.....	62
Appendix 3-11 Calibration certificate: Dipole (D2450V2).....	63
Appendix 3-12 Calibration certificate: Dipole (D5GHzV2)	72
Appendix 3-13 Calibration certificate: E-Field Probe (EX3DV4)	86
Appendix 3-14 References.....	97

REVISION HISTORY

Revision	Test report No.	Date	Page revised	Contents
Original	31GE0277-HO-01-A	August 12, 2011	-	-
1	31GE0277-HO-01-A-R01	December 6, 2011	P1,2,3	(p3) Deleted unnecessary EUT information for SAR testing in clause 2.2.

*. **By issue of new revision report, the report of an old revision becomes invalid.**

SECTION 1: Customer information

Company Name	CANON INC.
Brand Name	Canon
Address	30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501 Japan
Telephone Number	81-3-3757-6798
Facsimile Number	81-3-3757-8431
Contact Person	Kiyoshi Sahoyama

SECTION 2: Equipment under test (EUT)

2.1 Identification of EUT

Type of Equipment	Wireless Module
Model Number	CH9-1225
Serial Number	06
Condition of EUT	Production prototype (Not for sale; This sample is equivalent to mass-production items) (*. Receipt date of sample: July 13, 2011 / *. No modification by the test lab.)
Category Identified	Portable device
Tested consideration	During SAR test, the EUT was assembled into the Wireless File transmitter (model: DS585882) and operated by a full-charged rechargeable battery.
Platform Information	The EUT is assembled into the Wireless File transmitter, model: DS58588x.
Type of Equipment:	The model: DS58588x is a Wireless File transmitter. DS58588x operates by the rechargeable battery. DS58588x has the constant dc voltage circuit and supplies this constant dc power to the EUT. DS58588x is connected with the host device by the USB cable. The data transfer can be done by either wireless LAN or wired LAN.
Model Number / Serial:	DS585882 (*1) / serial number: 06
Manufacture:	Canon
Power rating:	DC8V (battery operation)
Size of EUT:	134.14(W) × 62.20(L) × 31.50(H) (mm)
Condition of EUT:	Engineering prototype

*1. The Wireless File transmitter of platform has variant models as DS585882 (tested sample), DS585881, DS585883, DS585884 and DS585885. These models are the same electrically and mechanically, but difference is only the country of the destination for export.

Model	DS585881 (*2)	DS585882	DS585883 (*2)	DS585884 (*2)	DS585885 (*2)
Frequency band	2412-2472MHz 5180-5320MHz 5500-5700Hz	2412-2462MHz 5180-5320MHz 5745-5825MHz	2412-2472MHz 5745-5805MHz	2412-2462MHz 5280-5320MHz 5500-5700MHz	2412-2472MHz 5180-5320MHz 5500-5825MHz

*2. These models are not exported to North America.

2.2 Product Description

Equipment type	Transceiver	Transceiver	Transceiver	Transceiver
Frequency of operation	2412-2462MHz	2412-2462MHz	5180-5320MHz (5190-5310MHz:11n(40HT))	5745-5825MHz (5755-5795MHz:11n(40HT))
Channel spacing	5MHz		20MHz(11a, 11n(20HT)), 40MHz(11n(40HT))	
Bandwidth	20MHz	20MHz, 40MHz(11n(40HT))		
ITU code	G1D	D1D		
Type of modulation	SSSS	OFDM		
Q'ty of Antenna	1 pc.			
Antenna type/	PIFA (Planar Inverted F Antenna)			
Model name	Dual Band WLAN Antenna Cable Assembly 2011 (P/N: 2174096-1)			
Antenna connector type	RF module side: U.FL connector compatible/ antenna side: soldered			
Antenna gain (Peak)	1.95 dBi (at2500MHz / 2400-2450-2500MHz points)		-1.32 dBi (at 5340MHz / 5160-5250-5340MHz points), -0.43 dBi (at 5785MHz / 5725-5785-5845MHz points)	
Transmit power	*. Refers to section 6 in this report.			
Power rating	DC 3.3V, *.The constant dc power is supplied from the battery operated Wireless File transmitter(DS58588x).			
Operation temperature range	-20 to +70 deg.C			

*. The EUT do not use the special transmitting technique such as "beam-forming" and "time-space code diversity."

SECTION 3: Test specification, procedures and results

3.1 Requirements for compliance testing defined by the FCC / Test specification

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992. According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

1. Specific Absorption Rate (SAR) is a measure of the rate of energy absorption due to exposure to an RF transmitting source (wireless portable device).
2. IEEE/ANSI Std. C95.1-1992 limits are used to determine compliance with FCC ET Docket 93-62.

Supplement C (Edition 01-01) to OET Bulletin 65 (Edition 97-01):

Supplement C (Edition 01-01) - Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions

OET Bulletin 65 (Edition 97-01) - Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields

IEEE Std. 1528-2003:

IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques Supplement C

In additions;

KDB 447498 D01(v04)(Nov.13, 2009): Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies

KDB 248227 (rev.1.2)(May 29, 2007): SAR Measurement Procedures for 802.11a/b/g Transmitters

3.2 Exposure limit

(A) Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body (averaged over the entire body)	Partial-Body (averaged over any 1g of tissue)	Hands, Wrists, Feet and Ankles (averaged over any 10g of tissue)
0.4	8.0	20.0

(B) Limits for General population/Uncontrolled Exposure (W/kg)

Whole-Body (averaged over the entire body)	Partial-Body (averaged over any 1g of tissue)	Hands, Wrists, Feet and Ankles (averaged over any 10g of tissue)
0.08	1.6	4.0

Occupational/Controlled Environments: are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments: are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

The limit applied in this test report is;

General population / Uncontrolled exposure, Partial-Body (averaged over any 1g of tissue) limit: 1.6 W/kg
--

3.3 Procedures and Results

Item	Test Procedure	Limit	Exclusion	Remarks	Result
Human exposure	FCC OET Bulletin 65, Supplement C	1.6 W/kg (FCC 47CFR §2.1093)	none	SAR measurement (in accordance with KDB447498, KDB248227)	Complied (*1)

Note: UL Japan's SAR Work Procedures No.13-EM-W0429 and 13-EM-W0430. Other than above, no addition, deviation nor exclusion has been made from standards

*1. The maximum SAR(1g) of each frequency band was as follows;

0.31 W/kg (IEEE 802.11b, 1Mbps(DBPSK/DSSS), 2462MHz/2412-2462 MHz band) (DTS)

0.70 W/kg (IEEE 802.11n(40HT), MCS0(BPSK/OFDM), 5190MHz/5180-5240MHz band) (NII)

0.30 W/kg (IEEE 802.11n(40HT), MCS0(BPSK/OFDM), 5795MHz/5745-5825MHz band) (DTS)

The SAR(1g) was <0.8W/kg for all configuration. Therefore according to the KDB447498 D01, the EUT was approved for used in multi-platform.

3.4 Test Location

No.7 shielded room (2.76(Width) × 3.76m(Depth) × 2.4m(Height)) for SAR testing.

UL Japan, Inc., Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone number: +81 463 50 6400 / Facsimile number: +81 463 50 6401

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

3.5 Confirmation before SAR testing

3.5.1 Correlation of Output Power between EMC and SAR tests

It was checked that the antenna port power was correlated within 0~+5% (FCC requirements)
The result is shown in Section 6.

- *. **Output power at SAR test:** SAR power was measured before SAR testing. (EUT serial number: 06)
For 2.4GHz band, the average and the peak power of 11b, 11g, 11n(20HT) and 11n(40HT) mode were measured at default channel
For 5GHz band, the average and the peak power of 11a, 11n(20HT) and 11n(40HT) mode were measured at all channel.
- *. **Output power at EMC radio test:** EMC power was measured during EMC testing. (EUT serial number: 06)
For the SAR vs. EMC power reference, the average and the peak power of 11b, 11g, 11a, 11n(20HT) and 11n(40HT) mode were measured at the same channel of SAR measured.

3.5.2 Average power for SAR tests

Step.1 Data rate check

The data rate check was measurement on the middle channel for 802.11b/g/n (2.4GHz) and the middle (or near the middle) default channel of 802.11a/n (5GHz).

11b		11g		11a		11n(20HT)			11n(40HT)		
Modulation	Data rate [Mbps]	Modulation	Data rate [Mbps]	Modulation	Data rate [Mbps]	Modulation	MCS Index	Spatial Stream	Modulation	MCS Index	Spatial Stream
DBPSK/DSSS	1	BPSK/OFDM	6	BPSK/OFDM	6	BPSK/OFDM	MCS0	1	BPSK/OFDM	MCS0	1
DQPSK/DSSS	2	BPSK/OFDM	9	BPSK/OFDM	9	QPSK/OFDM	MCS1	1	QPSK/OFDM	MCS1	1
CCK/DSSS	5.5	QPSK/OFDM	12	QPSK/OFDM	12	QPSK/OFDM	MCS2	1	QPSK/OFDM	MCS2	1
CCK/DSSS	11	QPSK/OFDM	18	QPSK/OFDM	18	16QAM/OFDM	MCS3	1	16QAM/OFDM	MCS3	1
		16QAM/OFDM	24	16QAM/OFDM	24	16QAM/OFDM	MCS4	1	16QAM/OFDM	MCS4	1
		16QAM/OFDM	36	16QAM/OFDM	36	64QAM/OFDM	MCS5	1	64QAM/OFDM	MCS5	1
		64QAM/OFDM	48	64QAM/OFDM	48	64QAM/OFDM	MCS6	1	64QAM/OFDM	MCS6	1
		64QAM/OFDM	54	64QAM/OFDM	54	64QAM/OFDM	MCS7	1	64QAM/OFDM	MCS7	1

Step.2 Decision of SAR test channel

For the SAR test reference, the average and peak output powers were measured on default channels of 802.11b/g/n(20HT)/n(40HT) (for 2.4GHz band) and all channels of 802.11a/n(20HT)/n(40HT) (for W52 and W58 band) by the calibrated power sensor and power meter (65MHz measurement bandwidth).

Mode	GHz	Channel	"Default Test Channel"				
			FCC 15.247		UNII		
			802.11b	802.11g			
802.11 b/g	2.412	1	√	Δ			
	2.437	6	√	Δ			
	2.462	11	√	Δ			
802.11a	UNII	5.18	36			√	
		5.20	40				*
		5.22	44				*
		5.24	48			√	
		5.26	52			√	
		5.28	56				*
		5.30	60				*
	5.32	64			√		
	UNII or FCC 15.247	5.745	149	√		√	
		5.765	153		*		*
		5.785	157	√			*
		5.805	161		*	√	
		FCC 15.247	5.825	165	√		

√ = "default test channels"

* = Possible 802.11a channels with maximum average output > the "default test channels"

Δ = Possible 802.11g channels with maximum average output ¼ dB ≥ the "default test channels"

3.6 Confirmation after SAR testing

It was checked that the power drift [W] is within ±5% in the evaluation procedure of SAR testing. The verification of power drift during the SAR test is that DASY4 system calculates the power drift by measuring the e-filed at the same location at beginning and the end of the scan measurement for each test position.

The result is shown in APPENDIX 2.

- *. DASY4 system calculation Power drift value[dB] = 20log(Ea)/(Eb) (where, Before SAR testing: Eb[V/m] / After SAR testing: Ea[V/m])
 Limit of power drift[W] = ±5%
 Power drift limit (X) [dB] = 10log(P_drift) = 10log(1.05/1) = 10log(1.05) - 10log(1) = 0.21dB
 from E-filed relations with power.
 $S = E \times H = E^2 / \eta = P / (4 \times \pi \times r^2)$ (η : Space impedance) → $P = (E^2 \times 4 \times \pi \times r^2) / \eta$
 Therefore, The correlation of power and the E-filed
 Power drift limit (X) dB = 10log(P_drift) = 10log(E_drift)^2 = 20log(E_drift)
 From the above mentioned, the calculated power drift of DASY4 system must be the less than ±0.21dB.

3.7 Measurement procedure

Operation mode: **IEEE 802.11b/g/a/n(20HT)/n(40HT)**

Step 1	Worst position search. (at lowest data rate, at the highest average power channel.)
Step 2	Change the channel (at the worst SAR position in step1.)
Step 3	Change the operation mode (at the worst SAR position in step1.)
Step 4	Change the separation distance to 5mm from touch (0mm), if it is necessary.
Step 5	Change the frequency band and repeat step1 to 4.

- *. Radiated power is monitored by Spectrum Analyzer during SAR test.

3.8 Test setup of EUT

Setup	Explanation
Top-touch	The top surface of EUT touched to the middle section of flat phantom. (*1)
Bottom-touch	The bottom surface of EUT touched to the middle section of flat phantom. (*1)
USB port side-touch	The “USB port side” surface of EUT touched to the middle section of flat phantom. (*1)
Antenna side-touch	The “Antenna side” surface of EUT touched to the middle section of flat phantom. (*1)
Switch side-touch	The “Switch side” surface of EUT touched to the middle section of flat phantom. (*1)

*1. For each test direction, the antenna section was closed to the phantom as much as possible.

- *. The SAR test did not applied to the “Battery side” of EUT, because the separation gap between the antenna section of EUT and the phantom bottom surface was more than 100mm and larger than other test direction.

SECTION 4: Operation of E.U.T. during testing

4.1 Operating modes for SAR testing

This EUT has IEEE.802.11b/g/a/11n(20HT)/11n(40HT) continuous transmitting modes.

The frequency and the modulation used in the SAR testing are shown as a following.

Operation mode	11b	11g	11n(20HT)	11n(40HT)	11a	11n(20HT)	11n(40HT)
Tx frequency band	2412-2462MHz			2422-2452MHz	5180-5320MHz 5745-5825MHz		5190-5310MHz 5755-5795MHz
Tested frequency	Refer to tested frequency list in below. (*2)				Refer to tested frequency list in below. (*2)		
Modulation	DBPSK/DSSS		BPSK/OFDM		BPSK/OFDM		
Data rate	1Mbps(*1)	6Mbps(*1)	MCS0(*1)		6Mbps(*1)	MCS0(*1)	
Crest factor	1.0(100% duty cycle)				1.0(100% duty cycle)		
Controlled software	Tera Term-rftest mode(*10) During SAR test, the EUT was connected with the host note PC via ribbon flat cable. The software installed in PC made the transmitting condition.						

*1. It was lowest data rate.

*2. Decision of SAR tested channels are described in the below the "SAR test applied channel list".

[SAR test applied channels list]

Mode	GHz	Channel	default		SAR tested channel					Remarks	
			11bga 11n(20HT)	11n (40HT)	11b	11g	11a	11n (20HT)	11n (40HT)		
802.11 b/g/n	2.412	1	√	√	✓	n/a(*4)	-	-	n/a(*4)	-	default channel.
	2.422	3	-	√	-	-	-	-	-	✓	worst average power of 11n(40HT).
	2.437	6	√	√	✓	n/a(*4)	-	-	n/a(*4)	✓	default channel
	2.452	9	-	√	-	-	-	-	-	✓	-
	2.462	11	√	-	✓	✓(*3,*4)	-	-	✓(*3,*4)	-	default channel *3. worst SAR channel of 11b. Replaced test channel to 40 from 36.
802.11 a/n	5.18	36	√	-	-	-	-	-	-	-	Replaced test channel to 40 from 36.
	5.19	38	-	√	-	-	-	-	-	✓	low channel of 11n(40HT).
	5.20	40	*	-	-	-	✓(*5)	✓(*6,*7)	-	-	*5. worst average power of 11a. *6. worst SAR channel of 11a, worst average power of 11n(20HT).
	5.22	44	*	-	-	-	-	-	-	-	-
	5.23	46	-	√	-	-	-	-	-	✓	middle channel of 11n(40HT).
	5.24	48	√	-	-	-	✓	n/a(*7)	-	-	default channel
	5.26	52	√	-	-	-	✓	n/a(*7)	-	-	default channel
	5.27	54	-	√	-	-	-	-	-	✓	middle channel of 11n(40HT).
	5.28	56	*	-	-	-	-	-	-	-	-
	5.30	60	*	-	-	-	-	-	-	-	-
	5.31	62	-	√	-	-	-	-	-	✓	high channel of 11n(40HT).
	5.32	64	√	-	-	-	✓	n/a(*7)	-	-	default channel
	5.745	149	√	-	-	-	-	-	-	-	Replaced test channel to 153 from 149.
	5.755	151	-	√	-	-	-	-	-	✓	low channel of 11n(40HT).
	5.765	153	*	-	-	-	✓(*8)	n/a(*7)	-	-	*8. worst average power of 11a.
	5.785	157	√	-	-	-	✓	✓(*9,*7)	-	-	default channel. *9. worst SAR channel of 11a.
5.795	159	-	√	-	-	-	-	-	✓	high channel of 11n(40HT).	
5.805	161	*	-	-	-	-	-	-	-	-	
5.825	165	√	-	-	-	✓	n/a(*7)	-	-	default channel.	

√ = "default test channels of requested by KDB248227"

* = Possible 802.11a channels with maximum average output > the "default test channels"

*4. For these operation mode, the average antenna terminal conducted power were not 0.25dB higher than 11b mode. (refer to section 6 in this report)

*7. For these operation mode, the average antenna terminal conducted power were not 0.25dB higher than 11a mode. (refer to section 6 in this report)

*10. The screen sample of the software used. (command: [antenna number] [channel] [bandwidth(0:20MHz/1:40MHz)] [power(13dBm)] [data rate] [rf-on/off])

```

COM19:115200baud - Tera Term VT
ファイル(F) 編集(E) 設定(S) コントロール(O) ウィンドウ(W) ヘルプ(H)
on
Dry> nell-attach
ioexp init
SDIOH Timer[0] is already created. [sdioh_ctrl.c<83>]
NELL(LUGH) version Feb 9 2011, 13:51:32
Dry> enterTEST
=====
=== Enter TEST MODE ===
=====
Dry> rftest 1 1 0 13 0 2
[testmode] setch : 1 ch
[testmode] set channel width : 20 MHz
[testmode] setrate : 1 Mbps
[testmode] get channel width : 20 MHz
[testmode] getch : 1 ch
[testmode] getrate : 1 Mbps
[testmode] set RF power : 13 dBm (corr_offset = 0xc3219e10, corr_1A = 0x0)
[testmode] duty cycle tx mode : on, data rate : 1 Mbps (50 %)
[testmode] duty cycle tx mode : off
[testmode] setrate : 1 Mbps
[testmode] get channel width : 20 MHz
[testmode] continuous tx mode : ON
Dry> rftest 1 1 0 13 0 18
[testmode] setrate : 1 Mbps
[testmode] get channel width : 20 MHz
[testmode] continuous tx mode : OFF
Dry>
    
```


SECTION 5: Uncertainty Assessment (SAR measurement)

Uncertainty of SAR measurement system	Under 3GHz	
	1g SAR	10g SAR
combined measurement uncertainty of the measurement system (k=1)	± 11.7%	± 11.4%
expanded uncertainty (k=2)	± 23.3%	± 22.8%

Error Description	Uncertainty Value	Probability distribution	Divisor	ci (1g)	ci (10g)	ui (1g) (std. uncertainty)	ui (10g) (std. uncertainty)	vi, veff
A Measurement System								
1 Probe calibration	±5.9 %	Normal	1	1	1	±5.9 %	±5.9 %	∞
2 Axial isotropy	±4.7 %	Rectangular	√3	0.7	0.7	±1.9 %	±1.9 %	∞
3 Hemispherical isotropy (*flat phantom, <5°)	±2.6 %	Rectangular	√3	0.7	0.7	±1.1 %	±1.1 %	∞
4 Boundary effects	±1.0 %	Rectangular	√3	1	1	±0.6 %	±0.6 %	∞
5 Probe linearity	±4.7 %	Rectangular	√3	1	1	±2.7 %	±2.7 %	∞
6 System detection limit	±1.0 %	Rectangular	√3	1	1	±0.6 %	±0.6 %	∞
7 System readout electronics	±0.3 %	Normal	1	1	1	±0.3 %	±0.3 %	∞
8 Response time	±0.8 %	Rectangular	√3	1	1	±0.5 %	±0.5 %	∞
9 Integration time	±2.6 %	Rectangular	√3	1	1	±1.5 %	±1.5 %	∞
10 RF ambient – noise	±3.0 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
11 RF ambient – reflections	±3.0 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
12 Probe positioner mechanical tolerance	±0.4 %	Rectangular	√3	1	1	±0.2 %	±0.2 %	∞
13 Probe positioning with respect to phantom shell	±2.9 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
14 Max.SAR evaluation	±1.0 %	Rectangular	√3	1	1	±0.6 %	±0.6 %	∞
B Test Sample Related								
15 Device positioning	±5.0 %	Normal	1	1	1	±5.0 %	±5.0 %	5
16 Device holder uncertainty	±5.0 %	Normal	1	1	1	±5.0 %	±5.0 %	5
17 Power drift	±5.0 %	Rectangular	√3	1	1	±2.9 %	±2.9 %	∞
C Phantom and Setup								
18 Phantom uncertainty	±4.0 %	Rectangular	√3	1	1	±2.3 %	±2.3 %	∞
19 Liquid conductivity (target)	±5.0 %	Rectangular	√3	0.64	0.43	±1.8 %	±1.2 %	∞
20 Liquid conductivity (meas.)	±2.9 %	Normal	1	0.64	0.43	±1.9 %	±1.2 %	3
21 Liquid permittivity (target)	±5.0 %	Rectangular	√3	0.6	0.49	±1.7 %	±1.4 %	∞
22 Liquid permittivity (meas.)	±2.9 %	Normal	1	0.6	0.49	±1.7 %	±1.4 %	3
Combined Standard Uncertainty						±11.7 %	±11.4 %	59
Expanded Uncertainty (k=2)						±23.3 %	±22.8 %	

* This measurement uncertainty budget is suggested by IEEE 1528 and determined by Schmid & Partner Engineering AG (DASY4 Uncertainty Budget). [6]

Uncertainty of SAR measurement system	5~6 GHz	
	1g SAR	10g SAR
combined measurement uncertainty of the measurement system (k=1)	± 13.6%	± 13.3%
expanded uncertainty (k=2)	± 27.2%	± 26.7%

Error Description	Uncertainty Value	Probability distribution	Divisor	ci (1g)	ci (10g)	ui (1g) (std. uncertainty)	ui (10g) (std. uncertainty)	vi, veff
A Measurement System								
1 Probe calibration	±6.8 %	Normal	1	1	1	±6.8 %	±6.8 %	∞
2 Axial isotropy	±4.7 %	Rectangular	√3	0.7	0.7	±1.9 %	±1.9 %	∞
3 Hemispherical isotropy (*flat phantom, <5°)	±2.6 %	Rectangular	√3	0.7	0.7	±1.1 %	±1.1 %	∞
4 Boundary effects	±2.0 %	Rectangular	√3	1	1	±1.2 %	±1.2 %	∞
5 Probe linearity	±4.7 %	Rectangular	√3	1	1	±2.7 %	±2.7 %	∞
6 System detection limit	±1.0 %	Rectangular	√3	1	1	±0.6 %	±0.6 %	∞
7 System readout electronics	±0.3 %	Normal	1	1	1	±0.3 %	±0.3 %	∞
8 Response time	±0.8 %	Rectangular	√3	1	1	±0.5 %	±0.5 %	∞
9 Integration time	±2.6 %	Rectangular	√3	1	1	±1.5 %	±1.5 %	∞
10 RF ambient – noise	±3.0 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
11 RF ambient - reflections	±3.0 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
12 Probe positioner mechanical tolerance	±0.8 %	Rectangular	√3	1	1	±0.5 %	±0.5 %	∞
13 Probe positioning with respect to phantom shell	±9.9 %	Rectangular	√3	1	1	±5.7 %	±5.7 %	∞
14 Max.SAR evaluation	±4.0 %	Rectangular	√3	1	1	±2.3 %	±2.3 %	∞
B Test Sample Related								
15 Device positioning	±5.0 %	Normal	1	1	1	±5.0 %	±5.0 %	∞
16 Device holder uncertainty	±5.0 %	Normal	1	1	1	±5.0 %	±5.0 %	∞
17 Power drift	±5.0 %	Rectangular	√3	1	1	±5.0 %	±2.9 %	∞
C Phantom and Setup								
18 Phantom uncertainty	±4.0 %	Rectangular	√3	1	1	±2.3 %	±2.3 %	∞
19 Liquid conductivity (target)	±5.0 %	Rectangular	√3	0.64	0.43	±1.8 %	±1.2 %	∞
20 Liquid conductivity (meas.)	±3.0 %	Normal	1	0.64	0.43	±1.9 %	±1.3 %	∞
21 Liquid permittivity (target)	±5.0 %	Rectangular	√3	0.6	0.49	±1.7 %	±1.4 %	∞
22 Liquid permittivity (meas.)	±3.2 %	Normal	1	0.6	0.49	±1.9 %	±1.6 %	∞
Combined Standard Uncertainty						±13.6 %	±13.3 %	∞
Expanded Uncertainty (k=2)						±27.2 %	±26.7 %	

* This measurement uncertainty budget is suggested by Schmid & Partner Engineering AG. [6]

6.1.2 5180-5320MHz band (W52/53 band) (802.11a/n(20HT)/n(40HT))

Worst data rate / worst channel determination (with full charged battery#1) / vs. power at EMC test (EUT serial number: 06)

Table with columns: Ch, Freq, D/R, Ant, Tx mode, Modulation, P/M Reading, Cbl.Loss, Att.loss, Power Reading Results, Δworst, PAR, Ave, Δ(sar-emo), Pk, Δ(sar-emo). Includes sub-tables for [Output power] and [Data Rate change].

* The average antenna terminal conducted power of lowest data rate was worst. Therefore, each channel was measured at lowest data rate.

Table with columns: Ch, Freq, D/R, Ant, Tx mode, Modulation, P/M Reading, Cbl.Loss, Att.loss, Power Reading Results, Δworst, PAR, Ave, Δ(sar-emo), Pk, Δ(sar-emo). Includes sub-tables for [Output power] and [Data Rate change].

* The average antenna terminal conducted power of lowest data rate was worst. Therefore, each channel was measured at lowest data rate.

Table with columns: Ch, Freq, D/R, Ant, Tx mode, Modulation, P/M Reading, Cbl.Loss, Att.loss, Power Reading Results, Δworst, PAR, Ave, Δ(sar-emo), Pk, Δ(sar-emo). Includes sub-tables for [Output power] and [Data Rate change].

* The average power of higher data rate was less than 0.25dB higher than the lowest data rate. Therefore, each channel was measured at lowest data rate.

- * Calculating formula: Results = ["P/M Reading"] + ["Cbl.loss"(Cable loss)] + ["Att.loss"(Attenuator)]
* At the same sample, the difference between the SAR reference power and the power of EMC test was not less than 0dB and not higher than 0.21dB.
* SAR reference; Measured date: May 9, 2011 / Measured by: Hiroshi Naka / Place: preparation room of No. 7 shielded room. (25 deg.C/44%RH)
* EMC test; Measured date: May 18 and 19, 2011 / Measured by: Tetsuya Arai / This reference is described in the test report of 31CE0052-HO-01-A and -B.
* The maximum average power of 11a(20HT) was less than 0.25dB higher than the corresponding 11a. However, the SAR test was applied the maximum average power channel of 11n(20HT).
* A red-letter figure shows the maximum power of SAR reference (in data rate, in channel) and of EMC test.
* The duty cycle of each mode and on each data rate were 100% (no off time) in the software used.

6.1.3 5745-5825MHz band (W58 band) (802.11a/n(20HT)/n(40HT))

Worst data rate / worst channel determination (with full charged battery#1) / vs. power at EMC test (EUT serial number: 06)

[Output power]												Tx mode: 11a(W58)				5745-5825MHz				*PAR=Peak(dB)-Ave(dB)[dB]				Power at EMC test			
Ch.	Freq. [MHz]	D/R [Mbps]	Ant. No.	worst: o default: x	Modulation	P/M Reading		Cbl.Loss [dB]	Att.loss [dB]	Power Reading Results				Δworst [dB]	PAR [dB]	Power at EMC test											
						Ave.[dBm]	Pk[dB]			Ave[dBm]	Pk[dBm]	Ave[mW]	Pk[mW]			Ave. [dB]	Δ(sar- emc) [dB]	Pk [dB]	Δ(sar- emc)								
149	5745	6	single	x l	BPSK OFDM	1.64	11.03	0.90	10.06	12.60	21.99	18.20	158.12	-0.36	9.39												
153	5765	6	single	o	BPSK OFDM	2.00	11.12	0.90	10.06	12.96	22.08	19.77	161.44	0.00	9.12												
157	5785	6	single	x	BPSK OFDM	1.90	10.66	0.90	10.06	12.86	21.62	19.32	145.21	-0.10	8.76	12.86	0.00	21.57	0.05								
161	5805	6	single		BPSK OFDM	1.86	10.53	0.90	10.06	12.82	21.49	19.14	140.93	-0.14	8.67												
165	5825	6	single	x	BPSK OFDM	1.59	10.39	0.90	10.06	12.55	21.35	17.99	136.46	-0.41	8.80												
[Data Rate change]																Δlow rate				Ave Δave pk Δpk							
157	5785	6	single		BPSK OFDM	1.90	10.66	0.90	10.06	12.86	21.62	19.32	145.21	0.00	8.76	12.86	0.00	21.57	0.05								
157	5785	9	single		BPSK OFDM	1.93	10.56	0.90	10.06	12.89	21.52	19.45	141.91	0.03	8.63	12.88	0.01	21.34	0.18								
157	5785	12	single		QPSK OFDM	1.93	10.70	0.90	10.06	12.89	21.66	19.45	146.55	0.03	8.77	12.87	0.02	21.59	0.07								
157	5785	18	single	o	QPSK OFDM	1.99	10.28	0.90	10.06	12.95	21.24	19.72	133.05	0.09	8.29	12.94	0.01	21.17	0.07								
157	5785	24	single		16QAM OFDM	1.92	10.86	0.90	10.06	12.88	21.82	19.41	152.05	0.02	8.94	12.79	0.09	21.74	0.08								
157	5785	36	single		16QAM OFDM	1.85	10.79	0.90	10.06	12.81	21.75	19.10	149.62	-0.05	8.94	12.73	0.08	21.57	0.18								
157	5785	48	single		64QAM OFDM	1.92	10.41	0.90	10.06	12.88	21.37	19.41	137.09	0.02	8.49	12.76	0.12	21.25	0.12								
157	5785	54	single		64QAM OFDM	1.84	10.61	0.90	10.06	12.80	21.57	19.05	143.55	-0.06	8.77	12.75	0.05	21.53	0.04								

* The average power of higher data rate was less than 0.25dB higher than the lowest data rate. Therefore, each channel was measured at lowest data rate.

[Output power]												Tx mode: 11n(20HT)(W58)				5745-5825MHz				*PAR=Peak(dB)-Ave(dB)[dB]				Power at EMC test			
Ch.	Freq. [MHz]	D/R [Mbps]	Ant. No.	worst: o default: x	Modulation	P/M Reading		Cbl.Loss [dB]	Att.loss [dB]	Power Reading Results				Δworst [dB]	PAR [dB]	Power at EMC test											
						Ave.[dBm]	Pk[dB]			Ave[dBm]	Pk[dBm]	Ave[mW]	Pk[mW]			Ave. [dB]	Δ(sar- emc) [dB]	Pk [dB]	Δ(sar- emc)								
149	5745	MCS0	single	x l	BPSK OFDM	1.83	10.23	0.90	10.06	12.79	21.19	19.01	131.52	-0.19	8.40												
153	5765	MCS0	single	o	BPSK OFDM	2.02	10.36	0.90	10.06	12.98	21.32	19.86	135.52	0.00	8.34												
157	5785	MCS0	single	x	BPSK OFDM	1.91	10.32	0.90	10.06	12.87	21.28	19.36	134.28	-0.11	8.41	12.82	0.05	21.08	0.20								
161	5805	MCS0	single		BPSK OFDM	1.77	10.31	0.90	10.06	12.73	21.27	18.75	133.97	-0.25	8.54												
165	5825	MCS0	single	x	BPSK OFDM	1.56	10.26	0.90	10.06	12.52	21.22	17.86	132.43	-0.46	8.70												
[Data Rate change]																Δlow rate				Ave Δave pk Δpk							
157	5785	MCS0	single		BPSK OFDM	1.91	10.32	0.90	10.06	12.87	21.28	19.36	134.28	0.00	8.41	12.82	0.05	21.08	0.20								
157	5785	MCS1	single		QPSK OFDM	1.92	10.27	0.90	10.06	12.88	21.23	19.41	132.74	0.01	8.35	12.84	0.04	21.12	0.11								
157	5785	MCS2	single		QPSK OFDM	1.96	10.42	0.90	10.06	12.92	21.38	19.59	137.40	0.05	8.46	12.85	0.07	21.19	0.19								
157	5785	MCS3	single	o	16QAM OFDM	1.98	10.40	0.90	10.06	12.94	21.36	19.68	136.77	0.07	8.42	12.94	0.00	21.18	0.18								
157	5785	MCS4	single		16QAM OFDM	1.94	10.30	0.90	10.06	12.90	21.26	19.50	133.66	0.03	8.36	12.90	0.00	21.10	0.16								
157	5785	MCS5	single		64QAM OFDM	1.96	10.25	0.90	10.06	12.92	21.21	19.59	132.13	0.05	8.29	12.88	0.04	21.01	0.20								
157	5785	MCS6	single		64QAM OFDM	1.94	10.27	0.90	10.06	12.90	21.23	19.50	132.74	0.03	8.33	12.89	0.01	21.05	0.18								
157	5785	MCS7	single		64QAM OFDM	1.93	10.27	0.90	10.06	12.89	21.23	19.45	132.74	0.02	8.34	12.84	0.05	21.12	0.11								

* The average power of higher data rate was less than 0.25dB higher than the lowest data rate. Therefore, each channel was measured at lowest data rate.

[Output power]												Tx mode: 11n(40HT)(W58)				5755-5795MHz				*PAR=Peak(dB)-Ave(dB)[dB]				Power at EMC test			
Ch.	Freq. [MHz]	D/R [Mbps]	Ant. No.	worst: o default: x	Modulation	P/M Reading		Cbl.Loss [dB]	Att.loss [dB]	Power Reading Results				Δworst [dB]	PAR [dB]	Power at EMC test											
						Ave.[dBm]	Pk[dB]			Ave[dBm]	Pk[dBm]	Ave[mW]	Pk[mW]			Ave. [dB]	Δ(sar- emc) [dB]	Pk [dB]	Δ(sar- emc)								
151	5755	MCS0	single		BPSK OFDM	1.73	10.20	0.90	10.06	12.69	21.16	18.58	130.62	-0.18	8.47												
159	5795	MCS0	single	o	BPSK OFDM	1.91	10.18	0.90	10.06	12.87	21.14	19.36	130.02	0.00	8.27	12.82	0.05	21.14	0.00								
[Data Rate change]																Δlow rate				Ave Δave pk Δpk							
159	5795	MCS0	single		BPSK OFDM	1.91	10.18	0.90	10.06	12.87	21.14	19.36	130.02	0.00	8.27	12.82	0.05	21.14	0.00								
159	5795	MCS1	single	o	QPSK OFDM	1.94	10.21	0.90	10.06	12.90	21.17	19.50	130.92	0.03	8.27	12.90	0.00	21.17	0.00								
159	5795	MCS2	single		QPSK OFDM	1.92	10.32	0.90	10.06	12.88	21.28	19.41	134.28	0.01	8.40	12.84	0.04	21.08	0.20								
159	5795	MCS3	single		16QAM OFDM	1.89	10.85	0.90	10.06	12.85	21.81	19.28	151.71	-0.02	8.96	12.82	0.03	21.63	0.18								
159	5795	MCS4	single		16QAM OFDM	1.89	10.48	0.90	10.06	12.85	21.44	19.28	139.32	-0.02	8.59	12.85	0.00	21.26	0.18								
159	5795	MCS5	single		64QAM OFDM	1.87	10.89	0.90	10.06	12.83	21.85	19.19	153.11	-0.04	9.02	12.83	0.00	21.67	0.18								
159	5795	MCS6	single		64QAM OFDM	1.93	10.45	0.90	10.06	12.89	21.41	19.45	138.36	0.02	8.52	12.87	0.02	21.40	0.01								
159	5795	MCS7	single		64QAM OFDM	1.92	10.23	0.90	10.06	12.88	21.19	19.41	131.52	0.01	8.31	12.88	0.00	21.18	0.01								

* The average power of higher data rate was less than 0.25dB higher than the lowest data rate. Therefore, each channel was measured at lowest data rate.

- * Calculating formula: Results = ["P/M Reading"] + ["Cbl.loss"(Cable loss)] + ["Att.loss"(Attenuator)]
- * At the same sample, the difference between the SAR reference power and the power of EMC test was not less than 0dB and not higher than 0.21dB. SAR reference; Measured date: May 9, 2011 / Measured by: Hiroshi Naka / Place: preparation room of No. 7 shielded room. (25 deg.C/44 %RH)
- * EMC test; Measured date: May 18 and 19, 2011 / Measured by: Tetsuya Arai / This reference is described in the test report of 31CE0052-HO-01-A and -B.
- * The maximum average power of 11a(20HT) was less than 0.25dB higher than the corresponding 11a. However, the SAR test was applied the maximum average power channel of 11n(20HT).
- * A red-letter figure shows the maximum power of SAR reference (in data rate, in channel) and of EMC test.
- * The duty cycle of each mode and on each data rate were 100% (no off time) in the software used.

Comparison of power on May 9, 2011 and July 15, 2011 (before SAR test)

Mode	Freq. [MHz]	Data Rate [Mbps]	Results (Average)			
			May 9, 2011		July 15, 2011	
			[dB]	[mW]	[dB]	[mW]
802.11a	5200	6	13.86	24.32	13.84	24.21
802.11n-40HT	5270	MCS0	13.49	22.34	13.45	22.13
802.11n-20HT	5765	MCS0	12.98	19.86	13.01	20.00

* From the above-mentioned result, it was judged that the performance of the RF module was the same.

SECTION 7: Measurement results

7.1 SAR for 2412-2462MHz band

Measurement date : July 21, 2011

Measurement by : Hiroshi Naka

[Liquid measurement (Body liquid)]

Used Target Frequency [MHz]	Target Body Tissue		Measured Body Tissue				Environment		Date measured
	Permittivity [-]	Conductivity [S/m]	Permittivity (εr) [-]	Conductivity (σ) [S/m]	Temp. [deg.C.]	Depth [mm]	Temp. [deg.C.]	Humidity [%]	
2450	52.7	1.95	50.15 (-4.8%)	1.935 (-0.8%)	23.5	158, in phantom	23.5	60	July 21, 2011, before SAR test.

*. The target value is a parameter defined in OET65 Supplement C.

[SAR measurement results (Body liquid)]

SAR measurement results											
Mode	Frequency		Modulation & Data rate [Mbps] / crest factor	EUT setup conditions			Liquid temp. [deg.C]		Power drift [dB]	SAR(1g) [W/kg] maximum value of multi-peak	Remarks
	ch	[MHz]		Position	Cap [mm]	Battery No.	Before	After			
Step 1: Worst position search											
11b	6(mid)	2437	DBPSK&DSSS / 1Mbps / 1.0	Antenna side-touch	0	1	23.3	23.3	0.173	0.26	(→Worst direction)
	6(mid)	2437	DBPSK&DSSS / 1Mbps / 1.0	Switch side-touch	0	2	23.3	23.3	0.145	-	Zoomscan was not applied, because the max.SAR value of area scan was 0.0841 mW/g and it was enough small.
	6(mid)	2437	DBPSK&DSSS / 1Mbps / 1.0	Bottom-touch	0	1	23.3	23.3	0.145	0.17	-
	6(mid)	2437	DBPSK&DSSS / 1Mbps / 1.0	Top-touch	0	2	23.3	23.3	0.160	< 0.10	-
	6(mid)	2437	DBPSK&DSSS / 1Mbps / 1.0	USB port side-touch	0	1	23.3	23.3	0.107	0.10	-
Step 2: Change the channel											
-	1(low)	2412	DBPSK&DSSS / 1Mbps / 1.0	Antenna side-touch	0	2	23.3	23.3	-0.002	0.24	-
-	11(high)	2462	DBPSK&DSSS / 1Mbps / 1.0	Antenna side-touch	0	1	23.3	23.3	0.009	0.31	→Worst SAR of 2.4GHz
Step 3: Change the operation mode											
11g	11	2462	BPSK&OFDM / 6Mbps / 1.0	Antenna side-touch	0	2	23.3	23.3	0.004	0.26	-(*)
11n (20HT)	11	2462	BPSK&OFDM / MCS0 / 1.0	Antenna side-touch	0	2	23.3	23.3	-0.114	0.29	-(*)
11n (40HT)	3	2422	BPSK&OFDM / MCS0 / 1.0	Antenna side-touch	0	2	23.3	23.3	-0.173	0.29	-
	6	2437	BPSK&OFDM / MCS0 / 1.0	Antenna side-touch	0	1	23.3	23.3	-0.186	0.27	-
	9	2452	BPSK&OFDM / MCS0 / 1.0	Antenna side-touch	0	1	23.3	23.3	0.143	0.26	-
Step 3: Change the separation distance											
11b	11	2462	BPSK&OFDM / 6Mbps / 1.0	Antenna side-touch	5	2	23.3	23.3	-0.147	0.12	More than 3dB smaller than the touch condition.

Notes:

*1. For these operation mode, the average antenna terminal conducted power were less than or not more than 0.25dB of 11b mode. (refer to section 6 in this report)

*. Battery was fully charged before starting the SAR measurement.

*. Calibration frequency of the SAR measurement probe (and used conversion factors)

SAR test frequency [MHz]	Probe calibration frequency [MHz]	Validity [MHz]	Used conversion factor	Uncertainty
2412	2450	-38MHz, within ±50 of cal.frequency	7.34	±12.0%
2437	2450	-13MHz, within ±50 of cal.frequency	7.34	±12.0%
2462	2450	+12MHz, within ±50 of cal.frequency	7.34	±12.0%

*. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

7.2 SAR for 5180-5320MHz band (W52/53 band)

Measurement date : July 19, 2011

Measurement by : Hiroshi Naka

[Liquid measurement (Body liquid)]

Used Target Frequency [MHz]	Target Body Tissue		Measured Body Tissue				Environment		Date measured
	Permittivity [-]	Conductivity [S/m]	Permittivity (εr) [-]	Conductivity (σ) [S/m]	Temp. [deg.C.]	Depth [mm]	Temp. [deg.C.]	Humidity [%]	
5200	49.01	5.299	49.90 (+1.8%)	5.402 (+1.9%)	24.0	150 in phantom	23.9	62	July 19, 2011 before SAR test
5240	48.96	5.346	49.89 (+1.9%)	5.480 (+2.5%)					
5260	48.93	5.369	49.76 (+1.7%)	5.542 (+3.2%)					
5320	48.85	5.439	49.59 (+1.5%)	5.600 (+2.9%)					
5190	49.30	5.288	49.89 (+1.8%)	5.414 (+2.4%)					
5230	48.97	5.334	49.77 (+1.6%)	5.476 (+2.7%)					
5270	48.92	5.381	49.67 (+1.5%)	5.541 (+3.0%)					
5310	48.87	5.428	49.61 (+1.5%)	5.626 (+3.7%)					

*. The target value is a parameter defined in OET65 Supplement C. In the current standards (e.g., IEEE 1528, OET 65 Supplement C), the dielectric parameters suggested for head and body tissue simulating liquid are given at 3000MHz and 5800MHz. As an intermediate solution, dielectric parameters for the frequencies between 5000 to 5800 MHz were obtained using linear interpolation. Furthermore, dielectric parameters for the frequencies above 5800MHz were obtained using linear extrapolation. (refer to Appendix 3-7 in this report)

[SAR measurement results (Body liquid)]

SAR measurement results												
Frequency			Modulation & Data rate [Mbps] / crest factor	EUT setup conditions			Liquid temp. [deg.C.]		Power drift [dB]	SAR(1g) [W/kg] maximum value of multi-peak	Remarks	
Mode	ch	[MHz]		Position	Gap [mm]	Battery No.	Before	After				
Step 1: Worst position search												
11a	40	5200	BPSK&OFDM / 6Mbps / 1.0	Antenna side-touch	0	2	23.6	23.5	-0.20	0.49	-	
	40	5200	BPSK&OFDM / 6Mbps / 1.0	Bottom-touch	0	1	23.4	23.4	-0.133	0.37	-	
	40	5200	BPSK&OFDM / 6Mbps / 1.0	Switch side-touch	0	2	23.4	23.4	-0.009	< 0.10	-	
	40	5200	BPSK&OFDM / 6Mbps / 1.0	Top-touch	0	1	23.4	23.4	0.185	0.15	-	
	40	5200	BPSK&OFDM / 6Mbps / 1.0	USB port side-touch	0	2	23.3	23.3	0.088	0.61	(→Worst direction)	
Step 2: Change the channel												
-	48	5240	BPSK&OFDM / 6Mbps / 1.0	USB port side-touch	0	1	23.3	23.2	0.050	0.52	-	
	52	5260	BPSK&OFDM / 6Mbps / 1.0	USB port side-touch	0	2	23.2	23.2	0.043	0.50	-	
	64	5320	BPSK&OFDM / 6Mbps / 1.0	USB port side-touch	0	1	23.2	23.2	0.032	0.40	-	
Step 3: Change the operation mode												
11n (20HT)	40	5200	BPSK&OFDM / MCS0 / 1.0	USB port side-touch	0	2	23.2	23.2	-0.041	0.64	-(*)	
11n (40HT)	38	5190	BPSK&OFDM / MCS0 / 1.0	USB port side-touch	0	1	23.2	23.1	0.0201	0.70	→Worst SAR of W52/53.	
	46	5230	BPSK&OFDM / MCS0 / 1.0	USB port side-touch	0	2	23.1	23.1	0.197	0.65	-	
	54	5270	BPSK&OFDM / MCS0 / 1.0	USB port side-touch	0	1	23.1	23.0	0.20	0.58	-	
	62	5310	BPSK&OFDM / MCS0 / 1.0	USB port side-touch	0	2	23.0	23.0	0.20	0.49	-	

Notes:

*1. For these operation mode, the average antenna terminal conducted power were less than or not more than 0.25dB of 11a mode. (refer to section 6 in this report)

*. Battery was fully charged before starting the SAR measurement.

*. Calibration frequency of the SAR measurement probe (and used conversion factors)

SAR test frequency [MHz]	Probe calibration frequency [MHz]	Validity [MHz]	Used conversion factor	Uncertainty
5190	5200	-10MHz, within ±50 of cal.frequency	4.10	±13.1%
5200	5200	0MHz, within ±50 of cal.frequency	4.10	±13.1%
5230	5200	+30MHz, within ±50 of cal.frequency	4.10	±13.1%
5240	5200	+40MHz, within ±50 of cal.frequency	4.10	±13.1%
5260	5300	-40MHz, within ±50 of cal.frequency	3.88	±13.1%
5270	5300	-30MHz, within ±50 of cal.frequency	3.88	±13.1%
5310	5300	+10MHz, within ±50 of cal.frequency	3.88	±13.1%
5320	5300	+20MHz, within ±50 of cal.frequency	3.88	±13.1%

*. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

7.3 5745-5825MHz band (W58 band)

Measurement date : July 20, 2011

Measurement by : Hiroshi Naka

[Liquid measurement (Body liquid)]

Used Target Frequency [MHz]	Target Body Tissue		Measured Body Tissue				Environment		Date measured
	Permittivity [-]	Conductivity [S/m]	Permittivity (εr) [-]	Conductivity (σ) [S/m]	Temp. [deg.C.]	Depth [mm]	Temp. [deg.C.]	Humidity [%]	
5765	48.25	5.959	48.89 (+1.2%)	6.231 (+4.6%)	23.6	149 in phantom	23.8	62	July 20, 2011 before SAR test
5785	48.22	5.982	48.80 (+1.2%)	6.256 (+4.6%)					
5825	48.17	6.029	48.70 (+1.1%)	6.320 (+4.8%)					
5755	48.26	5.947	48.90 (+1.3%)	6.232 (+4.8%)					
5795	48.21	5.994	48.83 (+1.3%)	6.272 (+4.6%)					

*. The target value is a parameter defined in OET65 Supplement C. In the current standards (e.g., IEEE 1528, OET 65 Supplement C), the dielectric parameters suggested for head and body tissue simulating liquid are given at 3000MHz and 5800MHz. As an intermediate solution, dielectric parameters for the frequencies between 5000 to 5800 MHz were obtained using linear interpolation. Furthermore, dielectric parameters for the frequencies above 5800MHz were obtained using linear extrapolation. (refer to Appendix 3-7 in this report)

[SAR measurement results (Body liquid)]

SAR measurement results											
Frequency			Modulation & Data rate [Mbps] / crest factor	EUT setup conditions			Liquid temp. [deg.C]		Power drift [dB]	SAR(Ig) [W/kg] maximum value of multi-peak	Remarks
Mode	ch	[MHz]		Position	Gap [mm]	Battery No.	Before	After			
Step 1: Worst position search											
11a	153	5765	BPSK&OFDM / 6Mbps / 1.0	Antenna side-touch	0	2	23.2	23.1	-0.048	0.29	(→Worst direction)
	153	5765	BPSK&OFDM / 6Mbps / 1.0	Switch side-touch	0	1	23.1	23.1	0.20	-	Zoomscan was not applied, because the max.SAR value of area scan was 0.0106 mW/g and it was enough small.
	153	5765	BPSK&OFDM / 6Mbps / 1.0	Top-touch	0	1	23.1	23.1	-0.157	0.16	-
	153	5765	BPSK&OFDM / 6Mbps / 1.0	Bottom-touch	0	2	23.1	23.1	-0.120	< 0.10	-
	153	5765	BPSK&OFDM / 6Mbps / 1.0	USB port side-touch	0	2	23.0	22.9	-0.197	< 0.10	-
Step 2: Change the channel											
-	157	5785	BPSK&OFDM / 6Mbps / 1.0	Antenna side-touch	0	1	22.9	22.9	-0.188	0.30 (0.301)	-
	165	5825	BPSK&OFDM / 6Mbps / 1.0	Antenna side-touch	0	2	22.9	22.8	-0.117	0.25	-
Step 3: Change the operation mode											
11n (20HT)	157	5785	BPSK&OFDM / MCS0 / 1.0	Antenna side-touch	0	1	22.8	22.8	-0.149	0.28	(*)
11n (40HT)	151	5755	BPSK&OFDM / MCS0 / 1.0	Antenna side-touch	0	2	22.8	22.7	-0.193	0.27	-
	159	5795	BPSK&OFDM / MCS0 / 1.0	Antenna side-touch	0	1	22.7	22.7	0.136	0.30 (0.303)	→Worst SAR of W58.

Notes:

*1. For these operation mode, the average antenna terminal conducted power were less than or not more than 0.25dB of 11a mode. (refer to section 6 in this report)

*. Battery was fully charged before starting the SAR measurement.

*. Calibration frequency of the SAR measurement probe (and used conversion factors)

SAR test frequency [MHz]	Probe calibration frequency [MHz]	Validity [MHz]	Used conversion factor	Uncertainty
5755	5800	-45MHz, within ±50 of cal.frequency	3.94	±13.1%
5765	5800	-35MHz, within ±50 of cal.frequency	3.94	±13.1%
5785	5800	-15MHz, within ±50 of cal.frequency	3.94	±13.1%
5795	5800	-5MHz, within ±50 of cal.frequency	3.94	±13.1%
5825	5800	+25MHz, within ±50 of cal.frequency	3.94	±13.1%

*. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.