



SAR TEST REPORT

Test Report No.: 10005570S-A

Applicant : Canon Inc.
Type of Equipment : Wireless Module
Model No. : RF401 (*. Installed into the RF401's platform (1))
FCC ID : AZD401
Test Standard : FCC 47CFR §2.1093,
Supplement C (Edition 01-01) to OET Bulletin 65
Test Result : Complied

Highest Reported SAR(1g) Value	Platform #	Platform type	Platform model	Remarks
< 0.1 W/kg	Platform (1)	Digital Video Camcorder (1)	ID0032	(DTS) 2437MHz, IEEE 802.11n(40HT), (MCS0, BPSK/OFDM) * Highest measured SAR(1g) value: 0.042 W/kg

*. **Highest reported SAR (1g) across exposure conditions for a platform (1) = "< 0.1 W/kg" = grant listing.**
*. Since highest reported SAR (1g) on the platform (1) which obtained in accordance with KDB447498 (v05) was under 0.8 W/kg, this EUT was approved to operate on multi-platform.

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by any agency of the Federal Government.
6. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.

Date of test: May 16, 2013

Test engineer: H. Naka

Hiroshi Naka
Engineer of WiSE Japan, UL Verification Service

Approved by: T. Imamura

Toyokazu Imamura
Leader of WiSE Japan, UL Verification Service

- The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.
 There is no testing item of "Non-accreditation".



REVISION HISTORY

Revision	Test report No.	Date	Page revised	Contents
Original	10005570S-A	May 27, 2013	-	-
-R01	10005570S-A	June 6, 2013	1,2,11,12	(P11) Antenna separation distance was illustrated. (P1,2,12) Related change of P11.

*. By issue of new revision report, the report of an old revision becomes invalid.

CONTENTS **PAGE**

REVISION HISTORY 2(-R01)
CONTENTS 2(-R01)
SECTION 1: Customer information 3
SECTION 2: Equipment under test (EUT) 3
 2.1 Identification of EUT 3
 2.2 Product Description 3
 2.3 Tx output power specification (antenna port terminal conducted) 4
 2.4 Maximum output power which may possible 4
SECTION 3: Test specification, procedures and results 5
 3.1 Test specification 5
 3.2 Exposure limit 5
 3.3 Procedure and result 5
 3.4 Test location 5
 3.5 Confirmation before SAR testing 6
 3.6 Confirmation after SAR testing 6
 3.7 Test setup of EUT and SAR measurement procedure 7
SECTION 4: Operation of EUT during testing 7
SECTION 5: Uncertainty assessment (SAR measurement) 8
SECTION 6: Confirmation before testing 9
 6.1 Assessment for the conducted power of EUT 9
SECTION 7: Measurement results 10
 7.1 SAR test results of Platform (1) 10

Contents of appendixes

APPENDIX 1: Photographs of test setup 11
 Appendix 1-1 Photograph of Platform (1) 11(-R01)
 Appendix 1-2 EUT and support equipment 12(-R01)
 Appendix 1-3 Photograph of test setup / Platform (1) 13
APPENDIX 2: SAR Measurement data 15
 Appendix 2-1 Evaluation procedure 15
 Appendix 2-2 Measurement data / Platform (1) 16
APPENDIX 3: Test instruments 19
 Appendix 3-1 Equipment used 19
 Appendix 3-2 Configuration and peripherals 20
 Appendix 3-3 Test system specification 21
 Appendix 3-4 Simulated tissues composition and parameter confirmation 22
 Appendix 3-5 Daily check data 22
 Appendix 3-6 Daily check measurement data 23
 Appendix 3-7 Daily check uncertainty 23
 Appendix 3-8 Calibration certificate: E-Field Probe (EX3DV4) 24
 Appendix 3-9 Calibration certificate: Dipole (D2450V2) 35

SECTION 1: Customer information

Company Name	Canon Inc.
Brand Name	Canon
Address	30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501 Japan
Telephone Number	+81-3-5482-8070
Facsimile Number	+81-3-3757-8431
Contact Person	Yasushi Sasaki

SECTION 2: Equipment under test (EUT)**2.1 Identification of EUT**

Type of Equipment	Wireless Module
Model Number	RF401
Serial Number	E80357
Condition of EUT	RF401: Production prototype (*. Not for sale: This sample is equivalent to mass-produced items.) *. Used platform (Platform (1): Digital video camcorder (1), model: ID0032): Production prototype (*. Not for sale: This sample is equivalent to mass-produced items.)
Receipt Date of Sample	May 5, 2013 (*. EUT for the power measurement.) May 16, 2013 (*. EUT for the SAR test. The EUT that had been measured the power of SAR test reference, was installed into the Platform (1)-Digital video camcorder (1) from the beginning.) *. After power measurement, the EUT was returned to the customer, and the RF wiring was changed to the original antenna line form the antenna conducted power measurement line of the SAR test. The EUT was installed into a Platform (1) which SAR tested, by the customer. *. No modification by the Lab.
Country of Mass-production	RF401: Philippines (*. Used platform (1): China)
Category Identified	Portable device *. Since EUT may contact and/or very close to a human body during Wi-Fi operation, the partial-body SAR (1g) shall be observed.
Rating	DC3.3V supplied form the platform equipment. *. The EUT is installed to the specified platform that was operated by either the re-chargeable Li-ion battery or ac adaptor. Since the battery operation showed smaller SAR, the platform which had built-in EUT was operated by an ac adaptor.
Feature of EUT	The EUT is a Wireless Module which installs into the multi-platform.
SAR Accessory	None

2.2 Product Description (Wireless module: RF401)

Equipment type	Transceiver
Frequency of operation	2412-2462MHz (11b,11g,,11n(20HT)), 2422-2452MHz (11n(40HT))
Channel spacing	5MHz
Bandwidth	20MHz(11b,11g,,11n(20HT)), 40MHz(11n(40HT))
ITU code	G1D, D1D
Type of modulation	DSSS(11b): CCK, DQPSK, DBPSK OFDM(11g,11n(20HT),11n(40HT)): 64QAM, 16QAM, QPSK, BPSK
Q'ty of Antenna	1 pc.
Antenna type	Monopole type chip antenna
Antenna gain (peak)	-0.94dBi
Transmit power and tolerance (Manufacture variation)	11b: 12dBm ±2.5dBm 11n(20HT): 12dBm ±2.5dBm 11g: 12dBm ±2.5dBm 11n(40HT): 12dBm ±2.5dBm *. Refer to clause 2.3 for more detail. *. The measured Tx output power (conducted) refers to section 6 in this report.
Maximum output power which may possible	11b: 14.5dBm 11n(20HT): 14.5dBm 11g: 14.5dBm 11n(40HT): 14.5dBm *. Refer to clause 2.4 for more detail.
Power supply	DC 3.3V (*. The power of DC3.3V is supplied from the platform via constant voltage circuit.)
Operation temperature range	-20 to +85 deg.C

*. The EUT do not use the special transmitting technique such as "beam-forming" and "time-space code diversity."

2.3 Tx output power specification (antenna port terminal conducted)

		Target Power (Tx output power specification) [dBm] (average)																											
		11b					11g								11n(20HT)														
[MHz]	CH	1	2	5.5	11	6	9	12	18	24	36	48	54	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
2412	1	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
2417	2	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
2422	3	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
2427	4	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
2432	5	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
2437	6	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
2442	7	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
2447	8	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
2452	9	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
2457	10	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
2462	11	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	

		Target Power (Tx output power specification) [dBm] (average)															
		11n(40HT)															
[MHz]	CH	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
2422	3	12	12	12	12	12	12	12	12	-	-	-	-	-	-	-	-
2427	4	12	12	12	12	12	12	12	12	-	-	-	-	-	-	-	-
2432	5	12	12	12	12	12	12	12	12	-	-	-	-	-	-	-	-
2437	6	12	12	12	12	12	12	12	12	-	-	-	-	-	-	-	-
2442	7	12	12	12	12	12	12	12	12	-	-	-	-	-	-	-	-
2447	8	12	12	12	12	12	12	12	12	-	-	-	-	-	-	-	-
2452	9	12	12	12	12	12	12	12	12	-	-	-	-	-	-	-	-

2.4 Maximum output power which may possible

		Maximum output power which may possible [dBm] (average)																											
		11b					11g								11n(20HT)														
[MHz]	CH	1	2	5.5	11	6	9	12	18	24	36	48	54	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
2412	1	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2417	2	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2422	3	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2427	4	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2432	5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2437	6	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2442	7	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2447	8	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2452	9	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2457	10	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	
2462	11	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	

		Maximum output power which may possible [dBm] (average)															
		11n(40HT)															
[MHz]	CH	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
2422	3	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	-	-	-	-	-	-	-	-
2427	4	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	-	-	-	-	-	-	-	-
2432	5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	-	-	-	-	-	-	-	-
2437	6	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	-	-	-	-	-	-	-	-
2442	7	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	-	-	-	-	-	-	-	-
2447	8	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	-	-	-	-	-	-	-	-
2452	9	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14.5	-	-	-	-	-	-	-	-

SECTION 3: Test specification, procedures and results

3.1 Requirements for compliance testing defined by the FCC / Test specification

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992. According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

1. Specific Absorption Rate (SAR) is a measure of the rate of energy absorption due to exposure to an RF transmitting source (wireless portable device).
2. IEEE/ANSI Std. C95.1-1992 limits are used to determine compliance with FCC ET Docket 93-62.

Supplement C (Edition 01-01) to OET Bulletin 65 (Edition 97-01):

Supplement C (Edition 01-01) - Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions

OET Bulletin 65 (Edition 97-01) - Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields

IEEE Std. 1528-2003:

IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques Supplement C

- In additions; **KDB 447498 D01 (v05):** General RF exposure guidance
 KDB 865664 D01 (v01): SAR measurement 100MHz to 6GHz
 KDB 248227 D01 (v01r02): SAR measurement procedures for 802.11a/b/g transmitters

- *. In this report, IEC 62209-1:2005 and IEC 62209-2:2010-03 are also considered as reference. The comment is attached to the portion to which IEC 62209-1 and IEC 62209-2 were referred to specially.

3.2 Exposure limit

Environments of exposure limit	Whole-Body (averaged over the entire body)	Partial-Body (averaged over any 1g of tissue)	Hands, Wrists, Feet and Ankles (averaged over any 10g of tissue)
(A) Limits for Occupational /Controlled Exposure (W/kg)	0.4	8.0	20.0
(B) Limits for General population /Uncontrolled Exposure (W/kg)	0.08	1.6	4.0

*.Occupational/Controlled Environments: are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

*.General Population/Uncontrolled Environments: are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

The limit applied in this test report is;

General population / uncontrolled exposure, Partial-Body (averaged over any 1g of tissue) limit: 1.6 W/kg

3.3 Procedures and Results

	Wi-Fi (DTS) / in Platform (1)
Test Procedure	FCC OET Bulletin 65, Supplement C
	SAR
Category	FCC 47CFR §2.1093
Results (SAR(1g))	Complied
Reported SAR value (*. Scaled)	< 0.1 W/kg
Measured SAR value	0.040 W/kg
Operation mode	11n(40HT), MCS0, BPSK/OFDM, 2437 MHz(6ch)
Output power (scaled factor)	13.49 dBm (×1.26)

Note: UL Japan's SAR Work Procedures No.13-EM-W0429 and 13-EM-W0430. No addition, deviation nor exclusion has been made from standards

Test outline: Where this product is built into a new platform, it was verified whether multiplatform conditions can be suited in according with section 2) of 5.2.2.2 in KDB447498 D01 (v05).

Consideration of the test results: **The highest reported SAR (1g) of Platform (1) was kept ≤ 0.8W/kg.**

Since highest reported SAR (1g) on the platform (1) which obtained in accordance with KDB447498 (v05) was under 0.8 W/kg, this EUT was approved to operate on multi-platform.

3.4 Test Location

No.7 shielded room (2.76m (Width) × 3.76m (Depth) × 2.4m (Height)) for SAR testing.

UL Japan, Inc., Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone number: +81 463 50 6400 / Facsimile number: +81 463 50 6401

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401

3.5 Confirmation before SAR testing

3.5.1 Correlation of Output Power between EMC and SAR tests

It was checked that the antenna port power was correlated within 0~+5% (FCC requirements). The result is shown in Section 6.

Test	Remarks	Serial number
SAR	Before SAR test, the RF wiring for the sample that was actually used for the SAR test, had been switched to the antenna conducted power measurement line from the antenna line, and then the output power was measured. The average and peak power of specified operation mode(s) were measured at default channel. After power measurement, the EUT was returned to the customer. Then, the EUT was installed in a Platform (1) which SAR tested, by the customer. *. The power was measured by the calibrated power sensor and power meter (65MHz measurement bandwidth).	E80357
EMC	Before SAR test, the peak power of EUT was measured in order to satisfy an EMC test requirement. The average power that was reference of SAR test was also measured additionally.	E80357

3.5.2 Average power for SAR tests

Step.1 Data rate check

The EUT supported the following data rate in each operation mode.

The output powers related with all data rate were measured for all operation mode at a middle channel.

11b		11g		11n(20HT)			11n(40HT)		
Modulation	Data rate [Mbps]	Modulation	Data rate [Mbps]	MCS Index	Spatial Stream	Modulation	MCS Index	Spatial Stream	Modulation
DBPSK/DSSS	1	BPSK/OFDM	6	MCS0	1	BPSK/OFDM	MCS0	1	BPSK/OFDM
DQPSK/DSSS	2	BPSK/OFDM	9	MCS1	1	QPSK/OFDM	MCS1	1	QPSK/OFDM
CCK/DSSS	5.5	QPSK/OFDM	12	MCS2	1	QPSK/OFDM	MCS2	1	QPSK/OFDM
CCK/DSSS	11	QPSK/OFDM	18	MCS3	1	16QAM/OFDM	MCS3	1	16QAM/OFDM
		16QAM/OFDM	24	MCS4	1	16QAM/OFDM	MCS4	1	16QAM/OFDM
		16QAM/OFDM	36	MCS5	1	64QAM/OFDM	MCS5	1	64QAM/OFDM
		64QAM/OFDM	48	MCS6	1	64QAM/OFDM	MCS6	1	64QAM/OFDM
		64QAM/OFDM	54	MCS7	1	64QAM/OFDM	MCS7	1	64QAM/OFDM

Step.2 Decision of SAR test channel

The following operation mode, data rate and channels were determined by the SAR reference power measured.

Mode	MHz	Channel	default	SAR tested channel				Remarks	
			11b/g/n(20HT)	11b	11g	11n(20HT)	11n(40HT)		
802.11 b/g/n	2412	1(*1)	√	n/a(*3)	n/a(*2)	n/a(*2)	n/a(*3)	*3. SAR test was only applied to a highest output channel of 11b and 11n(40HT), because the reported SAR (1g) value were less than 0.05W/kg and the peak SAR were less than 0.1W/kg. (KDB248227) *. Since the average powers of higher data rate were less than 0.25dB higher than the lowest data rate, SAR test was only applied to the lowest data rate. (KDB248227)	
	2422	3					n/a(*3)		
	2437	6	√	#	n/a(*2)	n/a(*2)	#		
	2452	9							n/a(*3)
	2462	11(*1)	√	n/a(*3)	n/a(*2)	n/a(*2)			

√ = "default test channels of requested by KDB248227", n/a: SAR test was not applied, # = SAR test was applied.

*1. Any output power reducing for channel 1 and 11 to meet restricted band requirements was not observed. Therefore channel 1 and 11 was selected for the default channels and SAR test was applied.

*2. Since the target average power of 11g and 11n(20HT) were less than 0.25dB higher than the corresponded 11b power, SAR test was not applied to the 11g and 11n(20HT) mode. (KDB248227)

3.6 Confirmation after SAR testing

It was checked that the power drift [W] is within ±5% in the evaluation procedure of SAR testing. The verification of power drift during the SAR test is that DASY5 system calculates the power drift by measuring the e-filed at the same location at beginning and the end of the scan measurement for each test position.

The result is shown in APPENDIX 2.

*. DASY5 system calculation Power drift value[dB] = 20log(Ea)/(Eb) (where, Before SAR testing: Eb[V/m] / After SAR testing: Ea[V/m])

Limit of power drift[W] = ±5%

Power drift limit (X) [dB] = 10log(P_drift) = 10log(1.05/1) = 10log(1.05) - 10log(1) = 0.21dB

from E-filed relations with power.

$S = E \times H = E^2 / \eta = P / (4 \times \pi \times r^2)$ (η : Space impedance) → $P = (E^2 \times 4 \times \pi \times r^2) / \eta$

Therefore, The correlation of power and the E-filed

Power drift limit (X) dB = 10log(P_drift) = 10log(E_drift)^2 = 20log(E_drift)

From the above mentioned, the calculated power drift of DASY5 system must be the less than ±0.21dB.

3.7 Test setup of EUT and SAR measurement procedure

After considering the outline of EUT, the SAR test was carried out on the following setup conditions.

*. Refer to Appendix 1 for test setup photographs.

Setup	Explanation of EUT setup position	Antenna to user distance	Applied SAR test?	SAR type
Bottom	The bottom surface of EUT was touched to the Flat phantom.	5.6mm	applied	Body (touch)
Top	The top surface (LCD side) of EUT was touched to the Flat phantom.	15.6mm	applied	
Left	The left hand grip portion of EUT was touched to the Flat phantom.	15.4mm	applied	
Right	The right hand grip portion of EUT was touched to the Flat phantom.	59.6mm	applied	
Front (Lens)	The left portion on front section (lens side) of EUT was touched to the Flat phantom.	15.3mm	applied	
Rear	The rear surface of EUT was touched to the Flat phantom.	80.3mm	applied	

*. **Antenna to user distance:** this means the distance from the antenna which is located inside a product to the surface of the product which an operator touches.

*. The LCD of platform was closed position for all setup described in above.

*. **Size of EUT: 76 mm (width) × 96 mm (depth) × 22 mm (height)** (manufacture's specification, when LCD and stands were closed.)

By the determined test setup shown above, the SAR test was applied in the following procedures.

Step 1	Change the positions.
Step 2	Change the operation mode. (at the worst position.)

*. During SAR test, the radiated power is always monitored by Spectrum Analyzer.

SECTION 4: Operation of EUT during testing

4.1 Operating modes for SAR testing

This EUT has IEEE.802.11b, 11g, 11n(20HT) and 11n(40HT) continuous transmitting modes.

The frequency and the modulation used in the SAR testing are shown as a following.

Operation mode	11b (*1)	11g	11n(20HT)	11n(40HT)
Tx frequency band	2412-2462MHz			2422-2452MHz
Tested frequency	2412MHz (*1)	- (*2)	- (*2)	2437MHz (*1)
Modulation	DBPSK/DSSS	- (*2)	- (*2)	BPSK/OFDM
Data rate	1Mbps (*3)	- (*2)	- (*2)	MCS0 (*3)
Crest factor	1.0 (100% duty cycle)	- (*2)	- (*2)	1.0 (100% duty cycle)
Controlled software	Software title: 168R2151.APP (Version 1.0) During SAR test, the output condition of the transmitter of the EUT was controlled by operation of the LCD of the EUT with the exclusive used 168R2151.APP software installed in the EUT.			

*1. SAR test was only applied to a highest output channel of 11b and 11n(40HT), because the reported SAR (1g) value were less than 0.05W/kg and the peak SAR were less than 0.1W/kg (KDB248227)

*2. Since the target average power of 11g and 11n(20HT) were less than 0.25dB higher than the corresponded 11b power, SAR test was not applied to the 11g and 11n(20HT) mode. (KDB248227)

*3. Since the average powers of higher data rate were less than 0.25dB higher than the lowest data rate, SAR test was only applied to the lowest data rate. (KDB248227)

SECTION 5: Uncertainty Assessment (SAR measurement)

Uncertainty of SAR measurement(v06) (*: Body tissue, ε & σ tolerance: $\leq \pm 5\%$, Tx: $\approx 100\%$ duty cycle)	Under 3 GHz	
	1g SAR	10g SAR
Combined measurement uncertainty of the measurement system (k=1)	$\pm 12.5\%$	$\pm 12.2\%$
Expanded uncertainty (k=2)	$\pm 25.0\%$	$\pm 24.4\%$

	Error Description (Under 3GHz) (v06)	Uncertainty Value	Probability distribution	Divisor	ci (1g)	ci (10g)	ui (1g) (std. uncertainty)	ui (10g) (std. uncertainty)	Vi, veff
A	Measurement System (DASY5)								
1	Probe Calibration Error	$\pm 6.0\%$	Normal	1	1	1	$\pm 6.0\%$	$\pm 6.0\%$	∞
2	Axial isotropy Error	$\pm 4.7\%$	Rectangular	$\sqrt{3}$	0.7	0.7	$\pm 1.9\%$	$\pm 1.9\%$	∞
3	Hemispherical isotropy Error ($< 5\text{deg}$, flat phantom)	$\pm 9.6\%$	Rectangular	$\sqrt{3}$	0.7	0.7	$\pm 3.9\%$	$\pm 3.9\%$	∞
4	Boundary effects Error	$\pm 1.4\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.8\%$	$\pm 0.8\%$	∞
5	Linearity Error	$\pm 4.7\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.7\%$	$\pm 2.7\%$	∞
6	Probe modulation response (CW)	$\pm 0.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.0\%$	$\pm 0.0\%$	∞
7	Sensitivity Error (detection limit)	$\pm 1.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$	∞
8	Response Time Error ($< 5\text{ms}/100\text{ms}$ wait)	$\pm 0.0\%$	Normal	1	1	1	$\pm 0.0\%$	$\pm 0.0\%$	∞
9	Integration Time Error (100% duty cycle)	$\pm 0.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.0\%$	$\pm 0.0\%$	∞
10	Readout Electronics Error(DAE)	$\pm 0.3\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.3\%$	$\pm 0.3\%$	∞
11	RF ambient conditions-noise	$\pm 3.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.7\%$	$\pm 1.7\%$	∞
12	RF ambient conditions-reflections	$\pm 3.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.7\%$	$\pm 1.7\%$	∞
13	Probe positioner mechanical tolerance	$\pm 1.1\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$	∞
14	Probe Positioning with respect to phantom shell	$\pm 2.9\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 1.7\%$	$\pm 1.7\%$	∞
15	Errors: Extrapol., Interpol. & Integration Algorithms	$\pm 1.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 0.6\%$	$\pm 0.6\%$	∞
B	Test Sample Related								
16	Test Sample Positioning Error	$\pm 5.0\%$	Normal	1	1	1	$\pm 5.0\%$	$\pm 5.0\%$	145
17	Device Holder or Positioner Tolerance	$\pm 3.6\%$	Normal	1	1	1	$\pm 3.6\%$	$\pm 3.6\%$	5
18	Test Sample Output Power Drift Error	$\pm 5.0\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 2.9\%$	$\pm 2.9\%$	∞
C	Phantom and Setup								
19	Phantom uncertainty (shape, thickness tolerances)	$\pm 7.5\%$	Rectangular	$\sqrt{3}$	1	1	$\pm 4.3\%$	$\pm 4.3\%$	∞
20	Target Liquid Conductivity Tolerance ($\leq 5\%$)	$\pm 5.0\%$	Rectangular	$\sqrt{3}$	0.64	0.43	$\pm 1.8\%$	$\pm 1.2\%$	∞
21	Measurement Liquid Conductivity Error	$\pm 2.9\%$	Normal	1	0.64	0.43	$\pm 1.9\%$	$\pm 1.2\%$	3
22	Target Liquid Permittivity Tolerance ($\leq 5\%$)	$\pm 5.0\%$	Rectangular	$\sqrt{3}$	0.6	0.49	$\pm 1.7\%$	$\pm 1.4\%$	∞
23	Measurement Liquid Permittivity Error	$\pm 2.9\%$	Normal	1	0.6	0.49	$\pm 1.7\%$	$\pm 1.4\%$	3
24	Liquid Conductivity-temp.uncertainty ($\leq 2\text{deg.C.}$)	$\pm 5.2\%$	Rectangular	$\sqrt{3}$	0.78	0.71	$\pm 2.3\%$	$\pm 2.1\%$	∞
25	Liquid Permittivity-temp.uncertainty ($\leq 2\text{deg.C.}$)	$\pm 0.8\%$	Rectangular	$\sqrt{3}$	0.23	0.26	$\pm 0.1\%$	$\pm 0.1\%$	∞
	Combined Standard Uncertainty						$\pm 12.5\%$	$\pm 12.2\%$	479
	Expanded Uncertainty (k=2)						$\pm 25.0\%$	$\pm 24.4\%$	

*. This measurement uncertainty budget is suggested by IEEE 1528, IEC 62209-2 and determined by Schmid & Partner Engineering AG (DASY5 Uncertainty Budget).

SECTION 6: Confirmation before testing

6.1 Assessment for the conducted power of EUT

6.1.1 SAR reference power data: worst data rate / worst channel determination and Comparison with EMC data

Mode	Freq. [MHz]	D/R [Mbps]	Cable Loss [dB]	Att. [dB]	D/F [dB]	Average power			PAR [dB]	Power tolerance & correction				Apply SAR test? (Y: yes)	Output power of EMC test (*3)		Remarks
						P/M Reading [dBm]	Result			Target & tolerance [dBm]	Deviation from max. [dB]	Scaled Factor [-]	≤2 dB? (Y: yes)		Aver. [dBm]	ΔSAR [dB]	
							[dBm]	[mW]									
11b (Pwr. Setting =12)	2437	1	0.67	10.02	0.00	2.60	13.29	21.3	2.63	12.0±2.5	-1.21	x1.32	Y	-(*)1	13.09	0.20	
	2437	2	0.67	10.02	0.00	2.62	13.31	21.4	2.63	12.0±2.5	-1.19	x1.32	Y	-(*)2	13.14	0.17	
	2437	5.5	0.67	10.02	0.00	2.61	13.30	21.4	2.03	12.0±2.5	-1.20	x1.32	Y	-	13.12	0.18	
	2437	11	0.67	10.02	0.00	2.59	13.28	21.3	2.59	12.0±2.5	-1.22	x1.32	Y	-	13.08	0.20	
	2412	1	0.67	10.02	0.00	2.89	13.58	22.8	2.62	12.0±2.5	-0.92	x1.24	Y	Y(*)1	-	-	Highest ch.(11b)
	2462	1	0.67	10.02	0.00	2.69	13.38	21.8	2.82	12.0±2.5	-1.12	x1.29	Y	-(*)1	-	-	
	2412	2	0.67	10.02	0.00	2.91	13.60	22.9	2.59	12.0±2.5	-0.90	x1.23	Y	-	13.40	0.20	vs. EMC data)
2462	2	0.67	10.02	0.00	2.63	13.32	21.5	2.88	12.0±2.5	-1.18	x1.31	Y	-	13.13	0.19	vs. EMC data)	
11g (*1) (Pwr. Setting =12)	2437	6	0.67	10.02	0.00	2.35	13.04	20.1	9.05	12.0±2.5	-1.46	x1.40	Y	-(*)3	12.90	0.14	
	2437	9	0.67	10.02	0.00	2.21	12.90	19.5	8.64	12.0±2.5	-1.60	x1.45	Y	-	12.73	0.17	
	2437	12	0.67	10.02	0.00	2.32	13.01	20.0	8.86	12.0±2.5	-1.49	x1.41	Y	-	12.83	0.18	
	2437	18	0.67	10.02	0.00	2.32	13.01	20.0	8.44	12.0±2.5	-1.49	x1.41	Y	-	12.81	0.20	
	2437	24	0.67	10.02	0.00	2.32	13.01	20.0	9.05	12.0±2.5	-1.49	x1.41	Y	-	12.84	0.17	
	2437	36	0.67	10.02	0.00	2.22	12.91	19.5	8.99	12.0±2.5	-1.59	x1.44	Y	-	12.78	0.13	
	2437	48	0.67	10.02	0.00	2.27	12.96	19.8	8.75	12.0±2.5	-1.54	x1.43	Y	-	12.84	0.12	
	2437	56	0.67	10.02	0.00	2.22	12.91	19.5	8.88	12.0±2.5	-1.59	x1.44	Y	-	12.79	0.12	
	2412	6	0.67	10.02	0.00	2.62	13.31	21.4	8.96	12.0±2.5	-1.19	x1.32	Y	-(*)3	13.13	0.18	Highest ch.(11g)
	2462	6	0.67	10.02	0.00	2.38	13.07	20.3	9.10	12.0±2.5	-1.43	x1.39	Y	-(*)3	12.89	0.18	
11n (20HT) (*1) (Pwr. Setting =12)	2437	MCS0	0.67	10.02	0.00	2.38	13.07	20.3	8.39	12.0±2.5	-1.43	x1.39	Y	-(*)3	12.94	0.13	
	2437	MCS1	0.67	10.02	0.00	2.32	13.01	20.0	8.44	12.0±2.5	-1.49	x1.41	Y	-	12.83	0.18	
	2437	MCS2	0.67	10.02	0.00	2.34	13.03	20.1	8.42	12.0±2.5	-1.47	x1.40	Y	-	12.91	0.12	
	2437	MCS3	0.67	10.02	0.00	2.32	13.01	20.0	8.45	12.0±2.5	-1.49	x1.41	Y	-	12.89	0.12	
	2437	MCS4	0.67	10.02	0.00	2.35	13.04	20.1	8.39	12.0±2.5	-1.46	x1.40	Y	-	12.86	0.18	
	2437	MCS5	0.67	10.02	0.00	2.34	13.03	20.1	8.25	12.0±2.5	-1.47	x1.40	Y	-	12.89	0.14	
	2437	MCS6	0.67	10.02	0.00	2.34	13.03	20.1	8.28	12.0±2.5	-1.47	x1.40	Y	-	12.88	0.15	
	2437	MCS7	0.67	10.02	0.00	2.33	13.02	20.0	8.40	12.0±2.5	-1.48	x1.41	Y	-	12.91	0.11	
	2412	MCS0	0.67	10.02	0.00	2.65	13.34	21.6	8.26	12.0±2.5	-1.16	x1.31	Y	-(*)3	13.14	0.20	Highest ch.(11n(20))
	2462	MCS0	0.67	10.02	0.00	2.42	13.11	20.5	8.44	12.0±2.5	-1.39	x1.38	Y	-(*)3	12.91	0.20	
11n (40HT) (Pwr. Setting =12)	2437	MCS0	0.67	10.02	0.00	2.80	13.49	22.3	8.36	12.0±2.5	-1.01	x1.26	Y	Y(*)1	13.37	0.12	Highest ch.(11n(40))
	2437	MCS1	0.67	10.02	0.00	2.78	13.47	22.2	8.24	12.0±2.5	-1.03	x1.27	Y	-	13.32	0.15	
	2437	MCS2	0.67	10.02	0.00	2.79	13.48	22.3	8.70	12.0±2.5	-1.02	x1.26	Y	-	13.35	0.13	
	2437	MCS3	0.67	10.02	0.00	2.78	13.47	22.2	8.81	12.0±2.5	-1.03	x1.27	Y	-	13.33	0.14	
	2437	MCS4	0.67	10.02	0.00	2.79	13.48	22.3	8.66	12.0±2.5	-1.02	x1.26	Y	-	13.32	0.16	
	2437	MCS5	0.67	10.02	0.00	2.74	13.43	22.0	8.81	12.0±2.5	-1.07	x1.28	Y	-	13.28	0.15	
	2437	MCS6	0.67	10.02	0.00	2.59	13.28	21.3	8.82	12.0±2.5	-1.22	x1.32	Y	-	13.11	0.17	
	2437	MCS7	0.67	10.02	0.00	2.57	13.26	21.2	8.47	12.0±2.5	-1.24	x1.33	Y	-	13.08	0.18	
	2412	MCS0	0.67	10.02	0.00	2.70	13.39	21.8	8.37	12.0±2.5	-1.11	x1.29	Y	-(*)1	13.20	0.19	
	2462	MCS0	0.67	10.02	0.00	2.24	12.93	19.6	8.58	12.0±2.5	-1.57	x1.44	Y	-(*)1	12.74	0.19	

*. EUT serial number: "E80357" for SAR test and SAR reference power measurement / "E80357" for EMC test.
 The difference between the SAR reference power and the power of EMC test was not less than 0dB and not higher than 0.21dB.
Therefore it was judged that EUT condition that was used for SAR test was equivalent to the EMC test.

*. Freq.: Frequency, D/R: Data Rate, Att.: Attenuator loss, D/F: Duty Factor (0dB=100% duty cycle), n/a: not applied, PAR: Peak average ratio.
 *. Calculating formula: Results (Ave)=[("P/M Reading")+("Cable loss")+("Attenuator")+("duty factor")], PAR (dBm)=[Peak power (dBm)]-[Average power (dBm)]
 Deviation form max.: Power deviation (Deviation [dB])= "results power (average)" - "Max.-specification output power (average)"
 Scaled Factor: Power scaled factor for obtained SAR value, Scaled Factor [-]=1/(10^(("Deviation from max."/10))

*1. SAR test was only applied to a highest output channel of 11b and 11n(40HT), because the reported SAR (1g) value that had been SAR tested were less than 0.05W/kg and the peak SAR were less than 0.1W/kg. (KDB248227)
 *2. Since the average powers of higher data rate were less than 0.25dB higher than the lowest data rate, SAR test was only applied to the lowest data rate. (KDB248227)
 *3. Since the target average power of 11g and 11n(20HT) were less than 0.25dB higher than the corresponded 11b power, SAR test was not applied to the 11g and 11n(20HT) mode. (KDB248227)

*. Uncertainty of antenna port conducted test; Power measurement uncertainty above 1GHz for this test was: (±) 1.5dB
 *. SAR reference; Date measured: May 13, 2013 / Measured by: Hiroshi Naka / Place: preparation room of No. 7 shielded room. (25 deg.C. / 52 %RH)
 "Power of EMC test"; this reference is described in the test report of 1005569S-A.

SECTION 7: Measurement results

7.1 SAR test results of Platform (1)-Digital video camcorder (1) (model: ID0032)

Measurement date: May 16, 2013

Measurement by: Hiroshi Naka

[Liquid measurement (Body simulated tissue)]

Target Frequency [MHz]	Liquid parameters						ASAR Coefficients		Remarks / Environment		
	Permittivity (εr) [-]			Conductivity [S/m]			Temp. [deg.C.]	Depth [mm]		ASAR (1g) [%]	Correction required?
	Target	Measured (Δεr)	%	Target	Measured (Δσ)	%					
2450	52.7	50.25	-4.7%	1.95	2.016	+3.4%	23.3	154	(+2.67)(*1)	not required.	May 16, 2013, before SAR test /ambient; 24.2 deg.C., 49%RH
2412 (1)	52.75	50.45	-4.4%	1.914	1.958	+2.3%			(+2.10)(*1)	not required.	
2437 (6)	52.72	50.33	-4.5%	1.938	1.996	+3.0%			(+2.47)(*1)	not required.	

*. The target value is a parameter defined in OET65 Supplement C. In the current standards (e.g., IEEE 1528, OET 65 Supplement C), the dielectric parameters suggested for head and body tissue simulating liquid are given at 1800-2000, 2450, and 3000MHz. As an intermediate solution, dielectric parameters for the frequencies between 2000 to 3000 MHz were obtained using linear interpolation. (Refer to Appendix 3-4)

*1. The number of ΔSAR(1g) of body simulated tissue was reference purpose only. ΔSAR coefficients are parameters defined in Annex F, IEC 62209-2:2010 (head tissue). In accordance with clause 6.1.1 of IEC62209-2; "If the correction ΔSAR has a negative sign, the measured SAR results shall not be corrected", the calculated ASAR values of the tested liquid had shown negative correction. Therefore the measured SAR was not required ΔSAR correction.
 $\Delta SAR(1g) = C_{\epsilon r} \times \Delta \epsilon r + C_{\sigma} \times \Delta \sigma$, $C_{\epsilon r} = -7.854E-4 \times f^3 + 9.402E-3 \times f^2 - 2.742E-2 \times f + 0.2026$ / $C_{\sigma} = 9.804E-3 \times f^3 - 8.661E-2 \times f^2 + 2.981E-2 \times f + 0.7829$

[SAR measurement results (Partial-Body)]

SAR measurement results (Body simulated tissue)													Reported SAR		Remarks	
Mode	[MHz] (CH)	Modulation /Data rate / Crest factor	EUT setup conditions			Liquid temp. [deg.C.]		Power drift [dB]	SAR (1g) [W/kg]			Data# in Appendix 2-2	SAR (1g) [W/kg]			
			Position (*1)	Gap [mm]	Battery / AC adaptor (*3)	Before	After		maximum value of multi-peak				Scaled factor	tune-up SAR		
									Observed	ASAR [%]	ASAR corrected					
Step 1: Change the positions																
11b	2412(1)	BPSK&DSSS /1Mbps /1.0	Bottom	0	AC adaptor	23.3	23.3	-0.17	0.037	-	-	Step 1-1	×1.24	0.05	-	
			Top (LCD)	0		23.5	23.5	-	(0.014)	*. Fast SAR (*2)	-	-	-	-	-	*. Polynomial-fit
			Left	0		23.5	23.5	-	(0.014)	*. Fast SAR (*2)	-	-	-	-	-	*. Polynomial-fit
			Front (Lens)	0		23.5	23.5	-	(0.00437)	*. Fast SAR (*2)	-	-	-	-	-	*. Polynomial-fit
			Rear	0		23.5	23.4	-	(0.00138)	*. Fast SAR (*2)	-	-	-	-	-	*. Polynomial-fit
			Right	0	Battery	23.4	23.4	-	(0.00253)	*. Fast SAR (*2)	-	-	-	-	-	*. Polynomial-fit
Step 2: Changed the operation mode.																
11n (40HT)	2437(6)	BPSK&OFDM /1Mbps /1.0	Bottom	0	AC adaptor	23.3	23.3	-0.11	0.042	-	-	Step 2-1	×1.26	0.05	>Highest SAR. *Reported SAR(1g): <0.1W/kg	
					Battery	23.3	23.3	-0.88	0.034	-	-	Step 2-2	×1.26	0.04	(*3)	

Notes:

- *. Gap: It is the separation distance between the nearest position of EUT outer surface and the bottom outer surface of phantom; n/a: not applied.
- *1. The LCD of platform was closed position for all setup described in above test setup.
- *2. Fast SAR algorithm; Douglas, M.G., Chou, C-K.; Accurate and Fast Estimation of Volumetric SAR from Planner Scans from 30 MHz to 6 GHz;” Bioelectromagnetics Society 29th Annual Meeting, June 2007.
- *3. The platform (1) (digital video camcorder) was operated by either the re-chargeable Li-ion battery or ac adaptor. Since the battery operation showed smaller SAR than AC adaptor operation and showed the higher power drift, the platform (1) (digital video camcorder) was operated by an ac adaptor.
- *. During test, the platform (1) (digital video camcorder) was operated without all signal interface cables.
- *. SAR test was only applied to a highest output channel of 11b and 11n(40HT), because the reported SAR (1g) value that had been SAR tested were less than 0.05W/kg and the peak SAR were less than 0.1W/kg. (KDB248227)
- *. Since the average powers of higher data rate were less than 0.25dB higher than the lowest data rate, SAR test was only applied to the lowest data rate. (KDB248227)
- *. Since the target average power of 11g and 11n(20HT) were less than 0.25dB higher than the corresponded 11b power, SAR test was not applied to the 11g and 11n(20HT) mode. (KDB248227)
- *. Calibration frequency of the SAR measurement probe (and used conversion factors)

SAR test frequency	Probe calibration frequency	Validity [MHz]	Used conversion factor	Uncertainty
2412 MHz	2450 MHz	-38MHz, within ±50 of calibration frequency	6.77	±12.0%
2437 MHz	2450 MHz	-13MHz, within ±50 of calibration frequency	6.77	±12.0%

*. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.