

CANON INC.

HEADQUARTERS

30-2, SHIMOMARUKO 3-CHOME, OHTA-KU, TOKYO 146-8501 JAPAN

PHONE: (03)3758-2111

June 20, 2011

FCC ID

: AZDBM70659

Model

: BM70659

Applicant

: Canon Inc.

## Request for Limited Modular Transmitter Approval

This Wireless LAN Module (Model: BM70659) is designed by Canon Inc.

This modular transmitter will be equipped only in the medical device described in the SAR Test Report, which is produced by Canon Inc. or the manufacturer consigned the production by Canon Inc.

This modular transmitter complies with the modular transmitters basic requirements (Item 1 to 8) in FCC Part 15 Subpart C Section 15.212 as indicated below:

## [Modular transmitters basic requirements]

- (1) Have its own RF shielding: This modular transmitter has its own RF shielding. Please refer to the external photo.
- (2) Have buffered modulation/data inputs: Data input to this modular transmitter is controlled as not generating excessive data speed and abnormal modulation.
- (3) Have its own power supply regulation: This modular transmitter is provided with stable power supply DC3.5V from the host device and has power supply regulator which provides DC3.0V and DC1.8V. Please refer to the block diagram.
- (4) Comply with the antenna and transmission system requirements of § 15.203, 15.204(b) and 15.204(c): This module has a unique coupling/antenna connector (U-FL). This modular transmitter will always be used in the configuration in which it was authorized.
- (5) Tested in a stand-alone configuration: The modular transmitter has been performed the testing as a stand alone and then confirmed the compliance.
  - Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in FCC § 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module. The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available: This modular transmitter complies with AC line conducted requirements. AC/DC power lines and data input/output lines does not contain ferrites, and the lengths of these lines are typical of actual use. All peripherals used during the testing are unmodified and commercially available. Please refer to the test report.
- (6) Equipped with either a permanently affixed label or must be capable of electronically displaying its FCC ID: FCC ID is shown on the label and permanently affixed to this modular transmitter. Please refer to the label drawing. If the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module: If the FCC ID is not visible, FCC ID will also be displayed on the host device. Please refer to the installation manual.
- (7) Comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements: The necessary explanation to be complied with this requirement is contained in the manual. Please refer to the installation manual.
- (8) Comply with any applicable RF exposure requirements in its final configuration: The modular transmitter complies with FCC radiation exposure requirement. Please refer to the SAR Test Report.

SHUICHI KUROIWA

Manager Canon Inc.