



Canon Inc.
7-5-1, Hakusan, Toride-shi,
Ibaraki-ken, 302-8501, Japan

Request for transmitter Limited Modular Approval

Transmitter Module Characteristics

Item Requirements EUT

1	Yes	Have its own RF shielding	See pictures
2	Yes	Have buffered modulation/data inputs (if such inputs are provided),	Refer schematic IC120.
3	No	Have it own power supply regulation	Power regulation of 3.3 V coming from extension card.
4	Yes	Meet the antenna requirements of Section 15.203	Antenna connector MMCX and MXTK
5	No	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module but, the module must not be inside another case during testing	Test in representative host printer (plastic enclosure, DC provided by extension card)

6	<p>Yes Be labeled with its own FCC ID number, and if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.</p>	See label diagram
7	<p>Yes The modular transmitter is manufactured so that the user cannot influence the operation of the transmitter that will operate outside of the scope of the regulations.</p>	
8	<p>Yes Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF exposure compliance in accordance with Section 15.247(b)(4).</p>	Refer to RF exposure calculation and manual draft

Certified By:  Masayuki Hiraide

Date: 2027.6.8