



Canon Inc.  
7-5-1, Hakusan, Toride-shi,  
Ibaraki-ken, 302-8501, Japan

### Request for Transmitter Limited Modular Approval

#### Transmitter Modular Characteristics

Item		Requirements	EUT
1	Yes	Have its own RF shielding	See pictures
2	Yes	Have buffered modulation/data inputs (if such inputs are provided)	Refer to schematic IC120
3	No	Have its' own power supply regulation	Power regulation of 3.3V coming from extension card
4	Yes	Meet the antenna requirements of section 15.203	Antenna connector MMCX and MXTK
5	No	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module, but the module must not be inside another case during testing	Test in representative host printer (metal enclosure, DC provided by extension card)
6	Yes	Be labelled with its' own FCC ID number, and if the FCC ID is not visible when the module is installed inside another device the outside of the device into which the module is installed must also display a label referring to the enclosed module	See label diagram
7	Yes	The modular transmitter is manufactured so that the user cannot influence the operation of the transmitter that will operate outside of the scope of the regulation.	
8	Yes	Address compliance with the commission's RF exposure limits in sections 1.1310 and 2.1093. In addition spread spectrum transmitters operating under Section 15.247 are required to address RF exposure compliance in accordance with Section 15.247 (b) (4).	Refer to RF exposure calculation and the manual

Certified by:  Masayuki Hiraide

Date: \_\_\_\_\_