

# Maximum Permissive Exposure

**FCC ID: AZPR7014B-24G**  
**Product Name: Radio Control**  
**Model No: R7014SB**

1. According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 Limits for Maximum Permissible Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

**Futaba Corporation** declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on ANSI/FCC recommendation.

Based on safety distance (r) **20cm**, the antenna gain (G) is **0.292Numerical**, and the highest power output (P) is **16.110mW**, the power density (S) is **0.000936mW/cm<sup>2</sup>**.

RF Exposure Calculations:

$$S = (P * G) / (4 * \pi * r^2) \text{ or } r = \sqrt{(P * G) / (4 * \pi * S)}$$

**Where :**

Based on safety distance (r)=	20 cm		
Highest Power Output (P)=	12.071 dBm =	<b>16.110 mW</b>	
Antenna Gain (G)=	-5.35 dBi =	<b>0.292 Numerical</b>	
MPE (S) = (P*G) / (4*π*r <sup>2</sup> ) =	<b>= (24.060*0.305)/(4*π*20<sup>2</sup>)=</b>		<b>0.000936 mW/cm<sup>2</sup></b>

Sincerely Yours,



Mr. Ben Cheng  
 Manager  
 AUDIX Technology Corporation