

Maximum Permissible Exposure

FCC ID: AZPR404SBS-24G

Product Name: Radio Control

Model No: R404SBS, R404SBS-E

1. According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 Limits for Maximum Permissible Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	f/300	6
1500-100,000	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

Futaba Corporation declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on ANSI/FCC recommendation.

2. MPE Calculation

Based on safety distance (r) **20cm**, the antenna gain (G) is **1.541 Numerical**, and the highest power output (P) is **1.393mW.**, the power density (S) is **0.000427mW/cm².**

RF Exposure Calculations:

$$S = (P * G) / (4 * \pi * r^2) \text{ or } r = \sqrt{(P * G) / (4 * \pi * S)}$$

Where :

Based on safety distance (r)=	20 cm
Highest Power Output (P)=	1.44 dBm = 1.393 mW
Antenna Gain (G)=	1.878 dBi = 1.541 Numerical
MPE (S) = (P*G) / (4*π*r ²) =	= (1.393*1.541)/(4*π*20²)= 0.000427 mW/cm²

Sincerely Yours,



Mr. Ben Cheng

Manager

AUDIX Technology Corporation